



# Haskell, A Purely Functional Programming Language

Authors: Joel Aumedes and Marc Cervera  
Maria Teresa Alsinet - Language Processors  
Superior Polytechnic School - University Of Lleida



ESCOLA  
POLITÈCNICA SUPERIOR  
UNIVERSITAT DE LLEIDA


# Contents

1. Introduction
2. Starting out
3. Types and Typeclasses
4. Syntax in functions
5. Recursion
6. Higher order functions
7. Modules
8. Making our own Types and Typeclasses
9. Input and output
10. What's next?



## Learn You a Haskell for Great Good!

**A Beginner's Guide**



**Miran Lipovača**



# Introduction

- Haskell is a purely functional programming language.
- Haskell is lazy, that means that unless specifically told otherwise, Haskell won't execute functions and calculate things until it's really forced to show you a result.
- Haskell is elegant and concise.

# Introduction: How to use Haskell

- To dive into Haskell, you only need a text editor (Notepad++, vim, Atom, VisualStudio code...) and a Haskell compiler such as GHC.
- To start coding, you have to open a CMD and type: ghci.

```
admin@anonymous: ~$ ghci
GHCi, version 8.8.4: https://www.haskell.org/ghc/ :? for help
Prelude>
```

# Starting out

## Basic Arithmetic


```
Prelude> 5 * 5  
25  
Prelude> 1000 / 2 * 3  
1500.0
```

## Using Lists

```
Prelude> 1:[2,3,4,5]  
[1,2,3,4,5]  
Prelude> "Hello" ++ "World"  
HelloWorld  
Prelude> head [0,1,2]  
0
```

## First functions


```
Prelude> max 5 12  
12  
Prelude> doubleMe x = x + x  
Prelude> doubleMe 10  
20  
Prelude> isBig x = if x > 100 then "Yes!" else "No!!"
```



# Starting out

## Ranges

```
Prelude> [1 .. 20]  
[1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20]  
Prelude> ['A' .. 'G']  
"ABCDEFGH"  
Prelude> take 5 [10, 20..]  
[10, 20, 30, 40, 50]
```



## List comprehensions

```
Prelude> [x*2 | x <- [1 .. 10]]  
[2,4,6,8,10,12,14,16,18,20]  
Prelude> onlyUppercase xs = [c | c <- xs, c `elem` ['A' .. 'Z']]  
Prelude> onlyUppercase "Hello My Friend!"  
"HMF"
```



# Types and Typeclasses

Everything in Haskell has a type...

```
Prelude> :t 'a'
'a' :: Char
Prelude> :t False
False :: Bool
Prelude> :t "Hello!"
"Hello!" :: [Char]
```

... even functions!

```
Prelude> shout x = x ++ "!!!"
Prelude> :t shout
shout :: [Char] -> [Char]
```



**Int, Integer, Float, Double, Bool, Char**

```
Prelude> {
Prelude| addThree :: Int -> Int -> Int -> Int
Prelude| addThree x y z = x + y + z
Prelude| :}
Prelude> :t addThree
addThree :: Int -> Int -> Int -> Int
```

# Types and Typeclasses



Type variables

```
Prelude> :t head  
head :: [a] -> a
```

Typeclasses

```
Prelude> :t 19  
19 :: Num p => p  
Prelude> :t (==)  
(==) :: Eq a => a -> a -> Bool
```

**Eq, Ord, Show, Read, Num, Fractional**



# Syntax in Functions

## Pattern matching

```
numeroCinc :: (Integral a) => a -> [Char]
numeroCinc 5 = "Number five!"
numeroCinc x = "Not a five"
Prelude> numeroCinc 5
"Number five!"
```

```
head' :: [a] -> a
head' [] = error "Head of an empty list!"
head' (x:_) = x
```

```
teams :: [Char] -> [Char]
teams "Ferrari" = "Very fast"
teams "McLaren" = "Not so fast"
Prelude> teams "Haas"
*** Exception: Non-exhaustive patterns in function teams
```

## Guards

```
diceResults :: (Integral a) => a -> [Char]
diceResults x
  | x == 1 = "Number 1!"
  | x == 2 = "Second!"
  | x == 3 = "The third!"
  | otherwise = "Very nice!"
```



# Syntax in Functions

```
bmiTell :: (RealFloat a) => a -> a -> String
bmiTell weight height
  | bmi <= 18.5 = "You are underweight!"
  | bmi <= 25.0 = "You have normal weight, not bad."
  | bmi <= 30.0 = "You are overweight, built like a croissant"
  | otherwise = "You are obese"
where bmi = weight / height ^ 2
```

[illegible]

# Recursion



- Recursion is a way of defining functions in which the function is applied inside its own definition.
- Fun fact: Definitions in mathematics are often given recursively.
  - A clear example is the Fibonacci sequence, that is given recursively.
- Recursion is important to Haskell.

```
fac :: Int -> Int
fac n
  | n < 2 = 1
  | otherwise = n * fac $ n - 1
```

```
fac :: Int -> Int
fac n
  | n < 0 = error "Are you stupid?"
  | n == 0 = 1
  | n == 1 = 1
  | n > 1 = n * fac $ n - 1
```

# Recursion

```
fib :: Int -> Int
fib 0 = 0
fib 1 = 1
fib n = fib (n - 1) + fib (n - 2)
-- Very inefficient!!
```



```
invertedPair :: (Num a) => [a] -> [(a,a)]
invertedPair [] = []
invertedPair (x:xs) = (x, negate x):invertedPair xs
```

# Higher order functions

## Curried functions

```
Prelude> max 4 5  
5  
Prelude> (max 4) 5  
5
```

```
Prelude> map (max 4) [1..6]  
[4,4,4,4,5,6]  
Prelude> applyTwice f x = f (f x)  
Prelude> applyTwice (+3) 5  
11
```

## Lambdas

```
Prelude> filter (\x -> x > 4) [1..6]  
[5,6]  
Prelude> filter (>4) [1..6]  
[5,6]
```




# Higher Order Functions

## Folds and scans

```
sum' :: (Num a) => [a] -> a
sum' xs = foldl (\acc x -> acc + x) 0 xs
Prelude> sum' [1..5]
15
```

```
sum' :: (Num a) => [a] -> a
sum' xs = foldr1 (\x acc -> acc + x) xs
Prelude> sum' [1..5]
15
```



## Function application

```
Prelude> length $ filter (>=10) [1..20]
11
```

## Function composition

```
Prelude> map (\x -> negate (abs x)) [5,-3,-6,7,-3,2,-19,24]
[-5,-3,-6,-7,-3,-2,-19,-24]
Prelude> map (negate . abs) [5,-3,-6,7,-3,2,-19,24]
[-5,-3,-6,-7,-3,-2,-19,-24]
```

# Modules



Defining a module

Importing a module

```
import Data.List
Prelude>:m + Data.List
```

**Data.List, Data.Char, Data.Map, Data.Set, Text.Regex**

```
module Conversions
( euroToDollar
, dollarToEuro
, celsiusToFahrenheit
, fahrenheitToCelsius)
where

euroToDollar = (*0.87)
...
```

# Making our own Types and Typeclasses

```
data Bool = False | True
```

```
data Content = Movie Int [[Char]] | TVShow Int Int [[Char]]
```

Pattern Matching

```
numberOfSeasons :: Content -> Int  
numberOfSeasons (Movie _) = error "Not a TV Show!"  
numberOfSeasons (TVShow seasons _) = seasons
```

Record Syntax

```
type String = [Char]  
data Car = Car { model :: String,  
                 make  :: String,  
                 year  :: Int } deriving (Show)
```

Type parameters

```
data Maybe a = Nothing | Just a
```





# Input and output

```
main = putStrLn "Hello, world!"
```

```
main = do  
  putStrLn "What's your name?"  
  name <- getLine  
  putStrLn "Nice to meet you, " ++ name
```


```
main = do  
  contents <- getContents  
  print $ length $ filter (=='\n') contents
```




# What's next?

<http://learnyouahaskell.com/chapters>

**Functors**





**Applicative functors**



**Monoids**

**Monads**



Thank you for your attention!

---