



MultiQueryRetriever

Distance-based vector database retrieval embeds (represents) queries in high-dimensional space and finds similar embedded documents based on "distance". But, retrieval may produce difference results with subtle changes in query wording or if the embeddings do not capture the semantics of the data well. Prompt engineering / tuning is sometimes done to manually address these problems, but can be tedious.

The `MultiQueryRetriever` automates the process of prompt tuning by using an LLM to generate multiple queries from different perspectives for a given user input query. For each query, it retrieves a set of relevant documents and takes the unique union across all queries to get a larger set of potentially relevant documents. By generating multiple perspectives on the same question, the `MultiQueryRetriever` might be able to overcome some of the limitations of the distance-based retrieval and get a richer set of results.

```
# Build a sample vectorDB
from langchain.vectorstores import Chroma
from langchain.document_loaders import WebBaseLoader
from langchain.embeddings.openai import OpenAIEmbeddings
from langchain.text_splitter import RecursiveCharacterTextSplitter

# Load blog post
loader = WebBaseLoader("https://lilianweng.github.io/posts/2023-06-23-agent/")
data = loader.load()

# Split
text_splitter = RecursiveCharacterTextSplitter(chunk_size=500,
chunk_overlap=0)
splits = text_splitter.split_documents(data)

# VectorDB
embedding = OpenAIEmbeddings()
vectordb = Chroma.from_documents(documents=splits, embedding=embedding)
```

API Reference:

- `Chroma` from `langchain.vectorstores`
- `WebBaseLoader` from `langchain.document_loaders`
- `OpenAIEmbeddings` from `langchain.embeddings.openai`

- `RecursiveCharacterTextSplitter` from `langchain.text_splitter`

Simple usage

Specify the LLM to use for query generation, and the retriever will do the rest.

```
from langchain.chat_models import ChatOpenAI
from langchain.retrievers.multi_query import MultiQueryRetriever

question = "What are the approaches to Task Decomposition?"
llm = ChatOpenAI(temperature=0)
retriever_from_llm = MultiQueryRetriever.from_llm(
    retriever=vectordb.as_retriever(), llm=llm
)
```

API Reference:

- `ChatOpenAI` from `langchain.chat_models`
- `MultiQueryRetriever` from `langchain.retrievers.multi_query`

```
# Set logging for the queries
```

```
import logging
```

```
logging.basicConfig()
```

```
logging.getLogger("langchain.retrievers.multi_query").setLevel(logging.INFO)
```

```
unique_docs = retriever_from_llm.get_relevant_documents(query=question)
len(unique_docs)
```

```
INFO:langchain.retrievers.multi_query:Generated queries: ['1. How
can Task Decomposition be approached?', '2. What are the different
methods for Task Decomposition?', '3. What are the various approaches
to decomposing tasks?']
```

Supplying your own prompt

You can also supply a prompt along with an output parser to split the results into a list of queries.

```
from typing import List
from langchain import LLMChain
from pydantic import BaseModel, Field
from langchain.prompts import PromptTemplate
from langchain.output_parsers import PydanticOutputParser

# Output parser will split the LLM result into a list of queries
class LineList(BaseModel):
    # "lines" is the key (attribute name) of the parsed output
    lines: List[str] = Field(description="Lines of text")

class LineListOutputParser(PydanticOutputParser):
    def __init__(self) -> None:
        super().__init__(pydantic_object=LineList)

    def parse(self, text: str) -> LineList:
        lines = text.strip().split("\n")
        return LineList(lines=lines)

output_parser = LineListOutputParser()

QUERY_PROMPT = PromptTemplate(
    input_variables=["question"],
    template="""You are an AI language model assistant. Your task is to
generate five
different versions of the given user question to retrieve relevant
documents from a vector
database. By generating multiple perspectives on the user question,
your goal is to help
the user overcome some of the limitations of the distance-based
similarity search.
Provide these alternative questions seperated by newlines.
Original question: {question}""",
)

llm = ChatOpenAI(temperature=0)

# Chain
llm_chain = LLMChain(llm=llm, prompt=QUERY_PROMPT,
```

```
output_parser=output_parser)
```

```
# Other inputs
```

```
question = "What are the approaches to Task Decomposition?"
```

API Reference:

- `PromptTemplate` from `langchain.prompts`
- `PydanticOutputParser` from `langchain.output_parsers`

```
# Run
```

```
retriever = MultiQueryRetriever(
    retriever=vectordb.as_retriever(), llm_chain=llm_chain,
    parser_key="lines"
) # "lines" is the key (attribute name) of the parsed output
```

```
# Results
```

```
unique_docs = retriever.get_relevant_documents(
    query="What does the course say about regression?"
)
len(unique_docs)
```

```
INFO:langchain.retrievers.multi_query:Generated queries: ["1. What
is the course's perspective on regression?", '2. Can you provide
information on regression as discussed in the course?', '3. How does
the course cover the topic of regression?', "4. What are the course's
teachings on regression?", '5. In relation to the course, what is
mentioned about regression?']
```