

# STATISTICAL COMPUTATIONAL METHODS

## Seminar Nr. 6, Queuing Systems

1. Performance of a car wash center is modeled by the Bernoulli single-server queuing process with 2-minute frames. Cars arrive every 10 minutes, on the average, and the average service time is 6 minutes. There are no cars at the center at 10:00 a.m., when the center opens. What is the probability that at 10:04 one car is being washed and another is waiting?

2. A metered parking lot with two parking spaces represents a Bernoulli two-server queuing system with capacity limited by two cars and 30-second frames. Cars arrive at the rate of one car every 4 minutes and each car is parked for 5 minutes, on the average.

- find the transition probability matrix for the number of parked cars;
- find the steady-state distribution for the number of parked cars;
- what fraction of the time are both parking spaces vacant?
- what fraction of arriving cars will not be able to park?
- every 2 minutes of parking costs 25 cents; assuming all drivers use all the parking time they pay for, how much money is the parking lot going to raise every 24 hours?

3. Trucks arrive at a weigh station according to a Poisson process with average rate of 1 truck every 10 minutes. Inspection times are Exponential with the average of 3 minutes. When a truck is on scale, the other arrived trucks stay in line waiting for their turn. Compute

- the expected number of trucks at the weigh station at any time;
- the proportion of time when the weigh station is empty;
- the expected time each truck spends at the station, from arrival to departure;
- (7.12) the fraction of time there are fewer than 2 trucks in the weigh station.

4. A toll area on a highway has three toll booths and works as an M/M/3 queuing system. On the average, cars arrive at the rate of one car every 5 seconds, and it takes 12 seconds to pay the toll, not including the waiting time. Compute the fraction of time when there are ten or more cars waiting in the line.

5. Sports fans tune to a local sports radio station according to a Poisson process with the rate of three fans every two minutes and listen to it for an Exponential amount of time with the average of 20 minutes.

- what queuing system is the most appropriate for this situation?
- compute the expected number of concurrent listeners at any time;
- find the fraction of time when 40 or more fans are tuned to this station.

### 6. Simulation of a D/G/1 queuing system.

A doctor schedules her patients to arrive at equal 15-minute intervals. Patients are then served in the order of their arrivals, and each of them needs a Gamma time with the doctor, that has parameters  $\alpha = 4$  and  $\lambda = 10/3 \text{ min}^{-1}$ . Use Monte Carlo simulations to estimate

- the expected response time (how much time a patient spends in the doctor's office, on average);
- the expected waiting time;
- the probability that a patient has to wait before seeing the doctor.