



Programming Graphics Hardware

GPU Applications

Randy Fernando, Cyril Zeller



***n*VIDIA®**

Overview

- **Per-Pixel Displacement Mapping with Distance Functions**
- **Percentage-Closer Soft Shadows**
- **Introduction to General-Purpose Computation on GPUs**
- **Cloth Simulation on GPU**





Programming Graphics Hardware

Per-Pixel Displacement Mapping with Distance Functions


Cyril Zeller




*n*VIDIA®

Goal

- Adding small-scale geometric details stored as a texture:
 - To reduce memory
 - To simplify authoring
- Applications: wall, grating, fence, etc.



+



Height map

=



Diffuse light **without bump**

Diffuse light **with bumps**



Traditional Methods

- **Displacement mapping [Cook]:**

- Iteratively tessellate the mesh based on the height map

Caveat: Requires multiple rendering passes and VTF [Bunnell]

- **Bump mapping [Blinn]:**

- Shade using the normals computed from the height map

Caveat: Bumps don't occlude each other


Bump
mapping



Per-pixel
displacement
mapping


Ray Tracing Based Methods

- To handle bump occlusion, we need to intersect the view vector with the height field:
 - View-dependent displacement mapping [LWang]
 - Generalized displacement mapping [XWang]
 - Parallax mapping [Kaneko, Welsh]
 - Relief mapping [Policarpo]
 - Per-Pixel Displacement Mapping with Distance Functions [Donnelly]



Finding the Intersection: Uniform Sampling

- One way of finding the intersection is to sample the height map at uniformly spaced locations
- But:
 - Undersampling** is too risky (missed intersections)
 - Oversampling** is too costly




Finding the Intersection: Sphere Tracing

- **Sphere tracing** is used to accelerate raytracing of implicit surfaces [Hart]
- We pre-compute a **distance function** $d(P)$ that maps any 3D point P to its distance to the height field H : $d(P) = \text{distance}(P, H)$
- Then at run time, we step along the ray using the following formula:

$$P_{i+1} = P_i + d(P_i) \times V$$


where V is the normalized view vector




Distance Map

- The **distance function** is stored in a “thin” 3D texture (e.g. $H_{\text{width}} \times H_{\text{height}} \times 16$) called a **distance map**
- The computation of the distance map is based on [Danielsson]

1	3	4	4	2	5	5	4	4	2	2	1	1
---	---	---	---	---	---	---	---	---	---	---	---	---




A sample 1D height field



The corresponding 2D distance map

Vertex Shader


```
void VertexShader(  
    float4 position, // In model space  
    float3x3 modelToTangent, // Local tangent, normal and binormal  
    float4 eye, // In model space  
    float4 light, // In model space  
    uniform float4x4 modelToProjection,  
    out float4 positionProj,  
    inout float2 texCoord,  
    out float3 viewVector,  
    out float3 lightVector  
)  
{  
    // Transform position to projection space  
    positionProj = mul(modelToProjection, position);  
  
    // Transform view and light vectors to tangent space  
    viewVector = mul(modelToTangent, eye - position);  
    lightVector = mul(modelToTangent, light - position);  
}
```



Provide the pixel shader with the view and light vectors in tangent space

Pixel Shader

```
float4 PixelShader(  
    float2 texCoord, float3 viewVector, float3 lightVector,  
    uniform sampler2D colorMap,  
    uniform sampler2D normalMap,  
    uniform sampler3D distMap  
)  
{  
    // Normalize interpolated vectors  
    viewVector = normalize(viewVector);  
    lightVector = normalize(lightVector);  
  
    // Find intersection with height field,  
    // assuming the surface is locally planar  
    float3 point = float3(texCoord, 1);  
    for (int i = 0; i < NUM_ITERATIONS; ++i)  
        point += tex3D(distMap, point) * viewVector;  
  
    // Compute final color  
    float4 color = tex2D(colorMap, point.xy);  
    float3 normal = tex2D(normalMap, point.xy);  
    return dot(normal, lightVector) * color;  
}
```



Start at the
top of the
height field



Performance

- **NUM_ITERATIONS** depends on
 - Distance map resolution
 - Smoothness of data
- For the demo (256x256x16), using 16 iterations is more than enough
- Note that each iteration is `{tex; mad;}`, which runs in a single cycle on GeForce FX and GeForce 6
- On a GeForce 6800 GT, the previous shader runs at around 70 fps on 1280 x 1024 pixels with 16 iterations

References

- James Blinn. “Simulation of Wrinkled Surfaces”, *SIGGRAPH* 1978
- Per-Erik Danielsson. “Euclidean Distance Mapping”, *CGIP* 1980
- Robert Cook. “Shade Trees”, *SIGGRAPH* 1984
- John Hart. “Sphere Tracing: A Geometric Method for the Antialiased Ray Tracing of Implicit Surfaces”, *The Visual Computer*, 1996
- Tomomichi Kaneko, et al. “Detailed Shape Representation with Parallax Mapping”, *ICAT* 2001
- Lifeng Wang, et al. “View-Dependent Displacement Mapping”, *SIGGRAPH* 2003
- Xi Wang, et al. “Generalized Displacement Maps”, *EG* 2004
- Terry Welsh. “Parallax with Offset Limiting: A Per-Pixel Approximation of Uneven Surfaces”
- Fabio Policarpo. “Relief Mapping in a Pixel Shader Using Binary Search”
- Michael Bunnell. “Adaptive Tessellation of Subdivision Surfaces with Displacement Mapping”, *GPU Gems 2*, 2005
- William Donnelly. “Per-Pixel Displacement Mapping with Distance Functions”, *GPU Gems 2*, 2005



GPU Gems: Programming Techniques, Tips, and Tricks for Real-Time Graphics


- Practical real-time graphics techniques from experts at leading corporations and universities
- Great value:
 - Full color (300+ diagrams and screenshots)
 - Hard cover
 - 816 pages
 - CD-ROM with demos and sample code

For more, visit:
<http://developer.nvidia.com/GPUGems>

“GPU Gems is a cool toolbox of advanced graphics techniques. Novice programmers and graphics gurus alike will find the gems practical, intriguing, and useful.”

Tim Sweeney

Lead programmer of *Unreal* at Epic Games



“This collection of articles is particularly impressive for its depth and breadth. The book includes product-oriented case studies, previously unpublished state-of-the-art research, comprehensive tutorials, and extensive code samples and demos throughout.”


Eric Haines

Author of *Real-Time Rendering*

GPU Gems 2

Programming Techniques for High-Performance Graphics and General-Purpose Computation

- **880 full-color pages, 330 figures, hard cover**
- **\$59.99**
- **Experts from universities and industry**



“The topics covered in *GPU Gems 2* are critical to the next generation of game engines.”

— Gary McTaggart, Software Engineer at Valve, Creators of *Half-Life* and *Counter-Strike*

“*GPU Gems 2* isn’t meant to simply adorn your bookshelf—it’s required reading for anyone trying to keep pace with the rapid evolution of programmable graphics. If you’re serious about graphics, this book will take you to the edge of what the GPU can do.”

—Rémi Arnaud, Graphics Architect at Sony Computer Entertainment

The Source for GPU Programming

developer.nvidia.com

- Latest News
- Developer Events Calendar
- Technical Documentation
- Conference Presentations
- GPU Programming Guide
- Powerful Tools, SDKs and more ...



nVIDIA

Join our FREE registered developer program for early access to NVIDIA drivers, cutting edge tools, online support forums, and more.

developer.nvidia.com

©2004 NVIDIA Corporation. NVIDIA, and the NVIDIA logo are trademarks and/or registered trademarks of NVIDIA Corporation. Nalu is ©2004 NVIDIA Corporation. All rights reserved.