

3 FIB - Aplicacions i Serveis Web

[transpes] Unit 2: Web Technologies

Unit 2: Web Technologies

- Core techs
 - URIs
 - HTTP
- Server-Side techs
 - Java Servlets
- Restful Web Services

World Wide Web

*"The **World Wide Web** (known as "WWW", "Web" or "W3") is the universe of network-accessible information, the embodiment of human knowledge"*


W3C <http://www.w3.org/WWW/>

"Legend has it that every new technology is first used for something related to sex or pornography. That seems to be the way of humankind"

Tim Berners-Lee <http://www.theguardian.com/technology/2005/aug/12/uknews.onlinesupplement>

- The Web was created in 1989 by **Tim Berners-Lee** while working at the European Organization for Nuclear Research (CERN) in Geneva.
- The three initial basic components:
 - **HTML**: Markup language for formatting hypertext documents
 - **URI**: Uniform notation scheme for addressing accessible resources over the network
 - **HTTP**: Protocol for transporting messages over the network

World Wide Web: Typical Interaction



Uniform Resource Identifier (URI)

- "The Web is an information space. Human beings have a lot of mental machinery for manipulating, imagining, and finding their way in spaces. URIs are the points in that space" (W3C)
- A URI is a compact sequence of characters that identifies an abstract or physical resource. Its generic syntax defines four parts:

<scheme name> : <hierarchical part> [? <query>] [# <fragment>]

► Example:

http://user:pass@example.com:992/animal/bird?species=seagull#wings

The example URI is broken down into its components:

- scheme:** http
- authority:** user:pass@example.com:992 (includes login, host, and port)
- path:** /animal/bird
- query:** ?species=seagull
- fragment:** #wings

The hierarchical part (authority and path) and the query and fragment are collectively part of the URI's structure.

HyperText Transfer Protocol (HTTP)

- Request/response communication model
 - HTTP Request
 - HTTP Response
- Typical interaction (HTTP/1.0 or lower):
 - Web browser establishes a TCP/IP connection with the target Web server

- Web browser sends a HTTP ASCII request over the TCP/IP connection.
- Web server returns a HTTP MIME-like response and releases the TCP/IP connection
- HTTP/1.1 improvements:
 - Persistent connections: several request/response interactions in a single connection.
 - Request pipelining: multiple HTTP requests are sent without waiting for the corresponding responses.

HTTP Message Format

REQUEST_start_line RESPONSE_start_line	← start line
<Field-name-1>: <Value> <Field-name-2>: <Value> ...	← header fields
	← blank line (CRLF)
<lorem> ipsum dolor sit amet, consectetur adipiscing elit. Duis et ante nulla, ac vulputate metus. Nunc fringilla dignissim mauris quis placerat</lorem>	← body (optional)

- Request and response messages have the same generic format

HTTP Request Message

REQUEST_start_line := METHOD <Resource_path> HTTP_Version
 METHOD := GET | POST | HEAD | ...
 HTTP_Version := HTTP/1.0 | HTTP/1.1 | ...

► Example:

```
GET /index.html HTTP/1.1
```

```
Host: www.essi.upc.edu
Accept: text/html
```

HTTP Request Methods

GET	get a resource from the server
HEAD	get the header only (no response body)

POST	send data (usually in the request body) to the server
PUT	store request body on server
PATCH	pply partial modifications to a resource
TRACE	get the “final” request as it is received by the server (after it has potentially been modified by proxies)
OPTIONS	get a list of HTTP methods supported by the server
DELETE	delete a resource on the server

HTTP Header Fields in Req & Res

Field name	Description	Req/Res	Example
Accept	Content-Types that are acceptable	Req	Accept: text/plain
Authorization	Authentication credentials for HTTP authentication	Req	Authorization: Basic QWxhZGRpbjpvGVuIHNIc2FtZQ==
Cache-Control	Tells all caching mechanisms from server to client whether they may cache this object. Measured in seconds	Res	Cache-Control: max-age=3600
Cookie	an HTTP cookie previously sent by the server with Set-Cookie	Req	Cookie: UserID=JohnDoe;...
Content-Length	The length of the request body in octets (8-bit bytes)	Req/Res	Content-Length: 348
Content-Type	The mime type of this content	Req/Res	Content-Type: text/html; charset=utf-8
ETag	An identifier for a specific version of a resource, often a message digest	Res	ETag: "737060cd8c284d8af7ad3082f209582d"
Set-Cookie	an HTTP cookie	Res	Set-Cookie: UserID=JohnDoe;...

HTTP Response Message

Response_start_line := HTTP_Version Status_Code [explanation]

Status_Code := 100 ... 599

► Example:

```
HTTP/1.1 200 OK
```

```
Date: Fri, 19 Feb 2010 16:48:36 GMT
Server: Apache/2.2.14 (Unix)
Last-Modified: Tue, 02 Feb 2010 14:36:59 GMT
Content-Length: 17008
Content-Type: text/html
```

```
<html>
...
</html>
```

HTTP Standard Status codes

100 Continue
200 OK
201 Created
202 Accepted
203 Non-Authoritative
204 No Content
205 Reset Content
206 Partial Content
300 Multiple Choices
301 Moved Permanently
302 Found
303 See other
304 Not Modified
305 Use Proxy
307 Temporary Redirect

4xx Client's fault

400 Bad Request
401 Unauthorized
402 Payment Required
403 Forbidden
404 Not Found
405 Method Not Allowed
406 Not Acceptable
407 Proxy Authentication Required
408 Request Timeout
409 Conflict
410 Gone
411 Length Required
412 Precondition Failed
413 Request Entity Too Large
414 Request-URI Too Long
415 Unsupported Media Type
416 Requested Range Not Satisfiable
417 Expectation Failed

500 Internal Server Error
501 Not Implemented
502 Bad Gateway
503 Service Unavailable
504 Gateway Timeout
505 HTTP Version Not supported

5xx Server's fault


Multipurpose Internet Mail Extensions (MIME) Types

- The MIME type defines the request or response body's content and is used for the appropriate processing
- Not only for mail
- See "Accept" and "Content-type" header fields

- Some examples:

MIME type	Description
text/plain	Raw textual data
text/html	HTML document
text/xml	XML document
application/javascript	Javascript
application/soap+xml	SOAP message
application/json	JSON data
multipart/form-data	HTML Form fields

Server-side computing




Passing data through HTTP requests

- Query string pairs key=value
 - GET /directory.php?userid=3439
- Path attributes:
 - DELETE /users/3439
- HTTP Request Body (POST & PUT)
 - POST /asw01ss/wot HTTP/1.1
 - Content-type: application/x-www-form-urlencoded
 - author=Menganito&tweet_text=Text+de+prova

- HTTP Headers: Standard and Custom
- Cookies

“EnWEBats” Example

The Web Form



The screenshot shows a Mozilla Firefox browser window titled "Annual suscription to EnWEBats - Mozilla Firefox". The address bar shows the page title "Annual suscription to EnW...". The main content area displays the heading "Annual subscription to the magazine *EnWEBats*: 100 euros". Below the heading are several form fields: "Full Name:" with the value "Walter Kurtz", "Address:" with the value "78 Tahoma Drive", "City:" with the value "Los Sauces", and "Postal Code:" with the value "08997". There are also fields for "Credit Card Number:" (8888999977770000) and "Expires: (MM/YY)" (09/14). Below these are radio buttons for "AMEX" and "VISA", with "VISA" selected. There is a checkbox for "Express Mail (+10 euros):" which is checked. At the bottom left is a "Submit" button.

Annual suscription to EnWEBats - Mozilla Firefox

Fitxer Edita Visualitza Historial Adreces d'interès Eines Ajuda

Annual suscription to EnW...

Annual subscription to the magazine *EnWEBats*: 100 euros

Full Name:

Address:


City: Postal Code:

Credit Card Number: Expires: (MM/YY)

AMEX ☐ VISA ☒

Express Mail (+10 euros): ☒

The Output



enwebats.html

```
<html>
....
<form action="subscribe" method="post">
Full Name: <input name="name" size="57">
Address: <input name="address" size="57">
City: <input name="city" size="32">
Postal Code: <input name="postcode" size="5">
Credit Card Number: <input name="cardnum" size="19">
Expires: (MM/YY) <input name="expdate" size="5">
AMEX <input name="cardtype" value="amex" type="radio">
  VISA <input name="cardtype" value="visa" type="radio">
Express Mail (+10 euros): <input name="express"
  type="checkbox">
<input value="Submit" type="submit"> </p> </form>
....
</html>
```

HTTP Request

POST /subscribe HTTP/1.1

Host: www.enwebats.com

Content-type: application/x-www-form-urlencoded


name=Walter+Kurtz&address=78+Tahoma+Drive&
city=Los+Sauces&postcode=08997&cardnum=88889
99977770000&expdate=09%2F14&cardtype=visa&expres
s=on

Subscribe.java

@WebServlet("/subscribe")

```
public class Subscribe extends HttpServlet {  
    public void doPost(javax.servlet.http.HttpServletRequest req,  
                       javax.servlet.http.HttpServletResponse res)  
        throws ServletException, IOException {  
        res.setContentType("text/html");  
        PrintWriter output = res.getWriter();  
        output.println("<html>");  
        output.println("<title>Subscription OK</title>");  
        output.println("<body bgcolor=white>");  
        output.println("<h3>Your subscription have been processed  
successfully:</h3>");  
        output.println("<table border=0>");  
        Enumeration paramNames = req.getParameterNames();  
        while (paramNames.hasMoreElements()) {  
            String name = (String) paramNames.nextElement();  
            String value = req.getParameter(name);  
            output.println("<tr><td>"+name+": </td><td>"+value+"</td></tr>");  
        }  
        output.println("</table></body></html>");  
        output.close();  
    }  
}
```

Java Servlets: Request Scenario



- A Servlet is an object that receives a request and generates a response based on that request.
- A Web container is essentially the component of a Web server that interacts with the servlets. The Web container is responsible for
 - Managing the lifecycle of servlets.
 - Mapping a URI to a particular servlet.
 - Ensuring that the URI requester has the correct access rights.

subscribe.php

```

<?php function print_row($item, $key) {
    echo "<tr><td>$key: </td><td>$item</td></tr>\n";
}??>
<html>
<head>
<title>Subscription OK</title>
</head>
<body bgcolor=white>
<h3>Your subscription have been processed
    successfully:</h3>
<BR>
<BR>
<table border=0 width=50%>
<?php array_walk($_POST, 'print_row'); ?>
</table>
</body>
</html>

```

HTTP: Two Important Remarks

- HTTP is stateless:
 - The Web Server handles each HTTP request independently and there is no easy way to keep track of each client request and to associate it with a previous one.
 - However, managing state is important for many applications: a single use case scenario often involves navigating through a number of Web pages. Without a state management mechanism, you would have to continually supply all previous information entered for each new Web page.
- HTTP is one-way:
 - Clearly separated roles: Clients -Web browsers- make requests to -Web- Servers, no vice versa.
 - HTTP 2.0 now supports push notifications.

Session State Management in Web Apps

Solution	Implementation	Benefits	Drawbacks
On the Client	<ul style="list-style-type: none"> Hidden Form Fields HTTP Cookies URI Rewriting Browser's localStorage & sessionStorage 	No problems with load-balanced server clusters	Security concerns if data not encrypted
On the Web container	HttpSession (Java), \$_SESSION (PHP), and the like	Easy-to-use APIs	Load-balanced server clusters require special treatments
On a DB	Stored in a DB table	<ul style="list-style-type: none"> Sharable Recoverable 	May penalize DB performance

RESTful Web Services

- RESTful Web Services expose their data and functionality through resources identified by URI
- Uniform Interface Principle: Clients interact with resources through a fixed set of verbs.
 - Example HTTP:
 - POST (create) | GET (read) | PUT (update) | DELETE
- Multiple representations (MIME types) for the same resource: XML, JSON, ...
- Hyperlinks model resource relationships and valid state transitions for dynamic protocol description and discovery

RESTful WS: URI Design Guidelines

- Two URI patterns per resource:
 - Collection: /products (plural noun)
 - Element: /product/:id (e.g. /product/41714)
- Filters:
 - /products?made_in=Italy&state=in_stock
- Versioning:
 - /v1/products
- Positioning:
 - /products?limit=25&offset=50
- Non-resources (e.g. calculate, convert, ...):
 - /convert?from=EUR&to=CNY&amount=100 (**verbs**, not nouns)

RESTful WS: Example (adapted from Wikipedia)

Resource	GET	PUT	POST	DELETE
http://www.x.com/api/products	List the members (URIs and perhaps other details) of the collection. For example list all the products.	Replace the entire collection with another collection.	Create a new entry in the collection. The new entry's ID is assigned automatically and is usually returned by the operation.	Delete the entire collection.
http://www.x.com/api/products/41714	Retrieve a representation of the addressed member of the collection, expressed in an appropriate Internet media type.	Update the addressed member of the collection, or if it doesn't exist, create it.	Treat the addressed member as a collection in its own right and create a new entry in it.	Delete the addressed member of the collection.