

Patterns for Domain Layer

Patterns for Domain Layer

- Adapter
- Abstract Factory
- Singleton
- Strategy
- Template Method
- Access to the Data Layer
- References

Adapter Pattern

Adapter Pattern


- Overview
- Static View
- Dynamic View
- Example
- References

Overview


- Context
 - The interface of an existing class (or a set of subclasses) does not match the one needed
- Problem
 - How to resolve incompatible interfaces, or provide a stable interface to similar components with different interfaces?
- Solution
 - Convert the interface of a class (Adaptee class) into another interface (Adapter class) clients (Client class) expects.
 - Adapter lets classes work together that couldn't otherwise because of incompatible interfaces.
 - Also known as Wrapper.

Static View

- Two options:
- Class adapter




- Object adapter (useful when one adapter adapts more than one adaptee)




Dynamic View

- Class adapter




- Object adapter



Example

- The NextGen POS system needs to support several kinds of external services, including tax calculators, credit authorization services, inventory services, and account systems, among others. Each has a different API, which cannot be changed.
- A solution is to add a level of indirection with objects that adapt the varying external interfaces to a consistent interface used within the software system.

Example



Example

- *makePayment* contract (partial) of the Domain Layer

context DomainLayer :: makePayment(amount:Money)

-- make the Payment of the current Sale

exc: 1.1: the amount is negative or zero


...

post: 2.1 creates an instance of payment


...

post: 2.3 the system calls the *postSale* operation of the *Accounting System* with the current sale as a parameter

Example



Example



Remember that it is better to use the interface (IAccountingAdapter) instead of a specific object of a class (SAPAccountingAdapter) to avoid the implementation dependency.

References

- *Design Patterns: Elements of Reusable Object-Oriented Software*
E. Gamma; R. Helm; R. Johnson; J. Vlissides
Addison-Wesley, 1995, pp. 139-150.
- *Applying UML and Patterns*
C. Larman
Prentice Hall, 2005 (Third edition), ch. 26

Abstract Factory Pattern


Abstract Factory Pattern

- Overview
- Static View
- Dynamic View
- Simple or Concrete Factory
- Example
- References


Overview

- Context
 - Systems that create, represent and compose a family of products that should be used together and that we do not want to reveal their implementations.
- Problem
 - Who should be responsible for creating objects when there are special considerations, such as a family of related or dependent objects?
- Solution
 - Provide an interface for creating families of related or dependent objects without specifying their concrete classes.

Static View



Dynamic View



The sequence diagrams of the other operations are similar

Simple or Concrete Factory


- Simple or Concrete Factory is not a GoF pattern (introduced by Gamma et al.), but extremely widespread.
- It is a variation of Abstract Factory Pattern where an object called Factory is the responsible for creating objects with a complex creation logic or for a better cohesion.

Example

- In the NextGen POS system the use of adapters raises a new problem in the design.
- In the Adapter pattern solution for external services with varying interfaces, who creates the adapters?


```
context DomainLayer :: makePayment(amount:Money)
  -- make the Payment of the current Sale
exc: 1.1: the amount is negative or zero
  ...
post: 2.1 creates an instance of payment
  ...
post: 2.3 the system calls the postSale operation of the Accounting
  System with the current sale as a parameter
```

Example



note that the factory methods return objects typed to an interface rather than a class, so that the factory can return any implementation of the interface

Example



References

- *Design Patterns: Elements of Reusable Object-Oriented Software*
E. Gamma; R. Helm; R. Johnson; J. Vlissides
Addison-Wesley, 1995, pp. 87-96.
- *Applying UML and Patterns*
C. Larman
Prentice Hall, 2005 (Third edition), ch. 26

Singleton Pattern



Singleton Pattern

- Overview
- Static View
- Dynamic View
- Example
- References


Overview

- Context
 - Systems that have classes with exactly one instance that must be accessible
- Problem
 - There must be exactly one instance of a class, and it must be accessible to clients from a well-known access point.
 - A global variable makes an object accessible, but it doesn't keep you from instantiating multiple objects.
- Solution
 - Define a class operation of the class that returns the singleton.

Static and Dynamic View



The UML stereotype indicates that visibility to this instance was achieved by the singleton pattern



Example

- In the NextGen POS system the use of service factory raises a new problem in the design.
- Who creates the factory itself, and how is it accessed?

context DomainLayer :: makePayment(amount:Money)

-- make the Payment of the current Sale

exc: 1.1: the amount is negative or zero


...

post: 2.1 creates an instance of payment


...

post: 2.3 the system call the *postSale* operation of the *Accounting System* with the current sale as a parameter

Example



Example



References

- *Design Patterns: Elements of Reusable Object-Oriented Software*
E. Gamma; R. Helm; R. Johnson; J. Vlissides
Addison-Wesley, 1995, pp. 127-134.
- *Applying UML and Patterns*
C. Larman
Prentice Hall, 2005 (Third edition), ch. 26

Strategy Pattern


Strategy Pattern

- Overview
- Static View
- Dynamic View
- Example
- References


Overview

- Context
 - Systems that have related classes differing only in their behavior
- Problem
 - How to design for varying, but related, algorithms or policies?
How to design for the ability to change these algorithms or policies?
 - Including these algorithms in the clients makes them bigger, harder to maintain and extend.
- Solution
 - Define classes that encapsulate different algorithms. An algorithm that is encapsulated in this way is called a strategy.

Static View



Dynamic View




- The *AlgorithmInterface* method is different for each ConcreteStrategy class
- A similar sequence diagram for the ConcreteStrategyC


Example

- In the NextGen POS system the pricing strategy for a sale can vary. During one period it may be 10% off all sales, later it may be 10 euros off if sale total is greater than 200 euros, and myriad other variations.
- How do we design for these varying pricing algorithms?


Example



Example



Example



References

- *Design Patterns: Elements of Reusable Object-Oriented Software*
E. Gamma; R. Helm; R. Johnson; J. Vlissides
Addison-Wesley, 1995, pp. 315-324.
- *Applying UML and Patterns*
C. Larman
Prentice Hall, 2005 (Third edition), ch. 26

Template Method Pattern

Template Method Pattern


- Overview
- Static View
- Dynamic View
- Example
- References

Overview


- Context
 - The definition of an operation in a hierarchy has some common behaviour to all subclasses but also some specific behaviour for each of them.
- Problem
 - Replicating the common behaviour in all subclasses requires code duplication and therefore a more costly maintenance.
- Solution
 - To define the algorithm (the operation) in the superclass, invoking abstract operations (with their signature defined in the superclass) that are implemented as methods in the subclasses.
 - The concrete operation is called *template*
 - The new operations are called *primitives*
 - The operation at the superclass defines the common behaviour whilst the abstract operations identify the specific behaviour, that is described in each subclass.

Overview


- Context: Starting situation



Static View




Dynamic View



Example

- Specification data conceptual model:




Textual Integrity Constraints:

Identifiers: (Worker, dni); (Company, cif)


There cannot exist two departments with the same name in the same company

- We want to design an operation in class *Worker* to compute the salary that has to be paid to employees working in different companies:
 - salary of Assistant = base salary of a *Worker* + *hoursEx* * *priceHEx*
 - salary of Employee = base salary of a *Worker* + *plusDep* / number of *Workers*

Example



Example



References

- *Design Patterns: Elements of Reusable Object-Oriented Software*
E. Gamma; R. Helm; R. Johnson; J. Vlissides
Addison-Wesley, 1995, pp. 325-330.
- *Applying UML and Patterns.*
C. Larman
Prentice Hall, 2005 (3rd edition), chap. 38.11

Access to the Data Layer

Access to the Data Layer

- Combining Patterns to Access to the Data Layer
- Example
- References


Combining Patterns to Access to the Data Layer

- Throughout domain layer design unit, we assume Domain Model just with operations of individual access and obtaining all the elements.
- The Data Layer must be ready to change the implementation of the operations to access and (in case of Transaction Script, modify data)


Combining Patterns to Access to the Data Layer

- For each persistent class of the Domain model that has one or more identifiers, an adapter should be defined.
- A factory (singleton) to create all the adapters should be defined.


Example



Example



Example



context CtrlPerson::get(dni: String): Person

exc: person-not-exists: there is no *Person* identified by *dni*

post: 2.1 returns person with *dni*

context CtrlPerson::exists(dni: String): Bool


post: 2.1 returns true if the person with *dni* exists, false otherwise

context CtrlPerson::all(): Set(Person)

post: 2.1 returns all the Persons existing in the system

Example

- Sequence diagram to obtain a Person by its dni.



References

- *Design Patterns: Elements of Reusable Object-Oriented Software*
E. Gamma; R. Helm; R. Johnson; J. Vlissides
Addison-Wesley, 1995, pp. 87-96, 127-138, 185-194.
- *Applying UML and Patterns*
C. Larman
Prentice Hall, 2005 (Third edition).