

Project Knowledge Base

Generated on: Fri Jul 31 12:05:06 2026

File: all_java_code_report.txt

all_java_code_report.txt

[illegible]

File: CMakeLists.txt

2

File: SSAIModule.hpp

File: PythonExecutor.hpp

File: FilePatcher.cpp

File: SSAIModule.cpp

File: ScriptValidator.cpp

File: QLMEngine.hpp

3

```
1 // Copyright 2019 Google LLC
2 //
3 // Licensed under the Apache License, Version 2.0 (the "License");
4 // you may not use this file except in compliance with the License.
5 // You may obtain a copy of the License at
6 //
7 // http://www.apache.org/licenses/LICENSE-2.0
8 //
9 // Unless required by applicable law or agreed to in writing, software
10 // distributed under the License is distributed on an "AS IS" BASIS,
11 // WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
12 // See the License for the specific language governing permissions and
13 // limitations under the License.
```

File: GeminiClient.hpp

```
1 // Copyright 2019 Google LLC
2 //
3 // Licensed under the Apache License, Version 2.0 (the "License");
4 // you may not use this file except in compliance with the License.
5 // You may obtain a copy of the License at
6 //
7 // http://www.apache.org/licenses/LICENSE-2.0
8 //
9 // Unless required by applicable law or agreed to in writing, software
10 // distributed under the License is distributed on an "AS IS" BASIS,
11 // WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
12 // See the License for the specific language governing permissions and
13 // limitations under the License.
```

File: CatCore.c

```
1 // Copyright 2019 Google LLC
2 //
3 // Licensed under the Apache License, Version 2.0 (the "License");
4 // you may not use this file except in compliance with the License.
5 // You may obtain a copy of the License at
6 //
7 // http://www.apache.org/licenses/LICENSE-2.0
8 //
9 // Unless required by applicable law or agreed to in writing, software
10 // distributed under the License is distributed on an "AS IS" BASIS,
11 // WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
12 // See the License for the specific language governing permissions and
13 // limitations under the License.
```

File: GeminiClient.cpp

```
1 // Copyright 2019 Google LLC
2 //
3 // Licensed under the Apache License, Version 2.0 (the "License");
4 // you may not use this file except in compliance with the License.
5 // You may obtain a copy of the License at
6 //
7 // http://www.apache.org/licenses/LICENSE-2.0
8 //
9 // Unless required by applicable law or agreed to in writing, software
10 // distributed under the License is distributed on an "AS IS" BASIS,
11 // WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
12 // See the License for the specific language governing permissions and
13 // limitations under the License.
```

File: ScriptValidator.hpp

```
1 // Copyright 2019 Google LLC
2 //
3 // Licensed under the Apache License, Version 2.0 (the "License");
4 // you may not use this file except in compliance with the License.
5 // You may obtain a copy of the License at
6 //
7 // http://www.apache.org/licenses/LICENSE-2.0
8 //
9 // Unless required by applicable law or agreed to in writing, software
10 // distributed under the License is distributed on an "AS IS" BASIS,
11 // WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
12 // See the License for the specific language governing permissions and
13 // limitations under the License.
```

File: QLMEngine.cpp

```
1 // Copyright 2019 Google LLC
2 //
3 // Licensed under the Apache License, Version 2.0 (the "License");
4 // you may not use this file except in compliance with the License.
5 // You may obtain a copy of the License at
6 //
7 // http://www.apache.org/licenses/LICENSE-2.0
8 //
9 // Unless required by applicable law or agreed to in writing, software
10 // distributed under the License is distributed on an "AS IS" BASIS,
11 // WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
12 // See the License for the specific language governing permissions and
13 // limitations under the License.
```

File: FilePatcher.hpp

```
1 // Copyright 2019 Google LLC
2 //
3 // Licensed under the Apache License, Version 2.0 (the "License");
4 // you may not use this file except in compliance with the License.
5 // You may obtain a copy of the License at
6 //
7 // http://www.apache.org/licenses/LICENSE-2.0
8 //
9 // Unless required by applicable law or agreed to in writing, software
10 // distributed under the License is distributed on an "AS IS" BASIS,
11 // WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
12 // See the License for the specific language governing permissions and
13 // limitations under the License.
```

File: PythonExecutor.cpp

```
1 // Copyright 2019 Google LLC
2 //
3 // Licensed under the Apache License, Version 2.0 (the "License");
4 // you may not use this file except in compliance with the License.
5 // You may obtain a copy of the License at
6 //
7 // http://www.apache.org/licenses/LICENSE-2.0
8 //
9 // Unless required by applicable law or agreed to in writing, software
10 // distributed under the License is distributed on an "AS IS" BASIS,
11 // WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
12 // See the License for the specific language governing permissions and
13 // limitations under the License.
```

File: CatCore.h

[illegible]

File: main.cpp

1. 下列各句，没有语病的一项是（3分）
 A. 在《中国好声音》的舞台上，选手们演唱的动听的歌声，赢得了观众的热烈掌声。
 B. 通过《中国好声音》的选拔，选手们将踏上打开职业生涯之门的新征程。
 C. 选手们演唱的动听的歌声，赢得了观众的热烈掌声，这是《中国好声音》的魅力所在。
 D. 选手们演唱的动听的歌声，赢得了观众的热烈掌声，这是《中国好声音》的魅力所在。

File: TerminalPane.hpp

1. 下列哪个不是 Python 的变量名？
 A. 123abc
 B. abc123
 C. abc_def
 D. _abc_def

2. 下列哪个不是 Python 的运算符？
 A. +
 B. *
 C. %
 D. &

3. 下列哪个不是 Python 的容器类型？
 A. list
 B. tuple
 C. dict
 D. set

4. 下列哪个不是 Python 的异常类型？
 A. ValueError
 B. TypeError
 C. IndexError
 D. KeyError

5. 下列哪个不是 Python 的模块？
 A. math
 B. random
 C. datetime
 D. sys

6. 下列哪个不是 Python 的函数？
 A. print
 B. len
 C. max
 D. min

7. 下列哪个不是 Python 的类？
 A. object
 B. str
 C. int
 D. float

8. 下列哪个不是 Python 的异常处理语句？
 A. try
 B. except
 C. finally
 D. else

9. 下列哪个不是 Python 的异常处理语句？
 A. try
 B. except
 C. finally
 D. else

10. 下列哪个不是 Python 的异常处理语句？
 A. try
 B. except
 C. finally
 D. else

File: DatabasePane.hpp

1. **Introduction**
 The purpose of this report is to analyze the impact of the COVID-19 pandemic on the global economy and to provide recommendations for mitigating its effects. The report is structured as follows:
 1.1. Background and Context
 The COVID-19 pandemic, caused by the SARS-CoV-2 virus, emerged in late 2019 and spread globally in early 2020. It has resulted in a significant loss of life and economic activity, with many countries implementing lockdown measures to contain the virus.
 1.2. Objectives
 The objectives of this report are to:
 - Analyze the economic impact of the pandemic.
 - Identify the sectors most affected by the pandemic.
 - Provide recommendations for mitigating the economic impact.
 1.3. Methodology
 The methodology used in this report is a combination of secondary data analysis and expert interviews. Secondary data was collected from various sources, including government reports, academic journals, and news articles. Expert interviews were conducted with economists and public health officials to gain insights into the pandemic's impact and potential mitigation strategies.
 2. **Economic Impact**
 The COVID-19 pandemic has had a profound impact on the global economy, leading to a sharp decline in GDP and a rise in unemployment. The impact has been particularly severe in the service sector, which has experienced a significant loss of revenue and jobs.
 2.1. Global GDP
 The global GDP has declined significantly since the onset of the pandemic. According to the International Monetary Fund (IMF), the global GDP is projected to decline by 3.5% in 2020, with a recovery expected in 2021.
 2.2. Unemployment
 The unemployment rate has risen sharply in many countries, with the global average projected to reach 5.8% in 2020. The impact has been particularly severe in the service sector, where unemployment is projected to reach 10.5% in 2020.
 2.3. Inflation
 Inflation has remained relatively stable in most countries, with the global average projected to be 2.5% in 2020. However, some countries have experienced a rise in inflation due to the impact of the pandemic on the supply chain.
 3. **Sectors Most Affected**
 The sectors most affected by the COVID-19 pandemic are the service sector, manufacturing, and retail. The service sector, which includes tourism, hospitality, and retail, has experienced a significant loss of revenue and jobs. Manufacturing has also been affected, with many factories closing due to the impact of the pandemic on the supply chain. Retail has also experienced a significant loss of revenue and jobs.
 3.1. Service Sector
 The service sector, which includes tourism, hospitality, and retail, has experienced a significant loss of revenue and jobs. The impact has been particularly severe in the tourism and hospitality sectors, which have experienced a significant loss of revenue and jobs.
 3.2. Manufacturing
 Manufacturing has also been affected, with many factories closing due to the impact of the pandemic on the supply chain. The impact has been particularly severe in the automotive and electronics sectors, which have experienced a significant loss of revenue and jobs.
 3.3. Retail
 Retail has also experienced a significant loss of revenue and jobs. The impact has been particularly severe in the clothing and footwear sectors, which have experienced a significant loss of revenue and jobs.
 4. **Recommendations**
 To mitigate the economic impact of the COVID-19 pandemic, governments and businesses should implement the following recommendations:
 4.1. Government
 - Implement fiscal and monetary policies to stimulate economic growth.
 - Provide financial support to businesses and individuals affected by the pandemic.
 - Implement measures to protect the health and safety of the population.
 4.2. Businesses
 - Implement measures to protect the health and safety of employees and customers.
 - Diversify revenue streams to reduce reliance on a single sector.
 - Implement measures to improve operational efficiency.
 5. **Conclusion**
 The COVID-19 pandemic has had a profound impact on the global economy, leading to a sharp decline in GDP and a rise in unemployment. The impact has been particularly severe in the service sector, which has experienced a significant loss of revenue and jobs. To mitigate the economic impact of the pandemic, governments and businesses should implement the recommendations outlined in this report.

```

// 1. 定义一个空数组
var arr = [];

// 2. 定义一个函数，接收一个参数，返回一个数组
function arrPush(arr, value) {
    // 3. 将参数添加到数组末尾
    arr.push(value);
    // 4. 返回数组
    return arr;
}

// 5. 调用函数，将元素添加到数组
arrPush(arr, 1);
arrPush(arr, 2);
arrPush(arr, 3);

// 6. 输出数组
console.log(arr);

```

```

1  #!/usr/bin/perl
2
3  use strict;
4  use warnings;
5
6  my $VERSION = "1.0.0";
7
8  my $help = "
9  Usage: perl script.pl [options]
10
11  Options:
12  -h, --help            Display this help message
13  -v, --version          Display the version number
14  -f, --file FILE        Input file name
15  -o, --output FILE      Output file name
16  -d, --debug            Enable debug mode
17  -s, --size SIZE        File size in bytes
18  -t, --type TYPE        File type
19  -m, --mode MODE        File mode
20  -u, --user USER        Username
21  -g, --group GROUP      Group name
22  -p, --perms PERMS      Permissions
23  -c, --checksum CHECKSUM Checksum
24  -e, --encoding ENCODING Encoding
25  -i, --ignore IGNORE     Ignore errors
26  -q, --quiet            Quiet mode
27  -n, --no-color          No color
28  -w, --width WIDTH       Window width
29  -H, --help             Display this help message
30
31  Examples:
32  perl script.pl -f file.txt -o output.txt
33  perl script.pl -f file.txt -o output.txt -d
34  perl script.pl -f file.txt -o output.txt -s 1024
35  perl script.pl -f file.txt -o output.txt -t text
36  perl script.pl -f file.txt -o output.txt -m 0755
37  perl script.pl -f file.txt -o output.txt -u user
38  perl script.pl -f file.txt -o output.txt -g group
39  perl script.pl -f file.txt -o output.txt -p 0755
40  perl script.pl -f file.txt -o output.txt -c 1234567890
41  perl script.pl -f file.txt -o output.txt -e utf8
42  perl script.pl -f file.txt -o output.txt -i
43  perl script.pl -f file.txt -o output.txt -q
44  perl script.pl -f file.txt -o output.txt -n
45  perl script.pl -f file.txt -o output.txt -w 80
46  perl script.pl -f file.txt -o output.txt -H
47
48  Copyright (c) 2020, Author
49  All rights reserved.
50
51  License: MIT
52
53  See README for more details.
54
55  ";
56
57  my $file = "";
58  my $output = "";
59  my $debug = 0;
60  my $size = 0;
61  my $type = "";
62  my $mode = "";
63  my $user = "";
64  my $group = "";
65  my $perms = "";
66  my $checksum = "";
67  my $encoding = "";
68  my $ignore = 0;
69  my $quiet = 0;
70  my $no_color = 0;
71  my $width = 80;
72
73  while (my $arg = shift @ARGV) {
74      if ($arg eq "-h" || $arg eq "--help") {
75          print $help;
76          exit 0;
77      }
78      if ($arg eq "-v" || $arg eq "--version") {
79          print $VERSION;
80          exit 0;
81      }
82      if ($arg eq "-f" || $arg eq "--file") {
83          $file = shift @ARGV;
84      }
85      if ($arg eq "-o" || $arg eq "--output") {
86          $output = shift @ARGV;
87      }
88      if ($arg eq "-d" || $arg eq "--debug") {
89          $debug = 1;
90      }
91      if ($arg eq "-s" || $arg eq "--size") {
92          $size = shift @ARGV;
93      }
94      if ($arg eq "-t" || $arg eq "--type") {
95          $type = shift @ARGV;
96      }
97      if ($arg eq "-m" || $arg eq "--mode") {
98          $mode = shift @ARGV;
99      }
100     if ($arg eq "-u" || $arg eq "--user") {
101         $user = shift @ARGV;
102     }
103     if ($arg eq "-g" || $arg eq "--group") {
104         $group = shift @ARGV;
105     }
106     if ($arg eq "-p" || $arg eq "--perms") {
107         $perms = shift @ARGV;
108     }
109     if ($arg eq "-c" || $arg eq "--checksum") {
110         $checksum = shift @ARGV;
111     }
112     if ($arg eq "-e" || $arg eq "--encoding") {
113         $encoding = shift @ARGV;
114     }
115     if ($arg eq "-i" || $arg eq "--ignore") {
116         $ignore = 1;
117     }
118     if ($arg eq "-q" || $arg eq "--quiet") {
119         $quiet = 1;
120     }
121     if ($arg eq "-n" || $arg eq "--no-color") {
122         $no_color = 1;
123     }
124     if ($arg eq "-w" || $arg eq "--width") {
125         $width = shift @ARGV;
126     }
127     if ($arg eq "-H" || $arg eq "--help") {
128         print $help;
129         exit 0;
130     }
131 }
132
133 # Main logic here
134
135 # Example of a simple operation
136 if ($file) {
137     # Read file content
138     my $content = "";
139     if ($debug) {
140         print "Reading file: $file\n";
141     }
142     open my $fh, "<$file" or die "Cannot open file: $file\n";
143     while (my $line = <$fh) {
144         $content .= $line;
145     }
146     close $fh;
147
148     # Write to output file
149     if ($output) {
150         open my $out_fh, ">$output" or die "Cannot open output file: $output\n";
151         print $out_fh $content;
152         close $out_fh;
153     }
154
155     # Calculate checksum
156     my $checksum = "";
157     if ($checksum) {
158         $checksum = md5($content);
159     }
160
161     # Print results
162     if (!$quiet) {
163         print "File: $file\n";
164         print "Output: $output\n";
165         print "Checksum: $checksum\n";
166     }
167 }
168
169 # End of script
170

```

1. **Identify the main components of the system.**
 2. **Define the scope and objectives of the study.**
 3. **Review the literature on the topic.**
 4. **Design the experimental setup.**
 5. **Collect and analyze data.**
 6. **Draw conclusions and discuss the results.**
 7. **Write the report and prepare for presentation.**

```

// 打印结果，并返回
return {
  data: res.data,
  total: res.total
};
}

// 调用接口
const res = await request({
  url: 'http://localhost:3000/api/users',
  method: 'GET'
});

// 打印结果
console.log(res);

```

【例 1-10】某企业 2013 年 12 月 31 日有关资产、负债和所有者权益账户余额如下表所示。

资产	负债和所有者权益
货币资金 1000000	短期借款 1000000
应收账款 1000000	应付账款 1000000
存货 1000000	预收账款 1000000
固定资产 1000000	实收资本 1000000
无形资产 1000000	资本公积 1000000
长期股权投资 1000000	盈余公积 1000000
其他资产 1000000	其他所有者权益 1000000
合计 7000000	合计 7000000

【例 1-11】某企业 2013 年 12 月 31 日有关资产、负债和所有者权益账户余额如下表所示。

资产	负债和所有者权益
货币资金 1000000	短期借款 1000000
应收账款 1000000	应付账款 1000000
存货 1000000	预收账款 1000000
固定资产 1000000	实收资本 1000000
无形资产 1000000	资本公积 1000000
长期股权投资 1000000	盈余公积 1000000
其他资产 1000000	其他所有者权益 1000000
合计 7000000	合计 7000000

1. 下列各数中，是正有理数的是（ ）
A. -2 B. 0 C. 1 D. -1

2. 下列各数中，是负有理数的是（ ）
A. 2 B. 0 C. 1 D. -1

3. 下列各数中，是正有理数的是（ ）
A. -2 B. 0 C. 1 D. -1

4. 下列各数中，是负有理数的是（ ）
A. 2 B. 0 C. 1 D. -1

5. 下列各数中，是正有理数的是（ ）
A. -2 B. 0 C. 1 D. -1

6. 下列各数中，是负有理数的是（ ）
A. 2 B. 0 C. 1 D. -1

7. 下列各数中，是正有理数的是（ ）
A. -2 B. 0 C. 1 D. -1

8. 下列各数中，是负有理数的是（ ）
A. 2 B. 0 C. 1 D. -1

9. 下列各数中，是正有理数的是（ ）
A. -2 B. 0 C. 1 D. -1

10. 下列各数中，是负有理数的是（ ）
A. 2 B. 0 C. 1 D. -1

File: CustomIconProvider.hpp

```
1 // CustomIconProvider.hpp
2
3 #ifndef CUSTOMICONPROVIDER_HPP
4 #define CUSTOMICONPROVIDER_HPP
5
6 #include "IconProvider.hpp"
7
8 class CustomIconProvider : public IconProvider
9 {
10 public:
11     CustomIconProvider() {}
12     CustomIconProvider(const CustomIconProvider& other) {}
13     CustomIconProvider& operator=(const CustomIconProvider& other) {}
14     ~CustomIconProvider() {}
15
16     // Implement the IconProvider interface
17     std::string GetIconName(const std::string& path) const override
18     {
19         // ...
20     }
21
22     // ...
23
24 private:
25     // ...
26
27 };
28
29 #endif
```

File: ProjectTypeView.hpp

```
1 // ProjectTypeView.hpp
2
3 #ifndef PROJECTTYPEVIEW_HPP
4 #define PROJECTTYPEVIEW_HPP
5
6 #include "ProjectType.hpp"
7
8 class ProjectTypeView : public ProjectType
9 {
10 public:
11     ProjectTypeView() {}
12     ProjectTypeView(const ProjectTypeView& other) {}
13     ProjectTypeView& operator=(const ProjectTypeView& other) {}
14     ~ProjectTypeView() {}
15
16     // Implement the ProjectType interface
17     std::string GetProjectType() const override
18     {
19         // ...
20     }
21
22     // ...
23
24 private:
25     // ...
26
27 };
28
29 #endif
```

File: GeminiPane.hpp

```
1 // GeminiPane.hpp
2
3 #ifndef GEMINIPANE_HPP
4 #define GEMINIPANE_HPP
5
6 #include "Pane.hpp"
7
8 class GeminiPane : public Pane
9 {
10 public:
11     GeminiPane() {}
12     GeminiPane(const GeminiPane& other) {}
13     GeminiPane& operator=(const GeminiPane& other) {}
14     ~GeminiPane() {}
15
16     // Implement the Pane interface
17     void SetContent(const std::string& content) override
18     {
19         // ...
20     }
21
22     // ...
23
24 private:
25     // ...
26
27 };
28
29 #endif
```

File: EditorHost.hpp

```
1 // EditorHost.hpp
2
3 #ifndef EDITORHOST_HPP
4 #define EDITORHOST_HPP
5
6 #include "Editor.hpp"
7
8 class EditorHost : public Editor
9 {
10 public:
11     EditorHost() {}
12     EditorHost(const EditorHost& other) {}
13     EditorHost& operator=(const EditorHost& other) {}
14     ~EditorHost() {}
15
16     // Implement the Editor interface
17     void SetEditor(const Editor& editor) override
18     {
19         // ...
20     }
21
22     // ...
23
24 private:
25     // ...
26
27 };
28
29 #endif
```

File: PdfComposerPane.hpp

```
1 // PdfComposerPane.hpp
```

File: DesignerPane.hpp

File: PdfViewerPane.hpp

File: ProjectHighlighter.cpp

8

File: DiffDialog.hpp

File: HexEditorPane.hpp

File: EditorPane.hpp

File: ProjectHighlighter.hpp

File: EditorPane.cpp

9

File: OpenProjectView.hpp

File: BrowserPane.hpp

File: LogcatPane.hpp

File: SettingsView.hpp

11

File: GitPane.hpp

File: GitPane.hpp

```
1 // GitPane.hpp
2
3 #ifndef GIT_PANE_HPP
4 #define GIT_PANE_HPP
5
6 #include "Git.h"
7 #include "GitPane.h"
8
9 #include "GitPane.h"
10
11 #endif
```

File: InspectionPane.hpp

```
1 // InspectionPane.hpp
2
3 #ifndef INSPECTION_PANE_HPP
4 #define INSPECTION_PANE_HPP
5
6 #include "InspectionPane.h"
7
8 #include "InspectionPane.h"
9
10 #endif
```

File: MainWindow.hpp

```
1 // MainWindow.hpp
2
3 #ifndef MAIN_WINDOW_HPP
4 #define MAIN_WINDOW_HPP
5
6 #include "MainWindow.h"
7
8 #include "MainWindow.h"
9
10 #endif
```

File: ShellScriptingPane.hpp

```
1 // ShellScriptingPane.hpp
2
3 #ifndef SHELL_SCRIPTING_PANE_HPP
4 #define SHELL_SCRIPTING_PANE_HPP
5
6 #include "ShellScriptingPane.h"
7
8 #include "ShellScriptingPane.h"
9
10 #endif
```

File: ProjectWorkspace.hpp

```
1 // ProjectWorkspace.hpp
2
3 #ifndef PROJECTWORKSPACE_HPP
4 #define PROJECTWORKSPACE_HPP
5
6 #include "ProjectWorkspace.h"
7
8 namespace ProjectWorkspace {
9
10     // ProjectWorkspace class
11     class ProjectWorkspace {
12     public:
13         ProjectWorkspace();
14         ProjectWorkspace(const ProjectWorkspace&);
15         ProjectWorkspace& operator=(const ProjectWorkspace&);
16         ~ProjectWorkspace();
17
18         // Methods
19         void AddProject(const Project& project);
20         void RemoveProject(const Project& project);
21         void ListProjects();
22         void Save();
23         void Load();
24         void Clear();
25
26     private:
27         // Attributes
28         std::vector<Project> projects;
29         std::string workspacePath;
30     };
31
32 } // namespace ProjectWorkspace
33
34 #endif
```

File: SavesPane.hpp

```
1 // SavesPane.hpp
2
3 #ifndef SAVESPANE_HPP
4 #define SAVESPANE_HPP
5
6 #include "SavesPane.h"
7
8 namespace SavesPane {
9
10     // SavesPane class
11     class SavesPane {
12     public:
13         SavesPane();
14         SavesPane(const SavesPane&);
15         SavesPane& operator=(const SavesPane&);
16         ~SavesPane();
17
18         // Methods
19         void AddSave(const Save& save);
20         void RemoveSave(const Save& save);
21         void ListSaves();
22         void Save();
23         void Load();
24         void Clear();
25
26     private:
27         // Attributes
28         std::vector<Save> saves;
29         std::string savesPath;
30     };
31
32 } // namespace SavesPane
33
34 #endif
```

File: FileSystemService.cpp

```
1 // FileSystemService.cpp
2
3 #include "FileSystemService.h"
4
5 namespace FileSystemService {
6
7     // FileSystemService class
8     class FileSystemService {
9     public:
10         FileSystemService();
11         FileSystemService(const FileSystemService&);
12         FileSystemService& operator=(const FileSystemService&);
13         ~FileSystemService();
14
15         // Methods
16         void CreateDirectory(const std::string& path);
17         void RemoveDirectory(const std::string& path);
18         void ListDirectories();
19         void Save();
20         void Load();
21         void Clear();
22
23     private:
24         // Attributes
25         std::vector<std::string> directories;
26         std::string filePath;
27     };
28
29 } // namespace FileSystemService
```

File: SyntaxScanner.hpp

```
1 // SyntaxScanner.hpp
2
3 #ifndef SYNTAXSCANNER_HPP
4 #define SYNTAXSCANNER_HPP
5
6 #include "SyntaxScanner.h"
7
8 namespace SyntaxScanner {
9
10     // SyntaxScanner class
11     class SyntaxScanner {
12     public:
13         SyntaxScanner();
14         SyntaxScanner(const SyntaxScanner&);
15         SyntaxScanner& operator=(const SyntaxScanner&);
16         ~SyntaxScanner();
17
18         // Methods
19         void AddToken(const Token& token);
20         void RemoveToken(const Token& token);
21         void ListTokens();
22         void Save();
23         void Load();
24         void Clear();
25
26     private:
27         // Attributes
28         std::vector<Token> tokens;
29         std::string tokensPath;
30     };
31
32 } // namespace SyntaxScanner
33
34 #endif
```

File: PersistenceService.cpp

```
1 // PersistenceService.cpp
2
3 #include "PersistenceService.h"
4
5 #include <iostream>
6 #include <string>
7 #include <vector>
8 #include <map>
9 #include <algorithm>
10
11 using namespace std;
12
13 PersistenceService::PersistenceService() {
14     // Initialize data structures
15     mUsers = map<string, User>();
16     mBooks = map<string, Book>();
17     mReviews = map<string, Review>();
18 }
19
20 PersistenceService::~PersistenceService() {
21     // Cleanup
22 }
23
24 void PersistenceService::AddUser(const string& username, const string& password) {
25     User user(username, password);
26     mUsers[username] = user;
27 }
28
29 void PersistenceService::AddBook(const string& title, const string& author) {
30     Book book(title, author);
31     mBooks[title] = book;
32 }
33
34 void PersistenceService::AddReview(const string& title, const string& reviewer, const string& reviewText) {
35     Review review(title, reviewer, reviewText);
36     mReviews[title + reviewer] = review;
37 }
38
39 bool PersistenceService::Authenticate(const string& username, const string& password) const {
40     if (mUsers.find(username) != mUsers.end()) {
41         const User& user = mUsers[username];
42         return user.password == password;
43     }
44     return false;
45 }
46
47 vector<Book> PersistenceService::GetBooksByAuthor(const string& author) const {
48     vector<Book> books;
49     for (const auto& book : mBooks) {
50         if (book.second.author == author) {
51             books.push_back(book.second);
52         }
53     }
54     return books;
55 }
56
57 vector<Review> PersistenceService::GetReviewsByBook(const string& title) const {
58     vector<Review> reviews;
59     for (const auto& review : mReviews) {
60         if (review.first.find(title) != string::npos) {
61             reviews.push_back(review.second);
62         }
63     }
64     return reviews;
65 }
66
67 void PersistenceService::PrintAllData() const {
68     cout << "Users:" << endl;
69     for (const auto& user : mUsers) {
70         cout << user.first << " " << user.second.password << endl;
71     }
72     cout << "Books:" << endl;
73     for (const auto& book : mBooks) {
74         cout << book.first << " " << book.second.author << endl;
75     }
76     cout << "Reviews:" << endl;
77     for (const auto& review : mReviews) {
78         cout << review.first << " " << review.second.reviewer << " " << review.second.reviewText << endl;
79     }
80 }
```

File: DialogService.hpp

```
1 // DialogService.hpp
2
3 #ifndef DIALOGSERVICE_HPP
4 #define DIALOGSERVICE_HPP
5
6 #include <iostream>
7 #include <string>
8
9 using namespace std;
10
11 class DialogService {
12 public:
13     DialogService() {}
14     ~DialogService() {}
15
16     void ShowWelcome() const {
17         cout << "Welcome to the application!" << endl;
18     }
19
20     void ShowMenu() const {
21         cout << "Menu:" << endl;
22         cout << "1. Add User" << endl;
23         cout << "2. Add Book" << endl;
24         cout << "3. Add Review" << endl;
25         cout << "4. Authenticate" << endl;
26         cout << "5. Get Books by Author" << endl;
27         cout << "6. Get Reviews by Book" << endl;
28         cout << "7. Print All Data" << endl;
29         cout << "8. Exit" << endl;
30     }
31
32     int GetChoice() const {
33         int choice;
34         do {
35             choice = 0;
36             while (choice < 1 || choice > 8) {
37                 cout << "Enter a valid choice (1-8): ";
38                 if (!choice) {
39                     choice = 1;
40                 }
41             }
42         } while (choice < 1 || choice > 8);
43         return choice;
44     }
45
46     string GetInput() const {
47         string input;
48         do {
49             input = "";
50             while (input.empty()) {
51                 cout << "Enter input: ";
52             }
53         } while (input.empty());
54         return input;
55     }
56
57     void GetChoiceAndInput(int choice) const {
58         if (choice == 1) {
59             string username = GetInput();
60             string password = GetInput();
61             AddUser(username, password);
62         } else if (choice == 2) {
63             string title = GetInput();
64             string author = GetInput();
65             AddBook(title, author);
66         } else if (choice == 3) {
67             string title = GetInput();
68             string reviewer = GetInput();
69             string reviewText = GetInput();
70             AddReview(title, reviewer, reviewText);
71         } else if (choice == 4) {
72             string username = GetInput();
73             string password = GetInput();
74             Authenticate(username, password);
75         } else if (choice == 5) {
76             string author = GetInput();
77             GetBooksByAuthor(author);
78         } else if (choice == 6) {
79             string title = GetInput();
80             GetReviewsByBook(title);
81         } else if (choice == 7) {
82             PrintAllData();
83         } else if (choice == 8) {
84             Exit();
85         }
86     }
87
88     void Exit() const {
89         cout << "Exiting application..." << endl;
90     }
91 };
92
93 #endif
```

File: GitService.cpp

```
1 // GitService.cpp
2
3 #include "GitService.h"
4
5 #include <iostream>
6 #include <string>
7 #include <vector>
8 #include <map>
9 #include <algorithm>
10
11 using namespace std;
12
13 GitService::GitService() {
14     // Initialize data structures
15     mUsers = map<string, User>();
16     mBooks = map<string, Book>();
17     mReviews = map<string, Review>();
18 }
19
20 GitService::~GitService() {
21     // Cleanup
22 }
23
24 void GitService::AddUser(const string& username, const string& password) {
25     User user(username, password);
26     mUsers[username] = user;
27 }
28
29 void GitService::AddBook(const string& title, const string& author) {
30     Book book(title, author);
31     mBooks[title] = book;
32 }
33
34 void GitService::AddReview(const string& title, const string& reviewer, const string& reviewText) {
35     Review review(title, reviewer, reviewText);
36     mReviews[title + reviewer] = review;
37 }
38
39 bool GitService::Authenticate(const string& username, const string& password) const {
40     if (mUsers.find(username) != mUsers.end()) {
41         const User& user = mUsers[username];
42         return user.password == password;
43     }
44     return false;
45 }
46
47 vector<Book> GitService::GetBooksByAuthor(const string& author) const {
48     vector<Book> books;
49     for (const auto& book : mBooks) {
50         if (book.second.author == author) {
51             books.push_back(book.second);
52         }
53     }
54     return books;
55 }
56
57 vector<Review> GitService::GetReviewsByBook(const string& title) const {
58     vector<Review> reviews;
59     for (const auto& review : mReviews) {
60         if (review.first.find(title) != string::npos) {
61             reviews.push_back(review.second);
62         }
63     }
64     return reviews;
65 }
66
67 void GitService::PrintAllData() const {
68     cout << "Users:" << endl;
69     for (const auto& user : mUsers) {
70         cout << user.first << " " << user.second.password << endl;
71     }
72     cout << "Books:" << endl;
73     for (const auto& book : mBooks) {
74         cout << book.first << " " << book.second.author << endl;
75     }
76     cout << "Reviews:" << endl;
77     for (const auto& review : mReviews) {
78         cout << review.first << " " << review.second.reviewer << " " << review.second.reviewText << endl;
79     }
80 }
```

File: GitService.hpp

```
1 // GitService.hpp
2
3 #ifndef GITSERVICE_HPP
4 #define GITSERVICE_HPP
5
6 #include <iostream>
7 #include <string>
8
9 using namespace std;
10
11 class GitService {
12 public:
13     GitService() {}
14     ~GitService() {}
15
16     void ShowWelcome() const {
17         cout << "Welcome to the application!" << endl;
18     }
19
20     void ShowMenu() const {
21         cout << "Menu:" << endl;
22         cout << "1. Add User" << endl;
23         cout << "2. Add Book" << endl;
24         cout << "3. Add Review" << endl;
25         cout << "4. Authenticate" << endl;
26         cout << "5. Get Books by Author" << endl;
27         cout << "6. Get Reviews by Book" << endl;
28         cout << "7. Print All Data" << endl;
29         cout << "8. Exit" << endl;
30     }
31
32     int GetChoice() const {
33         int choice;
34         do {
35             choice = 0;
36             while (choice < 1 || choice > 8) {
37                 cout << "Enter a valid choice (1-8): ";
38                 if (!choice) {
39                     choice = 1;
40                 }
41             }
42         } while (choice < 1 || choice > 8);
43         return choice;
44     }
45
46     string GetInput() const {
47         string input;
48         do {
49             input = "";
50             while (input.empty()) {
51                 cout << "Enter input: ";
52             }
53         } while (input.empty());
54         return input;
55     }
56
57     void GetChoiceAndInput(int choice) const {
58         if (choice == 1) {
59             string username = GetInput();
60             string password = GetInput();
61             AddUser(username, password);
62         } else if (choice == 2) {
63             string title = GetInput();
64             string author = GetInput();
65             AddBook(title, author);
66         } else if (choice == 3) {
67             string title = GetInput();
68             string reviewer = GetInput();
69             string reviewText = GetInput();
70             AddReview(title, reviewer, reviewText);
71         } else if (choice == 4) {
72             string username = GetInput();
73             string password = GetInput();
74             Authenticate(username, password);
75         } else if (choice == 5) {
76             string author = GetInput();
77             GetBooksByAuthor(author);
78         } else if (choice == 6) {
79             string title = GetInput();
80             GetReviewsByBook(title);
81         } else if (choice == 7) {
82             PrintAllData();
83         } else if (choice == 8) {
84             Exit();
85         }
86     }
87
88     void Exit() const {
89         cout << "Exiting application..." << endl;
90     }
91 };
92
93 #endif
```

File: FileSystemService.hpp

```
1 // FileSystemService.hpp
2
3 #ifndef FILESYSTEMSERVICE_HPP
4 #define FILESYSTEMSERVICE_HPP
5
6 #include <iostream>
7 #include <string>
8
9 using namespace std;
10
11 class FileSystemService {
12 public:
13     FileSystemService() {}
14     ~FileSystemService() {}
15
16     void ShowWelcome() const {
17         cout << "Welcome to the application!" << endl;
18     }
19
20     void ShowMenu() const {
21         cout << "Menu:" << endl;
22         cout << "1. Add User" << endl;
23         cout << "2. Add Book" << endl;
24         cout << "3. Add Review" << endl;
25         cout << "4. Authenticate" << endl;
26         cout << "5. Get Books by Author" << endl;
27         cout << "6. Get Reviews by Book" << endl;
28         cout << "7. Print All Data" << endl;
29         cout << "8. Exit" << endl;
30     }
31
32     int GetChoice() const {
33         int choice;
34         do {
35             choice = 0;
36             while (choice < 1 || choice > 8) {
37                 cout << "Enter a valid choice (1-8): ";
38                 if (!choice) {
39                     choice = 1;
40                 }
41             }
42         } while (choice < 1 || choice > 8);
43         return choice;
44     }
45
46     string GetInput() const {
47         string input;
48         do {
49             input = "";
50             while (input.empty()) {
51                 cout << "Enter input: ";
52             }
53         } while (input.empty());
54         return input;
55     }
56
57     void GetChoiceAndInput(int choice) const {
58         if (choice == 1) {
59             string username = GetInput();
60             string password = GetInput();
61             AddUser(username, password);
62         } else if (choice == 2) {
63             string title = GetInput();
64             string author = GetInput();
65             AddBook(title, author);
66         } else if (choice == 3) {
67             string title = GetInput();
68             string reviewer = GetInput();
69             string reviewText = GetInput();
70             AddReview(title, reviewer, reviewText);
71         } else if (choice == 4) {
72             string username = GetInput();
73             string password = GetInput();
74             Authenticate(username, password);
75         } else if (choice == 5) {
76             string author = GetInput();
77             GetBooksByAuthor(author);
78         } else if (choice == 6) {
79             string title = GetInput();
80             GetReviewsByBook(title);
81         } else if (choice == 7) {
82             PrintAllData();
83         } else if (choice == 8) {
84             Exit();
85         }
86     }
87
88     void Exit() const {
89         cout << "Exiting application..." << endl;
90     }
91 };
92
93 #endif
```

File: PersistenceService.hpp

```
1 // PersistenceService.hpp
2
3 #ifndef PERSISTENCESERVICE_HPP
4 #define PERSISTENCESERVICE_HPP
5
6 #include <iostream>
7 #include <string>
8
9 using namespace std;
10
11 class PersistenceService {
12 public:
13     PersistenceService() {}
14     ~PersistenceService() {}
15
16     void ShowWelcome() const {
17         cout << "Welcome to the application!" << endl;
18     }
19
20     void ShowMenu() const {
21         cout << "Menu:" << endl;
22         cout << "1. Add User" << endl;
23         cout << "2. Add Book" << endl;
24         cout << "3. Add Review" << endl;
25         cout << "4. Authenticate" << endl;
26         cout << "5. Get Books by Author" << endl;
27         cout << "6. Get Reviews by Book" << endl;
28         cout << "7. Print All Data" << endl;
29         cout << "8. Exit" << endl;
30     }
31
32     int GetChoice() const {
33         int choice;
34         do {
35             choice = 0;
36             while (choice < 1 || choice > 8) {
37                 cout << "Enter a valid choice (1-8): ";
38                 if (!choice) {
39                     choice = 1;
40                 }
41             }
42         } while (choice < 1 || choice > 8);
43         return choice;
44     }
45
46     string GetInput() const {
47         string input;
48         do {
49             input = "";
50             while (input.empty()) {
51                 cout << "Enter input: ";
52             }
53         } while (input.empty());
54         return input;
55     }
56
57     void GetChoiceAndInput(int choice) const {
58         if (choice == 1) {
59             string username = GetInput();
60             string password = GetInput();
61             AddUser(username, password);
62         } else if (choice == 2) {
63             string title = GetInput();
64             string author = GetInput();
65             AddBook(title, author);
66         } else if (choice == 3) {
67             string title = GetInput();
68             string reviewer = GetInput();
69             string reviewText = GetInput();
70             AddReview(title, reviewer, reviewText);
71         } else if (choice == 4) {
72             string username = GetInput();
73             string password = GetInput();
74             Authenticate(username, password);
75         } else if (choice == 5) {
76             string author = GetInput();
77             GetBooksByAuthor(author);
78         } else if (choice == 6) {
79             string title = GetInput();
80             GetReviewsByBook(title);
81         } else if (choice == 7) {
82             PrintAllData();
83         } else if (choice == 8) {
84             Exit();
85         }
86     }
87
88     void Exit() const {
89         cout << "Exiting application..." << endl;
90     }
91 };
92
93 #endif
```

File: PdfService.hpp

```
1 // PdfService.hpp
2
3 #ifndef PDFSERVICE_HPP
4 #define PDFSERVICE_HPP
5
6 #include <iostream>
7 #include <string>
8
9 using namespace std;
10
11 class PdfService {
12 public:
13     PdfService() {}
14     ~PdfService() {}
15
16     void ShowWelcome() const {
17         cout << "Welcome to the application!" << endl;
18     }
19
20     void ShowMenu() const {
21         cout << "Menu:" << endl;
22         cout << "1. Add User" << endl;
23         cout << "2. Add Book" << endl;
24         cout << "3. Add Review" << endl;
25         cout << "4. Authenticate" << endl;
26         cout << "5. Get Books by Author" << endl;
27         cout << "6. Get Reviews by Book" << endl;
28         cout << "7. Print All Data" << endl;
29         cout << "8. Exit" << endl;
30     }
31
32     int GetChoice() const {
33         int choice;
34         do {
35             choice = 0;
36             while (choice < 1 || choice > 8) {
37                 cout << "Enter a valid choice (1-8): ";
38                 if (!choice) {
39                     choice = 1;
40                 }
41             }
42         } while (choice < 1 || choice > 8);
43         return choice;
44     }
45
46     string GetInput() const {
47         string input;
48         do {
49             input = "";
50             while (input.empty()) {
51                 cout << "Enter input: ";
52             }
53         } while (input.empty());
54         return input;
55     }
56
57     void GetChoiceAndInput(int choice) const {
58         if (choice == 1) {
59             string username = GetInput();
60             string password = GetInput();
61             AddUser(username, password);
62         } else if (choice == 2) {
63             string title = GetInput();
64             string author = GetInput();
65             AddBook(title, author);
66         } else if (choice == 3) {
67             string title = GetInput();
68             string reviewer = GetInput();
69             string reviewText = GetInput();
70             AddReview(title, reviewer, reviewText);
71         } else if (choice == 4) {
72             string username = GetInput();
73             string password = GetInput();
74             Authenticate(username, password);
75         } else if (choice == 5) {
76             string author = GetInput();
77             GetBooksByAuthor(author);
78         } else if (choice == 6) {
79             string title = GetInput();
80             GetReviewsByBook(title);
81         } else if (choice == 7) {
82             PrintAllData();
83         } else if (choice == 8) {
84             Exit();
85         }
86     }
87
88     void Exit() const {
89         cout << "Exiting application..." << endl;
90     }
91 };
92
93 #endif
```

[illegible]

出版人：陳國治
 出版時間：2011年12月
 出版地點：中國·北京
 印刷時間：2011年12月
 印刷地點：中國·北京

© 2004 Blackwell Publishing Ltd
Journal of Internal Medicine 255: 111–117

1. 下列各句，没有语病的一项是（3分）
 A. 在“一带一路”的宏伟规划中，中国正以开放的姿态，广纳百川，吸引全球的目光。
 B. 随着“一带一路”倡议的深入实施，沿线国家间的贸易往来日益频繁，经济合作不断深化。
 C. 为了提升国民的环保意识，政府决定在全国范围内开展一场声势浩大的环保宣传活动。
 D. 面对日益严峻的环境问题，社会各界人士纷纷建言献策，希望政府能采取更有力措施。

1000

中国地质大学（北京）
 地球科学与资源学院
 地质工程研究所
 地址：北京市海淀区学院路29号
 邮编：100871

[illegible]

2012年 2月 27日

File: ide_full_skin_cyber.cpp

File: ide_full_skin_cyber.cpp

File: property_inspector_table.cpp

File: property_inspector_table.cpp

File: docking_setup.cpp

File: docking_setup.cpp

File: ide_command_palette.cpp

File: ide_command_palette.cpp

File: custom_font_loader.cpp

File: custom_font_loader.cpp

File: hex_editor_view.cpp

File: hex_editor_view.cpp

File: minimal_window.cpp

File: minimal_window.cpp

File: toolbar_and_status.cpp

File: toolbar_and_status.cpp

File: colored_console.cpp

File: colored_console.cpp

File: styling_vibrant.cpp

File: node_graph_basic.cpp

File: modal_popups.cpp

File: performance_monitor.cpp

File: notification_toasts.cpp

File: style_glass_neon.cpp

File: ide_dashboard_welcome.cpp

File: log_rotator.sh

17

File: dependency_checker.sh

```
#!/bin/bash
# dependency_checker.sh
# This script checks for missing dependencies for a given package.
# It uses the dpkg-query command to get the list of dependencies
# and compares it with the installed packages.
# If a dependency is missing, it prints the name of the package
# and the list of missing dependencies.
```

File: check_services.sh

```
#!/bin/bash
# check_services.sh
# This script checks the status of system services.
# It uses the systemctl command to get the status of each service.
# If a service is not running, it prints the name of the service
# and the command to start it.
```

File: password_gen.sh

```
#!/bin/bash
# password_gen.sh
# This script generates a random password of a given length.
```

File: valgrind_analyzer.sh

```
#!/bin/bash
# valgrind_analyzer.sh
# This script runs valgrind on a given program and analyzes the output.
```

File: db_migration_gen.sh

```
#!/bin/bash
# db_migration_gen.sh
# This script generates a database migration script for a given database.
```

File: gen_deb_package.sh

```
#!/bin/bash
# gen_deb_package.sh
# This script generates a Debian package for a given program.
```

File: find_duplicates.sh

```
#!/bin/bash
# find_duplicates.sh
# This script finds duplicate files in a given directory.
```

File: git_cleaner.sh

```
#!/bin/bash
# git_cleaner.sh
# This script cleans up a git repository by removing untracked files.
```

File: professional_boilerplate.sh

```
#!/bin/bash
# professional_boilerplate.sh
# This script generates a professional boilerplate for a given project.
```

```
#!/bin/sh
#
# theme_sync.sh
#
# This script syncs the theme files from the source to the target.
#
# Usage: theme_sync.sh [source] [target]
#
# Options:
# -s, --source [source] Source directory
# -t, --target [target] Target directory
# -h, --help Display this help message
#
# Example:
# theme_sync.sh /usr/share/themes/gnome /usr/share/themes/gnome
#
# Copyright (c) 2012 Canonical Ltd.
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>
#
```

File: theme_sync.sh

```
#!/bin/sh
#
# gen_rpm_package.sh
#
# This script generates an RPM package from the source files.
#
# Usage: gen_rpm_package.sh [source] [target]
#
# Options:
# -s, --source [source] Source directory
# -t, --target [target] Target directory
# -h, --help Display this help message
#
# Example:
# gen_rpm_package.sh /usr/share/themes/gnome /usr/share/themes/gnome
#
# Copyright (c) 2012 Canonical Ltd.
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>
#
```

File: gen_rpm_package.sh

```
#!/bin/sh
#
# automated_backup.sh
#
# This script performs an automated backup of the source files.
#
# Usage: automated_backup.sh [source] [target]
#
# Options:
# -s, --source [source] Source directory
# -t, --target [target] Target directory
# -h, --help Display this help message
#
# Example:
# automated_backup.sh /usr/share/themes/gnome /usr/share/themes/gnome
#
# Copyright (c) 2012 Canonical Ltd.
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>
#
```

File: automated_backup.sh

```
#!/bin/sh
#
# resource_integrity.sh
#
# This script checks the resource integrity of the source files.
#
# Usage: resource_integrity.sh [source] [target]
#
# Options:
# -s, --source [source] Source directory
# -t, --target [target] Target directory
# -h, --help Display this help message
#
# Example:
# resource_integrity.sh /usr/share/themes/gnome /usr/share/themes/gnome
#
# Copyright (c) 2012 Canonical Ltd.
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>
#
```

File: resource_integrity.sh

```
#!/bin/sh
#
# gen_suse_package.sh
#
# This script generates a SUSE package from the source files.
#
# Usage: gen_suse_package.sh [source] [target]
#
# Options:
# -s, --source [source] Source directory
# -t, --target [target] Target directory
# -h, --help Display this help message
#
# Example:
# gen_suse_package.sh /usr/share/themes/gnome /usr/share/themes/gnome
#
# Copyright (c) 2012 Canonical Ltd.
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>
#
```

File: gen_suse_package.sh

```
#!/bin/sh
#
# env_guard.sh
#
# This script guards the environment variables.
#
# Usage: env_guard.sh [source] [target]
#
# Options:
# -s, --source [source] Source directory
# -t, --target [target] Target directory
# -h, --help Display this help message
#
# Example:
# env_guard.sh /usr/share/themes/gnome /usr/share/themes/gnome
#
# Copyright (c) 2012 Canonical Ltd.
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>
#
```

File: env_guard.sh

```
#!/bin/sh
#
# project_vacuum.sh
#
# This script performs a project vacuum.
#
# Usage: project_vacuum.sh [source] [target]
#
# Options:
# -s, --source [source] Source directory
# -t, --target [target] Target directory
# -h, --help Display this help message
#
# Example:
# project_vacuum.sh /usr/share/themes/gnome /usr/share/themes/gnome
#
# Copyright (c) 2012 Canonical Ltd.
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>
#
```

File: project_vacuum.sh

```
#!/bin/sh
#
# validate_headers.sh
#
# This script validates the headers of the source files.
#
# Usage: validate_headers.sh [source] [target]
#
# Options:
# -s, --source [source] Source directory
# -t, --target [target] Target directory
# -h, --help Display this help message
#
# Example:
# validate_headers.sh /usr/share/themes/gnome /usr/share/themes/gnome
#
# Copyright (c) 2012 Canonical Ltd.
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>
#
```

File: validate_headers.sh

```
#!/bin/sh
#
# validate_headers.sh
#
# This script validates the headers of the source files.
#
# Usage: validate_headers.sh [source] [target]
#
# Options:
# -s, --source [source] Source directory
# -t, --target [target] Target directory
# -h, --help Display this help message
#
# Example:
# validate_headers.sh /usr/share/themes/gnome /usr/share/themes/gnome
#
# Copyright (c) 2012 Canonical Ltd.
#
# This program is free software: you can redistribute it and/or modify
# it under the terms of the GNU General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# This program is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU General Public License for more details.
#
# You should have received a copy of the GNU General Public License
# along with this program. If not, see <http://www.gnu.org/licenses/>
#
```

File: todo_scanner.sh

```
#!/bin/sh
#
# todo_scanner.sh
#
# This script scans the current directory for files containing
# TODO items and prints them to the console.
#
# Usage:
#   ./todo_scanner.sh
```

File: asset_optimizer.sh

```
#!/bin/sh
#
# asset_optimizer.sh
#
# This script optimizes assets by removing unnecessary
# data and compressing the remaining data.
#
# Usage:
#   ./asset_optimizer.sh
```

File: color_logger.sh

```
#!/bin/sh
#
# color_logger.sh
#
# This script logs messages to the console with
# color formatting.
#
# Usage:
#   ./color_logger.sh
```

File: release_packager.sh

```
#!/bin/sh
#
# release_packager.sh
#
# This script packages the release files into a
# single archive.
#
# Usage:
#   ./release_packager.sh
```

File: license_header_adder.sh

```
#!/bin/sh
#
# license_header_adder.sh
#
# This script adds a license header to the
# beginning of each file in the current
# directory.
#
# Usage:
#   ./license_header_adder.sh
```

File: bulk_renamer.sh

```
#!/bin/sh
#
# bulk_renamer.sh
#
# This script renames a bulk of files in the
# current directory.
#
# Usage:
#   ./bulk_renamer.sh
```

File: pre_commit_check.sh

```
#!/bin/sh
#
# pre_commit_check.sh
#
# This script checks the current directory for
# files that need to be committed.
#
# Usage:
#   ./pre_commit_check.sh
```

File: start_docs_server.sh

```
#!/bin/sh
#
# start_docs_server.sh
#
# This script starts a web server to serve the
# documentation files.
#
# Usage:
#   ./start_docs_server.sh
```

File: ram_alert.sh

```
#!/bin/sh
#
# ram_alert.sh
#
# This script alerts the user when the system
# memory is low.
#
# Usage:
#   ./ram_alert.sh
```

File: gen_appimage.sh

1. 下列各句，没有语病的一句是（ ）
A. 在 2008 年 5 月 12 日汶川大地震发生后，全国人民都献出了自己的一份力量。
B. 在 2008 年 5 月 12 日汶川大地震发生后，全国人民都献出了自己的一份力量。
C. 在 2008 年 5 月 12 日汶川大地震发生后，全国人民都献出了自己的一份力量。
D. 在 2008 年 5 月 12 日汶川大地震发生后，全国人民都献出了自己的一份力量。

File: system_monitor.sh

[illegible]

File: project_scaffold.sh

1. 下列哪个选项不是 Python 的变量名？
 A. my_var_1
 B. 1_my_var
 C. my_var_1_2
 D. my_var_1_2_3

2. 下列哪个选项不是 Python 的保留字？
 A. and
 B. as
 C. with
 D. from

3. 下列哪个选项不是 Python 的运算符？
 A. +
 B. *
 C. %
 D. //

4. 下列哪个选项不是 Python 的容器类型？
 A. list
 B. tuple
 C. dict
 D. set

5. 下列哪个选项不是 Python 的异常类型？
 A. ValueError
 B. TypeError
 C. NameError
 D. FileNotFoundError

6. 下列哪个选项不是 Python 的模块？
 A. math
 B. random
 C. sys
 D. os

7. 下列哪个选项不是 Python 的函数？
 A. def
 B. lambda
 C. yield
 D. return

8. 下列哪个选项不是 Python 的类？
 A. class
 B. def
 C. lambda
 D. yield

9. 下列哪个选项不是 Python 的装饰器？
 A. @decorator
 B. def
 C. lambda
 D. yield

10. 下列哪个选项不是 Python 的上下文管理器？
 A. with
 B. as
 C. with
 D. as

File: gen_docs.sh

1. **Identify the main components of the system.**
The system consists of a **client** and a **server**. The client is responsible for sending requests to the server, and the server is responsible for processing these requests and returning responses.

2. **Describe the flow of data.**
Data flows from the client to the server via a **network**. The client sends a request, and the server returns a response.

3. **Identify the protocols used.**
The system uses the **HTTP** protocol for communication between the client and the server.

4. **Describe the architecture.**
The architecture is a **client-server** architecture. The client is a separate entity from the server, and they communicate over a network.

5. **Identify the components of the client.**
The client consists of a **browser** and a **web application**. The browser is responsible for displaying the content, and the web application is responsible for handling user interactions.

6. **Describe the components of the server.**
The server consists of a **web server** and a **database**. The web server is responsible for serving the content, and the database is responsible for storing and retrieving data.

7. **Identify the data sources.**
The data sources are the **client** and the **server**. The client provides input data, and the server provides output data.

8. **Describe the data flow.**
Data flows from the client to the server via a **network**. The client sends a request, and the server returns a response.

9. **Identify the components of the system.**
The system consists of a **client** and a **server**. The client is responsible for sending requests to the server, and the server is responsible for processing these requests and returning responses.

10. **Describe the flow of data.**
Data flows from the client to the server via a **network**. The client sends a request, and the server returns a response.

File: self_updater.sh

【例 1】 某企业 2013 年 12 月 31 日购入一台设备,入账价值为 200 万元,预计使用寿命为 8 年,预计净残值为 20 万元,采用年限平均法计提折旧。2014 年 12 月 31 日计提折旧额为 25 万元,不考虑其他因素,2014 年 12 月 31 日该设备累计折旧额为 () 万元。

【答案】 C

【解析】 2014 年 12 月 31 日该设备累计折旧额 = 200 × (1 - 20%) ÷ 8 × 1 = 25 (万元)。

File: auto_formatter.sh

参考文献 [1] 王德胜, 王德胜, 王德胜. 中国人口地理学[M]. 北京: 中国人口出版社, 2000.
 [2] 王德胜, 王德胜, 王德胜. 中国人口地理学[M]. 北京: 中国人口出版社, 2000.
 [3] 王德胜, 王德胜, 王德胜. 中国人口地理学[M]. 北京: 中国人口出版社, 2000.
 [4] 王德胜, 王德胜, 王德胜. 中国人口地理学[M]. 北京: 中国人口出版社, 2000.
 [5] 王德胜, 王德胜, 王德胜. 中国人口地理学[M]. 北京: 中国人口出版社, 2000.
 [6] 王德胜, 王德胜, 王德胜. 中国人口地理学[M]. 北京: 中国人口出版社, 2000.
 [7] 王德胜, 王德胜, 王德胜. 中国人口地理学[M]. 北京: 中国人口出版社, 2000.
 [8] 王德胜, 王德胜, 王德胜. 中国人口地理学[M]. 北京: 中国人口出版社, 2000.
 [9] 王德胜, 王德胜, 王德胜. 中国人口地理学[M]. 北京: 中国人口出版社, 2000.
 [10] 王德胜, 王德胜, 王德胜. 中国人口地理学[M]. 北京: 中国人口出版社, 2000.

File: branch_guard.sh

[illegible]

File: api_health_check.sh

[illegible]

File: check_leaks.sh

1. 在代码中，我们使用了 `try-except` 来捕获异常。如果发生异常，程序将不会继续执行，而是会跳转到 `except` 块中的代码。

File: check_hardcoded_keys.sh

```
#!/bin/sh
# Check for hardcoded keys in source files
find . -type f -name '*.c' -o -name '*.h' -o -name '*.cpp' -o -name '*.hpp' | xargs grep -l 'key' | xargs grep -l 'secret'
```

File: code_metrics.sh

```
#!/bin/sh
# Calculate code metrics for a directory
find . -type f -name '*.c' -o -name '*.h' -o -name '*.cpp' -o -name '*.hpp' | xargs wc -l | sort -nr
```

File: env_diff_checker.sh

```
#!/bin/sh
# Check for environment variable differences
diff $(cat .env) $(cat .env.prod)
```

File: docker_dev_env.sh

```
#!/bin/sh
# Docker development environment setup
docker run --rm -it --name dev_env ubuntu:18.04 /bin/bash
```

File: string_splitter.hpp

```
#include <iostream>
using namespace std;
```

File: file_reader_oop.cpp

```
#include <iostream>
using namespace std;
```

File: smart_pointer_demo.cpp

```
#include <iostream>
using namespace std;
```

File: cli_tool_getopt.cpp

```
#include <iostream>
using namespace std;
```

File: console_minimal.cpp

```
#include <iostream>
using namespace std;
```

File: date_time_util.hpp

```
1 // date_time_util.hpp
2
3 #ifndef DATE_TIME_UTIL_HPP
4 #define DATE_TIME_UTIL_HPP
5
6 #include <string>
7 #include <chrono>
8
9 namespace date_time_util {
10     std::string get_current_time_string();
11     std::string get_current_date_string();
12     std::string get_current_datetime_string();
13 }
14
15 #endif
```

File: singleton_pattern.hpp

```
1 // singleton_pattern.hpp
2
3 #ifndef SINGLETON_PATTERN_HPP
4 #define SINGLETON_PATTERN_HPP
5
6 #include <string>
7 #include <mutex>
8
9 namespace singleton_pattern {
10     class Singleton {
11     public:
12         static Singleton* get_instance();
13         Singleton() {}
14     };
15 }
16
17 #endif
```

File: oop_structure.hpp

```
1 // oop_structure.hpp
2
3 #ifndef OOP_STRUCTURE_HPP
4 #define OOP_STRUCTURE_HPP
5
6 #include <string>
7 #include <vector>
8
9 namespace oop_structure {
10     class Base {
11     public:
12         virtual ~Base() {}
13     };
14     class Derived : public Base {
15     public:
16         Derived() {}
17     };
18     std::vector<Base> get_objects();
19 }
20
21 #endif
```

File: benchmark_util.hpp

```
1 // benchmark_util.hpp
2
3 #ifndef BENCHMARK_UTIL_HPP
4 #define BENCHMARK_UTIL_HPP
5
6 #include <string>
7 #include <chrono>
8
9 namespace benchmark_util {
10     std::string get_current_time_string();
11     std::string get_current_date_string();
12     std::string get_current_datetime_string();
13 }
14
15 #endif
```

File: thread_pool_basic.cpp

```
1 // thread_pool_basic.cpp
2
3 #include <string>
4 #include <vector>
5 #include <thread>
6 #include <mutex>
7 #include <atomic>
8
9 namespace thread_pool_basic {
10     std::vector<std::thread> get_threads();
11     std::string get_current_time_string();
12     std::string get_current_date_string();
13     std::string get_current_datetime_string();
14 }
15
16 #endif
```

File: ssqilm_dynamic_scaffold.sh

```
1 #!/bin/bash
2
3 # ssqilm_dynamic_scaffold.sh
4
5 # This script is used to scaffold the ssqilm project.
6 # It creates the necessary directories and files.
7
8 # Usage:
9 #   ssqilm_dynamic_scaffold.sh
10
11 # Options:
12 #   -h: Display this help message
13 #   -v: Display the version number
14 #   -p: Project name (default: ssqilm)
```

File: ssqilm_docker_env.sh

```
1 #!/bin/bash
2
3 # ssqilm_docker_env.sh
4
5 # This script is used to set up the Docker environment for ssqilm.
6 # It installs the necessary dependencies and sets up the environment.
7
8 # Usage:
9 #   ssqilm_docker_env.sh
10
11 # Options:
12 #   -h: Display this help message
13 #   -v: Display the version number
14 #   -p: Project name (default: ssqilm)
```

File: ssqilm_git_guard.sh

```
1 #!/bin/bash
2
3 # ssqilm_git_guard.sh
4
5 # This script is used to guard the Git repository for ssqilm.
6 # It checks for unauthorized changes and prevents them.
7
8 # Usage:
9 #   ssqilm_git_guard.sh
10
11 # Options:
12 #   -h: Display this help message
13 #   -v: Display the version number
14 #   -p: Project name (default: ssqilm)
```

File: ssqilm_db_migrator.sh

```
1 #!/bin/bash
2
3 # ssqilm_db_migrator.sh
4
5 # This script is used to migrate the database for ssqilm.
6 # It runs the necessary SQL queries to update the database.
7
8 # Usage:
9 #   ssqilm_db_migrator.sh
10
11 # Options:
12 #   -h: Display this help message
13 #   -v: Display the version number
14 #   -p: Project name (default: ssqilm)
```

File: ssqllm_idempotent_append.sh

```
#!/bin/sh
# ssqllm_idempotent_append.sh
# This script appends the contents of the file 'ssqllm_idempotent_append.sh' to the file 'ssqllm_idempotent_append.sh'.
```

File: ssqllm_atomic_generator.sh

```
#!/bin/sh
# ssqllm_atomic_generator.sh
# This script generates the file 'ssqllm_atomic_generator.sh'.
```

File: ssqllm_surgical_patcher.sh

```
#!/bin/sh
# ssqllm_surgical_patcher.sh
# This script patches the file 'ssqllm_surgical_patcher.sh'.
```

File: performance_guidance_human.json

```
{
  "name": "performance_guidance_human",
  "description": "Performance guidance for human users."
}
```

File: greetings.json

```
{
  "name": "greetings",
  "description": "Greetings for the user."
}
```

File: resource_management_ui.json

```
{
  "name": "resource_management_ui",
  "description": "Resource management UI."
}
```

File: developer_support.json

```
{
  "name": "developer_support",
  "description": "Developer support."
}
```

File: ui_ux_design.json

```
{
  "name": "ui_ux_design",
  "description": "UI/UX design."
}
```

File: productivity_automation.json

```
{
  "name": "productivity_automation",
  "description": "Productivity automation."
}
```

File: documentation_learning.json

```
{
  "name": "documentation_learning.json",
  "version": "1.0.0",
  "description": "A JSON file containing documentation learning data."
}
```

File: system_info.json

```
{
  "name": "system_info.json",
  "version": "1.0.0",
  "description": "A JSON file containing system information data."
}
```

File: file_operations.json

```
{
  "name": "file_operations.json",
  "version": "1.0.0",
  "description": "A JSON file containing file operations data."
}
```

File: vcs_git_support.json

```
{
  "name": "vcs_git_support.json",
  "version": "1.0.0",
  "description": "A JSON file containing VCS Git support data."
}
```

File: human_feedback.json

```
{
  "name": "human_feedback.json",
  "version": "1.0.0",
  "description": "A JSON file containing human feedback data."
}
```

File: code_review_logic.json

```
{
  "name": "code_review_logic.json",
  "version": "1.0.0",
  "description": "A JSON file containing code review logic data."
}
```

File: error_handling.json

```
{
  "name": "error_handling.json",
  "version": "1.0.0",
  "description": "A JSON file containing error handling data."
}
```

File: extraordinary_coding.json

```
{
  "name": "extraordinary_coding.json",
  "version": "1.0.0",
  "description": "A JSON file containing extraordinary coding data."
}
```

File: sqlalchemy_specialization.json

```
{
  "name": "sqlalchemy_specialization.json",
  "version": "1.0.0",
  "description": "A JSON file containing sqlalchemy specialization data."
}
```

File: ide_navigation_help.json

```
{
  "name": "ide_navigation_help.json",
  "version": "1.0.0",
  "description": "A JSON file containing IDE navigation help data."
}
```

File: collaboration_git_human.json

File: collaboration_git_human.json

File: troubleshooting_ui.json

File: troubleshooting_ui.json

File: capabilities.json

File: capabilities.json

File: project_management.json

File: project_management.json

File: database_guidance.json

File: database_guidance.json

File: templates_logic.json

File: templates_logic.json

File: python_logic.json

File: python_logic.json

File: security_standards.json

File: security_standards.json

File: agent_core.json

File: agent_core.json

File: professionalism_ethics.json

```
#!/bin/sh
#
# log_rotator.sh
#
# This script rotates the log files of the system.
# It uses the 'logrotate' command to rotate the logs.
# The logs are rotated daily and are compressed.
# The old logs are moved to a directory named 'log_archive'.
# The script is run as root.
```

File: log_rotator.sh

```
#!/bin/sh
#
# dependency_checker.sh
#
# This script checks the dependencies of the system.
# It uses the 'dpkg-query' command to get the list of installed packages.
# The script is run as root.
```

File: dependency_checker.sh

```
#!/bin/sh
#
# 12-navigation-service.sh
#
# This script starts the 12-navigation-service.
# It uses the 'systemctl' command to start the service.
# The script is run as root.
```

File: 12-navigation-service.sh

```
#!/bin/sh
#
# cat_specialized_patterns.json
#
# This script generates the cat_specialized_patterns.json file.
# It uses the 'cat' command to concatenate the patterns.
# The script is run as root.
```

File: cat_specialized_patterns.json

```
#!/bin/sh
#
# 20.0-migrate-to-jetbrains.sh
#
# This script migrates the system to JetBrains.
# It uses the 'mv' command to move the files.
# The script is run as root.
```

File: 20.0-migrate-to-jetbrains.sh

```
#!/bin/sh
#
# check_services.sh
#
# This script checks the status of the services.
# It uses the 'systemctl' command to check the status.
# The script is run as root.
```

File: check_services.sh

```
#!/bin/sh
#
# 27
#
# This script is the 27th script in the series.
# It is a placeholder for future scripts.
# The script is run as root.
```

File: password_gen.sh

```
#!/bin/sh
#
# Generate a random password
#
# Usage: password_gen.sh [length]
#
# If no length is specified, the default is 16.
#
# The password is generated using the following command:
# tr -dc 'a-z0-9' < /dev/urandom | fold -w 16 | paste -d '' -s | tr -d '\n'
```

File: valgrind_analyzer.sh

```
#!/bin/sh
#
# Valgrind analyzer script
#
# Usage: valgrind_analyzer.sh [command] [args...]
```

File: 16.4-open-project.sh

```
#!/bin/sh
#
# 16.4-open-project.sh
#
# This script opens the project in the IDE.
#
# Usage: 16.4-open-project.sh
```

File: agent_personality.json

```
{
  "name": "Agent",
  "personality": {
    "traits": {
      "curiosity": 0.8,
      "creativity": 0.7,
      "empathy": 0.6,
      "intelligence": 0.9,
      "openness": 0.5,
      "conscientiousness": 0.4,
      "agreeableness": 0.3,
      "neuroticism": 0.2
    },
    "moods": {
      "happy": 0.1,
      "sad": 0.1,
      "angry": 0.1,
      "calm": 0.2,
      "excited": 0.1,
      "fearful": 0.1,
      "surprised": 0.1,
      "disgusted": 0.1
    }
  }
}
```

File: parallel_processing.json

```
{
  "name": "Parallel Processing",
  "config": {
    "threads": 4,
    "timeout": 30,
    "retry": 3
  }
}
```

File: cat_safety_and_rollback.json

```
{
  "name": "Cat Safety and Rollback",
  "config": {
    "safety": true,
    "rollback": true
  }
}
```

File: performance_precision.json

```
{
  "name": "Performance Precision",
  "config": {
    "precision": 0.001,
    "performance": 0.001
  }
}
```

File: db_migration_gen.sh

```
#!/bin/sh
#
# Database migration generator
#
# Usage: db_migration_gen.sh [command] [args...]
```

File: 17.4-fix-missing-symbols.sh

```
#!/bin/sh
#
# 17.4-fix-missing-symbols.sh
#
# This script fixes missing symbols in the binary.
```

File: 13.2.1-final-sidebar.sh

File: 13.1-theme-manager.sh

File: 07-core.sh

File: 13.7-create-views.sh

File: ssq1m_parallel_executor.sh

29

【例 1】 某企业 2013 年 12 月 31 日有关资产、负债和所有者权益科目余额如下表所示。

资产	负债和所有者权益
货币资金 1000000	短期借款 1000000
应收账款 1000000	应付账款 1000000
其他应收款 1000000	预收账款 1000000
存货 1000000	应付职工薪酬 1000000
固定资产 1000000	应交税费 1000000
无形资产 1000000	实收资本 1000000
长期股权投资 1000000	资本公积 1000000
其他流动资产 1000000	盈余公积 1000000
其他非流动资产 1000000	未分配利润 1000000
合计 7000000	合计 7000000

【例 2】 某企业 2013 年 12 月 31 日有关资产、负债和所有者权益科目余额如下表所示。

资产	负债和所有者权益
货币资金 1000000	短期借款 1000000
应收账款 1000000	应付账款 1000000
其他应收款 1000000	预收账款 1000000
存货 1000000	应付职工薪酬 1000000
固定资产 1000000	应交税费 1000000
无形资产 1000000	实收资本 1000000
长期股权投资 1000000	资本公积 1000000
其他流动资产 1000000	盈余公积 1000000
其他非流动资产 1000000	未分配利润 1000000
合计 7000000	合计 7000000

1. 本報社址：台北市中正區延平南路77號5樓505室
 2. 本報社址：台北市中正區延平南路77號5樓505室
 3. 本報社址：台北市中正區延平南路77號5樓505室
 4. 本報社址：台北市中正區延平南路77號5樓505室
 5. 本報社址：台北市中正區延平南路77號5樓505室
 6. 本報社址：台北市中正區延平南路77號5樓505室
 7. 本報社址：台北市中正區延平南路77號5樓505室
 8. 本報社址：台北市中正區延平南路77號5樓505室
 9. 本報社址：台北市中正區延平南路77號5樓505室
 10. 本報社址：台北市中正區延平南路77號5樓505室

```

1  # 设置日志级别
2  log_level = "INFO"
3  # 设置日志格式
4  log_format = "%(asctime)s %(levelname)s %(message)s"
5  # 设置日志输出文件
6  log_file = "logs/app.log"
7  # 设置日志输出模式
8  log_mode = "a"
9  # 设置日志文件大小
10 log_max_size = 1024 * 1024
11 # 设置日志文件备份数量
12 log_max_backup = 5
13 # 设置日志文件权限
14 log_file_permissions = "0666"
15 # 设置日志文件所有者
16 log_file_owner = "root"
17 # 设置日志文件组
18 log_file_group = "root"
19 # 设置日志文件路径
20 log_file_path = "/var/log/app/"
21 # 设置日志文件名称
22 log_file_name = "app.log"
23 # 设置日志文件完整路径
24 log_file_full_path = "/var/log/app/app.log"
25 # 设置日志文件完整路径
26 log_file_full_path = "/var/log/app/app.log"
27 # 设置日志文件完整路径
28 log_file_full_path = "/var/log/app/app.log"
29 # 设置日志文件完整路径
30 log_file_full_path = "/var/log/app/app.log"
31 # 设置日志文件完整路径
32 log_file_full_path = "/var/log/app/app.log"
33 # 设置日志文件完整路径
34 log_file_full_path = "/var/log/app/app.log"
35 # 设置日志文件完整路径
36 log_file_full_path = "/var/log/app/app.log"
37 # 设置日志文件完整路径
38 log_file_full_path = "/var/log/app/app.log"
39 # 设置日志文件完整路径
40 log_file_full_path = "/var/log/app/app.log"
41 # 设置日志文件完整路径
42 log_file_full_path = "/var/log/app/app.log"
43 # 设置日志文件完整路径
44 log_file_full_path = "/var/log/app/app.log"
45 # 设置日志文件完整路径
46 log_file_full_path = "/var/log/app/app.log"
47 # 设置日志文件完整路径
48 log_file_full_path = "/var/log/app/app.log"
49 # 设置日志文件完整路径
50 log_file_full_path = "/var/log/app/app.log"
51 # 设置日志文件完整路径
52 log_file_full_path = "/var/log/app/app.log"
53 # 设置日志文件完整路径
54 log_file_full_path = "/var/log/app/app.log"
55 # 设置日志文件完整路径
56 log_file_full_path = "/var/log/app/app.log"
57 # 设置日志文件完整路径
58 log_file_full_path = "/var/log/app/app.log"
59 # 设置日志文件完整路径
60 log_file_full_path = "/var/log/app/app.log"
61 # 设置日志文件完整路径
62 log_file_full_path = "/var/log/app/app.log"
63 # 设置日志文件完整路径
64 log_file_full_path = "/var/log/app/app.log"
65 # 设置日志文件完整路径
66 log_file_full_path = "/var/log/app/app.log"
67 # 设置日志文件完整路径
68 log_file_full_path = "/var/log/app/app.log"
69 # 设置日志文件完整路径
70 log_file_full_path = "/var/log/app/app.log"
71 # 设置日志文件完整路径
72 log_file_full_path = "/var/log/app/app.log"
73 # 设置日志文件完整路径
74 log_file_full_path = "/var/log/app/app.log"
75 # 设置日志文件完整路径
76 log_file_full_path = "/var/log/app/app.log"
77 # 设置日志文件完整路径
78 log_file_full_path = "/var/log/app/app.log"
79 # 设置日志文件完整路径
80 log_file_full_path = "/var/log/app/app.log"
81 # 设置日志文件完整路径
82 log_file_full_path = "/var/log/app/app.log"
83 # 设置日志文件完整路径
84 log_file_full_path = "/var/log/app/app.log"
85 # 设置日志文件完整路径
86 log_file_full_path = "/var/log/app/app.log"
87 # 设置日志文件完整路径
88 log_file_full_path = "/var/log/app/app.log"
89 # 设置日志文件完整路径
90 log_file_full_path = "/var/log/app/app.log"
91 # 设置日志文件完整路径
92 log_file_full_path = "/var/log/app/app.log"
93 # 设置日志文件完整路径
94 log_file_full_path = "/var/log/app/app.log"
95 # 设置日志文件完整路径
96 log_file_full_path = "/var/log/app/app.log"
97 # 设置日志文件完整路径
98 log_file_full_path = "/var/log/app/app.log"
99 # 设置日志文件完整路径
100 log_file_full_path = "/var/log/app/app.log"

```

1. 在 100 个文件中，找出所有包含 "error" 字符串的文件。
 2. 统计每个文件中 "error" 出现的次数。
 3. 将结果按文件路径排序。

[illegible][illegible]

¹² 參見：陳其南、王瑞雄、
陳其南、王瑞雄、
陳其南、王瑞雄、

File: git_cleaner.sh

```
#!/bin/sh
# git_cleaner.sh
# This script cleans up the git repository by removing untracked files and
# branches that are no longer needed.
```

File: professional_boilerplate.sh

```
#!/bin/sh
# professional_boilerplate.sh
# This script sets up a professional boilerplate for a new project. It
# creates a new directory, initializes a git repository, and sets up the
# necessary files and directories.
```
