

# A structural theorem for local algorithms with applications to coding, testing and privacy

**Marcel Dall'Agnol**

University of Warwick

**Tom Gur**

University of Warwick

**Oded Lachish**

Birkbeck, University of London

HALG 2022

Main result

Techniques

Applications

Main result

Techniques

Applications

An efficient transformation from **local**  
to **sample-based** algorithms.

An efficient transformation from **local**  
to **sample-based** algorithms.

**Local:** inspects a small part of the input string  $x$

**Sample-based:** access by random  $(i, x_i)$  samples

# An efficient transformation from local to sample-based algorithms.

**Local:** inspects a small part of the input string  $x$

**Sample-based:** access by random  $(i, x_i)$  samples

But why?

## Sample-based access buys

- Privacy

## Sample-based access buys

- Privacy
- Efficient repetition: running  $q$ -query  $L_1, \dots, L_t$  on the same input takes
  - $O(qt \log t)$  queries in general
  - $O(q \log t)$  queries by **reusing samples**



Local + robust  
( $O(1)$  queries)

Local + sample-based  
( $o(n)$  queries)

$L$

$\Rightarrow$

$S$

Local + robust  
( $O(1)$  queries)




$L$



Local + sample-based  
( $o(n)$  queries)

$S$

Local + robust  
( $O(1)$  queries)



$L$



Local + sample-based  
( $o(n)$  queries)

$S$

Local + robust  
( $O(1)$  queries)



$L$

$\Rightarrow$

Local + sample-based  
( $o(n)$  queries)

$S$

Local + robust  
( $O(1)$  queries)




$L$

$\Rightarrow$

Local + sample-based  
( $o(n)$  queries)

$S$

Local + robust  
( $O(1)$  queries)



$L$

0/1

$\Rightarrow$

Local + sample-based  
( $o(n)$  queries)

$S$

Local + robust  
( $O(1)$  queries)

Local + sample-based  
( $o(n)$  queries)

$L$


$\Rightarrow$

$S$

Local + robust  
( $O(1)$  queries)

Local + sample-based  
( $o(n)$  queries)

$L$






Local + robust  
( $O(1)$  queries)

Local + sample-based  
( $o(n)$  queries)

$L$




Local + robust  
( $O(1)$  queries)

Local + sample-based  
( $o(n)$  queries)

$L$

$\Rightarrow$




$S$

0/1

# Property tester

Property  $\Pi \subseteq \{0, 1\}^n$ , proximity parameter  $\varepsilon > 0$




Tester  $T$  computes

$$f(x) = \begin{cases} 1, & \text{if } x \in \Pi \\ 0, & \text{if } x \text{ is } \varepsilon\text{-far from } \Pi. \end{cases}$$

# Property tester

Property  $\Pi \subseteq \{0, 1\}^n$ , proximity parameter  $\varepsilon > 0$




Tester  $T$  computes

$$f(x) = \begin{cases} 1, & \text{if } x \in \Pi \\ 0, & \text{if } x \text{ is } \varepsilon\text{-far from } \Pi. \end{cases}$$

# Property tester

Property  $\Pi \subseteq \{0,1\}^n$ , proximity parameter  $\varepsilon > 0$




Tester  $T$  **robustly** computes

$$g(x) = \begin{cases} 1, & \text{if } x \in \Pi \\ 0, & \text{if } x \text{ is } 2\varepsilon\text{-far from } \Pi. \end{cases}$$

# Property tester

Property  $\Pi \subseteq \{0,1\}^n$ , proximity parameter  $\varepsilon > 0$



Tester  $T$  **robustly** computes

$$g(x) = \begin{cases} 1, & \text{if } x \in \Pi \\ 0, & \text{if } x \text{ is } 2\varepsilon\text{-far from } \Pi. \end{cases}$$

## Theorem

*Any function computed by a  $q$ -query robust local algorithm admits a sample-based algorithm with sample complexity*

$$n^{1-\tilde{\Omega}(1/q^2)}.$$

$$(q = \Omega(\sqrt{\log n}) \implies \text{sample complexity } \Omega(n))$$

### Theorem

*Any function computed by a  $q$ -query robust local algorithm admits a sample-based algorithm with sample complexity*

$$n^{1-\tilde{\Omega}(1/q^2)}.$$

$$(q = \Omega(\sqrt{\log n}) \implies \text{sample complexity } \Omega(n))$$

### Theorem

*This transformation cannot achieve sample complexity*


$$n^{1-\omega(1/q)}.$$




Main result

Techniques

Applications







$$x_1 = 1$$

$$x_3 = 0$$


$$x_5 = 0$$




$$Q_T = \left\{ \left\{ \begin{array}{c} 1 \\ 4 \\ 5 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 4 \\ 2 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 3 \\ 5 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 3 \\ 9 \end{array} \right\} \right\}$$




$$Q_T = \left\{ \left\{ \begin{array}{c} 1 \\ 4 \\ 5 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 4 \\ 2 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 3 \\ 5 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 3 \\ 9 \end{array} \right\} \right\}$$



$$Q_T = \left\{ \left\{ \begin{array}{c} 1 \\ 4 \\ 5 \end{array} \right\}, \quad \left\{ \begin{array}{c} 1 \\ 4 \\ 2 \end{array} \right\}, \quad \left\{ \begin{array}{c} 1 \\ 3 \\ 5 \end{array} \right\}, \quad \left\{ \begin{array}{c} 1 \\ 3 \\ 9 \end{array} \right\} \right\}$$




$$Q_T = \left\{ \left\{ \begin{array}{c} 1 \\ 4 \\ 5 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 4 \\ 2 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 3 \\ 5 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 3 \\ 9 \end{array} \right\} \right\}$$



$$Q_T = \left\{ \left\{ \begin{array}{c} 1 \\ 4 \\ 5 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 4 \\ 2 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 3 \\ 5 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 3 \\ 9 \end{array} \right\} \right\}$$






$$Q_T = \left\{ \left\{ \begin{array}{c} 1 \\ 4 \\ 5 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 4 \\ 2 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 3 \\ 5 \end{array} \right\}, \left\{ \begin{array}{c} 1 \\ 3 \\ 9 \end{array} \right\} \right\}$$

$$Q = \bigcup_T Q_T$$


# Daisy partition theorem



An *arbitrary*  $\mathcal{Q}$  ( $|\mathcal{Q}| \approx n$ ) can be partitioned into  $\mathcal{D}_0, \dots, \mathcal{D}_q$ .  
 $\mathcal{D}_i$  has:

- petals of size  $i$
- small kernel  $|K_i|$
- bounded petal intersection

# Daisy partition theorem




An *arbitrary*  $\mathcal{Q}$  ( $|\mathcal{Q}| \approx n$ ) can be partitioned into  $\mathcal{D}_0, \dots, \mathcal{D}_q$ .

$\mathcal{D}_i$  has:

- petals of size  $i$
- small kernel  $|K_i|$
- bounded petal intersection

# Daisy partition theorem




An arbitrary  $\mathcal{Q}$  ( $|\mathcal{Q}| \approx n$ ) can be partitioned into  $\mathcal{D}_0, \dots, \mathcal{D}_q$ .

$\mathcal{D}_i$  has:

- petals of size  $i$
- small kernel  $|K_i|$
- bounded petal intersection

# Daisy partition theorem



An arbitrary  $\mathcal{Q}$  ( $|\mathcal{Q}| \approx n$ ) can be partitioned into  $\mathcal{D}_0, \dots, \mathcal{D}_q$ .

$\mathcal{D}_i$  has:

- petals of size  $i$
- small kernel  $|K_i|$
- bounded petal intersection

Main result

Techniques

Applications

## Relaxed LDC lower bound

Any  $C : \{0, 1\}^k \rightarrow \{0, 1\}^n$  has  $n = k^{1+\tilde{\Omega}(1/q^2)}$ .

## Relaxed LDC lower bound

Any  $C : \{0, 1\}^k \rightarrow \{0, 1\}^n$  has  $n = k^{1+\tilde{\Omega}(1/q^2)}$ .

(Previously  $k^{1+\tilde{\Omega}(1/2^{2q})}$ ; best upper bound is  $k^{1+O(1/q)}$ )



## Relaxed LDC lower bound

Any  $C : \{0, 1\}^k \rightarrow \{0, 1\}^n$  has  $n = k^{1+\tilde{\Omega}(1/q^2)}$ .

(Previously  $k^{1+\tilde{\Omega}(1/2^{2q})}$ ; best upper bound is  $k^{1+O(1/q)}$ )

## Near-optimality of “P $\neq$ NP for testers”

$q$ -query tester with short proof  $\implies n^{1-\tilde{\Omega}(1/q^2)}$ -query tester.

## Relaxed LDC lower bound

Any  $C : \{0, 1\}^k \rightarrow \{0, 1\}^n$  has  $n = k^{1+\tilde{\Omega}(1/q^2)}$ .

(Previously  $k^{1+\tilde{\Omega}(1/2^{2q})}$ ; best upper bound is  $k^{1+O(1/q)}$ )

## Near-optimality of “P $\neq$ NP for testers”

$q$ -query tester with short proof  $\implies n^{1-\tilde{\Omega}(1/q^2)}$ -query tester.

Best separation:  $q$  vs.  $n^{1-O(1/q)}$  queries with  $O(\log n)$ -long proof

## Relaxed LDC lower bound

Any  $C : \{0, 1\}^k \rightarrow \{0, 1\}^n$  has  $n = k^{1+\tilde{\Omega}(1/q^2)}$ .

(Previously  $k^{1+\tilde{\Omega}(1/2^{2q})}$ ; best upper bound is  $k^{1+O(1/q)}$ )




## Near-optimality of “P $\neq$ NP for testers”

$q$ -query tester with short proof  $\implies n^{1-\tilde{\Omega}(1/q^2)}$ -query tester.

Best separation:  $q$  vs.  $n^{1-O(1/q)}$  queries with  $O(\log n)$ -long proof

## Adaptive-to-sample-based transformation for testers

$q$ -query tester  $\implies n^{1-\tilde{\Omega}(1/q^2)}$ -query sample-based tester.



Thank you!