

INTRODUCTION TO LINUX

MARCEL JAR

CONTENTS

I	INTRODUCTION TO COMMAND LINE INTERFACES	1
1	COMMAND LINE INTERFACE, TERMINAL, AND SHELL	2
1.1	Terminology	3
1.2	Shells	4
	Exercises	4
2	BASIC SHELL COMMANDS I	5
2.1	Accessing a Terminal Emulator	5
2.2	Terminal Basics	5
2.3	date	6
2.4	whoami	6
2.5	pwd	7
2.6	ls	7
2.7	cd	8
2.8	Relative and Absolute Paths	9
2.8.1	Relative Path	10
2.8.2	Absolute Path	10
2.9	clear	11
2.10	Command History	11
	Exercises	11
3	BASIC SHELL COMMANDS II	13
3.1	mkdir	13
3.2	rmdir	14
3.3	touch	14
3.4	rm	15
3.5	mv	16
3.5.1	Moving files and folders accross directories . .	16
3.5.2	Renaming files and folders	17
3.6	cp	17
3.6.1	Copying files within the working directory . .	18
3.6.2	Copying files to other directories	18
	Exercises	19
4	GETTING HELP	21
4.1	help	21
4.2	man	22
4.2.1	Sections	23
4.3	whatis	24
4.4	apropos	24
4.5	info	24
	Exercises	25
5	READING AND EDITING TEXT FILES FROM THE SHELL	28
5.1	Reading text files	28

5.1.1	more	28
5.1.2	Less	29
5.2	Editing Text Files	31
5.2.1	nano	31
5.2.2	vi and vim	32
	Exercises	37

LIST OF FIGURES

Figure 1.1	Notepad application for Windows 7.	2
Figure 2.1	Directory tree.	9
Figure 2.2	Directory tree for questions 9, 10, and 11. . . .	12
Figure 3.1	Directory tree for questions.	20
Figure 5.1	Vi operational modes and the keys required to change modes.	34

LIST OF TABLES

Table 1.1	Linux Shells	4
Table 2.1	Long list information for the seneca.pdf file. .	8
Table 4.1	Manual Page Sections	23
Table 4.2	Shortcuts to navigate info pages	25
Table 5.1	Less navigation keys.	30
Table 5.2	Information displayed in vim	33
Table 5.3	Keys to switch to insert mode.	34
Table 5.4	List of some command mode important com- mands.	35
Table 5.5	List of some extended mode important com- mands.	36

LISTINGS

Listing 4.1	Manual page for the mkdir command.	27
Listing 5.1	less user interface.	30
Listing 5.2	Nano's user interface.	31
Listing 5.3	vim 's user interface.	33

ACRONYMS

CLI	Command Line Interface
GUI	Graphical User Interface
UI	User Interface
OS	Operating System

Part I

INTRODUCTION TO COMMAND LINE INTERFACES

In the following chapters, we introduce the concept of command line interfaces, and explain how they can be accessed, as well as their relationship with the **shell**. Following, we present some basic **shell** commands together with methods to get help about these commands. Finally, we end this part by introducing a series of tools that can be used to read and edit text files using a command line interface.

COMMAND LINE INTERFACE, TERMINAL, AND SHELL

Most User Interfaces (UI) rely on visual cues to guide the user. For example, on Microsoft Windows, the user can use the mouse (or the finger in a touchscreen device) to click on an icon representing a folder to see its contents. Another example would be that, by clicking on a x symbol at the top right edge* of an application, the application is closed. As yet another example, drop-down menus with items such as File, Edit, and About, are commonplace, as seen in Figure 1.1.

**In Apple and Linux systems, this symbol might be on the top left edge.*




Figure 1.1: Notepad application for Windows 7.

A UI that relies of visual cues, as the ones described above, is called a Graphical User Interface (GUI). The invention of such interfaces played a major role in the popularization of computers in the 80s. This is due to the fact that most users are more comfortable using such interfaces, as opposed to Command Line Interfaces (CLI) that have been around since the late 60s.

In a CLI, as opposed to an intuitive graphical interface, the user is presented with a **shell*** prompt in which it can write commands to be interpreted by the **shell**. You can see an example below of a CLI in which a user entered the command **ls** to list all files and folders in the working directory*.

```
marcel@dell:~$ ls
Documents      Downloads      Pictures
Music          Video         seneca.pdf
marcel@dell:~$
```

**Shells are explained in Sections 1.1 and 1.2.*

In this book, the words **folder and **directory** are used interchangeably.*

In order to properly use a **CLI**, the user needs to learn a series of commands that the shell understands, as well as the syntax of these commands. Hence, it should come to no surprise that most regular users prefer to use **GUIs** which do not incur in such steep learning curves.

If you are reading this book, however, I expect you not to be a regular user. In fact, I expect you to be starting a career as systems analyst, a software developer, or other positions in the IT industry. For people like you, having a clear understanding of how to use a **CLI** presents a number of advantages:

- There are tasks that can only be achieved by using a **CLI** because no **GUI** has been created to perform them.
- Some tasks can be performed, using a **CLI**, in a fraction of the time it would take using a **GUI** tool.
- **CLIs** can be accessed remotely in a fast and straightforward fashion, allowing you to control multiple systems from a single computer
- Users can quickly create scripts that run on **CLIs** to automate repetitive tasks such as: adding new users to the system, backing up data, updating the system, etc.
- The steps required to perform some actions using **GUIs** can vary a lot depending on which **OS**, or Linux distribution, you are using. On the other hand, they are normally identical using a **CLI**. In fact, the same commands* can be used in all Linux distributions, Apple computers, and since 2016, even in Windows systems.

**With a few notable exceptions.*

Most Linux distributions have a **GUI** that allow regular users to achieve daily tasks such as web browsing, email, or writing documents. However, all Linux distributions also come with a terminal emulator that allow super users to do much more using a **CLI**.

1.1 TERMINOLOGY

Before moving forward to learn how to use a Linux **CLI**, It is important to notice the difference between three concepts that are often used interchangeably:

CLI The **CLI** is just the technical name of the method by which we interact with a computer by means of written instructions.

TERMINAL All major Linux distributions have a **GUI**. However, they normally also provide you with a terminal, or more precisely a terminal emulator. A terminal emulator is nothing else than a program that provides us with a **CLI** to interact with the **shell**.

SHELL The **shell** is a software that reads keyboard commands and passes them to the **OS** to carry out. Such commands could be used to perform simple tasks like listing the files in a particular folder, adding users to the system, creating folders, or complex tasks such as upgrading the **OS**, installing applications, etc.

1.2 SHELLS

As mentioned before, a **shell** is a software that interprets commands passed by the user, and passes them to the **OS**. However, just like there are multiple languages such as English, Spanish, or Mandarin, there are multiple shells available. Table 1.1 below presents a description of a few such shells*.

**Many other shells exist, such as dash, ksh, etc.*

sh	The Bourne shell, which has been distributed as the default shell for Unix since 1979.
bash	Bourne Again Shell, an upgraded version of sh , written by the GNU Project, which has become the <i>de facto</i> standard Linux shell.
csh or tcsh	A Unix shell using a syntax similar to the C programming language. tcsh is identical to csh , with the addition of some extra features such as command-line completion.

Table 1.1: Linux Shells

In this book, we will cover exclusively the **bash shell**. This is due to the fact that **bash** is the default shell for the most widely used Linux distributions. In fact, it is hard to find a Linux distribution that does not come with a **bash shell**. That said, after learning how to use one shell, it is much easier to learn other shells, as they share many concepts and syntax.

EXERCISES

1. Explain, with your own words, what is a Command Line Interface (**CLI**).
2. Explain, with your own words, what is a Graphical User Interface (**GUI**).
3. What is the relationship between a terminal emulator, and a shell?
4. Which commands are used to list all files in the working directory using the following shells: sh, bash, csh, dash, and ksh?

BASIC SHELL COMMANDS I

In this chapter we will cover how to get access to a terminal emulator, as well as some very basic **bash** commands.

2.1 ACCESSING A TERMINAL EMULATOR

Once a user logs into a Linux OS with a GUI, there are multiple ways to get access to a **terminal emulator**. Some methods work only on a specific distribution, whereas some methods work on most distributions. In what follows, a list of methods to access terminal emulators are presented for some of the most popular desktop environments*. The most common Linux distribution for each desktop environment is presented in the margin notes.

**Desktop environments are covered in Appendix XXX.*

GNOME3 Press the super (windows) button to call the list of applications, and then type **terminal** in the search field, or search for the terminal in the provided applications list.

Debian, Red Hat, Fedora, CentOS, Kali

KDE Click on the start button at the lower left, and then click on accessories, and finally on **terminal**.

OpenSUSE, Kubuntu, Slackware

UNITY Press the super (windows) button to call the dash (or conversely click on the dash button at the upper left), and then type **terminal**.

Ubuntu

In all of these desktop environments, the terminal emulator can also be started by pressing **ctrl+alt+T**.

2.2 TERMINAL BASICS

Once the terminal emulator starts, the user is presented with an application displaying a blinking cursor at a **shell prompt**, just like shown below.

```
marcel@dell:~$
```

This prompt contains important information about the current parameters of the shell, namely: the username (**marcel**), system name (**dell**), and working directory (represented by a tilde [~]).*. A brief description of these parameters follows:

**The \$ separates command prompts from these current parameters.*

USERNAME Linux systems, as any Unix-like system, was designed to allow multiple users to access the system. When a terminal emulator starts, it assumes the user to be the same one that logged

in into the GUI system. in Chapter XX, we will show how the **su** command can be used to switch users. In the example above, the username is **marcel**.

SYSTEM NAME During the installation of Linux systems, users are required to give your system (local machine) a name. When a terminal emulator starts, it assumes that you are using the local machine. In chapter XXX we will see how to log into remote machines using the **ssh** command. In the example above, my local machine is called is **dell**.

WORKING DIRECTORY Imagine that you issue a command to create a file. In which directory will this file be created? The answer is: in the current **working directory**. When a terminal emulator starts, it assumes by default that you are at the home folder (directory) of the user currently logged in. Hence, whichever actions you perform will, by default, affect this directory. In Section 2.7, we will show how to use the **cd** command to change directories. In the example above, this home folder, which is located at **/home/marcel** is represented by a tilde (~).

In what follows, a number of basic **bash*** commands are presented.

2.3 **date**

To ask what day is today, you can type **date** in the terminal emulator and press enter. The shell will verify the date with the **OS**, display it in the terminal, and start a new prompt line ready to receive more commands, as shown below*. Note that the terminal also shows the current time and the time zone (Eastern Daylight Time - EDT).

```
marcel@dell:~$ date
Wed May 18 19:20:55 EDT 2016
marcel@dell:~$
```

Note that shell commands are **case-sensitive**. I.e., the shell differentiates between upper-case and lower-case letters. For example, while **date** is a valid command, **Date** and **DATE** are not.

2.4 **whoami**

Not all terminal emulators display the username at each command prompt. Therefore, the shell needs to provide a method to verify the username of the current user. This is accomplished by the **whoami** (who am I) command, as shown below.

```
marcel@dell:~$ whoami
marcel
```

You can easily switch shells by typing the name of the shell you want to switch to. For example, you can type **dash to start using a **dash shell**.*

**For the following commands, we will omit this new prompt line.*

2.5 pwd

As mentioned before, when a terminal emulator is open, it needs a directory to act as a starting point. In most Linux system, this starting point is the user's home folder, located at `/home/username`, represented by a tilde (`~`).

As we will show later, users can move to different directories using the shell. The shell's current location is called **working directory**. This is due to the fact that this is the directory that the shell will, by default, act (work) upon. In order to see in which directory you are currently at, you can type **pwd*** in the terminal emulator and press enter. The shell will then print the working directory in the terminal, as shown below.

**short for print working directory.*

```
marcel@dell:~$ pwd
/home/marcel
```

2.6 ls

To obtain a list of all files and folders present in the working directory, as demonstrated in Chapter 1, you can use the **ls*** command. The shell will then print a list of all files and folders, as shown below*.

**short for list.*

**Some terminal emulators use colours to distinguish between files, folders, scripts, etc.*

```
marcel@dell:~$ ls
Documents      Downloads      Pictures
Music          Video         seneca.pdf
```

The list command, by default, does not show hidden files*. In order to do so, you must add the option **-a** or **-all** to the **ls** command, as shown below:

**Hidden files are files whose names starts with a . (dot).*

```
marcel@dell:~$ ls
Documents      Downloads      Pictures
Music          Video         seneca.pdf
marcel@dell:~$ ls -a
.              ..            Documents
Downloads      Pictures      Music
Video          seneca.pdf    .System.conf
```

Note that in the command above, the file **.System.conf** only appears when the **ls** command is issued with the **-a** option. Also, note that two extra directories appear: a folder (**.**) and a folder (**..**). These are not real directories. They are simply hard links to the self (**.**) and parent (**..**) directories.

The list command can also be used to gather information about the files and folders in the current working directory. To do so, the **long list** option **-l** must be invoked, as shown below:

```
marcel@dell:~$ ls -a -l
drwxrwxr-x  3 marcel marcel  4096 Jun 21 23:06 .
```

```

drwxr-xr-x 54 marcel marcel 4096 Jun 21 18:59 ..
drwxrwxr-x 2 marcel marcel 4096 Jun 21 23:06 Documents
drwxrwxr-x 2 marcel marcel 4096 Jun 21 23:06 Downloads
drwxrwxr-x 2 marcel marcel 4096 Jun 21 23:06 Pictures
drwxrwxr-x 2 marcel marcel 4096 Jun 21 23:06 Music
drwxrwxr-x 2 marcel marcel 4096 Jun 21 23:06 Video
-rw-rw-r-- 1 marcel marcel 12238 Jun 29 22:54 seneca.pdf
-rw-rw-r-- 1 marcel marcel 126 Jun 28 20:52 .System.conf

```

This long list provides a number of columns containing information about each file. In Table 2.1, we explain what the information in each column represents using the file **seneca.pdf** as an example.

column	example	meaning
1	-rw-rw-r--	File type and permission sets. These topics are covered in Chapter XX.
2	1	Number of hard links to this file. Links are covered in Chapter XX.
3	marcel	Name of the user owner of the file. The concepts of users and ownership are covered in Chapter XX.
4	marcel	Name of the group owner of the file. The concepts of groups and ownership are covered in Chapter XX.
5	12238	Size of the file in bytes.
6	Jun 29 22:54	Timestamp indicating when the file was edited for the last time.
7	seneca.pdf	File name.

Table 2.1: Long list information for the **seneca.pdf** file.

2.7 cd

To switch working directories, you need only to use the **cd*** command, followed by the name of the directory you want to go. For example, assuming that the folders shown in the previous command's output do exist, typing **cd Documents** results in:

**short for change directory.*

```

marcel@dell:~$ pwd
/home/marcel
marcel@dell:~$ cd Documents
marcel@dell:Documents$ pwd
/home/marcel/Documents

```

The command **cd** by itself always sends the user back to the user's home folder. Also, the command **cd ..** sends the user to the parent

folder of the working directory, and the command **cd -** sends the user back to the previous working directory. The parent folder is the folder hierarchically above the current folder. For example, the folder **/home/marcel** is the parent folder of **/home/marcel/Documents**.

Finally, note that if you enter the name of a directory that does not exist, the shell will return an error message and then it will start a new prompt line ready to receive more commands, as shown next.

```
marcel@dell:~$ cd DOCUMENTS
bash: cd: DOCUMENTS: No such file or directory
marcel@dell:~$
```

2.8 RELATIVE AND ABSOLUTE PATHS

In our previous example using the **cd** command, we switched working directories from one folder, **/home/marcel**, to one of its immediate subfolders, **/home/marcel/Documents**. However, you might face more complex situations in which you have a directory tree as shown in Figure 2.1, and you want to switch the current working directory from any folder directly to any other folder.




Figure 2.1: Directory tree.

For example, given the directory tree shown in Figure 2.1, how can we directly switch working directories for the following cases:

- from **/home** directly to **/home/marcel/Personal**
- from **/home/marcel/Seneca** directly to **/media**

- from **/home/marcel/Seneca** to **/media/Seneca**

The solution to all these cases is: “by providing either a **relative path** or an **absolute path** to the desired folders.” In what follows, we define these two concepts*.

**Note that the concepts of relative and absolute paths also apply to files.*

2.8.1 Relative Path

When a relative path is provided, the shell assumes that the starting point of the path is the current working directory. For example, given that you are currently in **/home**, you can switch your working directory to **/home/marcel/Personal** by issuing the command: **cd marcel/Personal**, as shown in what follows.

```
marcel@dell:home$ pwd
/home
marcel@dell:home$ cd marcel/Personal
marcel@dell:Personal$ pwd
/home/marcel/Personal
```

2.8.2 Absolute Path

Absolute paths always start with **/** and provide the complete path for the desired folder or file. For example, given that your working directory is **/home/marcel/Seneca**, you can switch to **/media** by issuing the command: **cd /media**, or you can switch to **/media/Seneca** by issuing the command: **cd /media/Seneca**, as shown in what follows.

**/ denotes the root, of all directories in a Linux system.*

```
marcel@dell:Seneca$ pwd
/home/marcel/Seneca
marcel@dell:Seneca$ cd /media
marcel@dell:media$ pwd
/media
```

```
marcel@dell:Seneca$ pwd
/home/marcel/Seneca
marcel@dell:Seneca$ cd /media/Seneca
marcel@dell:Seneca$ pwd
/media/Seneca
```

Relative and absolute paths can be compared to addresses in navigation systems. For example, if you live in Toronto, and you want to go to a place within the city, you can type on your navigation device an address such as 200 King Street. The device will assume that this address is in Toronto-ON, Canada. This would be compared to a relative address, as the starting point is assumed to be the city of Toronto. However, if you are in Toronto and you want to go to 200 King Street in Buffalo-NY, you would need to enter the complete address, including the city, state, and sometimes even the country. This

would be compared to an absolute value, as the address is completely defined.

2.9 **clear**

All commands you enter, as well as their outputs, stay in the screen and you are given a new shell prompt at the bottom to keep working with the shell. This can lead to a very polluted screen containing a lot of information that is no longer necessary.

In order to clear the screen from all previous commands and outputs, you simply have to issue the **clear** command. This command will erase from your terminal all information in it and provide you with a command prompt at the top to keep working with the shell.

It is important to note that this command simply clears the terminal display. Any variables* that have been defined, or any modifications to the state of the shell will not be changed by this command.

**Variables are covered in Chapter XXX.*

2.10 COMMAND HISTORY

You can use the up (↑) and down (↓) arrow keys in order to navigate the commands you have previously entered in your shell. For example, by hitting the up arrow key once, you will get the previously entered command. Hitting the up arrow again, will get you the command you entered prior to that one.

EXERCISES

1. Describe two methods to open a terminal emulator on a Ubuntu Linux OS.
2. Given the command prompt below, who is the user currently logged into the shell? Also, what is the name of the local machine? Finally, what is the current working directory?

```
john@lenovo:~$
```

3. What is the relationship between a **terminal emulator**, and a **shell**?
4. Which commands are used to list all files in the working directory using the following shells: bash, csh, dash, and ksh?
5. Which command can be used to show in the terminal what time is it?
6. What is the output of the **ls -l** command? What does the 6th column represents?

7. How can you move back to the latest previously accessed working directory using only one shell command?
8. What happens when you apply the parent folder parameter to the `cd` command twice. In other words, what happens when you issue a `cd ../../` command? Given the directory tree shown in Figure 2.2, answer the following questions:




Figure 2.2: Directory tree for questions 9, 10, and 11.

9. Write a command to switch your working directory from **marcel** to **Seneca** using only one shell command?
10. Write a command to switch your working directory from **media** to **marcel** using only one shell command.
11. Given that your working directory is **media**, can you use a relative path to move to **Seneca**? If yes, can you also use an absolute path? Which one of these options seem more appropriate in this case?

BASIC SHELL COMMANDS II

In our previous chapter, we covered a number of bash commands which could be used to: gather information from the system and user (**date**, **whoami**, **pwd**), get information about files and folders (**ls**), or to change the current working directory (**cd**).

None of the commands could be used to alter files, folders, or change the configurations of the system, though. I.e., they have no lasting effect in the system.

In this chapter, we will cover a series of commands that have lasting effects in files, folders, and possibly the system. The commands we are covering in this chapter can be used to create and remove files and folders, as well as to rename and make copies of them.

3.1 **mkdir**

To create new folders, the **mkdir*** command can be used, followed by the name(s) of the folder(s) to be created. In the example below, a folder called **Samples** is created in the current working directory.

**short for make directory.*

```
marcel@dell:~$ ls
Documents      Downloads      Pictures
Music          Video          seneca.pdf
marcel@dell:~$ mkdir Samples
marcel@dell:~$ ls
Documents      Downloads      Pictures      Samples
Music          Video          seneca.pdf
```

Note that, by default, the new directory is created as a subfolder of the working directory. To create folders in other locations, without leaving the current working directory, you can use the **mkdir** command combined with relative or absolute paths, as shown below:

```
marcel@dell:~$ ls Documents
Seneca      Personal
marcel@dell:~$ mkdir ~/Documents/Samples
marcel@dell:~$ ls Documents
Seneca      Personal      Samples
```

Files and Folders with spaces in their names

In all examples that were given so far in this book, all files and folders do not contain spaces in their names. Issuing a command such as **mkdir My Documents** would create two folders,

one called **My** and another called **Documents**. This is because the shell cannot distinguish between an argument with a space, or two arguments without spaces.

Linux can handle files and folder with spaces, though. In order to do so, whenever you are referring to a file or folder with spaces in its name, each space needs to be preceded by a backslash (\). For example, you can create a folder called **My Documents** by issuing a command `mkdir My\Documents`.

3.2 `rmdir`

The `rmdir`* command, as the name suggests, deletes existing folders. For example, `rmdir Samples` will remove a folder **Samples** from the current working directory. It is important to note that it can only be used to remove empty folders. In case the folder is not empty, the shell returns an error message.

**short for remove directory.*

In the example below, the `rmdir` command is applied to both an empty folder **Samples**, and to a non-empty folder **Pictures**.

```
marcel@dell:~$ ls
Documents      Downloads      Pictures      Samples
Music          Video          seneca.pdf
marcel@dell:~$ rmdir Samples
marcel@dell:~$ ls
Documents      Downloads      Pictures      Music
Video          seneca.pdf
marcel@dell:~$ rmdir Pictures
rmdir: failed to remove 'Pictures': Directory not empty
marcel@dell:~$
```

3.3 `touch`

As shown in Section 2.6, files and folders in Linux have a timestamp indicating when they were edited for the last time. The `touch` command, when applied to an existing file, updates the timestamp of when it was last edited*. It is equivalent to opening the file, saving it, and then closing it. As an example, see the command prompt below:

**Updated timestamps are useful for some backup programs, among other uses.*

```
marcel@dell:~$ ls -l
total 0
-rw-rw-r-- 1 marcel marcel 0 Jul 12 11:31 final_exam.doc
-rw-rw-r-- 1 marcel marcel 0 Jun 21 20:30 introduction.ppt
-rw-rw-r-- 1 marcel marcel 0 May 10 21:41 seneca.pdf
marcel@dell:~$ touch final_exam.doc
marcel@dell:~$ ls -l
```

```
total 0
-rw-rw-r-- 1 marcel marcel 0 Jul 14 22:12 final_exam.doc
-rw-rw-r-- 1 marcel marcel 0 Jun 21 20:30 introduction.ppt
-rw-rw-r-- 1 marcel marcel 0 May 10 21:41 seneca.pdf
```

When applied to non-existing files, the **touch** command creates empty files, as shown below:

```
marcel@dell:~$ ls -l
total 0
-rw-rw-r-- 1 marcel marcel 0 Jul 14 22:12 final_exam.doc
-rw-rw-r-- 1 marcel marcel 0 Jun 21 20:30 introduction.ppt
-rw-rw-r-- 1 marcel marcel 0 May 10 21:41 seneca.pdf
marcel@dell:~$ touch mid_term.doc
marcel@dell:~$ ls -l
total 0
-rw-rw-r-- 1 marcel marcel 0 Jul 14 22:12 final_exam.doc
-rw-rw-r-- 1 marcel marcel 0 Jun 21 20:30 introduction.ppt
-rw-rw-r-- 1 marcel marcel 0 May 10 21:41 seneca.pdf
-rw-rw-r-- 1 marcel marcel 0 Jul 14 22:15 mid_term.doc
```

This second usage of the **touch** command is frequently used for testing purposes*.

tip: you to use **touch and **mkdir** in order to recreate the examples provided in this chapter..*

**short for remove.*

3.4 rm

To delete (remove) files, the **rm*** command can be used, followed by the name(s) of file(s) to be deleted from the working directory. See the example below:

```
marcel@dell:~$ ls
Documents      Downloads      Pictures
Music          Video         seneca.pdf
marcel@dell:~$ rm seneca.pdf
marcel@dell:~$ ls
Documents      Downloads      Pictures
Music          Video
```

The **rm** command can also be used to remove non-empty folders. To do so, we have to apply the **-r** (recursive) option followed by the name of the folder, as shown below.

```
marcel@dell:~$ ls
Documents      Downloads      Pictures
Music          Video         seneca.pdf
marcel@dell:~$ rm -r Pictures
marcel@dell:~$ ls
Documents      Downloads      Music
Video          seneca.pdf
```

Bash Design Goals

It is important to note that the commands described in this chapter don't normally ask for confirmation. For example, when deleting a file using the **rm** command, the **shell** will not ask the user if he/she is sure he/she wants to delete the file. Nor the file will be sent to a recycle bin from which it can be recovered. The file will simply be deleted.

The **shell** performs tasks that might incur in unforeseen consequences, such as accidentally deleting a number of files, in a much more direct way because of its design goals. As opposed to **GUI** interfaces where the goal normally is to provide a platform for inexperienced users to perform basic tasks, a **CLI** is normally designed with the goal of allowing experienced users to quickly perform complex tasks.

3.5 mv

The **mv*** command can be used in two distinct ways. As the name suggests, it can move a file, a folder, or a number of files and folders from one directory to another. However, it can also be used to rename single files or folders. Both uses of this command are described in what follows.

*short for move.

3.5.1 Moving files and folders accross directories

To move a single file from one directory to another, the **mv** command needs two arguments. The first being the name of the file in the working directory to be moved, and the second being the absolute or relative path of the directory we are moving the file to. See the example below:

```
marcel@dell:~$ ls
final_exam.doc  introduction.ppt  seneca.pdf
Folder
marcel@dell:~$ mv final_exam.doc Folder
marcel@dell:~$ ls
introduction.ppt  seneca.pdf  Folder
marcel@dell:~$ ls Folder
final_exam.doc
marcel@dell:~$
```

Note that, in this example, the file **final_exam.doc** disappears from the working directory and appears in the **Folder** directory.

Multiple files can be moved with a single **mv** command. To do so, you first need to provide the names of all files you intend to move as

arguments. Then, you need to provide the relative or absolute path of the directory you want to move them to as the very last argument. This technique is shown in what follows:

```
marcel@dell:~$ ls
final_exam.doc  introduction.ppt  seneca.pdf
Folder
marcel@dell:~$ mv final_exam.doc introduction.ppt Folder
marcel@dell:~$ ls
seneca.pdf  Folder
marcel@dell:~$ ls Folder
final_exam.doc  introduction.ppt
marcel@dell:~$
```

Note that, within this context, this command can also be applied to folders (directories). I.e., you can move an entire folder in your working directory into other folders using the exactly same syntax applied for files in this section.

3.5.2 Renaming files and folders

Imagine the **mv** command being used with two arguments, the first being a file name in the working directory, and the second being a name that doesn't match any directories. In this scenario, the **mv** command will rename the file indicated by the first argument to the name specified in the second*. See the example below:

```
marcel@dell:~$ ls
final_exam.doc  introduction.ppt  seneca.pdf
Folder
marcel@dell:~$ mv final_exam.doc final_exam_fall.doc
marcel@dell:~$ ls
final_exam_fall.doc  introduction.ppt  seneca.pdf
Folder
marcel@dell:~$
```

A command called **rename exists in **bash**. However, it is used to rename multiple files at once using regular expressions. Regular expressions are covered in Chapter XXX.*

In this example, you can see that the file **final_exam.doc** was renamed to **final_exam_fall.doc**.

You can also rename a folder using the same syntax applied for files in this section.

3.6 cp

The **cp*** command can be used to copy files and folders. It can be used in two distinct ways:

**short for copy.*

3.6.1 Copying files within the working directory

To create a copy of a file in the same working directory, the **cp** command should be used with two arguments. The first argument should be the name of the file to be copied, while the second argument should be the name of the copy, as shown below:

```
marcel@dell:~$ ls
final_exam.doc  introduction.ppt  seneca.pdf
Folder
marcel@dell:~$ cp final_exam.doc final_exam_fall.doc
marcel@dell:~$ ls
final_exam.doc  final_exam_fall.doc  introduction.ppt
seneca.pdf  Folder
marcel@dell:~$
```

To copy an entire folder in your working directory into another folder also in the working directory, you must use the recursive option **-r**, as shown in the example below:

```
marcel@dell:~$ ls
final_exam.doc  introduction.ppt  seneca.pdf
Folder
marcel@dell:~$ cp -r Folder Folder_Copy
marcel@dell:~$ ls
final_exam.doc  final_exam_fall.doc  introduction.ppt
seneca.pdf  Folder  Folder_Copy
marcel@dell:~$
```

3.6.2 Copying files to other directories

To create a copy of a file in the working directory to another directory, the second argument of the **cp** command must be the absolute or relative path of the directory in which you want to place a copy of the file. In this case, the new file will have the same name as the original file. See the example below:

```
marcel@dell:~$ ls
final_exam.doc  introduction.ppt  seneca.pdf
Folder
marcel@dell:~$ cp final_exam.doc Folder
marcel@dell:~$ ls
final_exam.doc  introduction.ppt  seneca.pdf
Folder
marcel@dell:~$ ls Folder
marcel@dell:~$ ls
final_exam.doc
marcel@dell:~$
```

Just as with the previous scenario, to copy an entire folder in the working directory to another directory, you also must use the recursive option **-r**. See the example below:

```
marcel@dell:~$ ls
final_exam.doc  introduction.ppt  seneca.pdf
Folder Music
marcel@dell:~$ cp Music Folder
cp: omitting directory 'Music'
marcel@dell:~$ ls Folder
final_exam.doc  introduction.ppt
marcel@dell:~$ cp -r Music Folder
marcel@dell:~$ ls Folder
final_exam.doc  introduction.ppt  Music
marcel@dell:~$
```

To copy all contents of a folder to another folder, but not the folder itself, you need to add **/.** to the end of the name of the folder you are copying, as shown below*:

```
marcel@dell:~$ ls
final_exam.doc  introduction.ppt  seneca.pdf
Folder Music
marcel@dell:~$ cp -r Music/. Folder
marcel@dell:~$ ls Folder
arcade_fire-ready_to_start.mp3  foo_fighters-walk.mp3
marcel@dell:~$
```

You can also use this technique with the **mv command.*

EXERCISES

1. What is the main difference between using the copy **cp**, and the move **mv** commands, when applied to files?
2. How can you delete a non-empty folder called **Archive** that exists in your working directory?
3. Which command can be used to move a file called **README.txt** from your working directory to its parent folder?
4. Which command can be used to create a folder called **Examples** inside a subfolder called **Documentation** that exists in your working directory. See the diagram below.
5. Still with regards to the diagram above, how can you move files **Example1.txt** and **Example2.txt** from the **Documentation** folder to its **Examples** subfolder, without changing your working directory.
6. Is it possible to delete multiple empty folders with only one **rmdir** command? If so, how can you delete two empty folders named **Tests** and **Assignments** from your working directory?




Figure 3.1: Directory tree for questions.

7. What happens when you apply the **touch** command to an existing file? Also, what happens when you apply this command to a non-existing file.
8. How can you make copies of the contents of a file called **exams.txt** from your working directory, to a file called **exams.txt** inside a subfolder **Classes** that exists in your working directory?
9. What happens when the first parameter of a **mv** command is a file, and the second parameter is a folder?
10. Which command can be used to copy the contents of a subfolder named **Folder1**, that exists in the current working directory, to another subfolder named **Folder1Copy** in the same working directory. Note that the subfolder **Folder1Copy** doesn't exist prior to the command you need to enter.

GETTING HELP

We have already covered in previous chapters a number of commands which can take multiple options and different numbers of arguments. For example, it was shown in Chapter 2 that the command **ls** can work in three different ways:

- By itself, this command prints the names of all files in the working directory.
- When provided with the name of another folder as an argument, this command prints the names of all files in the specified folder.
- If called with the option **-l***, this command gives all the information about files described on Table 2.1, as opposed to just listing their names.

There are many more options for the **ls command..*

The bash shell has hundreds of commands like **ls** that can take multiple options and different numbers of arguments. Hence, in order to be accessible to non-experts, it needs to provide its users with a way of knowing how to use those commands.

In this chapter we will cover different ways in which users can get help on how to use different commands.

4.1 help

By itself, the **help** command will list all **built-in*** commands. If one of the built-in commands is provided as an argument, this command provides a quick description of the provided command, and possibly a list of options. You can see below the output of entering **help pwd** on bash.

**Built-in commands are explained in the Built-in Commands box that follows.*

```
marcel@dell:~$ help pwd
pwd: pwd [-LP]
    Print the name of the current working directory.

Options:
    -L  print the value of $PWD if it names the current
        working directory
    -P  print the physical directory, without any symbolic
        links

By default, 'pwd' behaves as if '-L' were specified.
```

Exit Status:

Returns 0 unless an invalid option is given or the current directory cannot be read.

Note that **help** only covers built-in commands. It does not cover commands implemented as binary files in **/bin** or **/usr/bin**, such as **ls**, **rm**, **mv**, and many others.

Built-in Commands

Most commands in bash, such as **ls**, **rm**, and **touch** are implemented by binary files located in the **/bin** and **/usr/bin** folders. These commands are interpreted in the same way as any other application the shell can run. I.e., the shell asks the kernel to execute it, and after it has finished executing, the shell receives its output.

Built-in commands, on the other hand, are an integral part of the shell. They are not implemented in a separated file. The main reason why some commands are implemented directly inside the shell is because they need to change the state of the shell. For example, the **cd** command is a built-in command because it changes the current working directory. Commands implemented as binaries, such as **ls**, **rm**, and **touch**, cannot change the state of the shell.

Another reason for implementing some commands directly into the shell is because it normally enhances their performance.

4.2 **man**

Since the inception of Unix, it has become standard practice for the authors of scripts that implement shell commands to provide manual pages for them. This practice was continued by the GNU project when rewriting Unix as an open source project*.

All manual pages follow the same structure show in Listing 4.1 (page 27). I.e., they have the following sections:

Name States the name and purpose of the command

Synopsis Briefly describes the command syntax

Description Describes the command as well as its options

Authors Lists the authors of the script that implements the command

Reporting Bugs Provides a link to a page where bugs can be reported

Copyright States that the code is provided as free software

In fact, the author of the manual pages for many basic commands such as **ls and **rm** is no one less than Robert Stallman, the programmer that started the GNU project, as discussed in Chapter XXX.*

See Also Provides a list of related commands

To access manual pages, you need only to use the **man** command, followed by the name of the command you are trying to get information about.*. See the example below:

```
marcel@dell:~$ man mkdir
```

**Manual pages cover not only commands, but also daemons and config files.*

4.2.1 Sections

Note that the **mkdir** command appears with a **(1)** next to it at the top of Listing 4.1 (see page 27). This number denotes the section of the manual from where the information was retrieved. Some commands have the same name of **deamons** or **config files**. Hence, dividing manual pages in sections makes it possible for users to access the manual page for the right tool. Manual pages are divided in 9 sections, as shown in Table 4.1.

1	Executable programs or shell commands
2	System calls (functions provided by the kernel)
3	Library calls (functions within program libraries)
4	Special files (usually found in /dev)
5	File formats and conventions e.g. /etc/passwd
6	Games
7	Miscellaneous (including macro packages and conventions), e.g. man(7) , groff(7)
8	System administration commands (usually only for root)
9	Kernel routines [Non standard]

Table 4.1: Manual Page Sections

By default, **man COMMAND** retrieves the first occurrence of **COMMAND** in the manual pages. In order to access later occurrences, you need to provide the section as the first argument followed by the name of the command. For example, **passwd** is both a command, as well as a config file. To access the manual for the **passwd** command, one can write:

```
marcel@dell:~$ man passwd
```

or

```
marcel@dell:~$ man 1 passwd
```

However, to access the **passwd** config page manual, one needs to write:

```
marcel@dell:~$ man 5 passwd
```

4.3 **whatis**

As shown in Listing 4.1, each manual page comes with a description section. The **whatis** command searches the man page of the command provided as an argument and displays its description. See the example below:

```
marcel@dell:~$ whatis ls
ls (1)          - list directory contents
```

If the argument can be found in multiple sections, all descriptions are provided in the output, as shown below:

```
marcel@dell:~$ whatis passwd
passwd (1)      - change user password
passwd (5)      - the password file
```

4.4 **apropos**

In English, the word *apropos* means: *concerning, with reference to*. The **apropos** command is called using keywords as arguments. It returns a single line for each man page that contains one or more of the keyword(s) in its **NAME** section.

This command comes handy when you need to search for commands which names you are not certain of. See the example below*:

```
marcel@dell:~$ apropos rename
dpkg-name (1) - rename Debian packages to full package names
mv (1)        - move (rename) files
rename (1)     - renames multiple files
rename (2)     - change the name or location of a file
renameat (2)  - change the name or location of a file
```

**A few extra outputs from this command were omitted for simplicity.*

In this example you can see that the **mv** command can be used to rename a single file, while the **rename** command is normally only used to rename multiple files at once.

4.5 **info**

Man pages were designed in the early seventies. Hence, they can only display simple text and do not take advantage of newer technologies such as hyperlinks. Also, man pages can be quite terse and seldom provide examples.

In order to modernize the system documentation, the GNU project introduced the concept of info pages. Info pages are similar to man pages in which they provide a description of commands, daemons, and config files. However, they differ in two crucial aspects:

1. Info pages provide a much more in depth description of commands and the options they can take. Multiples examples are often provided.
2. Info pages are divided in nodes that can be accessed via hyperlinks*, **To follow a hyperlink, you need to press enter when you cursor is over a node title.* or with the shortcuts provided in Table 4.2.

q	Quits the info page
n	Moves to the next node
p	Moves back to the previous node
u	Go up to the parent node
h	Display a list of shortcuts to navigate info pages (exit it by pressing x)

Table 4.2: Shortcuts to navigate info pages

The choice between using a man page or an info page depends on the user. Some people prefer the terseness of man pages, while other find that it makes it hard to understand. On the other hand, some people like the level of detail present in info pages, as well as the fact that it contain examples, while others find it difficult to find the information they need among multiple nodes.

As a rule of thumb, you may want to read first the man page for a particular command, and only read its info page in case you could not find the information you needed.

EXERCISES

1. Why there is no help page for the **ls** command in bash?
2. Why there is no man page for the **alias** command in bash?
3. What is a built-in command?
4. Why are some commands implemented as built-ins, as opposed to being implemented as binary files?
5. Why are manual pages divided in sections?
6. Explain in which scenarios you would use the **whatis** command.
7. Explain in which scenarios you would use the **apropos** command.
8. what is the difference between a man page and an info page?

9. How can you use the **ls** command to show all files in the working directory (including hidden files), without also showing the implied **.** and **..** directories? *Hint: check its man or info pages.*
10. How can you use the **rm** command to remove an entire directory called **myFolder** in the working directory, while asking for confirmation before deleting each file inside **myFolder**? *Hint: check its man or info pages.*
11. How can you use the **cp** command to make copies of one file called **myFile** in the working directory, saving it into a folder called **myFolder**, only if there are no files called **myFile** inside **myFolder**, or if the file exists, but is older than the new copy you are trying to create. *Hint: check its man or info pages.*

```

1 MKDIR(1) User Commands MKDIR(1)
2
3 NAME
4     mkdir - make directories
5 SYNOPSIS
6     mkdir [OPTION]... DIRECTORY...
7 DESCRIPTION
8     Create the DIRECTORY(ies), if they do not already
9     exist.
10
11     Mandatory arguments to long options are mandatory
12     for short options too.
13
14     -m, --mode=MODE
15         set file mode (as in chmod), not a=rwx - umask
16     -p, --parents
17         no error if existing, make parent
18         directories as needed
19     -v, --verbose
20         print a message for each created directory
21     -Z      set SELinux security context of each created
22     directory to the default type
23     --context[=CTX]
24         like -Z, or if CTX is specified then set the
25         SELinux or SMACK security context to CTX
26     --help  display this help and exit
27     --version  output version information and exit
28 AUTHOR
29     Written by David MacKenzie.
30 REPORTING BUGS
31     GNU coreutils online help: <http://www.gnu.org/
32     software/coreutils/>
33     Report mkdir translation bugs to <http://
34     translationproject.org/team/>
35 COPYRIGHT
36     Copyright 2014 Free Software Foundation, Inc.
37     License GPLv3+: GNU GPL version 3 or later <http://gnu.
38     org/licenses/gpl.html>.
39     This is free software: you are free to change and
40     redistribute it. There is NO WARRANTY, to the extent
41     permitted by law.
42 SEE ALSO  mkdir(2)
43
44     Full documentation at: <http://www.gnu.org/software
45     /coreutils/mkdir> or available locally via: info '(
46     coreutils) mkdir invocation'
47
48 GNU coreutils 8.23 November 2015 MKDIR(1)

```

Listing 4.1: Manual page for the **mkdir** command.

READING AND EDITING TEXT FILES FROM THE SHELL

In Chapter 2, we learned how to create empty files with `touch`, rename them with `mv`, and even delete them using the `rm` command, among other things. However, so far we have not yet covered how to read the information contained in files, nor how to edit them using the terminal.

In this chapter, we will fill this gap by introducing tools that allow us to read text files (**more**, and **less**), as well as to edit text files (**nano**, **vim**).

5.1 READING TEXT FILES

5.1.1 **more**

To read simple text files on your terminal you can use **more**, by calling it with the name of the file you want to read passed as an argument. See the example below:

```
marcel@dell:~$ more poem
Nature's first green is gold,
Her hardest hue to hold.
Her early leafs a flower;
But only so an hour.
Then leaf subsides to leaf.
So Eden sank to grief,
So dawn goes down to day.
Nothing gold can stay.

marcel@dell:~$
```

This tool will display as much of the file as it fits the terminal screen*. To keep reading the file, you need to press the **Space** key. To quite **more** before reaching the end of the file you can press **q**.

more is quite outdated. Its most glaring limitation is that it doesn't allow you to scroll backwards while reading files. You can only scroll forward. So, while we included it here for historical reasons*, even its man page advises users to use the **less** tool instead.

*In the provided example, all text from the **poem** file was able to fit in the screen.

*some embedded systems still use **more** to take advantage of its small size.

5.1.2 **less**

The **less** command was created with the main goal of providing backwards scrolling to **more***. It has since become the *de facto* tool to read text files on the terminal. For example, all manual pages are displayed using **less**.

This command is quite different than all other commands we have learned on chapters 2 and 3. So far, issuing commands would normally result in the steps below:

1. The user calls a command which might take options and arguments
2. The command that was called processes the user's input
3. All command's outputs are displayed on the terminal
4. A new shell prompt is made available just below the previous command's output

When calling **less**, on the other hand, the following sequence of steps happens:

1. The user calls **less** providing the name of a text file as an argument, as shown in the example below:

```
marcel@dell:~$ less poem
```

2. **less** starts its own user interface, as shown in Listing 5.1, that takes over the entire terminal screen and displays the beginning of the document
3. The user can use a number of keys to navigate the document
4. The user enters a key to quit **less**' interface
5. A new command prompt is made available below the one in which the user called **less***.

By creating its own user interface, **less** can allow the user to perform actions that would either not be possible or very cumbersome otherwise, such as backwards scrolling and some advanced navigation methods. These actions can be performed using the keyboard. The most important keys to control **less** are shown in Table 5.1*.

Terminal User Interfaces

Many other tools create their own terminal user interface like **less**. Notable examples are the two text editors discussed later

**In fact, its name is a pun on the architecture's minimalist design motto "less is more".*

Note that the contents of the file opened in **less do not remain in the terminal screen after the user quits **less**.*

for a comprehensive list, check **less man or **info** pages.*

```

1 Nature's first green is gold,
2 Her hardest hue to hold.
3 Her early leafs a flower;
4 But only so an hour.
5 Then leaf subsides to leaf.
6 So Eden sank to grief,
7 So dawn goes down to day.
8 Nothing gold can stay.
9
10 poem (END)

```

Listing 5.1: less user interface.

ENTER or ↓	Moves forward by one line
Page Up or SPACE	Moves forward by one screen
y or ↑	Moves backward by one line
Page Down or b	Moves backward by one screen
g	Moves to the beginning of the file
G (Shift + g)	Moves to the end of the file
q	Quits less
h	Help

Table 5.1: Less navigation keys.

in this chapter, **nano** and **vim**, as well as the **top** command covered in Chapter XXX.

You can think of these tools the same way you think of applications such as MS Word, or your browser in a **GUI** environment. These tools run on top of your shell, the same way as those applications run on top of your **OS**. The only difference is that they normally take the whole terminal screen, as opposed to opening in a separate window, and normally can only be controlled via keyboard inputs (as opposed to mouse or touchscreen).

When using tools that create their own interface, it is important to understand that they generally do not understand bash commands. I.e., issuing commands such as **mkdir**, or **ls**, inside these tools will most likely result in an error message.

The ability to search for patterns is also a great feature introduced in **less**. To search for a pattern, you need only to type backslash (\) followed by the desired pattern and press **Enter**. For example, by entering **\folder**, you are shown the first occurrence of the word **folder** starting from the top of the current screen. To keep searching

for the next occurrence of the desired pattern, you can type **n**. To go back to a previous occurrence of the desired pattern, you can type **N** (**Shift + n**).

5.2 EDITING TEXT FILES

In this section we will cover two widely used text editors. **nano** for small edits, and **vim** for larger projects and scripts. There is another widely used text editor in the Linux world called **emacs**, with some really die-hard fans, that is not covered in this book. There are two reasons why **vim** was chosen over **emacs**. First, **vim** is available by default in more distributions. Second, the author itself is a **vim** enthusiast.

5.2.1 **nano**

The simplest way to edit a text file on terminal is by using the **nano** command. To do so, you need only to call **nano** followed by the name of the file you are trying to edit*, such as in the example below:

```
marcel@dell:~$ nano poem
```

In this example, a file called **poem** is opened, resulting in the user interface shown below:

**If no file name is provided, nano will open with a new empty file..*

```

1 GNU nano 2.2.6          File: poem
2
3 Nature's first green is gold,
4 Her hardest hue to hold.
5 Her early leafs a flower;
6 But only so an hour.
7 Then leaf subsides to leaf.
8 So Eden sank to grief,
9 So dawn goes down to day.
10 Nothing gold can stay.
11
12 ^G Get He^O WriteOut^R Read Fi^Y Prev Pag^K Cut Te^C Cur Pos
13 ^X Exit  ^J Justify ^W WhereIs^V Next Pag^U UnCut ^T To Spel
```

Listing 5.2: Nano's user interface.

Once a text file is open in **nano**, you can start editing it using the keyboard. To perform actions such as: saving the file, exiting **nano**, or getting help, you simply need to enter the shortcuts presented at the bottom of the interface*. For example, you can exit **nano** by entering **Ctrl + X**, or you can save the file by entering **Ctrl + O**.

**The ^ symbol stands for the Ctrl button.*

5.2.2 **vi** and **vim**

The **vi*** terminal-based text editor was released for Unix systems more than 40 years ago. It has since being ported to multiple systems and OSs, and many text editors are built upon it. **vi** is, together with text editors derived from it, the most widely used text editor for Linux, and can be found in all Unix and Linux distributions.

**short for visual.*

The most famous text editor derived from **vi**, **vim***, augments the capabilities of **vi** by introducing, among other things:

**short for vi improved.*

- Syntax highlighting for multiple programming languages.
- Spell check in more than 50 languages.
- Multilevel undo and redo. I.e., you can undo and redo multiple edits to the text, as opposed to only the last one.
- More user-friendly interface.

Over time, **vim** has become so ubiquitous in the Linux world that currently it is made available by default in most Linux distributions. In fact, this ubiquitousness has reached the point that, in some distributions, the command **vi** actually calls **vim** instead of **vi**.

In this section, we will cover how to perform basic tasks in **vim**. However, all methods described here also apply to **vi**, unless stated otherwise.

vim interface

Opening **vim** to start editing a file is as simple as opening **nano**. You simply need to call **vim** followed by the name of the file you are trying to edit*. See the example below:

```
marcel@dell:~$ vim poem
```

Not that in Listing 5.3, the **vim** user interface indicates empty lines with tildes (~). Also, **vim** provides the user with important information at the bottom of the terminal screen. Table 5.2 presents a list of all information that is displayed, as well as the corresponding values displayed in Listing 5.3.

If no file name is provided, **vim displays a splash screen with some help information. When you start inserting text, **vim** creates a new file.*

vim modes

Working with **vim** requires understanding its three modes of operation: **command mode**, **insert mode**, and **extended mode**. These modes are described below:

COMMAND MODE In this mode, which is also known as **normal mode**, you can use combinations of keys to enter commands. Commands can be used to copy and paste, delete blocks of text, or undo previous actions, among other things.

```

1 Nature's first green is gold,
2 Her hardest hue to hold.
3 Her early leafs a flower;
4 But only so an hour.
5 Then leaf subsides to leaf.
6 So Eden sank to grief,
7 So dawn goes down to day.
8 Nothing gold can stay.
9 ~
10 ~
11 ~
12 "poem" 9L, 210C                1,1                All

```

Listing 5.3: **vim**'s user interface.

File name	"poem"
Number of lines	9L
Number of characters	210C
Cursor position	1,1 (first line, first column)
Position of the screen	Indicates if you are at the Top , Bottom , or which percentage of text has already been read. In the example, All text is displayed.

Table 5.2: Information displayed in **vim**.

INSERT MODE In this mode you can type new text. Note that this is not the mode you need to be to copy or paste blocks of text.

EXTENDED MODE This mode, which is also known as **last-line mode***, can be used to save the current file, open more files, turn the spell check on and off, and quit **vim**, among other uses.

*The name *extended mode* is due to the fact that it was based on a previous text editor called **ex**.

Each time you start **vim**, it is in **command mode**. To switch to **insert mode**, you can press any of the following keys: **a**, **A**, **i**, **I**, **o**, or **O**. Each key results in starting the **insert mode** at a different position with regards to where the cursor is, as shown in Table 5.3. To switch back from **insert mode** to **command mode**, you need to press **Esc**.

To switch from **command mode** to **extended mode**, you need to press the colon key (:). To switch back, from the **extended mode** to the **command mode**, you need to press **Enter**. In Figure 5.1, you can see how to transition from different modes. Note that it is not possible to switch from **insert mode** to **extended mode**, or vice versa, directly.

- | | |
|---|--|
| i | Starts insert mode at the cursor |
| I | Starts insert mode at the beginning of the line the cursor is |
| a | Starts insert mode after the cursor |
| A | Starts insert mode at the end of the line the cursor is |
| o | Opens a new line below the cursor and starts insert mode on it |
| O | Opens a new line above the cursor and starts insert mode on it |

Table 5.3: Keys to switch to insert mode.




Figure 5.1: Vi operational modes and the keys required to change modes.

Command mode

In **command mode**, **vim** allows the user to perform a multitude of different operations in a fast and direct way by pressing different keys. In fact, **vim** is so powerful that many experienced programers prefer to use it even when editors with sophisticated GUIs are available.

Some commands are quite intuitive such as the arrow keys moving the cursor around character by character, or the **Page Up** and **Page Down** keys scrolling the text by one screen at a time. However, some commands can be a bit cryptic, such as **y*** standing for copy. Moreover, some commands require a sequence of keys to be pressed in an specific order to attain the desired outcomes.

In order to help new users to get familiar with **vim**, Table 5.4 presents some of the most used commands for **vim**^{*}. For a comprehensive list of **vim** commands, you can refer to its **man** page.

^{*}It is actually short for yank.

^{*}This table is introduced here to be used as a reference, not to simply be memorized..

Extended Mode

The **extended mode** is mostly used for file operations, such as saving files, opening files, etc. It is also used, however, to configure the behaviour of **vim**. For example, it is in **extended mode** that you can turn spell check on and off. Finally, the **extended mode** is also used to quit **vim**.

On Table 5.5, we show some of the most important operations that can be performed in extended mode. Remember that you need to type colon (:), while in command mode, to reach the extended mode.

u	Undo the latest command. Note that all edits performed each time you enter the insert mode are considered as just one command.
Ctrl+R	Redo changes that were undone using the u command.
dd	Deletes the line the cursor is on. Note that the line is saved on a clipboard which can be later pasted using the p command.
#dd	Where # stands for a number, deletes # lines starting at the one where the cursor is on and saves them on the clipboard.
yy	Copies (yanks) the line the cursor is on to the clipboard.
#yy	Where # stands for a number, copies (yanks) # lines starting at the one where the cursor is on to the clipboard.
v	Turns on visual mode that allows you to specify, using the arrow keys, which part of the text you want to act upon with other commands. For example, you can use v to select a few paragraphs, and then delete them all by pressing d .
p	Pastes the contents of the clipboard after the position the cursor is on.
P	Pastes the contents of the clipboard before the position the cursor is on.

Table 5.4: List of some **command mode** important commands.

:q	Quits vim . If any open files have non-saved edits, an error message is displayed.
:w	Saves the file under its current name. If the file hasn't been given a name yet, an error message appears.
:w file_name	Saves the file as <code>file_name</code> . If <code>file_name</code> is the same names as the currently open file, the file is overwritten
:e file_name	opens a new file, while placing the current file in a buffer. Having multiple files open when the same time can be very convenient. Specially when you need to copy parts of one file, and paste it into another.
:ls	Lists all currently opened files.
:b file_name	Switchs to a file called <code>file_name</code> currently open, i.e., currently in the open buffer. You can use <code>tab</code> to autocomplete the file name. You can also use its buffer number instead of its name.
:b#	Switchs to the previously opened file. This is very convenient when you need to go back and forth between two files.
:set spell spelllang=en_ca	Switchs spellcheck on, and assumes that the current language is Canadian English.
:set nospell	Switchs spellcheck on, and assumes that the current language is Canadian English.

Table 5.5: List of some extended mode important commands.

It is possible to combine commands. for example, you can save and exit **vim** by issuing a **:wq** command, instead of two separate **:w** and **:q** commands..

By default, **vim** tries to prevent users from making mistakes, such as quitting before saving edited files, or overwriting existing files. In case you want to override these security measures, you simply need to add an exclamation point (!) to the end of your command. For example, the command **:q!** quits **vim** without saving any open files.

Reading non simple-text file

All tools presented in this chapter will assume that the files being opened are simple-text encoded using an **ascii** table. I.e., they will translate sequences of 8 bits into characters. For example, a sequence **00100000** is translated to **Space**, **01100001** to

a (lower case), and so it goes. For a complete **ascii** table, see <http://www.asciitable.com/>.

In case you try to open a non-simple text file, such as pdf files or binary applications, using the tools presented in this chapter, you will see a seemingly random sequence of **ascii** characters. This happens because the tool will interpret whichever sequence of bits it finds using an **ascii** table. Even if these bits were not created to represent a simple text.

EXERCISES

1. What is the relationship between the **more** and the **less** commands?
2. How can you search for a particular word in **less**?
3. Cite two advantages of using **vim** over **nano**.
4. Type **vimtutor** on your shell prompt. It will open an iterative tutorial to help you practice your **vim** skills.
5. Which actions can you perform in **vim**'s **extended mode**?
6. Which actions can you perform in **vim**'s **command mode**?
7. Which command you would enter to delete 20 lines of text, starting with the current line?
8. Which command you would enter to be able to select parts of your text using the arrow keys, as opposed to entering the number of lines or words you wish to select?
9. Assume that you have two files in your current working directory called **text1** and **text2**. Explain, including all commands you need to enter, how can you copy some lines from one file, and paste it into another.