

Ex.No.: 9	SUB QUERIES
Date: 10/9/24	

### Objectives

After completing this lesson, you should be able to do the following:

- Define subqueries
- Describe the types of problems that subqueries can solve
- List the types of subqueries
- Write single-row and multiple-row subqueries

### **Using a Subquery to Solve a Problem**

Who has a salary greater than Abel's?

#### **Main query:**

Which employees have salaries greater than Abel's salary?

#### **Subquery:**

What is Abel's salary?

### Subquery Syntax

`SELECT select_list FROM table WHERE expr operator (SELECT select_list FROM table);`

- The subquery (inner query) executes once before the main query (outer query).
- The result of the subquery is used by the main query.

A subquery is a SELECT statement that is embedded in a clause of another SELECT statement. You can build powerful statements out of simple ones by using subqueries. They can be very useful when you need to select rows from a table with a condition that depends on the data in the table itself.

You can place the subquery in a number of SQL clauses, including the following:

- WHERE clause
- HAVING clause
- FROM clause

#### **In the syntax:**

*operator* includes a comparison condition such as >, =, or IN

**Note:** Comparison conditions fall into two classes: single-row operators



WHERE emp.employee\_id NOT IN (SELECT mgr.manager\_id FROM employees mgr);

Notice that the null value as part of the results set of a subquery is not a problem if you use the IN operator. The IN operator is equivalent to =ANY. For example, to display the employees who have subordinates, use the following SQL statement:

```
SELECT emp.last_name
FROM employees emp
WHERE emp.employee_id IN (SELECT mgr.manager_id FROM employees mgr);
```

Display all employees who do not have any subordinates:

```
SELECT last_name FROM employees
WHERE employee_id NOT IN (SELECT manager_id FROM employees WHERE manager_id
IS NOT NULL);
```

**Find the Solution for the following:**

1. The HR department needs a query that prompts the user for an employee last name. The query then displays the last name and hire date of any employee in the same department as the employee whose name they supply (excluding that employee). For example, if the user enters Zlotkey, find all employees who work with Zlotkey (excluding Zlotkey).

*select last\_name as last\_name, entry\_year as 'Hire Date' from employees  
where department\_id = (select department\_id from employee where  
last\_name = 'Zlotkey') and last\_name <> 'Zlotkey';*

2. Create a report that displays the employee number, last name, and salary of all employees who earn more than the average salary. Sort the results in order of ascending salary.

*select employee\_id as 'Employee\_id', last\_name as last\_name, salary  
as 'salary' from employees where salary > (select avg(salary)  
from employees) order by salary;*

3. Write a query that displays the employee number and last name of all employees who work in a department with any employee whose last name contains a u.

*select employee\_id, last\_name from employees where  
department\_id in (select department\_id from employees  
where last\_name like "%u%");*



4. The HR department needs a report that displays the last name, department number, and job ID of all employees whose department location ID is 1700.

```
select last_name, department_id, job_id from employees
where department_id in (select department_id from employees
where location_id=1700);
```

5. Create a report for HR that displays the last name and salary of every employee who reports to King.

```
select last_name, salary from employees where manager_name='King';
```

6. Create a report for HR that displays the department number, last name, and job ID for every employee in the Executive department.

```
select department_id, last_name, job_id from employees
where department_id = (
    select department_id from employees where department_name='Executive'
);
```

7. Modify the query 3 to display the employee number, last name, and salary of all employees who earn more than the average salary and who work in a department with any employee whose last name contains a u.

```
select employee_id, last_name, salary from employees
where salary > (select avg (salary) from employees)
and department_id in (
    select distinct department_id from employees where last_name
    like '%u%')
order by salary asc;
```



Evaluation Procedure	Marks awarded
Query(5)	5
Execution (5)	5
Viva(5)	5
Total (15)	15
Faculty Signature	