


# The Hadoop Ecosystem





Today's (exercise) focus






## **Airflow**




- Apache Open Source Project
- Model Task (e.g. ETL) Workflows
- Python Code Base
- Scheduling, Queues and Pools
- Cluster Ready
- Web UI
- DAG = Directed Acyclic Graph



→ a collection of all the tasks you want to run, organized in a way that reflects their relationships and dependencies.



### What do we want to do?



Gcloud Server (Connected to via SSH)



## Remove Previously created Docker Container

#### 1. Stop and Remove Images:

(This will delete all files you created within previous exercise. Save them somewhere outside the docker container, if you haven't done yet.)

```
docker stop hadoop
docker rm hadoop
```

```
docker stop pentaho
docker rm pentaho
```



# Start Hadoop/Hive/Spark Docker Container

#### 1. Pull Docker Image:

```
docker pull marcelmittelstaedt/spark_base:latest
```

#### 2. Start Docker Image:

```
docker run -dit --name hadoop \
    -p 8088:8088 -p 9870:9870 -p 9864:9864 -p 10000:10000 \
    -p 8032:8032 -p 8030:8030 -p 8031:8031 -p 9000:9000 \
    -p 8888:8888 --net bigdatanet \
    marcelmittelstaedt/spark_base:latest
```

3. Wait till first Container Initialization finished:

```
docker logs hadoop
[...]
Stopping nodemanagers
Stopping resourcemanager
Container Startup finished.
```



# Start Hadoop/Hive/Spark Docker Container

4. Get into Docker container:

```
docker exec -it hadoop bash
```

5. Switch to hadoop user:

```
sudo su hadoop

cd
```

6. Start Hadoop Cluster:

```
start-all.sh
```

7. Start HiveServer2:

hiveserver2



# Start Hadoop/Hive/Spark Docker Container

#### 8. Start HiveServer2:

```
hive/bin/hiveserver2
2018-10-02 16:19:08: Starting HiveServer2
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/hadoop/hive/lib/log4j-slf4j-impl-2.10.0.jar!/org/slf4
j/impl/StaticLoggerBinder.class]
SLF4J: Found binding in [jar:file:/home/hadoop/hadoop/share/hadoop/common/lib/slf4j-log4j12-1
.7.25.jar!/org/slf4j/impl/StaticLoggerBinder.class|
SLF4J: See http://www.slf4j.org/codes.html#multiple bindings for an explanation.
SLF4J: Actual binding is of type [org.apache.logging.slf4j.Log4jLoggerFactory]
Hive Session ID = b8d1efb3-fc8c-4ec8-bdf0-6a9a41e2ddaa
Hive\ Session\ ID = 32503981 - a5fd - 497e - b887 - faf3ec1e686e
Hive\ Session\ ID = 00f7eab4-5a29-4ce4-ad97-e90904d9206f
Hive Session ID = 100e54c5-14c6-4acc-b398-040152b08ebf
ſ... 1
```



# Start ETL (Airflow) Docker Container

1. Pull Docker Image:

```
docker pull marcelmittelstaedt/airflow:latest
```

2. Start Docker Image:

```
docker run -dit --name airflow \
    -p 8080:8080 \
    --net bigdatanet \
    marcelmittelstaedt/airflow:latest
```

3. Wait till first Container Initialization finished:

```
docker logs airflow
[...]
Successfully added `conn_id`=spark : spark://:@yarn:
Container Startup finished.
```



# Start ETL (Airflow) Docker Container

4. Get into Docker container:


docker exec -it airflow bash

5. Switch to airflow user:


sudo su airflow

cd






#### Graph View:




Airflow DAGs Data Profiling **▼** About ♥ Tree View: on DAG: IMDb IMDb Import # Graph View Task Duration Task Tries Landing Times Details ∳ Code Trigger DAG Base date: 2019-11-02 18:56:00 Number of runs: 25 \$ Go success running failed skipped up\_for\_reschedule up\_ ClearDirectoryOperator 🔵 CreateDirectoryOperator 🔘 DummyOperator 🥚 HdfsMkdirFileOperator 🥚 HdfsPutFileOperator 💮 HiveOperator 🌑 HttpDownloadOperator 🥚 SparkSubmitOperator 🌑 UnzipFileOperator Taks are executed O[DAG] within a defined order create\_import\_dir clear import dir download\_title\_ratings unzip\_title\_ratings Tasks have mkdir\_hdfs\_title\_ratings\_dir upload\_title\_ratings\_to\_hdfs dependencies create title ratings table add partition title ratings table dummy Tasks are e.g.: create\_top\_movies\_external\_table hive\_write\_top\_movies\_table - Create (HDFS) Directory pyspark\_write\_top\_tvseries\_to\_final create top tyseries external table - Execute HiveQuery download title basics - Execute PySpark Job unzip title basics mkdir\_hdfs\_title\_basics\_dir upload\_title\_basics\_to\_hdfs create title basics table add partition title basics table Odummy 

#### **Gantt View:**








## Create Simple Example DAG


#### 1. Open Dag File:

```
vi /home/airflow/airflow/dags/example dag.py
          from airflow import DAG
          from airflow.operators.bash operator import BashOperator
          from datetime import datetime, timedelta
              'owner': 'airflow'
                                                                                                     DAG Definition, e.g.
          dag = DAG('ExampleDAG', default args=args, description='Simple Example DAG',
                                                                                                           - Name
                   schedule interval='56 18 * * *',
                                                                                                  - Schedule Interval (Cron)
                   start date=datetime(2019, 10, 16), catchup=False, max active runs=1)
                                                                                                        - Description
          task 1 = BashOperator(
                                                                                                         - Start date
              task id='print date',
             bash command='date',
Task 1
              dag=dag)
          task 2 = BashOperator(
              task id='sleep',
              bash command='sleep 5',
Task 2
                                             Task Execution Order
              dag=dag)
                                        task_2 is dependent on task_1
          task 1 >> task 2
                                                                                                                 www.marcer-mittelstaedt.com
```


#### **Execute DAG:**




#### See executing DAG:



View Log of task *print date*:









#### See executing DAG:



## Pentaho Data Integration Exercises – IMDB

- 1. Execute IMDb DAG
- 2. Use Airflow and previous IMDb DAG to do following changes (vi /home/airflow/dags/imdb.py):
  - a) Extend Airflow IMDb DAG to also download name.basics.tsv.gz
  - b) **Extend Airflow IMDb DAG** to also import *name.basics.tsv* to HDFS raw layer.
  - c) **Create Hive table** *name\_basics* for *name.basics.tsv* in raw layer within DAG. Table should be partitioned by year, month and day of load date like the other tables.
  - d) Create table actors and extend IMDb Airflow DAG to fill table using Hive or PySpark:
    - make use of all columns within table name\_basics
    - add column alive which contains alive if actor is alive or dead if actor is dead
    - add column **age** which contains current age of actor (calculated by using birth and death year)
  - e) Run DAG



## **Well Done**



## **Stop Your VM Instances**

# 

gcloud compute instances stop big-data

