

# Goal

OpenAddresses.io provides regulary exports of worldwide adresses (we will focus on US south/west/midwest/northeast for now):

#### https://batch.openaddresses.io/data




```
{"type": "Feature", "properties": { "hash": "394d6a8e3e6cecbf", "number": "7705", "stree
t":"W LINCOLN AVE", "unit":"1", "city":"West Allis", "district":"", "region":"", "pos
tcode":"53219","id":""},"geometry":{"type":"Point","coordinates":[-88.0088621,43
.00258451}}
{"type": "Feature", "properties": { "hash": "6101cecbe71c7bbe", "number": "7705", "stree
t":"W LINCOLN AVE", "unit":"2", "city":"West Allis", "district":"", "region":"", "pos
tcode":"53219","id":""},"qeometry":{"type":"Point","coordinates":[-88.0088621,43
.00258451}}
{"type": "Feature", "properties": { "hash": "81e3634e904916db", "number": "1060", "stree
t":"N 115TH ST", "unit":"106", "city":"Wauwatosa", "district":"", "region":"", "postc
ode":"53226","id":""},"qeometry":{"type":"Point","coordinates":[-88.0551894,43.0
{"type":"Feature", "properties": { "hash": "fbf0248cdd1623ad", "number": "12137", "stre
et":"W BURLEIGH ST", "unit":"2", "city": "Wauwatosa", "district":"", "region":"", "pos
tcode":"53222","id":""},"geometry":{"type":"Point","coordinates":[-88.0649444,43
{"type": "Feature", "properties": { "hash": "6c5867d0d98b7e9a", "number": "11515", "stre
et":"W CLEVELAND AVE", "unit": "B231", "city": "West Allis", "district": "", "region": "
","postcode":"53227","id":""},"geometry":{"type":"Point","coordinates":[-88.0560
418,42.99465291}}
[\ldots]
```

### Goal

We want to make use of this data to validate adresses entered on a website, to check whether they are real or not.


#### Workflow:

- Gather data from OpenAddresses.io
- Save raw data (JSON files) to HDFS (partitioned by state
- shortcut, e.g. wi, nd, sd...)
- Optimize, reduce and clean raw data and save it to final directory on HDFS
- Export address data to end-user database (e.g. MySQL, MongoDB...)
- Provide a simple HTML Frontend which is able to:
  - read from end-user database
  - process user input (Street, City, Postcode...)
  - validate user input against OpenAddress data in enduser database
  - Display result (real or non real address)
- The whole data workflow must be implemented within an ETL workflow tool (e.g. Pentaho Data Integration or Airflow) and run automatically





# Dataflow: 1. Get Address Data



## Dataflow: 2. Raw To Final Transfer



/user/hadoop/openaddresses/**raw**/us/wi/\*.json /user/hadoop/openaddresses/**raw**/us/nd/\*.json /user/hadoop/openaddresses/**raw**/us/sd/\*.json









- move data from raw to final directory
- Convert/Explode data structure
- optimize and reduce data structure for later query purposes if necessary
- remove duplicates if necessary
- ...



/user/hadoop/openaddresses/final/us/wi/\*.parquet /user/hadoop/openaddresses/final/us/nd/\*.parquet /user/hadoop/openaddresses/final/us/sd/\*.parquet

. . .



### Dataflow: 3. Enhance Data And Save Results



/user/hadoop/openaddresses/final/us/wi/\*.parquet /user/hadoop/openaddresses/final/us/nd/\*.parquet /user/hadoop/openaddresses/final/us/sd/\*.parquet










- enhance data (e.g. add missing entries of street no's)
- use *Hive*, *Spark* or *PySpark*
- save everything to a enduser database (e.g. MySQL, MongoDB)







# Dataflow: 4. Provide Simple Web Interface





user database

validate user input against OpenAddress data in end-

Display result (real or non real address)