





# Agenda – 03.11.2025

01

**Presentation and Discussion: Exercise Of Last Lecture**  
ETL Workflow: Airflow

02

**Practical Exam Discussion**  
Grading, Timeline, Deliverables, Presentation Procedure, Exam Topics

03

**Work On Exam**  
Work on practical exam.

# Schedule

			<i>Lecture Topic</i>	<i>HandsOn</i>
29.09.2025	13:15-15:45	Ro. N/A	About This Lecture, Introduction to Big Data	Setup Google Cloud, Create Own Hadoop Cluster and Run MapReduce
06.10.2025	13:15-15:45	Ro. N/A	(Non-)Functional Requirements Of Distributed Data-Systems, Data Models and Access	Hive and HiveQL
13.10.2025	13:15-15:45	Ro. N/A	Challenges Of Distributed Data Systems: Partitioning	HiveQL via JDBC, Data Partitioning (with HDFS and Hive)
20.10.2025	13:15-15:45	Ro. N/A	Challenges Of Distributed Data Systems: Replication	Spark, Scala, PySpark and Jupyter Notebooks
27.10.2025	13:15-15:45	Ro. N/A	ETL Workflow and Automation & Batch and Stream Processing	Airflow
03.11.2025	13:15-15:45	Ro. N/A	Practical Exam	Work On Practical Exam
10.11.2025	13:15-15:45	Ro. N/A	Practical Exam	Work On Practical Exam
17.11.2025	13:15-15:45	Ro. N/A	Practical Exam	Work On Practical Exam
24.11.2025	13:15-15:45	Ro. N/A	Practical Exam Presentation	
01.12.2025	13:15-15:45	Ro. N/A	Practical Exam Presentation	





# Practical Exam

Topics, Deliverables, Presentation...



# Practical Exam - Grading

## Grade/Percentage:

- grade will be mixed with grade of another lecture
- therefore, the rating won't be a grade (1-6) but a percentage:


Percentage	Grade
100%	1.0
...	...
50%	4.0
...	...

## Timeline:

21.11.2025 23:59 All deliverables (next slide) will be delivered to following email address (DropBox, Google-Drive...):

[contact@marcel-mittelstaedt.com](mailto:contact@marcel-mittelstaedt.com)

24.11./01.12.2025 13:15-15:45 Presentation of Practical Exam

Studiengang Informatik		 <b>DHBW</b> Duale Hochschule Baden-Württemberg Stuttgart	
Klausurergebnisse (Punkte)			
Kurs:	TINF16		
Dozent:	bitte eintragen	Punkteschlüssel	Punkte
Datum:	bitte eintragen	Max. Punkte	60
Modul/Unit:	T2INF4902		bitte anpassen
Veranstaltung:	bitte eintragen		
	beides Ergebnis	0	0
	ungünstiges Ergebnis	0	0

Nr	Matrikelnummer	Punkte	Normiert
1		0	0
2		0	0
3		0	0
4		0	0
5		0	0
6		0	0
7		0	0
8		0	0
9		0	0
10		0	0
11		0	0
12		0	0
13		0	0
14		0	0
15		0	0
16		0	0
17		0	0
18		0	0
19		0	0
20		0	0
21		0	0
22		0	0
23		0	0
24		0	0
25		0	0
26		0	0
27		0	0
28		0	0



# Practical Exam - Deliverables

## Deliverables:

- A simple Documentation:
  - Explanation of whole ETL Workflow
  - List of Jobs/Transformations in Case of PDI or DAGs and Steps in Case of Airflow
  - Short description of the purpose of each job/transformation or task and applied business rules
  - all PDI Jobs, Transformations and related files (ktr, kjb, kettle.properties, shared.xml... files)
  - All Airflow DAGs and tasks
- All Scripts (e.g. Download) or other external applications called within PDI
- All Airflow DAGs, Python Files etc.
- All DDLs (CREATE Table...):
  - One file for each table
  - Table name = File Name, e.g.:
- Depending on Exam Type:
  - Code of Frontend Application and related Database (DDLs) or
  - Calculated KPIs



The screenshot shows a GitHub repository for 'BigData / solutions / 02\_mapreduce\_hive\_hive-ql / imdb\_actors.sql'. The file is owned by 'marcelmittelstaedt' and was last updated 16 days ago. It contains 9 lines of SQL code (8 lines of code, 318 bytes) for creating an external table named 'imdb\_actors'.

```
1 CREATE EXTERNAL TABLE IF NOT EXISTS imdb_actors(  
2     nconst STRING,  
3     primary_name STRING,  
4     birth_year INT,  
5     death_year STRING,  
6     primary_profession STRING,  
7     known_for_titles STRING  
8 ) COMMENT 'IMDb Actors' ROW FORMAT DELIMITED FIELDS TERMINATED BY '\t' STORED AS TEXTFILE LOCATION '/user/hadoop/imdb/a'
```

# Practical Exam - Presentation

## Procedure:

1. Start ETL Workflow
2. During execution:
  - Quickly explain data source
    - API
    - Data Structure
    - Approach for gathering data
  - Quickly Explain whole ETL Workflow
    - Explain Idea and purpose of each Job/Transformation
    - External resources/scripts (e.g. download)
    - Explain Data Model (Raw Layer, Final Layer, simple Frontend)
3. After execution:
  - Depending on Exam:
    - Demo of simple Frontend application or
    - Explanation of calculated KPIs



# Work On Practical Exam

Time to work on practical exam





# Use Spotify Audio Features To Categorize Music

Practical Exam



# Goal

Spotify provides an API for basic track information:

- **ID**, e.g. *2IEcSduKEXEK5KJ9hJzICz*
- **name**, e.g. *Gloana Bauer (Teenage Dirtbag)*
- **artist**, e.g. *D' HundskrippIn*
- ...

as well as related audio features:

- **energy**, e.g. *0.454*  
*Energy is a measure from 0.0 to 1.0 and represents a perceptual measure of intensity and activity. Typically, energetic tracks feel fast, loud, and noisy. For example, death metal has high energy, while a Bach prelude scores low on the scale.*
- **speechiness**, e.g. *0.0388*  
*Speechiness detects the presence of spoken words in a track. The more exclusively speech-like the recording (e.g. talk show, audio book, poetry), the closer to 1.0 the attribute value.*
- **loudness**, e.g. *-8.758*  
*The overall loudness of a track in decibels (dB). Loudness values are averaged.*
- **tempo**, e.g. *97.532*  
*The overall estimated tempo of a track in beats per minute (BPM)*
- **acousticness**, e.g. *0.268*  
*A confidence measure from 0.0 to 1.0 of whether the track is acoustic.*
- ...

<https://developer.spotify.com/documentation/web-api/reference/#/operations/get-audio-features>



# Goal

We want to make use of those audio features to automatically assign each track to a certain category:

***Metal***  
***Electro***


***Classic***  
***Podcast***

***Rock***  
***Soul***

***Vocal***  
***HipHop***

## Workflow:

- **Query** data from Spotify API
- **Save** raw data (JSON files) to HDFS
- **Optimize, reduce** and **clean** raw data and save it to **final** directory on HDFS
- **Calculate** categories (*Metal, Classic, Rock, ...*)
- **Join** track information and audio features and **save** everything to **end-user database** (e.g. MySQL, MongoDB...)
- Provide a simple HTML Frontend which reads from end-user database and displays result
- The whole data workflow **must be implemented** within an ETL **workflow tool** (e.g. Pentaho Data Integration or Airflow) and **run automatically**



ID	Song Title	Artist	Category
42	Savior	Rise Against	Rock
11	Ham Kummst	Seiler u Speer	Rock
13	No One	Alicia Keys	Soul
37	I Try	Macy Gray	Soul
55	Metalingus	Alter Bridge	Metal
56	The Trooper	Iron Maidon	Metal
77	Du	Cro	HipHop
88	Solala	Blumentopf	HipHop
...	...	...	...

# Dataflow: 1. Get Track Information

```
curl -X "GET" "https://api.spotify.com/v1/tracks/2IEcSduKEXEK5KJ9hJzlCz?market=DE" -H "Accept: application/json" -H "Content-Type: application/json" -H "Authorization: Bearer BBB0v7vCOHXxaUAshFUVIFbozLDO_ysq8cPb4wYR3oko_JfDcrUSEsy0Mq6P4cu5vvS0ljm6R24raME8o4qa2XNy02lhGGCufMgwGptf43s2OoAcbfJUfcsXA1-dpW19_x_3rG75ADnA4dlr25"
```

1



<https://api.spotify.com/v1/tracks/{id}>

<https://api.spotify.com/v1/audio-features/{id}>

2

```
[...]  
"album":{  
  "album_type":"single",  
  "artists":[  
    {  
      "href":"https://api.spotify.com/v1/artists/4x4nSliAvh7RM7dVxbs9aP",  
      "id":"4x4nSliAvh7RM7dVxbs9aP",  
      "name":"D'Hundskrippln",  
      "type":"artist",  
      "uri":"spotify:artist:4x4nSliAvh7RM7dVxbs9aP"  
    }  
  ]  
},  
"name":"Gloana Bauer (Teenage Dirtbag)",  
"release_date":"2016-07-01"  
[...]  
"href":"https://api.spotify.com/v1/tracks/2IEcSduKEXEK5KJ9hJzlCz", "id":"2IEcSduKEXEK5KJ9hJzlCz",  
[...]
```



[/user/hadoop/spotify/track\\_data/raw/...](/user/hadoop/spotify/track_data/raw/...)  
[/user/hadoop/spotify/audio\\_features/raw/...](/user/hadoop/spotify/audio_features/raw/...)


<https://developer.spotify.com/documentation/web-api/reference/#/operations/get-track>



[www.marcel-mittelstaedt.com](http://www.marcel-mittelstaedt.com)




# Dataflow: 2. Get Track Audio Features



<https://developer.spotify.com/documentation/web-api/reference/#/operations/get-audio-features>



# Dataflow: 3. Raw To Final Transfer



# Dataflow: 4. Run Analysis and Save Results



/user/hadoop/spotify/track\_data/final/...  
/user/hadoop/spotify/audio\_features/final/...



1

- calculate categories for each track, using Hive, Python, Spark or PySpark
- join track and audio feature data
- save everything to a end-user database (e.g. MySQL, MongoDB)



# Dataflow: 5. Provide Simple Web Interface



1

- Create a simple Website which reads and displays data from end-user database

ID	Song Title	Artist	Category
42	Savior	Rise Against	Rock
11	Ham Kummst	Seiler u Speer	Rock
13	No One	Alicia Keys	Soul
37	I Try	Macy Gray	Soul
55	Metalingus	Alter Bridge	Metal
56	The Trooper	Iron Maidon	Metal
77	Du	Cro	HipHop
88	Solala	Blumentopf	HipHop
...	...	...	...



# Use XKCD API To Build A Searchable Database of XKCD Comics


Practical Exam



# Goal

XKCD provides regularly comics:

- <https://xkcd.com/>
- JSON API: <https://xkcd.com/2054/info.0.json>



<https://xkcd.com/2054/>

```
{
  "month": "10",
  "num": 2054,
  "link": "",
  "year": "2018",
  "news": "",
  "safe_title": "Data Pipeline",
  "transcript": "",
  "alt": "\\\"Is the pipeline literally running from your laptop?\\\" \\\"Don't be silly, my laptop disconnects far too often to host a service we rely on. It's running on my phone.\\\"\"",
  "img": "https://imgs.xkcd.com/comics/data_pipeline.png",
  "title": "Data Pipeline",
  "day": "3"
}
```

2054.json



# Goal


We want to make use of this data to build a searchable database for XKCD comics.

## Workflow:

- **Gather data** from xkcd.com
- **Save raw data** (JSON files) to HDFS (partitioned by year, e.g. 2018, 2017, 2016...)
- **Optimize, reduce** and **clean raw data** and save it to **final** directory on HDFS
- **Export** xkcd data to **end-user database** (e.g. MySQL, MongoDB...)
- Provide a simple **HTML Frontend** which is able to:
  - read from end-user database
  - process user input (search phrase...)
  - checks against xkcd data in end-user database
  - Display result (comics containing search phrase)
- The whole data workflow **must be implemented** within an ETL **workflow tool** (e.g. Pentaho Data Integration or Airflow) and **run automatically**




# Dataflow: 1. Get XKCD Data





# Dataflow: 2. Raw To Final Transfer



# Dataflow: 3. Enhance Data And Save Results



/user/hadoop/xkcd/final/\*

...



1

- enhance data (e.g. for later querying)
- use *Hive*, *Spark* or *PySpark*
- save everything to a end-user database (e.g. *MySQL*, *MongoDB*)





# Use GeoLite2 To Create A Searchable IP and GeoLocation Database

Practical Exam





# Goal

Maxmind.com provides regulary exports of worldwide IP and Geolocation data:

- <https://dev.maxmind.com/geoiip/geolite2-free-geolocation-data>

```
curl -s http://ifconfig.me  
88.130.59.75
```

1

```
network,geoname_id,registered_country_geoname_id,represented_country_geoname_id,is_anonymous_proxy,is_satellite_provider,postal_code,latitude,longitude,accuracy_radius  
88.130.59.0/24,2939623,2921044,,0,0,85221,48.2600,11.4340,50  
[...]
```

2

```
geoname_id,locale_code,continent_code,continent_name,country_iso_code,country_name,subdivision_1_iso_code,subdivision_1_name,subdivision_2_iso_code,subdivision_2_name,city_name,metro_code,time_zone,is_in_european_union  
3205335,de,EU,Europe,DE,Deutschland,BY,Bayern,,Höhenkirchen-Siegersbrunn,,Europe/Berlin,1  
2939623,de,EU,Europe,DE,Deutschland,BY,Bayern,,Dachau,,Europe/Berlin,1  
3207410,de,EU,Europe,DE,Deutschland,BY,Bayern,,Rödingen,,Europe/Berlin,1  
3207412,de,EU,Europe,DE,Deutschland,BY,Bayern,,Rödingen,,Europe/Berlin,1  
3208324,de,EU,Europe,DE,Deutschland,BY,Bayern,,Asbach-Bäumenheim,,Europe/Berlin,1  
[...]
```

GeoLite2-City-Blocks-IPv4.csv

GeoLite2-City-Locations-[XX].csv




# Goal


We want to make use of this data to build a real time IP-Geolocation resolution as well as a searchable database for Ips and related Geolocations.

## Workflow:

- **Gather data** from maxmind.com
- **Save raw data** (CSV files) to HDFS (partitioned by country code, e.g. *de*, *es*, *en*...)
- **Optimize, reduce** and **clean raw data** and save it to **final** directory on HDFS
- **Export** Geolite2 data to **end-user database** (e.g. MySQL, MongoDB...)
- Provide a simple **HTML Frontend** which is able to:
  - **determine** a user's IP address, **lookup** and **show Geolocation**
  - process user input (IP...) and check against end-user database
  - Display result Geolocation
- The whole data workflow **must be implemented** within an ETL **workflow tool** (e.g. Pentaho Data Integration or Airflow) and **run automatically**



# Dataflow: 1. Get Geolite2 Data



# Dataflow: 2. Raw To Final Transfer



/user/hadoop/geo\_ip/**raw**/locations/de/\*.csv  
/user/hadoop/geo\_ip/**raw**/locations/es/\*.csv  
/user/hadoop/geo\_ip/**raw**/locations/en/\*.csv  
...  
/user/hadoop/geo\_ip/**raw**/blocks/\*IPv4\*.csv  
/user/hadoop/geo\_ip/**raw**/blocks/\*IPv6\*.csv



1

- move data from *raw* to *final* directory
- **optimize** and **reduce** data structure for later query purposes if necessary
- remove duplicates if necessary
- ...



/user/hadoop/geo\_ip/**final**/locations/de  
/user/hadoop/geo\_ip/**final**/locations/es/  
/user/hadoop/geo\_ip/**final**/locations/en/  
...  
/user/hadoop/geo\_ip/**final**/blocks/\*IPv4\*  
/user/hadoop/geo\_ip/**final**/blocks/\*IPv6\*

# Dataflow: 3. Enhance Data And Save Results



```
/user/hadoop/geo_ip/final/locations/de  
/user/hadoop/geo_ip/final/locations/es/  
/user/hadoop/geo_ip/final/locations/en/  
...  
/user/hadoop/geo_ip/final/blocks/*IPv4*  
/user/hadoop/geo_ip/final/blocks/*IPv6*
```




1

- enhance data (e.g. for later querying)
- use *Hive*, *Python*, *Spark* or *PySpark*
- save everything to a end-user database (e.g. *MySQL*, *MongoDB*)



# Dataflow: 4. Provide Simple Web Interface



- Provide a simple **HTML Frontend** which is able to:
  - **determine** a user's IP address, **lookup** and **show Geolocation**
  - process user input (IP...) and check against end-user database
  - Display result Geolocation



# Create MTG Trading Card Database By Crawler

Practical Exam




# Goal

magicthegathering.io provides up-to-date information regarding all MTG trading cards available:

- <https://gatherer.wizards.com/>

## Manta Riders

Details | Sets & Legality | Language | Discussion



**Oracle** **Printed**

**Card Name:** Manta Riders

**Mana Cost:** 1

**Converted Mana Cost:** 1

**Types:** Creature — Merfolk

**Card Text:** (F) Manta Riders gains flying until end of turn.

**Flavor Text:** "Water is firmament to the finned."  
—Oracle en-Vec

**P/T:** 1 / 1

**Expansion:** Tempest

**Rarity:** Common

**Artist:** Kaja Foglio

**Community Rating:**  
★★★★★  
Community Rating: 2,630 / 5 (27 votes)  
[Click here to view ratings and comments.](#)

```
<div class="smallGreyMono" style="margin-top: 5px;">
  <b class="ft"><b></b></b>
  <div id="ctl00_ctl00_ctl00_MainContent_SubContent_SubContent_nameRow" class="row">
    <div class="label">
      Card Name:</div>
    <div class="value">
      Manta Riders</div>
  </div>
  <div id="ctl00_ctl00_ctl00_MainContent_SubContent_SubContent_manarow" class="row manarow">
    <div class="label" style="line-height: 25px;">
      Mana Cost:</div>
    <div class="value">
      </div>
  </div>
  <div id="ctl00_ctl00_ctl00_MainContent_SubContent_SubContent_cmcrw" class="row">
    <div class="label" style="font-size: .7em;">
      Converted Mana Cost:</div>
    <div class="value">
      1</div>
  </div>
  <div id="ctl00_ctl00_ctl00_MainContent_SubContent_SubContent_typerw" class="row">
    <div class="label">
      Types:</div>
    <div class="value">
      Creature — Merfolk</div>
  </div>
  <div id="ctl00_ctl00_ctl00_MainContent_SubContent_SubContent_textrow" class="row">
    <div class="label">
      Card Text:</div>
    <div class="value">
      <div class="cardtextbox" style="padding-left: 10px;">: Manta Riders gains flying until end of turn.</div></div>
  </div>
</div>
```

<http://gatherer.wizards.com/Pages/Card/Details.aspx?multiverseid=4711>




# Goal

We want to make use of this data to build a searchable database of all MTG trading cards.


## Workflow:

- **Crawl** data from gatherer.wizards.com
- **Parse** required **information** and save them to **HDFS** (queryable through Hive)
- **Export** MTG data to **end-user database** (e.g. MySQL, MongoDB...)
- Provide a simple **HTML Frontend** which is able to:
  - read from end-user database
  - process user input (card name, text or artist)
  - **display search results**
- The whole data workflow **must be implemented** within an ETL **workflow tool** (e.g. Pentaho Data Integration or Airflow) and **run automatically**



# Dataflow: 1. Get MTG Data

Crawl HTML pages



# Dataflow: 3. Enhance Data And Save Results



/user/hadoop/mtg/\*



1


- enhance data (e.g. for later querying)
- use *Hive*, *Python*, *Spark* or *PySpark*
- save everything to a end-user database (e.g. *MySQL*, *MongoDB*)



# Dataflow: 4. Provide Simple Web Interface



1



- Provide a simple **HTML Frontend** which is able to:
  - read from end-user database
  - process user input (card name, text or artist)
  - **display search results**



# Create MTG Trading Card Database By API

Practical Exam



# Goal

magicthegathering.io provides up-to-date information regarding all MTG trading cards available:

- <https://docs.magicthegathering.io/>
- E.g. <https://api.magicthegathering.io/v1/cards/4711>




```
{
  "card": {
    "name": "Manta Riders",
    "manaCost": "{U}",
    "cmc": 1,
    "colors": [
      "Blue"
    ],
    "colorIdentity": [
      "U"
    ],
    "type": "Creature — Merfolk",
    "types": [
      "Creature"
    ],
    "subtypes": [
      "Merfolk"
    ],
    "rarity": "Common",
    "set": "TMP",
    "setName": "Tempest",
    "text": "{U}: Manta Riders gains flying until end of turn.",
    "flavor": "Water is firmament to the finned.\n—Oracle en-Vec",
    "artist": "Kaja Foglio",
    "power": "1",
    "toughness": "1",
    "layout": "normal",
    "multiverseid": 4711,
    "imageUrl": "http://gatherer.wizards.com/Handlers/Image.ashx?multiverseid=4711&type=card",
    [...]
  }
}
```

# Goal


We want to make use of this data to build a searchable database of all MTG trading cards.

## Workflow:

- **Gather data** from api.magicthegathering.io
- **Save raw data** (*JSON files*) to HDFS
- **Optimize, reduce and clean raw data** and save it to **final** directory on HDFS
- **Export** MTG data to **end-user database** (e.g. MySQL, MongoDB...)
- Provide a simple **HTML Frontend** which is able to:
  - read from end-user database
  - process user input (card name, text or artist)
  - **display search results**
- The whole data workflow **must be implemented** within an ETL **workflow tool** (e.g. Pentaho Data Integration or Airflow) and **run automatically**



# Dataflow: 1. Get MTG Data



# Dataflow: 2. Raw To Final Transfer



/user/hadoop/mtg/*raw*/\*.json



1

- move data from *raw* to *final* directory
- **optimize** and **reduce** data structure for later query purposes if necessary
- remove duplicates if necessary
- ...



/user/hadoop/mtg/*final*/\*

# Dataflow: 3. Enhance Data And Save Results



/user/hadoop/mtg/final/\*



1

- enhance data (e.g. for later querying)
- use *Hive*, *Spark* or *PySpark*
- save everything to a end-user database (e.g. *MySQL*, *MongoDB*)






# Dataflow: 4. Provide Simple Web Interface



1



- Provide a simple **HTML Frontend** which is able to:
  - read from end-user database
  - process user input (card name, text or artist)
  - **display search results**

# Use NYC Taxi Trip Record Data To Calculate Performance KPIs

Practical Exam



# Goal

NYC.gov provides monthly exports of NYC yellow taxi trip records:

- <https://www1.nyc.gov/site/tlc/about/tlc-trip-record-data.page>
- Latest Full Dumps:
  - [https://d37ci6vzurychx.cloudfront.net/trip-data/yellow\\_tripdata\\_2022-01.parquet](https://d37ci6vzurychx.cloudfront.net/trip-data/yellow_tripdata_2022-01.parquet)
  - [https://d37ci6vzurychx.cloudfront.net/trip-data/yellow\\_tripdata\\_2022-02.parquet](https://d37ci6vzurychx.cloudfront.net/trip-data/yellow_tripdata_2022-02.parquet)
  - [https://d37ci6vzurychx.cloudfront.net/trip-data/yellow\\_tripdata\\_2022-03.parquet](https://d37ci6vzurychx.cloudfront.net/trip-data/yellow_tripdata_2022-03.parquet)
  - ...

```
VendorID,tpep_pickup_datetime,tpep_dropoff_datetime,passenger_count,trip_distance,RatecodeID,store_and_fwd_flag,mta_tax,tip_amount,tolls_amount,improvement_surcharge,total_amount,congestion_surcharge,airport_fee
0 1 2022-01-01 00:35:40 2022-01-01 00:53:29 2.0 3.80 1.0 N .. 0.5 3.65 0.0 0.3 21.95 2.5 0.0
1 1 2022-01-01 00:33:43 2022-01-01 00:42:07 1.0 2.10 1.0 N .. 0.5 4.00 0.0 0.3 13.30 0.0 0.0
2 2 2022-01-01 00:53:21 2022-01-01 01:02:19 1.0 0.97 1.0 N .. 0.5 1.76 0.0 0.3 10.56 0.0 0.0
3 2 2022-01-01 00:25:21 2022-01-01 00:35:23 1.0 1.09 1.0 N .. 0.5 0.00 0.0 0.3 11.80 2.5 0.0
4 2 2022-01-01 00:36:48 2022-01-01 01:14:20 1.0 4.30 1.0 N .. 0.5 3.00 0.0 0.3 30.30 2.5 0.0
...
2463926 2 2022-01-31 23:36:53 2022-01-31 23:42:51 NaN 1.32 NaN None .. 0.5 2.39 0.0 0.3 13.69 NaN NaN
2463927 2 2022-01-31 23:44:22 2022-01-31 23:55:01 NaN 4.19 NaN None .. 0.5 4.35 0.0 0.3 24.45 NaN NaN
2463928 2 2022-01-31 23:39:00 2022-01-31 23:50:00 NaN 2.10 NaN None .. 0.5 2.00 0.0 0.3 16.52 NaN NaN
2463929 2 2022-01-31 23:36:42 2022-01-31 23:48:45 NaN 2.92 NaN None .. 0.5 0.00 0.0 0.3 15.70 NaN NaN
2463930 2 2022-01-31 23:46:00 2022-02-01 00:13:00 NaN 8.94 NaN None .. 0.5 6.28 0.0 0.3 35.06 NaN NaN
```

[2463931 rows x 19 columns]

[...]

*yellow\_tripdata\_2022-01.parquet*



[www.marcel-mittelstaedt.com](http://www.marcel-mittelstaedt.com)


# Goal

We want to make use of this data to calculate some KPIs

Workflow:

- **Gather data** from <https://www1.nyc.gov/site/tlc/about/tlc-trip-record-data.page>
- **Save raw data** (CSV files) to HDFS (partitioned by YYYY-MM)
- **Optimize, reduce and clean raw data** and save it to **final** directory on HDFS
- **Calculate KPIs** and **Export** them to an **Excel File**
- The whole data workflow **must be implemented** within an ETL **workflow tool** (e.g. Pentaho Data Integration or Airflow) and **run automatically**

# Dataflow: 1. Get TLC NYC Taxi Data



# Dataflow: 2. Raw To Final Transfer



/user/hadoop/nyc\_taxi/raw/2022-01/\*.csv  
/user/hadoop/nyc\_taxi/raw/2022-02/\*.csv  
/user/hadoop/nyc\_taxi/raw/2022-03/\*.csv  
...



1

- move data from *raw* to *final* directory
- **optimize** and **reduce** data structure for later query purposes if necessary
- remove duplicates if necessary
- ...



/user/hadoop/nyc\_taxi/final/2022-01/\*.csv  
/user/hadoop/nyc\_taxi/final/2022-02/\*.csv  
/user/hadoop/nyc\_taxi/final/2022-03/\*.csv  
...



# Dataflow: 3. Calculate And Export KPIs



/user/hadoop/nyc\_taxi/final/\*

...



1

- calculate KPIs and export them to Excel
- use *Hive*, *Spark* or *PySpark*



# Dataflow: 4. KPIs To Calculate

## Calculate per Month:

- Average Trip Duration (in minutes)
- Average Trip Distance (in miles)
- Average total amount (in USD)
- Average tip amount (in USD)
- Average passenger count (as Number)
- Usage Share by payment type (credit card, cash... in percent)
- Usage share per timeslot (in percent):
  - 00:00-06:00
  - 06:00-12:00
  - 12:00-18:00
  - 18:00-24:00



# Use *kaggle.com* Hubway Data To Calculate Bike Sharing Usage KPIs

Practical Exam



# Goal

kaggle.com provides monthly exports of Hubway bike sharing trip records:

- <https://www.bluebikes.com/>
- Latest Full Dumps: <https://www.kaggle.com/acmeyer/hubway-data>

```
"tripduration", "starttime", "stoptime", "start station id", "start station name", "start station latitude", "start station longitude", "end station id", "end station name", "end station latitude", "end station longitude", "bikeid", "usertype", "birth year", "gender"
"133", "2015-12-01 00:01:52", "2015-12-01 00:04:06", "9", "Agganis Arena - 925 Comm Ave.", "42.351246", "-71.115639", "41", "Packard's Comer - Comm. Ave. at Brighton Ave.", "42.352261", "-71.123831", "199", "Customer", "1995", "1"
"1522", "2015-12-01 00:05:30", "2015-12-01 00:30:53", "41", "Packard's Comer - Comm. Ave. at Brighton Ave.", "42.352261", "-71.123831", "54", "Tremont St / West St", "42.354979", "-71.063348", "876", "Customer", "1983", "1"
"153", "2015-12-01 00:07:46", "2015-12-01 00:10:20", "75", "Lafayette Square at Mass Ave / Main St / Columbia St", "42.36346469304347", "-71.10057324171066", "67", "MIT at Mass Ave / Amherst St", "42.3581", "-71.093198", "757", "Subscriber", "1995", "1"
"435", "2015-12-01 00:07:48", "2015-12-01 00:15:04", "68", "Central Square at Mass Ave / Essex St", "42.36507", "-71.1031", "29", "Innovation Lab - 125 Western Ave. at Batten Way", "42.363732", "-71.124565", "853", "Subscriber", "1988", "1"
"1208", "2015-12-01 00:12:15", "2015-12-01 00:32:23", "36", "Boston Public Library - 700 Boylston St.", "42.349673", "-71.077303", "110", "Harvard University Gund Hall at Quincy St / Kirkland S", "42.376369", "-71.114025", "437", "Customer", "1982", "1"
"1117", "2015-12-01 00:16:31", "2015-12-01 00:35:09", "31", "Seaport Hotel", "42.348833", "-71.041747", "67", "MIT at Mass Ave / Amherst St", "42.3581", "-71.093198", "1161", "Subscriber", "1988", "1"
"1287", "2015-12-01 00:16:50", "2015-12-01 00:38:18", "10", "B.U. Central - 725 Comm. Ave.", "42.350406", "-71.108279", "23", "Mayor Martin J Walsh - 28 State St", "42.35892", "-71.057629", "565", "Subscriber", "1966", "1"
```


# Goal

We want to make use of this data to calculate some Usage KPIs.

## Workflow:

- **Gather data** from <https://www.kaggle.com/acmeyer/hubway-data>
- **Save raw data** (CSV files) to HDFS (partitioned by YYYYMM)
- **Optimize, reduce and clean raw data** and save it to **final** directory on HDFS
- **Calculate KPIs** and **Export** them to an **Excel File**
- The whole data workflow **must be implemented** within an ETL **workflow tool** (e.g. Pentaho Data Integration or Airflow) and **run automatically**

# Dataflow: 1. Get Hubway Bike Sharing Data



# Dataflow: 2. Raw To Final Transfer



/user/hadoop/hubway/**raw**/201606/\*.csv  
/user/hadoop/hubway/**raw**/201607/\*.csv  
/user/hadoop/hubway/**raw**/201608/\*.csv  
...



1

- move data from *raw* to *final* directory
- **optimize** and **reduce** data structure for later query purposes if necessary
- remove duplicates if necessary
- ...



/user/hadoop/hubway/**final**/201606/\*.csv  
/user/hadoop/hubway/**final**/201607/\*.csv  
/user/hadoop/hubway/**final**/201608/\*.csv  
...



# Dataflow: 3. Calculate And Export KPIs



/user/hadoop/hubway/final/201606/\*  
/user/hadoop/hubway/final/201607/\*  
/user/hadoop/hubway/final/201608/\*  
...



1

- calculate KPIs and export them to Excel
- use *Hive*, *Spark* or *PySpark*



# Dataflow: 4. KPIs To Calculate

## Calculate per Month:

- Average Trip Duration (in minutes)
- Average Trip Distance (in km)
- Usage Share by gender (in percent)
- Usage Share by age (in percent)
- Top 10 most used bikes
- Top 10 most start stations
- Top 10 most end stations
- Usage share per timeslot (in percent):
  - 00:00-06:00
  - 06:00-12:00
  - 12:00-18:00
  - 18:00-24:00



# Use OpenCellID Data To Estimate GSM/UMTS/LTE Coverage

Practical Exam



# Goal

OpenCellID.com provides regulary exports of worldwide cell data:

- <https://www.opencellid.org>
- Latest Full Dump and Diffs: <https://www.opencellid.org/downloads.php>

## Full Database

- [cell\\_towers.csv.gz](#)  
Updated: 2021-03-21 (982MB)

## Differential

- [OCID-diff-cell-export-2021-03-21-T000000.csv.gz](#) (829KB)
- [OCID-diff-cell-export-2021-03-20-T000000.csv.gz](#) (1526KB)
- [OCID-diff-cell-export-2021-03-19-T000000.csv.gz](#) (1534KB)
- [OCID-diff-cell-export-2021-03-18-T000000.csv.gz](#) (1550KB)
- [OCID-diff-cell-export-2021-03-17-T000000.csv.gz](#) (1540KB)
- [OCID-diff-cell-export-2021-03-16-T000000.csv.gz](#) (1434KB)
- [OCID-diff-cell-export-2021-03-15-T000000.csv.gz](#) (545KB)

```
radio,mcc,net,area,cell,unit,lon,lat,range,samples,changeable,created,updated,averageSignal
UMTS,262,2,801,86355,0,13.285512,52.522202,1000,7,1,1282569574,1300155341,0
GSM,262,2,801,1795,0,13.276907,52.525714,5716,9,1,1282569574,1300155341,0
GSM,262,2,801,1794,0,13.285064,52.524,6280,13,1,1282569574,1300796207,0
UMTS,262,2,801,211250,0,13.285446,52.521744,1000,3,1,1282569574,1299466955,0
UMTS,262,2,801,86353,0,13.293457,52.521515,1000,2,1,1282569574,1291380444,0
UMTS,262,2,801,86357,0,13.289106,52.53273,2400,3,1,1282569574,1298860769,0
UMTS,262,3,1107,83603,0,13.349675,52.497575,3102,222,1,1282672189,1300710809,0
GSM,262,2,776,867,0,13.349711,52.497367,1000,214,1,1282672189,1301575206,0
GSM,262,3,1107,13971,0,13.349743,52.497437,1000,212,1,1282672189,1300710809,0
GSM,262,3,1107,355,0,13.34963,52.497378,1000,198,1,1282672189,1300710809,0
UMTS,262,3,1107,329299,0,13.349223,52.497519,3041,186,1,1282672189,1299860879,0
```

cell\_towers.csv




# Goal

We want to make use of this data to estimate the coverage of GSM, UMTS and LTE for a certain place (*latitude, longitude*).

## Workflow:

- **Gather data** from OpenCellID.com
- **Save raw data** (CSV files) to HDFS (partitioned by radio, e.g. GSM, UMTS, LTE...)
- **Optimize, reduce** and **clean raw data** and save it to **final** directory on HDFS
- **Export** address data to **end-user database** (e.g. MySQL, MongoDB...)
- Provide a simple **HTML Frontend** which is able to:
  - read from end-user database
  - process user input (Latitude, Longitude...)
  - checks against OpenCellID data in end-user database
  - Display result (GSM, LTE and UMTS coverage)
- The whole data workflow **must be implemented** within an ETL **workflow tool** (e.g. **Pentaho Data Integration** or **Airflow**) and **run automatically**



<b>Latitude:</b>	<input type="text" value="52.254409790039"/>	<b>Result:</b>
<b>Longitude:</b>	<input type="text" value="13.436965942383"/>	GSM: <b>very good</b>
		UMTS: <b>good</b>
		LTE: <b>poor</b>
<input type="button" value="Check Cell Coverage!"/>		

# Dataflow: 1. Get Cell Data

Get **Initial data** cell\_towers.csv.gz  
as well as **Diffs** (OCID-diff-cell-export-2021-03-21-T000000.csv.gz) for  
every future execution of ETL Workflow  
(Airflow or Pentaho Data Integration)

1



<https://www.opencellid.org>


2



/user/hadoop/opencellid/**raw**/\*.csv

...

# Dataflow: 2. Raw To Final Transfer





# Dataflow: 3. Enhance Data And Save Results



/user/hadoop/opencellid/final/\*

...



1


- enhance data (e.g. for later querying)
- use *Hive*, *Spark* or *PySpark*
- save everything to a end-user database (e.g. *MySQL*, *MongoDB*)



# Dataflow: 4. Provide Simple Web Interface



1



- Provide a simple **HTML Frontend** which is able to:
  - read from end-user database
  - process user input (Latitude, Longitude...)
  - checks against OpenCellID data in end-user database
  - Display result (GSM, LTE and UMTS coverage)



# Use OpenAddresses Data To Validate Adresses


Practical Exam



# Goal

OpenAddresses.io provides regular exports of worldwide addresses (we will focus on US south/west/midwest/northeast for now):

- <https://batch.openaddresses.io/data>



```
{ "type": "Feature", "properties": { "hash": "394d6a8e3e6cecbf", "number": "7705", "street": "W LINCOLN AVE", "unit": "1", "city": "West Allis", "district": "", "region": "", "postcode": "53219", "id": "" }, "geometry": { "type": "Point", "coordinates": [-88.0088621, 43.0025845] } }
{ "type": "Feature", "properties": { "hash": "6101cecb71c7bbe", "number": "7705", "street": "W LINCOLN AVE", "unit": "2", "city": "West Allis", "district": "", "region": "", "postcode": "53219", "id": "" }, "geometry": { "type": "Point", "coordinates": [-88.0088621, 43.0025845] } }
{ "type": "Feature", "properties": { "hash": "81e3634e904916db", "number": "1060", "street": "N 115TH ST", "unit": "106", "city": "Wauwatosa", "district": "", "region": "", "postcode": "53226", "id": "" }, "geometry": { "type": "Point", "coordinates": [-88.0551894, 43.0441061] } }
{ "type": "Feature", "properties": { "hash": "fbf0248cdd1623ad", "number": "12137", "street": "W BURLEIGH ST", "unit": "2", "city": "Wauwatosa", "district": "", "region": "", "postcode": "53222", "id": "" }, "geometry": { "type": "Point", "coordinates": [-88.0649444, 43.0741544] } }
{ "type": "Feature", "properties": { "hash": "6c5867d0d98b7e9a", "number": "11515", "street": "W CLEVELAND AVE", "unit": "B231", "city": "West Allis", "district": "", "region": "", "postcode": "53227", "id": "" }, "geometry": { "type": "Point", "coordinates": [-88.0560418, 42.9946529] } }
[ ... ]
```




# Goal

We want to make use of this data to validate addresses entered on a website, to check whether they are real or not.

## Workflow:

- **Gather data** from OpenAddresses.io
- **Save raw data** (*JSON files*) to HDFS (partitioned by state shortcut, e.g. *wi, nd, sd...*)
- **Optimize, reduce** and **clean raw data** and save it to **final** directory on HDFS
- **Export** address data to **end-user database** (e.g. MySQL, MongoDB...)
- Provide a simple **HTML Frontend** which is able to:
  - read from end-user database
  - process user input (Street, City, Postcode...)
  - validate user input against OpenAddress data in end-user database
  - Display result (real or non real address)
- The whole data workflow **must be implemented** within an **ETL workflow tool** (e.g. **Pentaho Data Integration** or **Airflow**) and **run automatically**



The image shows a computer monitor with a web form on the screen. The form is titled 'Check Address!' and contains four input fields: 'Street:', 'Street No:', 'City:', and 'Postcode:'. The 'Street' field contains 'W CANAL ST', 'Street No' contains '400', 'City' contains 'Milwaukee', and 'Postcode' contains '53201'. There is also a 'State:' field containing 'Wisconsin' and a green button labeled 'Check Address!'.

Street:	Street No:
W CANAL ST	400
City:	Postcode:
Milwaukee	53201
State:	Check Address!
Wisconsin	

# Dataflow: 1. Get Address Data

Get <https://batch.openaddresses.io/data>

1



<http://results.openaddresses.io/>

2

Name	
us	
nd	
sd	
mn	
ne	
ks	
ia	
md	
wi	
wood-addresses-county.geojson	
winnebago-addresses-county.geojson	
waushara-addresses-county.geojson	
waupaca-addresses-county.geojson	
waukesha-addresses-county.geojson	
washington-addresses-county.geojson	
walworth-addresses-county.geojson	
milwaukee-addresses-county.geojson	
milwaukee-addresses-county.geojson	
vernon-addresses-county.geojson	
trempealeau-addresses-county.geojson	
statewide-addresses-state.geojson	
st_croix-addresses-county.geojson	
sheboygan-addresses-county.geojson	
sauk-addresses-county.geojson	
rock-addresses-county.geojson	
richland-addresses-county.geojson	
portage-addresses-county.geojson	
polk-addresses-county.geojson	
pierce-addresses-county.geojson	
outagamie-addresses-county.geojson	
oneida-addresses-county.geojson	
oconto-addresses-county.geojson	
milwaukee-addresses-county.geojson	
marathon-addresses-county.geojson	
manitowoc-addresses-county.geojson	



`/user/hadoop/openaddresses/raw/us/wi/*.json`  
`/user/hadoop/openaddresses/raw/us/nd/*.json`  
`/user/hadoop/openaddresses/raw/us/sd/*.json`  
...



# Dataflow: 2. Raw To Final Transfer



/user/hadoop/openaddresses/**raw**/us/wi/\*.json  
/user/hadoop/openaddresses/**raw**/us/nd/\*.json  
/user/hadoop/openaddresses/**raw**/us/sd/\*.json  
...



1

- move data from **raw** to **final** directory
- Convert/Explode data structure
- **optimize and reduce data structure** for later query purposes if necessary
- remove duplicates if necessary
- ...



/user/hadoop/openaddresses/**final**/us/wi/\*.parquet  
/user/hadoop/openaddresses/**final**/us/nd/\*.parquet  
/user/hadoop/openaddresses/**final**/us/sd/\*.parquet  
...



# Dataflow: 3. Enhance Data And Save Results



```
/user/hadoop/openaddresses/final/us/wi/*.parquet  
/user/hadoop/openaddresses/final/us/nd/*.parquet  
/user/hadoop/openaddresses/final/us/sd/*.parquet  
...
```



1

- enhance data (e.g. add missing entries of street no's)
- use *Hive*, *Spark* or *PySpark*
- save everything to a end-user database (e.g. *MySQL*, *MongoDB*)



# Dataflow: 4. Provide Simple Web Interface



1

A computer monitor displays a web form for address validation. The form has four input fields: 'Street' with the value 'W CANAL ST', 'Street No' with the value '400', 'City' with the value 'Milwaukee', and 'State' with the value 'Wisconsin'. There is also a 'Postcode' field with the value '53201'. A green button labeled 'Check Address!' is located at the bottom right of the form.

- Provide a simple **HTML Frontend** which is able to:
  - read from end-user database
  - process user input (Street, City, Postcode...)
  - validate user input against OpenAddress data in end-user database
  - Display result (real or non real address)



Good Luck and have fun!

GOOD LUCK  
AND  
HAVE FUN!



# Please choose an exam topic!

Practical Exam 2025/2026

Menüs 100% 123 Stand...

https://tinyurl.com/BigDataPracticalExam20252026

	A	B	C	D
1	#	Exam Topic	Vorname	Nachname
2	1	Address Validation		
3	2	Address Validation		
4	3	Address Validation		
5	4	Calculate GSM/UMTS/LTE Coverage		
6	5	Calculate GSM/UMTS/LTE Coverage		
7	6	Calculate GSM/UMTS/LTE Coverage		
8	7	Calculate Hubway Bike Sharing Usage KPIs		
9	8	Calculate Hubway Bike Sharing Usage KPIs		
10	9	Calculate Hubway Bike Sharing Usage KPIs		
11	10	Calculate New York City Taxi Performance KPIs		
12	11	Calculate New York City Taxi Performance KPIs		
13	12	Calculate New York City Taxi Performance KPIs		
14	13	Create MTG Trading Card Database By API		
15	14	Create MTG Trading Card Database By API		
16	15	Create MTG Trading Card Database By API		
17	16	Create MTG Trading Card Database By Crawler		
18	17	Create MTG Trading Card Database By Crawler		
19	18	Create MTG Trading Card Database By Crawler		
20	19	Create Searchable XKCD Database		
21	20	Create Searchable XKCD Database		
22	21	Create Searchable XKCD Database		
23	22	Create Searchable IP Geolocation Database		
24	23	Create Searchable IP Geolocation Database		
25	24	Create Searchable IP Geolocation Database		
26	25	Automatic Spotify Music Categorization		
27	26	Automatic Spotify Music Categorization		
28	27	Automatic Spotify Music Categorization		
29				

<https://tinyurl.com/BigDataPracticalExam20252026>



# Stop Your VM Instances

**DON'T FORGET TO  
STOP YOUR VM  
INSTANCE!**



```
gcloud compute instances stop big-data
```

