

IF3111 – Model Entity Relationship

Wikan Danar
Departemen Teknik Informatika
Institut Teknologi Bandung



IF-ITB/WD dari Silberschatz, modifikasi YA/29 Juli 2003
IF3111 – Model ER


Page 1

Weak Entity Sets

- An entity set that does not have a primary key is referred to as a *weak entity set*.
- The existence of a weak entity set depends on the existence of a *identifying entity set*
 - it must relate to the identifying entity set via a total, one-to-many relationship set from the identifying to the weak entity set
 - Identifying relationship depicted using a double diamond
- The *discriminator (or partial key)* of a weak entity set is the set of attributes that distinguishes among all the entities of a weak entity set.
- The primary key of a weak entity set is formed by the primary key of the strong entity set on which the weak entity set is existence dependent, plus the weak entity set's discriminator.

Weak Entity Sets (Cont.)

- We depict a weak entity set by double rectangles.
- We underline the discriminator of a weak entity set with a dashed line.
- *payment-number* – discriminator of the *payment* entity set
- Primary key for *payment* – (*loan-number*, *payment-number*)



Weak Entity Sets (Cont.)

- Note: the primary key of the strong entity set is not explicitly stored with the weak entity set, since it is implicit in the identifying relationship.
- If *loan-number* were explicitly stored, *payment* could be made a strong entity, but then the relationship between *payment* and *loan* would be duplicated by an implicit relationship defined by the attribute *loan-number* common to *payment* and *loan*

More Weak Entity Set Examples


- In a university, a *course* is a strong entity and a *course-offering* can be modeled as a weak entity
- The discriminator of *course-offering* would be *semester* (including year) and *section-number* (if there is more than one section)
- If we model *course-offering* as a strong entity we would model *course-number* as an attribute.

Then the relationship with *course* would be implicit in the *course-number* attribute

Specialization

- Top-down design process; we designate subgroupings within an entity set that are distinctive from other entities in the set.
- These subgroupings become lower-level entity sets that have attributes or participate in relationships that do not apply to the higher-level entity set.
- Depicted by a *triangle* component labeled ISA (E.g. *customer* "is a" *person*).
- **Attribute inheritance** – a lower-level entity set inherits all the attributes and relationship participation of the higher-level entity set to which it is linked.

Specialization Example



Generalization

- A bottom-up design process – combine a number of entity sets that share the same features into a higher-level entity set.
- Specialization and generalization are simple inversions of each other; they are represented in an E-R diagram in the same way.
- The terms specialization and generalization are used interchangeably.

Specialization and Generalization (Contd.)

- Can have multiple specializations of an entity set based on different features.
- E.g. *permanent-employee* vs. *temporary-employee*, in addition to *officer* vs. *secretary* vs. *teller*
- Each particular employee would be
 - a member of one of *permanent-employee* or *temporary-employee*,
 - and also a member of one of *officer*, *secretary*, or *teller*
- The ISA relationship also referred to as **superclass - subclass** relationship



Design Constraints on a Specialization/Generalization

- Constraint on which entities can be members of a given lower-level entity set.
 - condition-defined
 - user-defined
- Constraint on whether or not entities may belong to more than one lower-level entity set within a single generalization.
 - Disjoint
 - an entity can belong to only one lower-level entity set
 - Noted in E-R diagram by writing *disjoint* next to the ISA triangle
 - Overlapping
 - an entity can belong to more than one lower-level entity set




Design Constraints on a Specialization/Generalization (Contd.)

- Completeness constraint -- specifies whether or not an entity in the higher-level entity set must belong to at least one of the lower-level entity sets within a generalization.
 - **total** : an entity must belong to one of the lower-level entity sets
 - **partial**: an entity need not belong to one of the lower-level entity sets

Aggregation


- Consider the ternary relationship *works-on*, which we saw earlier
- Suppose we want to record managers for tasks performed by an employee at a branch



Aggregation (Cont.)

- Relationship sets *works-on* and *manages* represent overlapping information
 - Every *manages* relationship corresponds to a *works-on* relationship
 - However, some *works-on* relationships may not correspond to any *manages* relationships
 - So we can't discard the *works-on* relationship
- Eliminate this redundancy via *aggregation*
 - Treat relationship as an abstract entity
 - Allows relationships between relationships
 - Abstraction of relationship into new entity
- Without introducing redundancy, the following diagram represents:
 - An employee works on a particular job at a particular branch
 - An employee, branch, job combination may have an associated manager


E-R Diagram With Aggregation




E-R Design Decisions

- The use of an attribute or entity set to represent an object.
- Whether a real-world concept is best expressed by an entity set or a relationship set.
- The use of a ternary relationship versus a pair of binary relationships.
- The use of a strong or weak entity set.
- The use of specialization/generalization – contributes to modularity in the design.
- The use of aggregation – can treat the aggregate entity set as a single unit without concern for the details of its internal structure.

E-R Diagram for a Banking Enterprise



Summary of Symbols Used in E-R Notation



Summary of Symbols (Cont.)

