

Résumé des principaux objets JavaScript (3 colonnes : propriétés, méthodes, événements)

Window		
closed	alert()	
document	blur()	onload
frames	clearInterval()	onunload
history	clearTimeout()	ononline
location	close()	onoffline
name	confirm()	onmessage
opener	focus()	
parent	open()	
scrollbars	postMessage()	
self	print()	
top	setInterval()	
	setTimeout()	

document		
alinkColor	clear()	onvisibilitychange
anchors	close()	
applets	getElementById()	
bgColor	getElementsByClassName()	
cookie	getElementsByName()	
domain	getElementsByTagName()	
fgColor	open()	
forms	querySelector()	
form	querySelectorAll()	
hidden	write()	
ids	writeln()	
images		
lastModified		
layers		
linkColor		
links		
plugins		
referrer		
title		
URL/location		
vlinkColor		

location		
host	replace()	
hostname	reload()	
href		
pathname		
port		
protocol		
search		

history		
current	back()	popstate
length	forward()	
next	go()	
previous	pushState()	
state	replaceState()	

* et ses propriétés :
customError
patternMismatch
rangeOverflow
rangeUnderflow
stepMismatch
tooLong
typeMismatch
valueMissing
valid

form		
action	checkValidity()	onclick
elements	reset()	oninvalid
id	submit()	onreset
length		onsubmit
method		
name		
target		

text, texarea, password		
defaultValue	blur()	onblur
disabled	focus()	onchange
form	select()	onclick
id	setCustomValidity()	onfocus
name		oninput
pattern		oninvalid
readOnly		onmouseout
type		onmouseover
validity*		onselect
value		
valueAsDate		

button, reset, submit		
disabled	blur()	onblur
form	click()	onclick
id	focus()	onfocus
type		onmousedown
value		onmouseout
		onmouseover
		onmouseup

radio, checkbox		
checked	blur()	onblur
defaultChecked	click()	onclick
disabled	focus()	onfocus
id		onmouseout
form		onmouseover
name		
type		
value		

hidden		
defaultValue		
form		
id		
name		
type		
value		

fileUpload		
disabled	blur()	onblur
form	focus()	onchange
id	select()	onclick
name		oninput
readOnly		onfocus
type		onmouseout
value		onmouseover

select		
disabled	blur()	onblur
form	focus()	onchange
id		onclick
length		onfocus
name		onmouseout
options		onmouseover
selectedIndex		
value		
type		

option		
defaultSelected		
id		
index		
selected		
text		
value		

link		
id		onclick
host		onmouseout
hostname		onmouseover
href		
pathname		
port		
protocol		
search		
target		

navigator		
appCodeName		onoffline
appName		ononline
appVersion		
battery		
geolocation*		
language		
mimeTypes		
onLine		
platform		
plugins		
userAgent		

* et ses méthodes :
getCurrentPosition()
watchPosition()

localStorage/sessionStorage		
length	clear()	
	getItem()	
	removeItem()	
	setItem()	

image		
border		onclick
id		onmouseout
height		onmouseover
hspace		
lowsrc		
name		
src		
vspace		
width		

Tout élément HTML affichable		
className	addEventListener()	onclick
classList	matchesSelector()	onmouseover
dataset		onmouseout
id		
style		

event (argument** de fonction)		
className	addEventListener()	onclick
classList	matchesSelector()	onmouseover
data		onmouseout
dataset		
id		
style		
target		

** et d'autres propriétés
spécifiques en fonction de
l'événement

Math		
PI	abs()	
SQRT1_2	ceil()	
SQRT2	floor()	
	max()	
	min()	
	pow()	
	random()	
	round()	
	sqrt()	

Date		
	getDate()	
	getDay()	
	getFullYear()	
	getHours()	
	getMinutes()	
	getMonth()	
	getSeconds()	
	getTime()	
	getYear()	
	setDate()	
	setFullYear()	
	setHours()	
	setMinutes()	
	setMonth()	
	setSeconds()	
	setTime()	
	setYear()	
	toString()	

String		
length	big()	
	blink()	
	bold()	
	charAt()	
	charCodeAt()	
	concat()	
	fixed()	
	fontcolor()	
	fontsize()	
	fromCharCode()	
	indexOf()	
	italics()	
	lastIndexOf()	
	match()	
	replace()	
	search()	
	small()	
	split()	
	strike()	
	sub()	
	substr()	
	substring()	
	sup()	
	toLowerCase()	
	toUpperCase()	