Closing Edge Loops at Quantization Time: Helix Constraints for T-Mesh Quantization

Research note — draft, not peer reviewed

openclare project

17 October 2026

Abstract

Automatic quad remeshers produce edge loops that wind round a part of the shape as helices instead of closing into rings, a defect that makes such meshes awkward to edit by hand. Bommes et al. [2] identified these *q-helices* and remove them after meshing, by grid-preserving operators applied to the finished quad mesh. We take the opposite route and prevent them where the integer structure of the mesh is decided: in the quantization of a T-mesh. A straight walk across the rectangles of a T-mesh that comes back to its start defines a *turn*; we show that the pitch of the corresponding helix is a linear form in the integer lengths of the arcs, so that closing the helix is a linear constraint on the quantization. We add such constraints to a minimum-deviation-flow quantizer [5] through a least-change projection and targeted repair walks, select among a few ways of finding turns by the share of spiral edges they leave, and guard against folds and budget drift. On our bench the share of edges on spiral loops at 3,000 quads drops from 16.7% to 6.0% on twelve models; on a human body remeshed at the face count of the hand-made base mesh it drops from 12.1% to 1.1%, below the 2.5% of the hand-made mesh. We relate turns to the twist of flat cylinders in the theory of Jenkins–Strebel differentials [10] and list the open problems that a complete treatment would need to solve.

1 Introduction

Field-aligned quad remeshing has reached a level where element shape and alignment are rarely the limiting factor. What remains is structure: the way edge loops run across the surface. Artists expect a loop round an arm, a leg or a neck to be a ring. Automatic methods often produce a helix instead: the loop goes round, comes back one or a few rows further, and winds along the whole part. The problem is old and well identified: Bommes et al. showed in 2011 that helical configurations are what keeps the base complex of an otherwise good quad mesh dense [2].

This note documents an approach developed in the open-source remesher openclare, and positions it against the literature we could check. Our contributions are:

1. *Turns* of a T-mesh and their *shift*: a straight walk across the rectangles of a T-mesh that returns to its starting side, and a linear form in the arc lengths whose integer value is the pitch of the helix the walk becomes in the quad mesh (Section 3).

2. Closing turns within T-mesh quantization: a least-change projection of the target lengths, an integer search, and repair walks judged on the turns, with safeguards on folds, distortion and budget (Section 4).

3. A classification of the edge loops of a quad mesh into closed, spiral, open and border loops, with spirals of order up to four (Section 5), and a bench that holds automatic remeshers against meshes modelled by hand (Section 6).

The results are preliminary: one seed per model, one implementation, and heuristics where an exact formulation is still missing (Section 8).

2 Background and related work

Counting singularities. On a closed surface of genus g, the valences $k(v)$ of a quad mesh satisfy $\sum_v (4-k(v)) = 4\chi = 8(1-g)$. With only valences 3 and 5, $n_3 - n_5 = 8(1-g)$: a sphere or a closed human body needs at least eight vertices of valence three. This bound says how many singular vertices are needed, not where they go; a hand-made human base mesh has hundreds.

Quad meshes as quartic differentials. Lei et al. [6] show that a closed quad mesh induces a Riemann surface and a meromorphic quartic differential $\omega = (dz)^4$ whose zeros and poles are the singular vertices, a vertex of valence k being of order $k-4$; conversely a quartic differential with finite trajectories induces a quad mesh. The divisor of singularities then satisfies the Abel–Jacobi condition, and a divisor satisfying it is the divisor of a meromorphic quartic differential. Zheng et al. [11] optimize the singularity configuration by integer programming to satisfy the condition. Two points matter here. First, the condition is stated with holomorphic one-forms, which a surface of genus zero does not have; our reading is that in genus zero it adds nothing to the degree condition (this is an inference, not a statement of the papers). Second, the paper lists as an open problem the guarantee that all trajectories are *finite*. A trajectory that is not finite is precisely an edge loop that does not close: the helices of this note.

Closed trajectories. A quadratic differential all of whose non-critical horizontal trajectories are closed is a Jenkins–Strebel differential [10]; the complement of its critical graph is a union of flat cylinders, each with a height and a *twist*, the shift with which the cylinder is glued back after a cut along its core curve. In a quad mesh, a ring of quads is such a cylinder; a helix is a cylinder whose gluing is shifted by a whole number of rows. Section 3 makes this precise at the level of a T-mesh.

Helices in quad meshes. Bommes et al. [2] define a *q-helix* as a dual parametric line of a quad mesh with an integer *pitch* h and *turn length* τ: walking τ steps along it is equivalent to h side-steps. They detect minimal q-helices ($h \leq \tau$, no sub-helix of smaller pitch) by the self-intersections of orthogonal dual lines, and remove them greedily with *grid-preserving operators*: closed dual paths of shift and collapse steps, found by a graph search, that keep the mesh all-quad and its singularities in place. Tangential smoothing then repairs the distortion the shifts introduce. Their experiments remove most helices (from 19–52 down to 1–23 per model) and coarsen the base complex accordingly. They note that aligning pairs of singularities directly in the parametrization, as Myles et al. do for T-meshes [9], is ambiguous to automate. The approach works on a finished mesh; it does not touch the parametrization or its quantization.

T-mesh quantization. Integer-grid maps [1] and their quantization decide the integer structure of a quad mesh. Campen et al. quantize via the integer lengths of the arcs of a T-mesh traced in a seamless parametrization [4]. Lyon et al. solve a constrained version as an integer linear program, bounding the directional deviation of the separatrices of the resulting layout [8] (we could only read the abstract). Heistermann et al. cast quantization as a minimum-deviation flow on a bi-directed graph and give a fast approximate solver and an exact refinement [5]; openclare follows their formulation. To our knowledge none of these constrains the helices: the lengths are chosen for consistency, validity and closeness to the parametrization, and the loops close or spiral as a side effect.

Loops by construction. Dual loops meshing [3] builds a layout from loops traced on the surface, which close by construction; it produces coarse layouts rather than dense field-aligned meshes.

Measuring loops. QuadGPT [7] counts *quad rings* (closed loops of faces) and *quad lines* (open strips) and uses the share of faces in rings and the mean length of lines as reward signals for preference optimization; it does not report them as evaluation metrics, nor does it tell spirals from open lines.

3 Turns of a T-mesh

Setting. A T-mesh is a partition of the surface into rectangles, the *patches*, whose sides are made of *arcs*; nodes where a trace stops on another are T-junctions, and the singular vertices of the field are nodes. Each patch P has local coordinates with its first corner at the origin and its sides along the axes. A quantization assigns every arc a a length $\ell_a \in \mathbb{Z}_{\geq 0}$ such that opposite sides of every patch have equal length; the quad mesh is then read off as the integer grid of each patch.

Definition 1 (Turn)**.** *A* turn γ *is a straight walk across patches: it enters a patch through a side, leaves through the opposite side at the same distance from the corresponding corner, enters the neighbouring patch across the arc it reaches, and so on, until it comes back into its first patch through its first side, with the four quarter-turns of the crossings summing to zero.*

Crossing from patch P to patch Q across an arc composes a quarter-turn rotation of the local frame with a translation whose components are signed sums of arc lengths along the rims of P and Q: the position of a rim point is the sum of the lengths of the arcs between it and the first corner.

Proposition 1 (The shift of a turn is linear)**.** *For a turn γ there are integer coefficients c_a, independent of the lengths, such that after a full turn a point of the first side has moved across the walking direction by*

$$s_\gamma(\ell) = \sum_a c_a \, \ell_a.$$

For integer lengths, the dual line of the quad mesh that follows γ comes back $s_\gamma(\ell)$ rows beside itself: it closes into a ring if and only if $s_\gamma(\ell) = 0$, and is otherwise a helix of pitch $|s_\gamma(\ell)|$ in the sense of [2].

Sketch. Each crossing is a map $x \mapsto R_k x + t$ with R_k a rotation by k quarter-turns and t a vector whose entries are sums of $\pm\ell_a$. The composition along γ has total rotation zero, hence is a translation $T_\gamma(\ell)$, linear in ℓ with integer coefficients. Its component along the walking direction does not move a point of the first side off that side; its component across is $s_\gamma(\ell)$. The walk crosses no singularity (singularities are nodes, never inside a patch), so the quad mesh is a regular grid along it, and a dual line at distance o from the first corner comes back at distance $o + s_\gamma(\ell)$. □

In openclare (`quantization/tubes.rs`) the shift is built once per turn as an expression in the arc lengths, by composing the rim expressions of the crossed patches; evaluating it with the real lengths of the parametrization gives the *real shift*, the twist the field itself would give the cylinder.

Remark 1. *A turn round a part of the shape whose real shift is far from zero is not a rounding artefact: the field winds round the part. We only hold turns whose real shift is a small share of their length, the* lean*; a turn round a group of singularities, by contrast, may legitimately come back shifted.*

4 Closing turns in quantization

The quantizer of openclare minimizes, as in [5], a weighted deviation $\sum_a w_a \, |\ell_a - \lambda \, r_a|$ of the integer lengths from the scaled real lengths λr_a, subject to the balance of each patch, by cancelling improving walks in a strip network; the scale λ is searched for the number of quads asked for, and arcs that would merge two singularities are held open. Closing turns is a side constraint that is not a flow constraint. We handle it in three steps.

Finding turns. From points at given shares along each side of each patch, we walk straight across patches and keep the walks that return. A turn is *held* if its real shift is above a small threshold and its lean below a bound, and if its length is below a multiple of the side of the T-mesh (the side of a square of its area). Several *ways* are tried: starting shares $\{0.5\}$ or $\{0.2, 0.5, 0.8\}$, lean bounds 0.05 or 0.12, length bounds 2 or 6 sides.

Least-change projection. The target lengths are changed as little as possible, in the weighted least squares sense, for every held turn to have zero shift and every patch to stay balanced:

$$\min_x \sum_a \frac{(x_a - r_a)^2}{w_a} \quad \text{s.t.} \quad Ax = 0, \quad s_\gamma(x) = 0 \;\; \forall \gamma \in H,$$

solved by a sparse Cholesky factorization of $AW^{-1}A^\top$. If the system cannot be met, the held turn left with the largest shift is let go and the projection repeated.

Integer search and repair. The integer search of the quantizer runs on the projected targets. Rounding leaves some turns shifted by one or a few rows. Repair walks are then taken one at a time: a walk is guided by a bias along the arcs of the shifted turns, and accepted if it reduces the total shift, costs little in deviation, keeps the structure intact and the number of quads within tolerance. A second, *aimed* repair treats each held turn still shifted on its own: the bias is put on its arcs alone, and a walk is accepted if it shifts that turn less and the others no more.

Selection and safeguards. Each way gives a quantization. Its quad mesh connectivity is built and the share of edges on spiral loops measured (Section 5); the way with the fewest spirals is kept, provided its number of quads is within tolerance and its mean deviation from the real lengths at most 1.5 times that of the plain search. The ways are independent and run in parallel. After meshing, if the kept quantization makes a face fold over the surface, the plain quantization is meshed as well and the mesh with fewer folds kept.

5 Measuring loops

An edge loop is followed straight through every regular vertex (valence four, interior), each edge belonging to one loop. A loop is *closed* if it comes back to its start; *border* if it runs from border to border; *open* if it stops at an irregular vertex or a non-quad face; and *spiral*, whatever its ends, if a strip of quads leaving it across meets it again, the same way round, within $k_{\max} = 4$ quads. The last test catches helices of pitch up to four, including bundles of interleaved helices [2], while a ring is met again only round a whole torus or over a cap the other way round. We report the share of edges on each kind of loop, edges of borders left out.

6 Experiments

All numbers come from the openclare bench (repository `marcgardent/openclare`), one seed per model, measured on the output meshes against their sources. Models: twelve organic and

mechanical models for development, a corpus of 31 models for the full bench, and two human bodies from Blender's Essentials library (CC0) whose base meshes, modelled by hand, serve as references.

Spirals on the twelve development models, 3,000 quads. Table 1 shows the successive steps. Fidelity (Hausdorff distance, per mil of the diagonal) and the mean corner deviation stay within about one per cent; the last step trades a little of both for a third fewer spiral edges.

	spiral edges	Hausdorff (‰)	corner deviation (deg)
no closing	16.7%	8.77	4.75
closing, one way kept by spirals	9.7%	8.57	4.85
+ leaning ways, aimed repair	9.1%	8.58	4.91
+ longer turns, deviation cap	6.0%	8.68	5.01

Table 1: Mean over twelve models; each line adds to the one above.

Against other remeshers. On the full bench at 3,000 quads, the mean share of spiral edges is 19.1% for Quad Remesher, 21.9% for QuadriFlow and 25.3% for AutoRemesher, against 12.3% for openclare with the first version of closing (and 17.3% without).

Against the hand-made mesh. The male body of the Essentials library has a base mesh of 10,590 quads modelled by hand, with 2.5% of spiral edges. Remeshed by openclare at that count before closing, it had 12.1% (one leg was a single helix from hip to ankle, its turns leaning more than the first lean bound allowed). With the method of Section 4: 10,467 quads, 1.1% spiral edges, 36.2% of loops closed against 24.7% for the hand-made mesh, a Hausdorff distance of 4.6‰ against 6.5‰, and a mean corner deviation of 4.1 degrees against 9.2.

The quad sphere. Not a result of closing but of the field. An icosphere remeshed at 3,000 quads had 32 irregular vertices (20 of valence three, 12 of valence five), the pattern of its own facets, because the field was pulled towards curvature directions that a sphere does not have; at 1,000 quads it had the eight poles but no structure (a base complex of 1,010 patches) and 87% of spiral edges. With directions not trusted where the two principal curvatures are within 10% of one another, both give the layout of a cube: eight poles of valence three, six patches, no spiral.

7 An exact look at the closing system

To see how far the projection of Section 4 is from what the constraints allow, openclare exports, for each way of finding turns, the system it works on: the real lengths of the 2,069 arcs of the T-mesh of the male body at 10,590 quads, the 1,552 balance equations of its patches, every turn found with its shift, and the lower bounds the integer search placed on arcs to keep singularities apart (30 to 36 arcs held at length one). We solve it with HiGHS through SciPy, in real numbers.

Where the conflict lies. Every held turn can be closed on its own with all bounds kept. All held turns can be closed together if the lengths are only asked to be non-negative. With the bounds of separation, they cannot. Giving up the least total amount of those bounds needed to close all held turns, a linear program, shows that for three of the four ways examined a *single* arc must collapse, in two of them the same arc, 0.08 quad edges long, at the left wrist; the fourth needs eleven, round the eyes and the hands. The conflict between closing loops and keeping singularities apart is thus real, but very local.

How far the heuristic is. With every bound kept, the largest set of held turns that can be closed together is found by a mixed-integer program with one binary per turn (Table 2). The projection keeps far fewer: it removes, one at a time, the turn left most shifted by a least-squares projection whose negative lengths are clamped to zero, and a single clamped arc can make it drop dozens of turns that conflict with nothing.

way	held	kept by the projection	closable together, bounds kept
7	169	49	160
4	160	48	154
5	78	46	73
1	88	53	87
0	84	49	83
2	86	47	82
3	52	46	51
6	48	42	47

Table 2: Male body at 10,590 quads. Real numbers; the numbering of the ways is the order in which they finished.

In whole numbers, the same mixed-integer program did not finish within fifteen minutes on the two systems tried.

From reals to whole numbers. We then fed the engine better targets and measured what survives its integer search (Table 3). Aiming at the lengths of the linear program closes fewer loops in the end: the weighted L^1 objective puts the changes on few arcs, the deviation from the real lengths grows, and the variants with the fewest spirals are refused by the deviation cap. A projection that holds lengths at a floor instead of clamping them (an active-set method on the same Cholesky solver) keeps every held turn closed in real numbers; yet after the integer search 117 of 169 are shifted again, and the mesh spirals more. With the current projection, too, about 40% of the turns it kept are shifted after the integer search. The bottleneck is not the projection but the rounding: the integer search follows the targets but ignores the shifts.

targets of the integer search	turns closed in reals	still shifted after	spiral edges (mesh)
projection, clamped (current)	about 50	10–23 of them	1.1%
linear program, L^1	up to 160	—	11.9%
active set, floor 0	all held (up to 169)	117 of 169	3.3%
active set, floor half the real length	36–72	—	9.8%

Table 3: Male body at 10,590 quads, one run each; the mesh keeps the way with the fewest spirals, so its share is that of a single way.

8 Open problems

Open problem 1 (Exact formulation)**.** *Minimize the deviation of the quantization subject to balance, validity and $s_\gamma(\ell) = 0$ for a set of turns. This is a minimum-deviation flow with linear side constraints; how much of the exact machinery of [5] carries over is open. Section 7 shows that the linear relaxation already closes almost all held turns.*

Open problem 2 (Closing in whole numbers)**.** *The solutions of the balance and shift equations in whole numbers form a lattice. Can the integer search move within it, for instance from a*

reduced basis (Hermite normal form, LLL) and a nearest-plane rounding of the targets, instead of rounding first and repairing after? The measurements above say this is where the loops are lost.

Open problem 3 (Which turns)**.** *The straight walks that return are infinite in number; we sample them. Is there a finite set of turns, a basis in some homological sense of the regular region of the T-mesh, whose closing implies that every loop of the quad mesh closes?*

Open problem 4 (Feasibility)**.** *On a human torso, some held turns cannot be closed together: the projection lets them go. Our hypothesis is that pairs of singularities between two rings force a dislocation, and that closing all rings needs the poles to face one another, which the separation of singularities forbids at the scale of the T-mesh. A capped cylinder shows the same conflict: its layout of six patches exists, but only with arcs our quantizer will not bring to zero. On the male body the conflict comes down to one or a few arcs (Section 7). When is a set of turns simultaneously closable, in terms of the singularity configuration?*

Open problem 5 (Finite trajectories)**.** *In the language of [6]: given a singularity configuration on a surface of genus zero, when does a quartic differential with all trajectories finite exist, and how close to a given cross field can it be chosen? Our turns are its discrete, integer version.*

Towards proofs. Proposition 1 is elementary but its statement over a T-mesh with T-junctions is easy to get wrong. A formal proof in a proof assistant, over an abstract complex of rectangles with integer side lengths, would settle it and could carry the sufficiency question of the second problem for special classes of layouts.

Reproducibility. The method is implemented in openclare, Rust, branches `close-quantized` (closing, measure) and `quadsphere` (confidence floor, merged traces); the bench is driven by `bench/run.py` and the marks by `scripts/scores.py`.

References

[1] David Bommes, Henrik Zimmer, and Leif Kobbelt. Mixed-integer quadrangulation. *ACM Transactions on Graphics*, 28(3), 2009. Proc. SIGGRAPH 2009.

[2] David Bommes, Timm Lempfer, and Leif Kobbelt. Global structure optimization of quadrilateral meshes. *Computer Graphics Forum*, 30(2):375–384, 2011. Proc. Eurographics 2011. Read in full.

[3] Marcel Campen, David Bommes, and Leif Kobbelt. Dual loops meshing: Quality quad layouts on manifolds. *ACM Transactions on Graphics*, 31(4), 2012. doi: 10.1145/2185520.2185606. Proc. SIGGRAPH 2012. Abstract read.

[4] Marcel Campen, David Bommes, and Leif Kobbelt. Quantized global parametrization. *ACM Transactions on Graphics*, 34(6):1–12, 2015. doi: 10.1145/2816795.2818140. Proc. SIGGRAPH Asia 2015. Abstract read.

[5] Martin Heistermann, Jethro Warnett, and David Bommes. Min-deviation-flow in bi-directed graphs for T-mesh quantization. *ACM Transactions on Graphics*, 42(4), 2023. doi: 10.1145/3592437. Proc. SIGGRAPH 2023. Abstract read; our quantizer follows its formulation.

[6] Na Lei, Xiaopeng Zheng, Zhongxuan Luo, Feng Luo, and Xianfeng Gu. Quadrilateral mesh generation II: Meromorphic quartic differentials and Abel-Jacobi condition. *Computer Methods in Applied Mechanics and Engineering*, 366, 2020. Main theorems read (Thm. 4.7–4.13).

[7] Jian Liu, Chunshi Wang, Song Guo, Haohan Weng, Zhen Zhou, Zhiqi Li, Jiaao Yu, Yiling Zhu, Jing Xu, Biwen Lei, Zhuo Chen, and Chunchao Guo. QuadGPT: Native quadrilateral mesh generation with autoregressive models, 2025. Appendix B.2 read: quad rings and quad lines as reward signals.

[8] Max Lyon, Marcel Campen, and Leif Kobbelt. Quad layouts via constrained T-mesh quantization. *Computer Graphics Forum*, 40(2):305–314, 2021. doi: 10.1111/cgf.142634. Proc. Eurographics 2021. Abstract read; the full text was not openly accessible.

[9] Ashish Myles, Nico Pietroni, Denis Kovacs, and Denis Zorin. Feature-aligned T-meshes. *ACM Transactions on Graphics*, 29(4):1–11, 2010. As cited by [2].

[10] Kurt Strebel. *Quadratic Differentials*. Ergebnisse der Mathematik und ihrer Grenzgebiete. Springer, 1984.

[11] Xiaopeng Zheng, Yiming Zhu, Na Lei, Zhongxuan Luo, and Xianfeng Gu. Quadrilateral mesh generation III: Optimizing singularity configuration based on Abel-Jacobi theory, 2020. Abstract read.