

“query lite”

Índice Movies
busca
q = query
title tem star

/movies/_search?q=title:star

ano lançamento
maior que 2010
titulo tem trek

/movies/_search?q=+year:>2010+title:trek

Não é sempre tão simples...

- espaços etc. precisam ser codificados na URL.

/movies/_search?q=+year:>2010+title:trek



/movies/_search?q=%2Byear%3A%3E2010+%2Btitle%3Atrek

E pode ser
perigoso

Complexo e difícil de depurar

Pode ser um problema de
segurança se exposto aos usuários

Frágil: um único caractere errado
e tudo perdido

Pode ser bom para experimentos
rápidos

Saiba Mais.

Isso é conhecido como “URI Search”. Veja a documentação do Elasticsearch.

É bastante funcional, mas só é indicado para testes rápidos usando Curl

Docs

Parameters

edit

The parameters allowed in the URI are:

Name	Description
<code>q</code>	The query string (maps to the <code>query_string</code> query, see <i>Query String Query</i> for more details).
<code>df</code>	The default field to use when no field prefix is defined within the query.
<code>analyzer</code>	The analyzer name to be used when analyzing the query string.
<code>analyze_wildcard</code>	Should wildcard and prefix queries be analyzed or not. Defaults to <code>false</code> .
<code>batched_reduce_size</code>	The number of shard results that should be reduced at once on the coordinating node. This value should be used as a protection mechanism to reduce the memory overhead per search request if the potential number of shards in the request can be large.
<code>default_operator</code>	The default operator to be used, can be <code>AND</code> or <code>OR</code> . Defaults to <code>OR</code> .
<code>lenient</code>	If set to <code>true</code> will cause format based failures (like providing text to a numeric field) to be ignored. Defaults to <code>false</code> .
<code>explain</code>	For each hit, contain an explanation of how scoring of the hits was computed.
<code>_source</code>	Set to <code>false</code> to disable retrieval of the <code>_source</code> field. You can also retrieve part of the document by using <code>_source_include</code> & <code>_source_exclude</code> (see the request body documentation for more details)
<code>stored_fields</code>	The selective stored fields of the document to return for each hit, comma delimited. Not specifying any value will cause no fields to return.

PROF.
FERNANDO
AMARAL