

Concurrent programming

Linked Lists: Locking, Lock-Free and Beyond


Companion slides for

The Art of Multiprocessor Programming

by Maurice Herlihy, Nir Shavit, Victor Luchangco,
and Michael Spear

Modified by Piotr Witkowski

Last Lecture: Spin-Locks



Today: Concurrent Objects

- Adding threads should not lower throughput
 - Contention effects
 - Mostly fixed by Queue locks

Today: Concurrent Objects

- Adding threads should not lower throughput
 - Contention effects
 - Mostly fixed by Queue locks
- Should increase throughput
 - Not possible if inherently sequential
 - Surprising things are parallelizable

Coarse-Grained Synchronization

- Each method locks the object
 - Avoid contention using queue locks

Coarse-Grained Synchronization

- Each method locks the object
 - Avoid contention using queue locks
 - Easy to reason about
 - In simple cases

Coarse-Grained Synchronization

- Each method locks the object
 - Avoid contention using queue locks
 - Easy to reason about
 - In simple cases
- So, are we done?

Coarse-Grained Synchronization

- Sequential bottleneck
 - Threads “stand in line”

Coarse-Grained Synchronization

- Sequential bottleneck
 - Threads “stand in line”
- Adding more threads
 - Does not improve throughput
 - Struggle to keep it from getting worse

Coarse-Grained Synchronization

- Sequential bottleneck
 - Threads “stand in line”
- Adding more threads
 - Does not improve throughput
 - Struggle to keep it from getting worse
- So why even use a multiprocessor?
 - Well, some apps inherently parallel ...

This Lecture

- Introduce four “patterns”
 - Bag of tricks ...
 - Methods that work more than once ...

This Lecture

- Introduce four “patterns”
 - Bag of tricks ...
 - Methods that work more than once ...
- For highly-concurrent objects
 - Concurrent access
 - More threads, more throughput

First:

Fine-Grained Synchronization

- Instead of using a single lock ...

First:

Fine-Grained Synchronization

- Instead of using a single lock ...
- Split object into
 - Independently-synchronized components

First:

Fine-Grained Synchronization

- Instead of using a single lock ...
- Split object into
 - Independently-synchronized components
- Methods conflict when they access
 - The same component ...
 - At the same time

Second: Optimistic Synchronization

- Search without locking ...

Second: Optimistic Synchronization

- Search without locking ...
- If you find it, lock and check ...
 - OK: we are done
 - Oops: start over

Second: Optimistic Synchronization

- Search without locking ...
- If you find it, lock and check ...
 - OK: we are done
 - Oops: start over
- Evaluation
 - Usually cheaper than locking, but
 - Mistakes are expensive

Third:

Lazy Synchronization

- Postpone hard work

Third:

Lazy Synchronization

- Postpone hard work
- Removing components is tricky

Third:

Lazy Synchronization

- Postpone hard work
- Removing components is tricky
 - Logical removal
 - Mark component to be deleted

Third:

Lazy Synchronization

- Postpone hard work
- Removing components is tricky
 - Logical removal
 - Mark component to be deleted
 - Physical removal
 - Do what needs to be done

Fourth:

Lock-Free Synchronization

- Don't use locks at all
 - Use `compareAndSet()` & relatives ...

Fourth:

Lock-Free Synchronization

- Don't use locks at all
 - Use `compareAndSet()` & relatives ...
- Advantages
 - No Scheduler Assumptions/Support

Fourth:

Lock-Free Synchronization

- Don't use locks at all
 - Use `compareAndSet()` & relatives ...
- Advantages
 - No Scheduler Assumptions/Support
- Disadvantages
 - Complex
 - Sometimes high overhead

Linked List

- Illustrate these patterns ...
- Using a list-based Set
 - Common application
 - Building block for other apps

Set Interface

- Unordered collection of items

Set Interface

- Unordered collection of items
- No duplicates

Set Interface


- Unordered collection of items
- No duplicates
- Methods
 - `add(x)` put `x` in set
 - `remove(x)` take `x` out of set
 - `contains(x)` tests if `x` in set

List-Based Sets

```
public interface Set<T> {  
    public boolean add(T x) ;  
    public boolean remove(T x) ;  
    public boolean contains(T x) ;  
}
```

List-Based Sets


```
public interface Set<T> {  
    public boolean add(T x) ;  
    public boolean remove(T x) ;  
    public boolean contains(T x) ;  
}
```



Add item to set

List-Based Sets


```
public interface Set<T> {  
    public boolean add(T x);  
public boolean remove(T x);  
    public boolean contains(T x);  
}
```



Remove item from set

List-Based Sets

```
public interface Set<T> {  
    public boolean add(T x);  
    public boolean remove(T x);  
    public boolean contains(T x);  
}
```



Is item in set?

List Node

```
public class Node {  
    public T item;  
    public int key;  
    public volatile Node next;  
}
```

List Node

```
public class Node {  
    public T item;  
    public int key;  
    public volatile Node next;  
}
```



item of interest


List Node

```
public class Node {  
    public T item;  
    public int key;  
    public volatile Node next;  
}
```

Usually hash code


List Node

```
public class Node {  
    public T item;  
    public int key;  
    public volatile Node next;  
}
```



Reference to next node

The List-Based Set



Sorted with Sentinel nodes
(min & max possible keys)

Reasoning about Concurrent Objects

- Invariant
 - Property that always holds

Reasoning about Concurrent Objects

- Invariant
 - Property that always holds
- Established because
 - True when object is **created**
 - Truth **preserved** by each method
 - Each **step** of each method

Specifically ...

- Invariants preserved by
 - `add()`
 - `remove()`
 - `contains()`

Specifically ...

- Invariants preserved by
 - `add()`
 - `remove()`
 - `contains()`
- Most steps are trivial
 - Usually one step tricky
 - Often linearization point

Interference

- Invariants make sense only if
 - methods considered
 - are the only modifiers

Interference

- Invariants make sense only if
 - methods considered
 - are the only modifiers
- Language encapsulation helps
 - List nodes not visible outside class

Interference


- Invariants make sense only if
 - methods considered
 - are the only modifiers
- Language encapsulation helps
 - List nodes not visible outside class

Interference

- Freedom from interference needed even for removed nodes
 - Some algorithms traverse removed nodes
 - Careful with `malloc()` & `free()` !
- We rely on garbage collection

Abstract Data Types

- Concrete representation:



- Abstract Type:
 $\{a, b\}$

Abstract Data Types

- Meaning of rep given by abstraction map

$$S(\text{[]} \rightarrow \text{[a]} \rightarrow \text{[b]} \rightarrow \text{[]}) = \{a, b\}$$

Rep Invariant

- Which concrete values meaningful?
 - Sorted?
 - Duplicates?
- Rep invariant
 - Characterizes legal concrete reps
 - Preserved by methods
 - Relied on by methods

Blame Game

- Rep invariant is a **contract**
- Suppose
 - **add()** leaves behind 2 copies of x
 - **remove()** removes only 1
- Which is incorrect?

Blame Game

- Suppose
 - `add()` leaves behind 2 copies of `x`
 - `remove()` removes only 1

Blame Game

- Suppose
 - `add()` leaves behind 2 copies of `x`
 - `remove()` removes only 1
- Which is incorrect?
 - If rep invariant says *no duplicates*
 - `add()` is incorrect
 - Otherwise
 - `remove()` is incorrect

Rep Invariant (partly)


- Sentinel nodes
 - tail reachable from head
- Sorted
- No duplicates

Abstraction Map

- $S(\text{head}) =$
 - $\{ x \mid \text{there exists } a \text{ such that}$
 - $a \text{ reachable from head and}$
 - $a.\text{item} = x$
 - $\}$

Sequential List Based Set

`add()`




`remove()`




Sequential List Based Set


add()




remove()




Coarse-Grained Locking



Coarse-Grained Locking



Coarse-Grained Locking



Simple but hotspot + bottleneck

Coarse-Grained Locking

- Easy, same as synchronized methods
 - “One lock to rule them all ...”

Coarse-Grained Locking

- Easy, same as synchronized methods
 - “One lock to rule them all ...”
- Simple, clearly correct
 - Deserves respect!
- Works poorly with contention
 - Queue locks help
 - But bottleneck still an issue



Fine-grained Locking

- Requires **careful** thought
 - “Do not meddle in the affairs of wizards, for they are subtle and quick to anger”


Fine-grained Locking

- Requires **careful** thought
 - “Do not meddle in the affairs of wizards, for they are subtle and quick to anger”
- Split object into pieces
 - Each piece has own lock
 - Methods that work on disjoint pieces need not exclude each other


Hand-over-Hand locking




Hand-over-Hand locking




Hand-over-Hand locking




Hand-over-Hand locking




Hand-over-Hand locking




Removing a Node




remove(b)




Removing a Node




Removing a Node




Removing a Node




Removing a Node




Removing a Node




Concurrent Removes




Concurrent Removes




Concurrent Removes




Concurrent Removes




Concurrent Removes




Concurrent Removes




Concurrent Removes




Concurrent Removes




Concurrent Removes



Concurrent Removes




Uh, Oh




Uh, Oh

Bad news, c not removed




Problem

- To delete node **c**
 - Swing node **b**'s next field to **d**




- Problem is,
 - Someone deleting **b** concurrently could direct a pointer to **c**




Insight

- If a node is locked
 - No one can delete node's *successor*
- If a thread locks
 - Node to be deleted
 - And its predecessor
 - Then it works


Hand-Over-Hand Again




remove(b)




Hand-Over-Hand Again




Hand-Over-Hand Again




Hand-Over-Hand Again




Hand-Over-Hand Again




Hand-Over-Hand Again




Removing a Node




remove(b)




remove(c)




Removing a Node




Removing a Node




Removing a Node




Removing a Node




Removing a Node




Removing a Node




Removing a Node




Removing a Node




Removing a Node




Removing a Node




Removing a Node




Removing a Node




Removing a Node



Removing a Node



Removing a Node




Remove method

```
public boolean remove(T item) {  
    int key = item.hashCode();  
    Node pred, curr;  
    try {  
        ...  
    } finally {  
        curr.unlock();  
        pred.unlock();  
    }  
}
```

Remove method

```
public boolean remove(T item) {  
    int key = item.hashCode();  
    Node pred, curr;  
    try {  
        ...  
    } finally {  
        curr.unlock();  
        pred.unlock();  
    }  
}
```



Key used to order node

Remove method

```
public boolean remove(T item) {  
    int key = item.hashCode();  
    Node pred, curr;  
    try {  
        ...  
    } finally {  
        currNode.unlock();  
        predNode.unlock();  
    }  
}
```

Predecessor and current nodes

Remove method

```
public boolean remove(T item) {  
    int key = item.hashCode();  
    Node pred, curr;  
    try {  
        ...  
    } finally {  
        curr.unlock();  
        pred.unlock();  
    }  
}
```

**Make sure
locks released**

Remove method

```
public boolean remove(T item) {  
    int key = item.hashCode();  
    Node pred, curr;  
    try {  
        ...  
    } finally {  
        curr.unlock();  
        pred.unlock();  
    }  
}
```

Everything else


Remove method

```
try {  
    pred = head;  
    pred.lock();  
    curr = pred.next;  
    curr.lock();  
    ...  
} finally { ... }
```

Remove method

lock pred == head


```
try {  
    pred = head;  
    pred.lock();  
    curr = pred.next;  
    curr.lock();  
    ...  
} finally { ... }
```



Remove method

```
try {  
    pred = head;  
    pred.lock();  
    curr = pred.next;  
    curr.lock();  
    ...  
} finally { ... }
```


Lock current



Remove method


```
try {  
    pred = head;  
    pred.lock();  
    curr = pred.next;  
    curr.lock();  
    ...  
} finally { ... }
```

Traversing list



Remove: searching


```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```



Remove: searching

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```


Search key range



Remove: searching

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```


At start of each loop:
curr and pred locked



Remove: searching

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}
```


If item found, remove node



Remove: searching

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}
```


If node found, remove it



Remove: searching

Unlock predecessor


```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```



Remove: searching

Only one node locked!


```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```



Remove: searching

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```

demote current




Remove: searching

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = currNode;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```

Find and lock new current


**curr = curr.next;
curr.lock();**



Remove: searching

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = currNode;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```

Lock invariant restored



Remove: searching

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}
```

Otherwise, not present



return false;

Why does this work?

- To remove node e
 - Must lock e
 - Must lock e 's predecessor
- Therefore, if you lock a node
 - It can't be removed
 - And neither can its successor

Why remove() is linearizable

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```

- pred reachable from head
- curr is pred.next
- So curr.item is in the set

Why remove() is linearizable

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```

**Linearization point if
item is present**

Why remove() is linearizable

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```

**Node locked, so no other
thread can remove it**

Why remove() is linearizable

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}
```

return false;

Item not present

Why remove() is linearizable

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}
```

return false;

- pred reachable from head
- curr is pred.next
- pred.key < key
- key < curr.key

Why remove() is linearizable

```
while (curr.key <= key) {  
    if (item == curr.item) {  
        pred.next = curr.next;  
        return true;  
    }  
    pred.unlock();  
    pred = curr;  
    curr = curr.next;  
    curr.lock();  
}  
return false;
```

Linearization point



Adding Nodes

- To add node e
 - Must lock predecessor
 - Must lock successor
- Neither can be deleted
 - (Is successor lock actually required?)

Same Abstraction Map

- $S(\text{head}) =$
 - $\{ x \mid \text{there exists } a \text{ such that}$
 - $a \text{ reachable from head and}$
 - $a.\text{item} = x$
 - $\}$

Rep Invariant

- Easy to check that
 - tail always reachable from head
 - Nodes sorted, no duplicates


Drawbacks

- Better than coarse-grained lock
 - Threads can traverse in parallel
- Still not ideal
 - Long chain of acquire/release
 - Inefficient


Optimistic Synchronization

- Find nodes without locking
- Lock nodes
- Check that everything is OK


Optimistic: Traverse without Locking




Optimistic: Lock and Load




Optimistic: Lock and Load




What could go wrong?




What could go wrong?




What could go wrong?




What could go wrong?




What could go wrong?




What could go wrong?




What could go wrong?




Validate – Part 1




What Else Could Go Wrong?




What Else Could Go Wrong?




What Else Could Go Wrong?




What Else Could Go Wrong?




What Else Could Go Wrong?



Validate Part 2 (while holding locks)



Optimistic: Linearization Point



Same Abstraction Map

- $S(\text{head}) =$
 - $\{ x \mid \text{there exists } a \text{ such that}$
 - $a \text{ reachable from head and}$
 - $a.\text{item} = x$
 - $\}$


Invariants

- Careful: we may traverse deleted nodes
- But we establish properties by
 - Validation
 - After we lock target nodes


Correctness

- If
 - Nodes `b` and `c` both locked
 - Node `b` still accessible
 - Node `c` still successor to `b`
- Then
 - Neither will be deleted
 - OK to delete and return `true`


Unsuccessful Remove




Validate (1)



Validate (2)



OK Computer



Correctness

- If
 - Nodes **b** and **d** both locked
 - Node **b** still accessible
 - Node **d** still successor to **b**
- Then
 - Neither will be deleted
 - No thread can add **c** after **b**
 - OK to return **false**


Validation

```
private boolean
  validate(Node pred,
           Node curr) {
  Node node = head;
  while (node.key <= pred.key) {
    if (node == pred)
      return pred.next == curr;
    node = node.next;
  }
  return false;
}
```

Validation


```
private boolean  
validate(Node pred,  
         Node curr) {  
    Node node = head;  
    while (node.key <= pred.key  
        if (node == pred)  
            return pred.next == curr;  
        node = node.next;  
    }  
    return false;  
}
```

**Predecessor &
current nodes**



Validation


```
private boolean
validate(Node pred,
        Node curr) {
    Node node = head;
    while (node.key <= pred.key) {
        if (node == pred)
            return pred.next == curr;
        node = node.next;
    }
    return false;
}
```



Begin at the beginning

Validation


```
private boolean
validate(Node pred,
         Node curr) {
    Node node = head;
    while (node.key <= pred.key) {
        if (node == pred)
            return pred.next == curr;
        node = node.next;
    }
    return false;
}
```



Search range of keys

Validation


```
private boolean
validate(Node pred,
        Node curr) {
    Node node = head;
    while (node.key <= pred.key) {
        if (node == pred)
            return pred.next == curr;
        node = node.next;
    }
    return false;
}
```



Predecessor reachable

Validation

```
private boolean  
  validate(Node pred,  
           Node curr) {  
    Node node = head;  
    while (node.key <= pred.key) {  
      if (node == pred)  
        return pred.next == curr;  
      node = node.next;  
    }  
    return false;  
  }
```




Is current node next?

Validation

```
private boolean  
validate(Node pred,  
         Node curr) {  
    Node node = head;  
    while (node.key <= pred.key) {  
        if (node == pred)  
            return pred.next == curr;  
        node = node.next;  
    }  
    return false;  
}
```

Otherwise move on


node = node.next;



Validation


```
private boolean validate(Node pred,  
                          Node curr) {  
    Node node = head;  
    while (node.key <= pred.key) {  
        if (node == pred)  
            return pred.next == curr;  
        node = node.next;  
    }  
    return false;  
}
```

Predecessor not reachable




Remove: searching

```
public boolean remove(T item) {
    int key = item.hashCode();
    retry: while (true) {
        Node pred = head;
        Node curr = pred.next;
        while (curr.key <= key) {
            if (item == curr.item)
                break;
            pred = curr;
            curr = curr.next;
        } ...
    }
}
```



Remove: searching

```
public boolean remove(T item) {  
    int key = item.hashCode();  
    retry: while (true) {  
        Node pred = head;  
        Node curr = pred.next;  
        while (curr.key <= key) {  
            if (item == curr.item)  
                break;  
            pred = curr;  
            curr = curr.next;  
        } ...  
    }
```



Search key

Remove: searching

```
public boolean remove(T item) {  
    int key = item.hashCode();
```

```
    retry: while (true) {
```

```
        Node pred = head;
```

```
        Node curr = pred.next;
```

```
        while (curr.key <= key) {
```


```
            if (item == curr.item)
```

```
                break;
```

```
            pred = curr;
```

```
            curr = curr.next;
```

```
        } ... Retry on synchronization conflict
```




Remove: searching

```
public boolean remove(T item) {  
    int key = item.hashCode();  
    retry: while (true) {
```

```
        Node pred = head;  
        Node curr = pred.next;
```

```
        while (curr.key <= key) {  
            if (item == curr.item)  
                break;  
            pred = curr;  
            curr = curr.next;
```


Examine predecessor and current nodes



Remove: searching


```
public boolean remove(T item) {  
    int key = item.hashCode();  
    retry: while (true) {  
        Node pred = head;  
        Node curr = pred.next;  
        while (curr.key <= key) {  
            if (item == curr.item)  
                break;  
            pred = curr;  
            curr = curr.next;  
        }  
        ...  
    }  
}
```

Search by key



Remove: searching


```
public boolean remove(T item) {  
    int key = item.hashCode();  
    retry: while (true) {  
        Node pred = head;  
        Node curr = pred.next;  
        while (curr.key <= key)  
            if (item == curr.item)  
                break;  
        pred = curr;  
        curr = curr.next;  
    } Stop if we find item  
}
```



Remove: searching

```
public boolean remove(T item) {  
    int key = item.hashCode();  
    retry: while (true) {  
        Node pred = head;  
        Node curr = pred.next;  
        while (curr.key <= key) {  
            if (item == curr.item)  
                break;  
            pred = curr;  
            curr = curr.next;  
        }  
        ...  
    }  
}
```

Move along



On Exit from Loop

- If item is present
 - curr holds item
 - pred just before curr
- If item is absent
 - curr has first higher key
 - pred just before curr
- Assuming no synchronization problems

Remove Method

```
try {  
    pred.lock(); curr.lock();  
    if (validate(pred, curr) {  
        if (curr.item == item) {  
            pred.next = curr.next;  
            return true;  
        } else {  
            return false;  
        }  
    } finally {  
        pred.unlock();  
        curr.unlock();  
    }  
}
```

Remove Method

```
try {
```

```
    pred.lock(); curr.lock();  
    if (validate(pred, curr) {  
        if (curr.item == item) {  
            pred.next = curr.next;  
            return true;  
        } else {  
            return false;  
        }  
    }
```

```
    }}} finally {  
    pred.unlock();  
    curr.unlock();  
    }}}
```

Always unlock

Remove Method

```
try {  
    pred.lock(); curr.lock();  
    if (validate(pred, curr) {  
        if (curr.item == item) {  
            pred.next = curr.next;  
            return true;  
        } else {  
            return false;  
        }  
    } finally {  
        pred.unlock();  
        curr.unlock();  
    }  
}
```

Lock both nodes

Remove Method

```
try {  
    pred.lock(); curr.lock();  
    if (validate(pred, curr) {  
        if (curr.item == item) {  
            pred.next = curr.next;  
            return true;  
        } else {  
            return false;  
        }  
    }  
} finally {  
    pred.unlock();  
    curr.unlock();  
}
```

Check for synchronization conflicts

Remove Method

```
try {  
    pred.lock(); curr.lock();  
    if (validate(pred, curr) {  
        if (curr.item == item) {  
            pred.next = curr.next;  
            return true;  
        } else {  
            return false;  
        }  
    } finally {  
        pred.unlock();  
        curr.unlock();  
    }  
}
```

**target found,
remove node**

Remove Method

```
try {
    pred.lock(); curr.lock();
    if (validate(pred, curr) {
        if (curr.item == item) {
            pred.next = curr.next;
            return true;
        } else {
            return false;
        }
    } finally {
        pred.unlock();
        curr.unlock();
    }
}
```

target not found



Optimistic List

- Limited hot-spots
 - Targets of `add()`, `remove()`, `contains()`
 - No contention on traversals
- Moreover
 - Traversals are wait-free
 - Food for thought ...

So Far, So Good

- Much less lock acquisition/release
 - Performance
 - Concurrency
- Problems
 - Need to traverse list twice
 - `contains()` method acquires locks

Evaluation

- Optimistic is effective if
 - cost of scanning twice without locks is less than
 - cost of scanning once with locks
- Drawback
 - `contains()` acquires locks
 - 90% of calls in many apps

Lazy List

- Like optimistic, except
 - Scan once
 - `contains(x)` never locks ...
- Key insight
 - Removing nodes causes trouble
 - Do it “lazily”


Lazy List

- **remove ()**
 - Scans list (as before)
 - Locks predecessor & current (as before)
- Logical delete
 - Marks current node as removed (new!)
- Physical delete
 - Redirects predecessor's next (as before)


Lazy Removal




Lazy Removal




Lazy Removal



Lazy Removal



Lazy Removal




Lazy List

- All Methods
 - Scan through locked and marked nodes
 - Removing a node doesn't slow down other method calls ...
- Must still lock `pred` and `curr` nodes.


Validation

- No need to rescan list!
- Check that `pred` is not marked
- Check that `curr` is not marked
- Check that `pred` points to `curr`


Business as Usual




Business as Usual




Business as Usual




Business as Usual




Business as Usual




Business as Usual




Business as Usual



Business as Usual



Business as Usual



New Abstraction Map

- $S(\text{head}) =$
 - $\{ x \mid \text{there exists node } a \text{ such that}$
 - a reachable from head and
 - $a.\text{item} = x$ and
 - a is unmarked
 - $\}$

Invariant

- If not marked then item in the set
- and reachable from head
- and if not yet traversed it is reachable from pred

Validation

```
private boolean  
    validate(Node pred, Node curr) {  
return  
    !pred.marked &&  
    !curr.marked &&  
    pred.next == curr) ;  
}
```

List Validate Method

```
private boolean  
    validate(Node pred, Node curr) {  
    return  
        !pred.marked &&  
        !curr.marked &&  
        pred.next == curr);  
}
```

**Predecessor not
Logically removed**

List Validate Method

```
private boolean  
    validate(Node pred, Node curr) {  
    return  
        !pred.marked &&  
        !curr.marked &&  
        pred.next == curr);  
}
```



**Current not
Logically removed**

List Validate Method

```
private boolean  
    validate(Node pred, Node curr) {  
    return  
        !pred.marked &&  
        !curr.marked &&  
        pred.next == curr) ;  
}
```

**Predecessor still
Points to current**

Remove

```
try {  
    pred.lock(); curr.lock();  
    if (validate(pred, curr) {  
        if (curr.key == key) {  
            curr.marked = true;  
            pred.next = curr.next;  
            return true;  
        } else {  
            return false;  
        }  
    }  
} finally {  
    pred.unlock();  
    curr.unlock();  
}
```

Remove

```
try {  
    pred.lock(); curr.lock();  
    if (validate(pred, curr) {  
        if (curr.key == key) {  
            curr.marked = true;  
            pred.next = curr.next;  
            return true;  
        } else {  
            return false;  
        }  
    }  
} finally {  
    pred.unlock();  
    curr.unlock();  
}}
```

Validate as before

Remove

```
try {  
    pred.lock(); curr.lock();  
    if (validate(pred, curr) {  
        if (curr.key == key) {  
            curr.marked = true;  
            pred.next = curr.next;  
            return true;  
        } else {  
            return false;  
        }  
    }  
} finally {  
    pred.unlock();  
    curr.unlock();  
}}
```

Key found



Remove

```
try {  
    pred.lock(); curr.lock();  
    if (validate(pred, curr) {  
        if (curr.key == key) {  
            curr.marked = true;  
            pred.next = curr.next;  
            return true;  
        } else {  
            return false;  
        }  
    }  
} finally {  
    pred.unlock();  
    curr.unlock();  
}}
```

Logical remove

Remove

```
try {  
    pred.lock(); curr.lock();  
    if (validate(pred, curr) {  
        if (curr.key == key) {  
            curr.marked = true;  
            pred.next = curr.next;  
            return true;  
        } else {  
            return false;  
        }  
    } finally {  
        pred.unlock();  
        curr.unlock();  
    }  
}
```

physical remove

Contains

```
public boolean contains(T item) {  
    int key = item.hashCode();  
    Node curr = head;  
    while (curr.key < key) {  
        curr = curr.next;  
    }  
    return curr.key == key && !curr.marked;  
}
```

Contains

```
public boolean contains(T item) {  
    int key = item.hashCode();  
    Node curr = head;  
    while (curr.key < key) {  
        curr = curr.next;  
    }  
    return curr.key == key && !curr.marked;  
}
```

Start at the head

Contains

```
public boolean contains(T item) {  
    int key = item.hashCode();  
    Node curr = head;  
    while (curr.key < key) {  
        curr = curr.next;  
    }  
    return curr.key == key && !curr.marked;  
}
```

Search key range


Contains

```
public boolean contains(T item) {  
    int key = item.hashCode();  
    Node curr = head;  
    while (curr.key < key) {  
        curr = curr.next;  
    }  
    return curr.key == key && !curr.marked;  
}
```

**Traverse *without locking*
(nodes may have been removed)**


Contains

```
public boolean contains(T item) {  
    int key = item.hashCode();  
    Node curr = head;  
    while (curr.key < key) {  
        curr = curr.next;  
    }  
    return curr.key == key && !curr.marked;  
}
```



Present and undeleted?


Summary: Wait-free Contains



Use Mark bit + list ordering

1. Not marked ☐ in the set
2. Marked or missing ☐ not in the set

Lazy List



Lazy add () and remove () + Wait-free contains ()

Evaluation

- Good:
 - **contains ()** doesn't lock
 - In fact, its wait-free!
 - Good because typically high % contains()
 - Uncontended calls don't re-traverse
- Bad
 - Contended **add ()** and **remove ()** calls must re-traverse
 - Traffic jam if one thread delays

Traffic Jam

- Any concurrent data structure based on mutual exclusion has a weakness
- If one thread
 - Enters critical section
 - And “eats the big muffin”
 - Cache miss, page fault, descheduled ...
 - Everyone else using that lock is stuck!
 - Need to trust the scheduler....

Reminder: Lock-Free Data Structures



- No matter what ...
 - Guarantees minimal progress in any execution
 - i.e. Some thread will always complete a method call
 - Even if others halt at malicious times
 - Implies that implementation can't use locks

Lock-free Lists

- Next logical step
 - Wait-free `contains()`
 - lock-free `add()` and `remove()`
- Use only `compareAndSet()`
 - What could go wrong?

compareAndSet

```
public abstract class CASObject {  
    private int value;  
    public boolean synchronized  
        compareAndSet(int expected,  
                       int update) {  
        if (value==expected) {  
            value = update; return true;  
        }  
        return false;  
    } ... }  
}
```


compareAndSet

```
public abstract class CASObject {  
    private int value;  
    public boolean synchronized  
        compareAndSet(int expected,  
                       int update) {  
        if (value==expected) {  
            value = update; return true;  
        }  
        return false;  
    } ... }  
}
```

If value is as expected, ...

compareAndSet

```
public abstract class CASOBJECT{  
    private int value;  
    public boolean synchronized  
        compareAndSet(int expected,  
                       int update) {  
        if (value==expected) {  
            value = update; return true;  
        }  
        return false;  
    } ... }  
... replace it
```

A diagram consisting of two red-outlined speech bubbles. The first bubble points to the 'update' parameter in the function signature 'compareAndSet(int expected, int update)'. The second bubble points to the assignment 'value = update;' inside the 'if' block. Both the parameter and the assignment are highlighted with red boxes. A red arrow points from the text '... replace it' at the bottom right towards these two elements.

compareAndSet

```
public abstract class RMWRegister {  
    private int value;  
    public boolean synchronized  
        compareAndSet(int expected,  
                       int update) {  
        if (value==expected) {  
            value = update; return true;  
        }  
        return false;  
    } ... }  

```

Report success


compareAndSet

```
public abstract class RMWRegister {  
    private int value;  
    public boolean synchronized  
        compareAndSet(int expected,  
                       int update) {  
        if (value==expected) {  
            value = update; return true;  
        }  
        return false;  
    }  
    ...  
}
```

Otherwise report failure

Lock-free Lists

Logical Removal




Use CAS to verify pointer
is correct

Physical Removal


Not enough!

Problem...



The Solution: Combine Bit and Pointer

Logical Removal =
Set Mark Bit



Mark-Bit and Pointer
are CASed together
(AtomicMarkableReference)

Physical
Removal
CAS


Fail CAS: Node not
added after logical
Removal

Solution

- Use AtomicMarkableReference
- Atomically
 - Swing reference and
 - Update flag
- Remove in two steps
 - Set mark bit in next field
 - Redirect predecessor's pointer

Marking a Node

- **AtomicMarkableReference** class
 - Java.util.concurrent.atomic package



Extracting Reference & Mark

```
public Object get(boolean[] marked) ;
```

Extracting Reference & Mark

```
public Object get(boolean[] marked) ;
```

**Returns
reference**

**Returns mark at
array index 0!**

Extracting Mark Only

```
public boolean isMarked();
```



**Value of
mark**

Changing State

```
public boolean compareAndSet(  
    Object expectedRef,  
    Object updateRef,  
    boolean expectedMark,  
    boolean updateMark) ;
```

Changing State

**If this is the current
reference ...**

```
public boolean compareAndSet(  
    Object expectedRef,  
    Object updateRef,  
    boolean expectedMark,  
    boolean updateMark);
```

**And this is the
current mark ...**

Changing State

...then change to this
new reference ...

```
public boolean compareAndSet(  
    Object expectedRef,  
    Object updateRef,  
    boolean expectedMark,  
    boolean updateMark) ;
```

... and this new
mark

Changing State

```
public boolean attemptMark(  
    Object expectedRef,  
    boolean updateMark) ;
```


Changing State

```
public boolean attemptMark(  
    Object expectedRef,  
    boolean updateMark) ;
```

**If this is the current
reference ...**


Changing State

```
public boolean attemptMark(  
    Object expectedRef,  
    boolean updateMark);
```




**.. then change to
this new mark.**


Removing a Node





Removing a Node



Removing a Node




remove(b)



remove(c)


Removing a Node



Traversing the List

- Q: what do you do when you find a “logically” deleted node in your path?
- A: finish the job.
 - CAS the predecessor’s next field
 - Proceed (repeat as needed)

Lock-Free Traversal (only Add and Remove)




The Window Class

```
class Window {  
    public Node pred;  
    public Node curr;  
    Window(Node pred, Node curr) {  
        pred = pred; curr = curr;  
    }  
}
```

The Window Class

```
class Window {  
    public Node pred;  
    public Node curr;  
    Window(Node pred, Node curr) {  
        pred = pred; curr = curr;  
    }  
}
```



**A container for pred
and current values**

Using the Find Method

```
Window window = find(head, key);  
Node pred = window.pred;  
curr = window.curr;
```

Using the Find Method

```
Window window = find(head, key);
```

```
Node pred = window.pred;
```

```
curr = window.curr;
```

Find returns window

Using the Find Method

```
Window window = find(head, key);
```


```
Node pred = window.pred;  
curr = window.curr;
```

Extract pred and curr

The Find Method

```
Window window = find(item);
```


At some instant,




The Find Method

```
Window window = find(item);
```

At some instant,



not in list




Remove

```
public boolean remove(T item) {
    Boolean snip;
    while (true) {
        Window window = find(head, key);
        Node pred = window.pred, curr = window.curr;
        if (curr.key != key) {
            return false;
        } else {
            Node succ = curr.next.getReference();
            snip = curr.next.compareAndSet(succ, succ, false
true);
            if (!snip) continue;
            pred.next.compareAndSet(curr, succ, false, false);
            return true;
        }
    }
}
```

Remove


```
public boolean remove(T item) {  
    Boolean snip;  
    while (true) {  
        Window window = find(head, key);  
        Node pred = window.pred, curr = window.curr;  
        if (curr.key != key) {  
            return false;  
        } else {  
            Node succ = curr.next.getReference();  
            snip = curr.next.compareAndSet (succ, succ, false,  
true);  
            if (!snip) continue;  
            pred.next.compareAndSet(curr, succ, false, false);  
            return true;  
        }  
    }  
}
```



Keep trying

Remove


```
public boolean remove(T item) {
    Boolean snip;
    while (true) {
        Window window = find(head, key);
        Node pred = window.pred, curr = window.curr;
        if (curr.key != key) {
            return false;
        } else {
            Node succ = curr.next.getReference();
            snip = curr.next.compareAndSet(succ, succ, false,
true);
            if (!snip) continue;
            pred.next.compareAndSet(curr, succ, false, false);
            return true;
        }
    }
}
```



Find neighbors

Remove

```
public boolean remove(T item) {
    Boolean snip;
    while (true) {
        Window window = find(head, key);
        Node pred = window.pred, curr = window.curr;
        if (curr.key != key) {
            return false;
        } else {
            Node succ = curr.next.getReference();
            snip = curr.next.compareAndSet(succ, succ, false,
            true);
            if (!snip) continue;
            pred.next.compareAndSet(curr, succ, false, false);
            return true;
        }
    }
}
```



Not there ...


Remove

Try to mark node as deleted

```
public boolean remove(T item) {  
    Boolean snip;  
    while (true) {  
        Window window = find(head, key);  
        Node pred = window.pred, curr = window.curr;  
        if (curr.key != key) {  
            return false;  
        } else {  
            Node succ = curr.next.getReference();  
            snip = curr.next.compareAndSet(succ, succ, false,  
true);  
            if (!snip) continue;  
            pred.next.compareAndSet(curr, succ, false, false);  
            return true;  
        }  
    }  
}
```

Remove


If it doesn't work,
just retry, if it
does, job
essentially done



```
public boolean remove(T item) {  
    while (true) {  
        Window window = find(head, key);  
        Node pred = window.pred, curr = window.curr;  
        if (pred == null || pred.next == null) {  
            return false;  
        } else {  
            Node succ = curr.next.getReference();  
            snip = curr.next.compareAndSet(succ, succ, false,  
true);  
            if (!snip) continue;  
            pred.next.compareAndSet(curr, succ, false, false);  
            return true;  
        }  
    }  
}
```

Remove

```
public boolean remove(T item) {  
    Boolean snip;  
    while (true) {  
        Window window = find(head,
```



```
curr = window.curr;
```

**Try to advance reference
(if we don't succeed,
someone else did or will).**

```
    Node succ = curr.next.getReference();  
    snip = curr.next.compareAndSet(succ, succ, false,  
true);  
    if (!snip) continue;  
    pred.next.compareAndSet(curr, succ, false, false);  
    return true;  
}}}
```


Add

```
public boolean add(T item) {
    boolean splice;
    while (true) {
        Window window = find(head, key);
        Node pred = window.pred, curr = window.curr;
        if (curr.key == key) {
            return false;
        } else {
            Node node = new Node(item);
            node.next = new AtomicMarkableRef(curr, false);
            if (pred.next.compareAndSet(curr, node, false,
false)) {return true;}
        }
    }
}
```


Add

```
public boolean add(T item) {  
    boolean splice;  
    while (true) {  
        Window window = find(head, key);  
        Node pred = window.pred, curr = window.curr;  
        if (curr.key == key) {  
            return false;  
        } else {  
            Node node = new Node(item);  
            node.next = new AtomicMarkableRef(curr, false);  
            if (pred.next.compareAndSet(curr, node, false,  
false)) {return true;}  
        }  
    }  
}
```

Item already there


Add

```
public boolean add(T item) {  
    boolean splice;  
    while (true) {  
        Window window = find(head  
        Node pred = window.pred, curr = window.curr;  
        if (curr.key == key) {  
            return false;  
        } else {  
            Node node = new Node(item);  
            node.next = new AtomicMarkableRef(curr, false);  
            if (pred.next.compareAndSet(curr, node, false,  
false)) {return true;}  
        }  
    }  
}
```



create new node

Add

```
public boolean add(T item) {  
    boolean splice;  
    while (true) {  
        Window window = find(head, item);  
        Node pred = window.pred; curr = window.curr;  
  
          
  
        node.next = new AtomicMarkableRef(curr, false);  
        if (pred.next.compareAndSet(curr, node, false,  
false)) {return true;}  
    }  
}
```

**Install new node,
else retry loop**

Wait-free Contains

```
public boolean contains(T item) {  
    boolean marked;  
    int key = item.hashCode();  
    Node curr = head;  
    while (curr.key < key)  
        curr = curr.next;  
    Node succ = curr.next.get(marked);  
    return (curr.key == key && !marked[0])  
}
```

Wait-free Contains

```
public boolean contains(T item) {  
    boolean marked;  
    int key = item.hashCode();  
    Node curr = head;  
    while (curr.key < key)  
        curr = curr.next;  
    Node succ = curr.next.get(marked);  
    return (curr.key == key && !marked[0])  
}
```

**Only difference is
that we get and
check marked**

**Node succ = curr.next.get(marked);
return (curr.key == key && !marked[0])**

Lock-free Find

```
public Window find(Node head, int key) {  
    Node pred = null, curr = null, succ = null;  
    boolean[] marked = {false}; boolean snip;  
    retry: while (true) {  
        pred = head;  
        curr = pred.next.getReference();  
        while (true) {  
            succ = curr.next.get(marked);  
            while (marked[0]) {  
                ...  
            }  
            if (curr.key >= key)  
                return new Window(pred, curr);  
            pred = curr;  
            curr = succ;  
        }  
    }  
}
```


Lock-free Find

```
public Window find(Node head, int key) {  
    Node pred = null, curr = null, succ = null;  
    boolean[] marked = {false}; boolean snip;  
    retry: while (true) {  
        pred = head;  
        curr = pred.next.getReference();  
        while (true) {  
            succ = curr.next.get(marked);  
            while (marked[0]) {  
                ...  
            }  
            if (curr.key >= key)  
                return new Window(pred, curr);  
            pred = curr;  
            curr = succ;  
        }  
    }  
}
```

**If list changes
while traversed,
start over**

Lock-free Find

```
public Window find(Node head, int key) {  
    Node pred = null; Start looking from head  
    boolean[] marked = {false}; boolean snip;  
    retry: while (true) {  
        pred = head;  
        curr = pred.next.getReference();  
        while (true) {  
            succ = curr.next.get(marked);  
            while (marked[0]) {  
                ...  
            }  
            if (curr.key >= key)  
                return new Window(pred, curr);  
            pred = curr;  
            curr = succ;  
        }  
    }  
}
```



Lock-free Find

```
public Window find(Node head, int key) {  
    Node pred = null, curr = null, succ = null;  
    boolean[] marked = {false}; boolean snip;  
    retry: while (true) { Move down the list  
        pred = head;  
        curr = pred.next.getReference();  
        while (true) {  
            succ = curr.next.get(marked);  
            while (marked[0]) {  
                ...  
            }  
            if (curr.key >= key)  
                return new Window(pred, curr);  
            pred = curr;  
            curr = succ;  
        }  
    }  
}
```

Lock-free Find

```
public Window find(Node head, int key) {
    Node pred = null, curr = null, succ = null;
    boolean[] marked = {false}; boolean snip;
    retry: while (true) {
        pred = head;
        curr = pred.next.getReference();
        while (true) {
            succ = curr.next.get(marked);
            while (marked[0]) {
                ...
            }
            if (curr.key >= key)
                return new Window(pred, curr);
            pred = curr;
            curr = succ;
        }
    }
}
```

**Get ref to successor and
current deleted bit**

Lock-free Find

```
public Window find(Node head, int key) {
    Node pred = null, curr = null, succ = null;
    boolean[] marked = {false}; boolean snip;
    retry: while (true) {
        pred = head;
        curr = pred.next.getReference();
        while (true) {
            succ = curr.next.get(marked);
            while (marked[0]) {
                ...
            }
            if (curr.key >= key)
                return new Window(pred, curr);
            pred = curr;
        }
    }
}
```

**Try to remove deleted nodes in
path...code details soon**

Lock-free Find

```
public Window find(Node head, int key) {  
    Node pred = null, curr = null, succ = null;  
    boolean[] marked = {false}; boolean snip;  
    retry: while (true) {  
        pred = head;  
        curr = pred.next.getReference();  
        If curr key that is greater or  
        equal, return pred and curr  
        while (marked[0]) {  
            ...  
        }  
        if (curr.key >= key)  
            return new Window(pred, curr);  
        pred = curr;  
        curr = succ;  
    }  
}
```

Lock-free Find

```
public Window find(Node head, int key) {  
    Node pred = null, curr = null, succ = null;  
    boolean[] marked = {false}; boolean snip;  
    retry: while (true) {  
        pred = head;  
        curr = pred.next.getReference();  
        while (true) {  
            succ = curr.next.get(marked);  
            while (marked[0]) {  
                ...  
            }  
            if (curr.key >= key)  
                return new Window(pred, curr);  
            pred = curr;  
            curr = succ;  
        }  
    }  
}
```

**Otherwise advance window and
loop again**


Lock-free Find

```
retry: while (true) {  
    ...  
    while (marked[0]) {  
        snip = pred.next.compareAndSet(curr,  
                                         succ, false, false);  
        if (!snip) continue retry;  
        curr = succ;  
        succ = curr.next.get(marked);  
    }  
    ...  
}
```

Lock-free Find

Try to snip out node


```
retry: while (true) {  
    ...  
    while (marked[0]) {  
        snip = pred.next.compareAndSet(curr,  
                                         succ, false, false);  
        if (!snip) continue retry;  
        curr = succ;  
        succ = curr.next.get(marked);  
    }  
    ...  
}
```



Lock-free Find

**if predecessor's next field changed,
retry whole traversal**

```
retry: while (true) {  
    ...  
    while (marked[0]) {  
        snip = pred.next.compareAndSet(curr,  
                                         succ, false, false);  
        if (!snip) continue retry;  
        curr = succ;  
        succ = curr.next.get(marked);  
    }  
    ...  
}
```



Lock-free Find


Otherwise move on to check
if next node deleted

```
retry: while (true) {  
    ...  
    while (marked[0]) {  
        snip = pred.next.compareAndSet(curr,  
                                         succ, false, false);  
        if (!snip) continue retry;  
        curr = succ;  
        succ = curr.next.get(marked);  
    }  
    ...  
}
```


Performance

- Different list-based set implementations
- 16-node machine
- Vary percentage of **contains()** calls


High Contains Ratio



Low Contains Ratio



As Contains Ratio Increases



Summary

- Coarse-grained locking
- Fine-grained locking
- Optimistic synchronization
- Lazy synchronization
- Lock-free synchronization

“To Lock or Not to Lock”

- Locking vs. Non-blocking:
 - Extremist views on both sides
- The answer: nobler to compromise
 - Example: Lazy list combines blocking `add()` and `remove()` and a wait-free `contains()`
 - Remember: Blocking/non-blocking is a property of a method

This work is licensed under a [Creative Commons Attribution-ShareAlike 2.5 License](https://creativecommons.org/licenses/by-sa/3.0/).

- **You are free:**
 - **to Share** — to copy, distribute and transmit the work
 - **to Remix** — to adapt the work
- **Under the following conditions:**
 - **Attribution.** You must attribute the work to “The Art of Multiprocessor Programming” (but not in any way that suggests that the authors endorse you or your use of the work).
 - **Share Alike.** If you alter, transform, or build upon this work, you may distribute the resulting work only under the same, similar or a compatible license.
- For any reuse or distribution, you must make clear to others the license terms of this work. The best way to do this is with a link to
 - <http://creativecommons.org/licenses/by-sa/3.0/>.
- Any of the above conditions can be waived if you get permission from the copyright holder.
- Nothing in this license impairs or restricts the author's moral rights.