

IgrejaFy — Setup & Installation Guide

Clean setup and deployment documentation for new Windows machines

PRODUCTION READY

Updated: October 2026

1 Configure PHP Extensions (php.ini)

On a fresh Windows PHP installation (e.g., `C:\php\php.ini`), several required extensions are disabled by default. Remove the leading semicolon (`;`) from these directives:

```
extension_dir = "ext"
extension=fileinfo
extension=pdo_mysql
extension=mysqli
extension=zip
```

- **fileinfo:** Mandatory for Composer packages such as `league/flysystem`.
- **pdo_mysql & mysqli:** Required for Laravel database connection to MySQL.
- **zip:** Allows Composer to quickly extract vendor zip packages.

2 Install PHP Dependencies

Open PowerShell or Command Prompt in the project folder and download the vendor packages:

```
# For local development:
composer install

# For production deployments:
composer install --no-dev --optimize-autoloader
```

3 Database Setup & .env Configuration

A. Create the MySQL Database:

```
CREATE DATABASE IF NOT EXISTS igrejafy CHARACTER SET utf8mb4 COLLATE utf8mb4_unicode_ci;
```

B. Configure credentials in `.env` :

```
DB_CONNECTION=mysql
DB_HOST=127.0.0.1
DB_PORT=3306
DB_DATABASE=igrejafy
DB_USERNAME=root
DB_PASSWORD="your_password"
```

CRUCIAL GOTCHA — PASSWORDS WITH '#'

If your database password contains special characters (especially `#`), you **MUST wrap it in quotes** (e.g. `DB_PASSWORD="Gguihelo1990#"`). Without quotes, phpdotenv treats `#` as an inline comment and clips your password, causing `Access denied for user 'root'@'localhost' (1045)`.

4 Generate Application Key & Run Migrations

Initialize Laravel's cryptographic key and create all database tables:

```
# 1. Generate key
php artisan key:generate

# 2. Run migrations
php artisan migrate
```

All database tables (users, cache, jobs, people, baptisms, visits, etc.) will be created.

5 Frontend Dependencies & Asset Compilation

To prevent the error `'vite' is not recognized as an internal or external command`, install Node packages:

```
# 1. Install frontend packages (Vite, Tailwind, Bootstrap, etc.)
npm install

# 2. Build assets for production (generates public/build/manifest.json)
npm run build
```

PRODUCTION TIP

Once `npm run build` is executed, the compiled CSS and JS are saved in `public/build`. You do **not** need to keep `npm run dev` running in production.

QUICK CHECKLIST FOR FUTURE MACHINE INSTALLATIONS

```
# 1. PHP setup: Enable fileinfo, pdo_mysql, mysqli, zip in C:\php\php.ini
# 2. Install dependencies:
composer install
# 3. Environment: Copy .env.example to .env (if fresh clone) and configure DB
# 4. MySQL: CREATE DATABASE igrejafy;
# 5. Initialize application:
php artisan key:generate
php artisan migrate
npm install
npm run build
# 6. Run server:
php artisan serve
```