
- FAB NOTES:
 1. ALL DIMENSIONS ARE IN INCHES, UNLESS
 OTHERWISE NOTED.
- THE PWB SHALL BE FABRICATED TO IPC-6012, CLASS 2 AND WORKMANSHIP SHALL CONFORM TO IPC-4-600. CLASS 2. CURRENT REVISIONS.
- BOARD MATERIAL SHALL BE 180 Tg/340 Td 150LA FR-3TOR OR COUTVALENT, REMS/FRACH COMPLINIT AND LEAD FREE ASSIDENCY CAPABLE, BOMBO MATERIAL SCHEME OR COCCE INF-CLIBE, REMS/FRACHCO CERTIFIET OF CORE COMMANCE SHALL BE DELIVERED WITH EACH U.S.
- BOARD MATERIAL & CONSTRUCTION TO BE U.L. 94V
 APPROVED AND MARKED ON THE FINISHED BOARD.UL
 GUIDE NUMBER SHOULD BE MARKED ON THE FINISHED
 BOARD.

 ON THE FINISHED


 ON THE FIN
- 5. OVERALL BOARD THICKNESS TO BE .063 +/-.005" AND APPLIES AFTER ALL LAMINATION AND PLATING
- AND APPLIES AFTER ALL LAMINATION AND PLATIN PROCESSES, MEASURED FROM COPPER TO COPPER. 6. MAX. WARP & TWIST TO BE .0075 PER INCH.
- 7. BOARD MUST BE ELECTRICALLY TESTED USING SUPPLIED IPC-D-356 NETLIST.
- 8. 14 MIL TRACES ON LAYER 1 ARE 50 CHMS +/-10% THEY ARE REFERENCE TO LAYER 2 GROUND WITH SOLDERMASK CLEAR AWAY.

- PROCESS NOTES:

 1. APPLY LPI SOLDERMASK OVER BARE COPPER (SMOBC),
 SOLDERMASK SHALL CONFORM TO IPC-SM-840, CLASS H.
 CURDENT DRV. CORD OF MAKE TO BE DRY.
- 2. PLATE ALL EXPOSED AREAS WITH ELECTROLESS NICKEL IMMERSION GOLD. NICKEL:100 MICRO-INCHES MIN. GOLD:2-8 MICROINCHES MIN.
- SOLDERMASK ARTWORK HAS ZERO (0) OVERSIZED PADS.
 FABRICATION VENDOR IS ALLOWED TO ADJUST THE COMPONENT SOLDERMASK
 PADS TO MEET THEIR TOOLING REQUIREMENTS.
- A. APPLY NON-CONDUCTIVE LPI SILKSCREEN OR EQUIVALENT PER THE ARTWORK
 COLOR: WHITE
- 5. ALL VIAS ARE TENTED.



DESIGN CROSS SECTION CHART
TOTAL THICKNESS 63.1 MIL



CUSTOMER: TEXAS INSTRUMENTS			
BOARD NAME: LAUNCHXL-CC1350-4	LAYER NAME: Fabrication Drawing		
PROJECT NO: WCS034	BOARD REV:	RELEASE DATE: 2017-01-23	SHEET NO: 1 OF 1

DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILS				
FIGURE	SIZE	PLATED	QTY	
•	8.0	PLATED	1023	
•	8.0	PLATED	28	
•	10.0	PLATED	8	
	16.0	PLATED	21	
•	41.0	PLATED	75	
9	43.0	PLATED	1	
Øs.	126.0	PLATED	2	
	35.0	NON-PLATED	6	
	39.0	NON-PLATED	3	
•	126.0	NON-PLATED	4	
0	51.0x24.0	PLATED	2	