

Vagrant Puppetmaster demo

Marc Lambrichs

May 28, 2015

Abstract

First goal is to create a test environment for any application or set of applications using a central - but local! - vagrant box running puppetmaster, r10k and puppetdb.

In a different project we're creating a test environment with a combination of Elasticsearch, Logstash, Kibana (ELK-stack), combined with redis for caching. Having your own test environment allows you to develop and test your own puppetmodules, before pushing them on into a CI pipeline.

1 Prerequisites

Your environment should contain:

1. git
2. ruby
3. vagrant
4. virtualbox
5. and finally, some rubygems:
 - (a) vagrant-cachier
 - (b) vagrant-hosts
 - (c) vagrant-vbguest

Example: installing vagrant-cachier:

```
marc:~ marc$ sudo gem install vagrant-cachier
```

2 Structure

The puppetmaster functionality is split up in 3 separate repositories.

1. puppetmaster
2. hiera
3. r10k

All three of them, are - separate - git repositories, with different purposes. The *puppetmaster* repo contains a Vagrantfile that serves as our starting point for building a puppetmaster. The other two repositories, *r10k* and *hiera* are being used during the puppetmaster install to create a complete production-like environment of puppetmaster on a vagrant box. Our first goal is to install puppetmaster, so we can leave the *hiera* and *r10k* repo's, for now.

So check out the puppetmaster repository in a directory of your liking.

```
marc:~ marc$ mkdir vagrant
marc:~ marc$ cd vagrant
marc:~ marc$ git clone git@cassandra.melange-it.nl:/var/opt/git/generic/puppetmaster.git puppetmaster
marc:~ marc$ cd puppetmaster
marc:~ marc$ git submodule update --init --recursive
```

Before building, you need to add your own entry in puppetmaster/config/boxes.yaml.
Now, you're ready to install your own puppetmaster.

3 Boxes

To start up a puppetmaster using vagrant, we need to have a basic vagrant box upon which we put our necessary software. The definition of boxes you need are defined in the file config/boxes.yaml. Obviously, you could use your own box or get one from a public repo.
Take a look at <https://atlas.hashicorp.com/boxes/search> or <http://vagrantbox.es>.

4 Puppetmaster

4.1 Puppetmaster, r10k, puppetdb and foreman in one go

Cd into your puppetmaster directory and start up vagrant.

```
marc:~ marc$ cd ~/vagrant/puppetmaster
marc:puppetmaster marc$ vagrant up
```


This will start off a lot of output, ending with a *puppet apply* on your vagrant box. Next thing to do, is to check if everything is working.

4.2 Check and doublecheck


For convenience, add an entry to your local /etc/hosts file:

```
marc:puppetmaster marc$ sudo echo '10.0.0.2 puppet.arthurjames.local' >> /etc/hosts
```

First, let's check if your puppetdb is running. Open your browser with <http://puppet.arthurjames.local:8080> and you should see something like this:



Next, check if you can access foreman. On the same host on port 80 you should see:



If you can, check if you can log in to foreman with credentials *admin/changeme*. Probably no nodes have been recognized, so there are two options here:

- wait for 30 min (the default setting inbetween puppet agent runs)
- ssh into your vagrant box to kick off a puppetrun.

```

marc:~ marc$ cd ~/vagrant/puppetmaster
marc:puppetmaster marc$ vagrant ssh
Linux debian 3.2.0-4-amd64 #1 SMP Debian 3.2.65-1+deb7u1 x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Tue Apr 28 12:47:02 2015 from 10.0.2.2
vagrant@puppet:~$

```


Now you're logged in, do:

```

vagrant@puppet:~$ sudo puppet agent -v -t

```

After the puppetrun, you should be able to see 1 node defined.



5 Clients

5.1 Elasticsearch

5.2 Kibana

5.2.1 Kibana 3

5.2.2 Kibana 4

5.3 Logstash

5.4 Redis