

OFFERTA IMPIANTO FOTOVOLTAICO

Installazione residenziale - IVA inclusa

CON ACCUMULO CHIAVI IN MANO



DESCRIZIONE

6 kWp + 12,9 kWh	€ 12.690,00
8 kWp + 17,2 kWh	€ 15.390,00
9 kWp + 21,4 kWh	€ 17.190,00

- **GARANZIA ESTESA E PRESTAZIONI A LUNGO TERMINE 15 ANNI SUL PRODOTTO HVE**
- **PERCENTUALE GARANTITA: MANTENIMENTO DI UNA CAPACITÀ RESIDUA MINIMA DEL 80% DELLA CAPACITÀ NOMINALE PER 10 ANNI**
- **DESIGN E ROBUSTEZZA AMBIENTALE: ULTRA-SOTTILE → 140 MM**
- **GRADO MASSIMO DI PROTEZIONE → IP65**
 - LINEA EPS ANTI-BLACKOUT INCLUSA
 - INGRESSO NELLA SOLAIR CER → 20 anni di TIP sulla VENDITA

COSA COMPRENDE L'OFFERTA

INCENTIVO COMUNITÀ ENERGETICA RINNOVABILE (CER)

Entrando nella CER Solair, il cliente può:

- ✓ Condividere l'energia prodotta
- ✓ Ricevere incentivi sull'energia condivisa
- ✓ Ridurre ulteriormente il costo dell'energia

UN'OFFERTA CHIAVI IN MANO

- ✓ Fornitura moduli fotovoltaici ad alta efficienza
(LONGi / Trina Solar / Astro Energy - Modello a scelta senza variazione di prezzo)
- ✓ Inverter e sistema di accumulo (batterie)
(BYD con garanzia del produttore)
- ✓ Progettazione tecnica dell'impianto
- ✓ Installazione completa "chiavi in mano"
- ✓ Collaudo e messa in esercizio
- ✓ Pratiche di connessione con e-distribuzione
- ✓ Pratiche GSE (Scambio sul Posto / Ritiro Dedicato se applicabile)
- ✓ Assistenza tecnica post-installazione

MODALITÀ DI PAGAMENTO

• *Bonifico bancario:*

Avanzamento lavori standard:

- 30% dopo sopralluogo tecnico e validazione contrattuale -
- 50% a merce in cantiere
- 20% a lavoro completato

• *Possibilità di finanziamento con Credito a Consumo:*

Prima rata a 30 gg o 120 gg dall'installazione

Questo documento è una proposta indicativa.
Un nostro consulente è a disposizione per
personalizzare la tua richiesta sull'impianto

COSA COMPRENDE L'OFFERTA

1. Consulenza dedicata

Fissa una call con un nostro consulente interno cliccando sul link in CHAT

Durante la chiamata potremo:

- Personalizzare l'offerta in base ai tuoi consumi e agli obiettivi di risparmio
- Simulare l'impianto in tempo reale con il nostro software professionale
- Riservare le condizioni economiche agevolate attraverso un preventivo di conferma preliminare
- Richiedere il sopralluogo tecnico per la verifica finale

2. Sopralluogo tecnico

Un nostro tecnico incaricato effettuerà il sopralluogo presso l'immobile.

 ***Entro 14 giorni lavorativi riceverai la visita tecnica finalizzata alla conferma dell'offerta dell'impianto fotovoltaico.***

Il sopralluogo serve a:

- Confermare la fattibilità tecnica Verificare spazi,
- struttura e punto di connessione Validare
- definitivamente la soluzione proposta

3. Conferma finale

A seguito del sopralluogo:

1. Se la soluzione risulta pienamente coerente con quanto definito, si procede con i prossimi steps
2. Qualora emergano variazioni tecniche rilevanti, il cliente sarà libero di rivalutare la soluzione senza vincoli

4. Tempi di realizzazione

Una volta confermata la fattibilità:

- Avvio pratiche tecniche e amministrative Pianificazione
- installazione Realizzazione impianto chiavi in mano **entro 30 gg**
- **lavorativi**

Power-Box SH3/3.7/4.6/5/6K

SinglePhase Hybrid Inverter



KEY FEATURES



Energy Management

- Max. efficiency 97.7%
- Max. PV input current 16 A * 2
- 200% PV input oversizing
- Max. battery charge / discharge current 35 A



Safe & Convenient

- SPD type : DC II / AC III
- Working noise < 25 dB
- Quick installation and easy debugging



Powerful Backup

- THDv < 2%
- 200% peak output power
- Seamless on-grid / off-grid switching



Smart O & M

- Firmware OTA updates
- 24 / 7 online monitoring
- Smart remote diagnosis



TECHNICAL PARAMETERS

Models	Power-Box SH3K	Power-Box SH3.7K	Power-Box SH4.6K	Power-Box SH5K	Power-Box SH6K
Input (PV)					
Max. PV Input Power	6000 Wp	7360 Wp	8280 Wp	9000 Wp	9000 Wp
Max. PV Input Voltage			600 V		
Start-up Voltage			120 V		
MPPT Voltage Range			80 ~ 550 V		
Max. Current per MPPT			16 A		
Max. Short Circuit Current per MPPT			24 A		
Number of MPP Trackers			2		
Number of Strings per MPPT			1/1		
Battery					
Compatible Battery	BYD Battery-Box HVE or BYD Battery-Box HVB				
Battery Voltage	80 ~ 480 V				
Max. Charge / Discharge Current	35 A				
Max. Charge / Discharge Power	3000 W	3680 W	4600 W	5000 W	6000 W
AC Input / Output (Grid)					
Rated AC Input / Output Power	3000 W	3680 W	4600 W	5000 W	6000 W
Max. AC Input / Output Apparent Power	3300 VA	4050 VA	4600 VA	5500 VA	6600 VA
Rated AC Input / Output Current	13 A	16 A	20 A	21.7 A	26.1 A
Max. AC Input / Output Current	26 A / 15 A	32 A / 18 A	40 A / 20.9 A	44 A / 25 A	52 A / 30 A
Rated AC Voltage Range	1 / N / PE, 220 V / 230 V / 240 V				
AC Voltage Range	0.9 Ur ~ 1.1 Ur				
AC Grid Frequency	50 Hz (47.5 Hz ~ 52.5 Hz) / 60 Hz (57 Hz ~ 63 Hz)				
Power Factor	0.99, 0.8 leading ~ 0.8 lagging adjustable				
THDi	< 3%				
AC Output (Backup)					
Rated AC Output Power	3000 W	3680 W	4600 W	5000 W	6000 W
Peak Output Power	6000 VA, 10 s	7360 VA, 10 s	9200 VA, 10 s	10000 VA, 10 s	12000 VA, 10 s
Back-up Switch Time	< 13 ms	< 13 ms	< 13 ms	< 13 ms	< 13 ms
Max. AC Output Current	13 A	16 A	20 A	22 A	26 A
Rated Output Voltage	1 / N / PE, 220 V / 230 V / 240 V				
Rated Output Grid Frequency	50 Hz / 60 Hz				
THDv	< 2%				
Efficiency					
MPPT Efficiency	99.90%				
Max. Efficiency	97.70%				
EU Efficiency	96.60%				
Protection					
Protection Class	I				
Anti-islanding Protection	Yes				
DC Reverse Polarity Protection	Yes				
Insulation Monitoring	Yes				
DC Surge Protection	II				
AC Surge Protection	III				
Residual Current Monitoring	Yes				
AC Overcurrent Protection	Yes				
DC Overvoltage Protection	Yes				
DC Undervoltage Protection	Yes				
AC Short-circuit Protection	Yes				
Over Voltage Category	DC : II / AC : III				
Battery Reverse Charging From Grid	Yes				
Ground Fault	Yes				
Over-heat Protection	Yes				
General Data					
Operating Temperature Range	-25 °C~ +60 °C				
Relative Operating Humidity	0 ~ 100 %RH, Non-Condensing				
Operating Altitude	4000 m				
Cooling	Natural Convection				
Noise	< 25 dB				
Dimensions	480 mm * 480 mm * 180 mm				
Weight	20 kg				
Inverter Topology	Non-isolated				
Display	LED				
Parallel Operation	3				
Communication	WiFi, LAN, Bluetooth, RS485, CAN				
Ingress Protection	IP65				
Nighttime Power	< 13 W				
Standards Compliance					
Safety / EMCStandard	EN / IEC 62109-1 / 2, EN / IEC 62040-1, EN / IEC 62477-1, EN IEC 61000-6, EN IEC 61000-3				
Grid Connection Standard	CEI 0-21, EN 50549-1, VDE-AR-N 4105, UNE 217002, NTS TYPEA, G99				



BATTERY-BOX HVE



KEY FEATURES



Space Saving

One of the thinnest batteries in the world
with a thickness of only 140mm
Saving more space



Intelligence

Compatible with BYD inverters and APP,
integrated system for remote diagnosis and OTA



Ultra Safety

LFP expertise since 2002
1M+ systems in 100+ countries
Safety design from cell to pack



Flexibility

2 varied capacity modules
Flexible 12 capacity options



Easy Installation

Patented internal plug connection
Plug-and-play




Convenience

Wall- & floor-mounted
installation options

BATTERY-BOX HVE



HVE 4.2 / 6.4



HVE 23.6



3 x HVE 23.6

Maximum capacity of

70.92 kWh



TECHNICAL PARAMETERS HVE



HVE 4.2 Module



HVE 6.4 Module

BATTERY MODULE	4.29 kWh, 76.8 V, 347 x 660 x 140 mm, 42.1 kg			6.45 kWh, 115.2 V, 499 x 660 x 140 mm, 61.1 kg		
PERFORMANCE	HVE 6.4	HVE 8.5	HVE 10.7	HVE 12.9	HVE 12.8	HVE 15.0
Number of Modules	1(6)	2(4+4)	2(4+6)	2(6+6)	3(4+4+4)	3(4+4+6)
Usable Energy ^[1]	6.45 kWh	8.58 kWh	10.74 kWh	12.90 kWh	12.87 kWh	15.03 kWh
Operating Voltage	90 ~ 131.4 V	120 ~ 175.2 V	150 ~ 219 V	180 ~ 262.8 V	180 ~ 262.8 V	210 ~ 306.6 V
Dimensions(H/W/D)(mm) ^[2]	709 x 660 x 140	901 x 660 x 140	1054 x 660 x 140	1208 x 660 x 140	1247 x 660 x 140	1400 x 660 x 140
Weight	71.6 kg	94.7 kg	113.7 kg	132.7 kg	136.8 kg	155.8 kg
	HVE 17.1-1	HVE 19.3-1	HVE 17.1-2	HVE 19.3-2	HVE 21.4	HVE 23.6
Number of Modules	3(4+6+6)	3(6+6+6)	4(4+4+4+4)	4(4+4+4+6)	4(4+4+6+6)	4(4+6+6+6)
Usable Energy ^[1]	17.19 kWh	19.35 kWh	17.16 kWh	19.32 kWh	21.48 kWh	23.64 kWh
Operating Voltage	240 ~ 350.4 V	270 ~ 394.2 V	240 ~ 350.4 V	270 ~ 394.2 V	300 ~ 438 V	330 ~ 481.8 V
Dimensions(H/W/D)(mm) ^[2]	1553 x 660 x 140	1706 x 660 x 140	1592 x 660 x 140	1745 x 660 x 140	1898 x 660 x 140	2051 x 660 x 140
Weight	174.8 kg	193.8 kg	178.9 kg	197.9 kg	216.9 kg	235.9 kg

GENERAL DATA

Max.Charge and Discharge Current ^[3]	35 A
Peak Charge and Discharge Current ^[3]	70 A, 10 s
Scalability	Max. 3 in Parallel (70.92 kWh)
Installation Mode	Floor Stand (standard) / Wall Mount (optional)
Installation Scene	Indoor & outdoor installation
Communication	CAN / RS485
Round-trip Efficiency	≥ 95%
Applications	On Grid / On Grid + Backup / Off Grid
Operating Temperature	-20 °C to +55 °C
IP Class	IP65
Cooling	Natural Convection
Storage Humidity	5%~95%
Altitude ^[4]	< 4000 m
Warranty ^[5]	15 Years
Accessories (Optional)	BYD smart WIFI/LAN module, Wall-mounting Bracket
Certification	IEC 62619 / IEC 62040 / IEC 62477-1 / EN 61000-6-1/2/3/4 / EN 301489-1 / EN 301489-17 / EN 300328 / EN 62311 / VDE-AR-E 2510-50 / RCM / CEC / REACH / RoHS / UN38.3 BYD Power-Box SH3-6K, BYD Power-Box TH5-15K
Compatibilities	

[1] DC Usable Energy, Test conditions: 0.2C charge & discharge at + 25°C.

[2] This height does not include adjustable foot height.

[3] Charge derating will occur between -10°C and +10°C, discharge derating will occur between -20°C and +10°C.

[4] The output power may be affected by altitude. Please refer to the user manual for details.

[5] Conditions apply. Refer to BYD Battery-Box HVE Limited Warranty Letter.