

# 3GPP TS 33.514 V20.0.0 (2026-03)

---

*Technical Specification*

## **3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; 5G Security Assurance Specification (SCAS) for the Unified Data Management (UDM) network product class (Release 20)**

---



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP.. The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification.

Specifications and Reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices

---

Keywords

SCAS, UDM, product class, security, 5G

**3GPP**

Postal address

3GPP support office address  
650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE  
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet  
<http://www.3gpp.org>

# Contents

|                                                                                                              |    |
|--------------------------------------------------------------------------------------------------------------|----|
| Foreword.....                                                                                                | 4  |
| 1 Scope.....                                                                                                 | 6  |
| 2 References.....                                                                                            | 6  |
| 3 Definitions of terms, symbols and abbreviations.....                                                       | 6  |
| 3.1 Terms.....                                                                                               | 6  |
| 3.2 Symbols.....                                                                                             | 7  |
| 3.3 Abbreviations.....                                                                                       | 7  |
| 4 UDM-specific security requirements and related test cases.....                                             | 7  |
| 4.1 Introduction.....                                                                                        | 7  |
| 4.2 Security functional requirements on the UDM derived from 3GPP specifications and related test cases..... | 7  |
| 4.2.0 General.....                                                                                           | 7  |
| 4.2.1 User Privacy Procedure.....                                                                            | 8  |
| 4.2.1.1 De-concealment of SUPI from the SUCI based on the protection scheme used to generate the SUCI.....   | 8  |
| 4.2.1.2 Rejection of SUCIs using an ECIES protection scheme with an invalid public key.....                  | 9  |
| 4.2.1.3 Rejection of SUCIs using an uncompressed point with Profile B.....                                   | 9  |
| 4.2.2 Authentication and key agreement procedure.....                                                        | 10 |
| 4.2.2.1 Synchronization failure handling.....                                                                | 10 |
| 4.2.2.2 Storing of authentication status of UE by UDM.....                                                   | 11 |
| 4.2.3 Technical Baseline.....                                                                                | 12 |
| 4.2.3.1 Introduction.....                                                                                    | 12 |
| 4.2.3.2 Protecting data and information.....                                                                 | 12 |
| 4.2.3.2.1 Protecting data and information – general.....                                                     | 12 |
| 4.2.3.2.2 Protecting data and information – unauthorized viewing.....                                        | 12 |
| 4.2.3.2.3 Protecting data and information in storage.....                                                    | 12 |
| 4.2.3.2.4 Protecting data and information in transfer.....                                                   | 12 |
| 4.2.3.2.5 Logging access to personal data.....                                                               | 12 |
| 4.2.3.3 Protecting availability and integrity.....                                                           | 12 |
| 4.2.3.4 Authentication and authorization.....                                                                | 13 |
| 4.2.3.5 Protecting sessions.....                                                                             | 13 |
| 4.2.3.6 Logging.....                                                                                         | 13 |
| 4.2.4 Operating Systems.....                                                                                 | 13 |
| 4.2.5 Web Servers.....                                                                                       | 13 |
| 4.2.6 Network Devices.....                                                                                   | 13 |
| 4.2.7 User plane security procedures for TSC service.....                                                    | 13 |
| 4.2.7.1 UP Security enforcement configuration for TSC service.....                                           | 13 |
| 4.2.8 User plane security procedures for 5G LAN service.....                                                 | 14 |
| 4.2.8.1 UP security policy configuration for 5G LAN service.....                                             | 14 |
| 4.3 UDM-specific adaptations of hardening requirements and related test cases.....                           | 15 |
| 4.3.1 Introduction.....                                                                                      | 15 |
| 4.3.2 Technical baseline.....                                                                                | 15 |

## Copyright Notification

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© 2026, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).  
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members  
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners  
LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners  
GSM® and the GSM logo are registered and owned by the GSM Association

4.3.3 Operating systems..... 16

4.3.4 Web servers..... 16

4.3.5 Network devices..... 16

4.3.6 Network functions in service-based architecture..... 16

4.4 UDM-specific adaptations of basic vulnerability testing requirements and related test cases..... 16

4.4.1 Introduction..... 16

4.4.2 Port scanning..... 16

4.4.3 Vulnerability scanning..... 16

4.4.4 Robustness and fuzz testing..... 16

**Annex A (informative): Change history..... 17**

---

## Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

**might not** indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

**is** (or any other verb in the indicative mood) indicates a statement of fact

**is not** (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

---

# 1 Scope

The present document contains requirements and test cases that are specific to the UDM network product class. It refers to the Catalogue of General Security Assurance Requirements and formulates specific adaptations of the requirements and test cases. It also specifies the requirements and test cases unique to the UDM network product class.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 33.501: "Security architecture and procedures for 5G system".
- [3] 3GPP TS 33.117: "Catalogue of general security assurance requirements".
- [4] 3GPP TR 33.926 "Security Assurance Specification (SCAS) threats and critical assets in 3GPP network product classes".
- [5] 3GPP TS 23.501: "System Architecture for the 5G System (5GS)".
- [6] 3GPP TS 23.003: "Numbering, addressing and identification".
- [7] 3GPP TS 33.102: "3G security; Security architecture".
- [8] SECG SEC 1: Recommended Elliptic Curve Cryptography, Version 2.0, 2009. Available <http://www.secg.org/sec1-v2.pdf>
- [9] 3GPP TS 29.503: "Unified Data Management Services".
- [10] 3GPP TR 33.916: "Security Assurance Methodology (SECAM) for 3GPP network products".

---

# 3 Definitions of terms, symbols and abbreviations

## 3.1 Terms

For the purposes of the present document, the terms given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

**Subscription Identifier:** Defined in TS 33.501 [2] and in TS 23.003 [6].

**Subscription Concealed Identifier:** Defined in TS 33.501 [2].

**Subscription Identifier De-concealing Function:** Defined in TS 33.501 [2].

**Network Function:** As defined in TS 23.501 [5].

**Network Product:** As defined in TR 33.916 [10].

**Network Product Class:** As defined in TR 33.916 [10].

**Pcap file:** A file format used to store network packet data captured from a network interface.

**Screenshot:** A digital image that shows the contents of a display.

**Vulnerability:** As defined in TR 33.916 [10].

## 3.2 Symbols

Void.

## 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

|      |                                                              |
|------|--------------------------------------------------------------|
| 5GS  | 5G System                                                    |
| AMF  | Access and Mobility Management Function                      |
| AKA  | Authentication and Key Agreement                             |
| ARPF | Authentication credential Repository and Processing Function |
| AUSF | Authentication Server Function                               |
| AV   | Authentication Vector                                        |
| EAP  | Extensible Authentication Protocol                           |
| JSON | Javascript Object Notation                                   |
| SBA  | Service Based Architecture                                   |
| SBI  | Service Based Interfaces                                     |
| SIDF | Subscription Identifier De-concealing Function               |
| SUCI | Subscription Concealed Identifier                            |
| SUPI | Subscription Permanent Identifier                            |
| TSC  | Time Sensitive Communication                                 |
| UDM  | Unified Data Management                                      |
| UDR  | Unified Data Repository                                      |

---

# 4 UDM-specific security requirements and related test cases

## 4.1 Introduction

UDM specific security requirements include both requirements derived from UDM specific security functional requirements in relevant specifications as well as security requirements introduced in the present document derived from the threats specific to UDM as described in TR 33.926 [4].

## 4.2 Security functional requirements on the UDM derived from 3GPP specifications and related test cases

### 4.2.0 General

The general approach in TS 33.117 [3] clause 4.2.2.1 and all the requirements and test cases in TS 33.117 [3] clause 4.2.2.2 related to SBA/SBI aspect apply to the UDM network product class.



## 4.2.1 User Privacy Procedure

### 4.2.1.1 De-concealment of SUPI from the SUCI based on the protection scheme used to generate the SUCI

*Requirement Name:* De-concealment of SUPI from the SUCI based on the protection scheme used to generate the SUCI.

*Requirement Reference:* TS 33.501 [2], clause 5.8.2.

*Requirement Description:* The SIDF resolves the SUPI from the SUCI based on the protection scheme used to generate the SUCI as specified in TS 33.501 [2], clause 5.8.2.

*Threat References:* TR 33.926 [4], clause E.2.2.1, Incorrect SUCI de-concealment.

*Test Case:*

**Test Name:** TC\_DE-CONCEAL\_SUPI\_from\_SUCI\_UDM

**Purpose:**

Verify that the SIDF De-conceals the SUPI from the SUCI based on the protection scheme used to generate the SUCI.

**Pre-Condition:**

- UDM network product is connected in simulated/real network environment including an AUSF and AMF.
- Tester shall have access to the subscription data stored in UDR.
- Tester shall record the SUPI from the UE.
- Tester shall provision subscription data in the UDR and for the UE with the following protection schemes (see TS 33.501 [2], clause Annex C):
  - Null-scheme (mandatory to support).
  - Profile A (mandatory to support).
  - Profile B (mandatory to support).
  - any other implemented protection scheme as stated in the vendor documentation.

**Execution Steps:**

Tester shall capture the procedure between UDM and AUSF over N13 interface, AMF and AUSF over N12 interface using any network analyser.

For every implemented protection scheme the tester repeats the following steps:

1. Tester shall filter the Nudm\_UEAuthentication\_Get Response message sent from UDM to AUSF over N13 interface containing the SUPI.
2. Tester shall compare the SUPI gotten from UE and the SUPI retrieved from Nudm\_UEAuthentication\_Get Response message.

**NOTE:** The tester may filter the Nausf\_UEAuthentication\_Authenticate Response message sent from the UDM/AUSF to the AMF over N12 interface containing the SUPI, if the UDM and AUSF network products are collocated without an open N13 interface.

**Expected Results:**

SIDF resolves the SUPI from the SUCI based on the protection scheme used to generate the SUCI.

**Expected format of evidence:**

Evidence suitable for the interface, e.g., evidence can be presented in the form of screenshot/screen-capture.

#### 4.2.1.2 Rejection of SUCIs using an ECIES protection scheme with an invalid public key.

*Requirement Name:* Rejection of SUCIs using an ECIES protection scheme with an invalid public key.

*Requirement Reference:* TS 33.501 [2], clause C.3.3 with reference to SECG SEC 1 [8] clause 2.3.4.

*Requirement Description:* Output: An elliptic curve point P, or "invalid" as specified [8], clause 2.3.4.

*Threat References:* TR 33.926 [4], clause E.2.2.6, Invalid public key.

*Test Case:*

**Test Name:** TC\_REJECT\_SUCI\_PROFILE\_B\_INVALID\_PUBKEY\_UDM

**Purpose:**

Verify that the SIDF rejects the SUCI if it uses an ECIES protection scheme and contains an invalid point as the UE's public key for Profile B.

**Pre-Condition:**

- The tester has access to the public information of the SUCI profile (e.g., profile type, public key ...) of the UDM/SIDF under test.
- The tester has configured the UDM to use Profile B.
- The tester has access to a SUPI of provisioned subscriber.

**Execution Steps**

1. The tester selects an invalid point (NOTE 1) and uses the point as a public key to encrypt the SUPI based on the encryption defined in Annex C of 33.501 [2] and SECG SEC 1 [8] (NOTE 2).
2. The tester sends the SUCI to the Nudm\_UEAuthentication\_Get service of the UDM/ SIDF under test.

NOTE 1: An example invalid point for Profile B (of order 47) is:

0x049af0190d4e237c462c94c447052c770f6d348866f1dbbe29a0ee889f18835d6a973457a6730323716ef2c8a3723793be64b54cec40eb86ab194057c95baf8cfe.

NOTE 2: An example SUCI encrypted with the invalid point (above) for the MCC|MNC (274012) and MSIN (001002086) for Profile B (Annex C of 33.501 [2]) is: suci-0-274-012-0-2-

049af0190d4e237c462c94c447052c770f6d348866f1dbbe29a0ee889f18835d6a973457a6730323716ef2c8a3723793be64b54cec40eb86ab194057c95baf8cfe8cf9a0959454b74e31a331018b.

**Expected Results:**

The UDM/SIDF rejects the SUCI, and the UDM sends a Nudm\_UEAuthentication\_Get Response message with an HTTP status code "403 Forbidden" and may include additional error information in the response body (in "ProblemDetails" element) as specified in TS 29.503 [9], clause 5.4.2.2.2, 2b.

NOTE 3: Values for "ProblemDetails" may be AUTHENTICATION\_REJECTED or INVALID\_SCHEME\_OUTPUT as specified in TS 29.503 [9], clause 6.3.3.2.4.2.2-2.

**Expected format of evidence:**

Evidence suitable for the interface, e.g., evidence can be presented in the form of packet trace (e.g., pcap file).

#### 4.2.1.3 Rejection of SUCIs using an uncompressed point with Profile B.

*Requirement Name:* Rejection of SUCIs using an uncompressed point with Profile B.

*Requirement Reference:* TS 33.501 [2], clause C.3.4.0.

*Requirement Description:* Profile B shall use point compression to save overhead as specified in TS 33.501 [2], clause C.3.4.0.

*Threat References:* TR 33.926 [4], clause E.2.2.6, Invalid public key.

*Test Case:*

**Test Name:** TC\_REJECT\_SUCI\_PROFILE\_B\_NO\_COMPRESSION\_UDM

**Purpose:**

Verify that the SIDF rejects the SUCI if it uses the ECIES Profile B protection scheme and contains an uncompressed point as the UE's public key.

**Pre-Condition:**

Tester shall have access to the HN's public key for SUCI decryption with Profile B.

**Execution Steps**

1. The tester shall generate a SUCI for a registered SUPI with the protection scheme output for Profile B. Theephemeral public key of the UE should be in the uncompressed point format specified in SECG SEC 1 [8] clause 2.3.3. The remaining parts of the protection scheme output retain their format specified in SECG SEC 1 [8].

NOTE 1: The uncompressed point format shall have a size of 65 bytes, and the most significant byte shall be 0x04. The compressed point format shall have a size of 33 bytes, with 0x02 or 0x03 as the most significant byte. Test data in TS 33.501 [2], clause C.4.4.1.

2. The tester shall send the SUCI to the Nudm\_UEAuthentication\_Get service of the UDM/ SIDF under test.

**Expected Results:**

The SIDF rejects the SUCI, and the UDM sends a Nudm\_UEAuthentication\_Get Response message with an HTTP status code "403 Forbidden" and may include additional error information in the response body (in "ProblemDetails" element) as specified in TS 29.503 [9], clause 5.4.2.2.2, 2b.

NOTE 2: Values for "ProblemDetails" may be AUTHENTICATION\_REJECTED or INVALID\_SCHEME\_OUTPUT as specified in TS 29.503 [9], clause 6.3.3.2.4.2.2-2.

**Expected format of evidence:**

Evidence suitable for the interface, e.g., evidence can be presented in the form of packet trace (e.g., pcap file).

## 4.2.2 Authentication and key agreement procedure

### 4.2.2.1 Synchronization failure handling

*Requirement Name:* Synchronization failure handling

*Requirement Reference:* TS 33.501 [2], clause 6.1.3.3.2.

*Requirement Description:* When the UDM/ARPF receives an Nudm\_UEAuthentication\_Get Request message with a "synchronisation failure indication" it acts as described in TS 33.102 [7], clause 6.3.5 where ARPF is mapped to HE/AuC. The UDM/ARPF sends an Nudm\_UEAuthentication\_Get Response message with a new authentication vector for either EAP-AKA' or 5G-AKA depending on the authentication method applicable for the user to the AUSF as specified in TS 33.501 [2], clause 6.1.3.3.2.

*Threat References:* TR 33.926 [4], clause E.2.2.2, Synchronization failure.

*Test Case:*

**Test Name:** TC\_SYNC\_FAILURE\_HANDLING\_UDM

**Purpose:**

Verify that synchronization failure is recovered correctly in the home network.

**Pre-Conditions:**

Test environment with an AUSF. The AUSF or AMF may be simulated.

**Execution Steps:**

1. The tester sends an Nudm\_UEAuthentication\_Get Request message to the UDM under test with a "synchronisation failure indication" and parameters RAND and AUTS.
2. The UDM/ARPF performs steps 1-5 as described in TS 33.102, clause 6.3.5, and sends the Nudm\_UEAuthentication\_Get Response message to the AUSF.
3. The tester checks whether the Nudm\_UEAuthentication\_Get Response message sent from the UDM under test contains a new authentication vector.

**Expected Results:**

The UDM sends an Nudm\_UEAuthentication\_Get Response message with a new authentication vector to the AUSF.

NOTE: The expected results would be that the UDM/AUSF sends an Nausf\_UEAuthentication\_Authenticate Response message with EAP Request/AKA'-Challenge for EAP AKA', or 5G SE AV for 5G AKA to the AMF, if the UDM and AUSF network products are collocated without an open N13 interface.

**Expected format of evidence:**

Evidence suitable for the interface, e.g., Screenshot, packet capture or application log containing the operational results.

#### 4.2.2.2 Storing of authentication status of UE by UDM

*Requirement Name:* Storing of authentication status of UE by UDM.

*Requirement Reference:* TS 33.501 [2], clause 6.1.4.1a

*Requirement Description:* The UDM stores the authentication status of the UE (SUPI, authentication result, time stamp, and the serving network name) after authentication as specified in TS 33.501 [2], clause 6.1.4.1a.

*Threat References:* TR 33.926 [4], clause E.2.2.3, Failure to store of authentication status.

*Test Case:*

**Test Name:** TC\_AUTH\_STATUS\_STORE\_UDM

**Purpose:**

Verify that the UDM under test stores the authentication status of UE.

**Pre-Condition:**

- UDM network product is connected with an AUSF in simulated/real network environment.
- The tester shall have access to the UDM under test.

**Execution Steps:**

1. The tester shall send an Nudm\_UEAuthentication\_Get Request message to the UDM with the UE credentials and a selected serving network name.
2. The tester shall receive a successful Nudm\_UEAuthentication\_Get Response from the UDM.
3. The tester shall simulate the successful authentication by sending the Nudm\_UEAuthentication\_ResultConfirmation Request message with a selected timestamp to the UDM.
4. The tester shall receive a successful Nudm\_UEAuthentication\_ResultConfirmation Response message from the UDM.

5. The tester shall compare the serving network name stored in the UDM against the serving network name retrieved from the Nudm\_UEAuthentication\_Get Request message and the serving network name retrieved from the Nudm\_UEAuthentication\_ResultConfirmation Request message.
6. The tester shall compare the SUPI stored in the UDM (retrieved from the Nudm\_UEAuthentication\_ResultConfirmation Response message) against the SUPI retrieved from the Nudm\_UEAuthentication\_Get Response message.
7. The tester shall compare the timestamp stored in the UDM against the time of authentication procedure retrieved from the Nudm\_UEAuthentication\_ResultConfirmation Request message.

**Expected Results:**

The storing of authentication status (SUPI, timestamp, and the serving network name) of UE at the UDM is verified.

**Expected format of evidence:**

Evidence suitable for the interface, e.g., evidence can be presented in the form of packet capture or screenshot/screen-capture.

NOTE: Void

## 4.2.3 Technical Baseline

### 4.2.3.1 Introduction

The present clause provides baseline technical requirements.

### 4.2.3.2 Protecting data and information

#### 4.2.3.2.1 Protecting data and information – general

There are no UDM-specific additions to clause 4.2.3.2.1 of TS 33.117 [3].

#### 4.2.3.2.2 Protecting data and information – unauthorized viewing

There are no UDM-specific additions to clause 4.2.3.2.2 of TS 33.117 [3].

#### 4.2.3.2.3 Protecting data and information in storage

There are no UDM-specific additions to clause 4.2.3.2.3 of TS 33.117 [3].

#### 4.2.3.2.4 Protecting data and information in transfer

There are no UDM-specific additions to clause 4.2.3.2.4 of TS 33.117 [3].

#### 4.2.3.2.5 Logging access to personal data

There are no UDM-specific additions to clause 4.2.3.2.5 of TS 33.117 [3].

### 4.2.3.3 Protecting availability and integrity

There are no UDM-specific additions to clause 4.2.3.3 of TS 33.117 [3].

### 4.2.3.4 Authentication and authorization

There are no UDM-specific additions to clause 4.2.3.4 of TS 33.117 [3].

### 4.2.3.5 Protecting sessions

There are no UDM-specific additions to clause 4.2.3.5 of TS 33.117 [3].

#### 4.2.3.6 Logging

There are no UDM-specific additions to clause 4.2.3.6 of TS 33.117 [3].

### 4.2.4 Operating Systems

There are no UDM-specific additions to clause 4.2.4 of TS 33.117 [3].

### 4.2.5 Web Servers

There are no UDM-specific additions to clause 4.2.5 of TS 33.117 [3].

### 4.2.6 Network Devices

There are no UDM-specific additions to clause 4.2.6 of TS 33.117 [3].

## 4.2.7 User plane security procedures for TSC service

### 4.2.7.1 UP Security enforcement configuration for TSC service

*Requirement Name:* UP security enforcement configuration

*Requirement Reference:* TS 33.501 [2], clause L.3, TS 23.501 [5], clause 5.10.3.

*Requirement Description:*

"After the 5GS TSC-enabled UE is authenticated and data connection is set up, any data received from a TSC bridge or another 5GS TSC-enabled UE shall be transported between DS-TT (in the UE) and NW-TT (in the UPF) in a protected way using the mechanisms for UP security as described in clause 6.6.

The UP security enforcement information shall be set to "required" for data transferred from gNB to a 5GS TSC-enabled UE. This is also applicable to the gPTP messages sent in the user plane."

as specified in TS 33.501 [2], clause L.3.

"The SMF determines at PDU session establishment a User Plane Security Enforcement information for the user plane of a PDU session based on:

- subscribed User Plane Security Policy which is part of SM subscription information received from UDM; and
- User Plane Security Policy locally configured per (DNN, S-NSSAI) in the SMF that is used when the UDM does not provide User Plane Security Policy information.
- The maximum supported data rate per UE for integrity protection for the DRBs, provided by the UE in the Integrity protection maximum data rate IE during PDU Session Establishment. The UE supporting NR as primary RAT, i.e. NG-RAN access via Standalone NR, shall set the Integrity protection maximum data rate IE for Uplink and Downlink to full rate at PDU Session Establishment as defined in TS 24.501 [47]."

as specified in TS 23.501 [5], clause 5.10.3.

*Threat References:* TR 33.926 [4].

NOTE: The test case below only applies to the UDMs which support the setting and providing of User Plane Security Policy for dedicated TSC service.

*Test Case:*

Test Name: TC\_UP\_SECURITY\_ENFORCEMENT\_CONFIGURATION

**Purpose:**

Verify that UP security enforcement information is set to "required" for dedicated TSC service.

**Pre-Conditions:**

Test environment with SMF. The SMF may be simulated.

A dedicated DNN/S-NSSAI combination is defined to identify the TSC service.

The security policy is configured in the UDM.

**Execution Steps**

1. During the PDU session establishment procedure, the SMF sends a Nudm\_SDM\_Get Request message to the UDM under test with a dedicated DNN/S-NSSAI combination.
2. The UDM under test sends the Nudm\_SDM\_Get Response back to the SMF with UP security enforcement information.
3. The tester checks the UP security enforcement information contained in the Nudm\_SDM\_Get Response message.

**Expected Results:**

The confidentiality and integrity protection requirements of the UP security enforcement information are set to "required".

**Expected format of evidence:**

Save the logs and the communication flow in a .pcap file.

## 4.2.8 User plane security procedures for 5G LAN service

### 4.2.8.1 UP security policy configuration for 5G LAN service

*Requirement Name:* UP security enforcement configuration

*Requirement Reference:* TS 33.501 [2], clause K.3, TS 23.501 [5], clause 5.10.3.

*Requirement Description:* "To reduce incremental complexity added by security, all PDU sessions associated with a specific 5G LAN group should have the same UP security policy. When generating the policy enforcement information, and to avoid the redundant double protection, the SMF may consider information by a DN-AAA about DN protection mechanisms already applied."

as specified in TS 33.501 [2], clause K.3.

"The SMF determines at PDU session establishment a User Plane Security Enforcement information for the user plane of a PDU session based on:

- subscribed User Plane Security Policy which is part of SM subscription information received from UDM; and
- User Plane Security Policy locally configured per (DNN, S-NSSAI) in the SMF that is used when the UDM does not provide User Plane Security Policy information.
- The maximum supported data rate per UE for integrity protection for the DRBs, provided by the UE in the Integrity protection maximum data rate IE during PDU Session Establishment. The UE supporting NR as primary RAT, i.e. NG-RAN access via Standalone NR, shall set the Integrity protection maximum data rate IE for Uplink and Downlink to full rate at PDU Session Establishment as defined in TS 24.501 [47]."

as specified in TS 23.501 [5], clause 5.10.3.

*Threat References:* TR 33.926 [4].

NOTE 1: The test case below only applies to the UDMs which support the setting and providing of User Plane Security Policy for 5G LAN service.

*Test Case:*

Test Name: TC\_UP\_SECURITY\_ENFORCEMENT\_CONFIGURATION\_FOR\_5G\_LAN

**Purpose:**

Verify that UP security policy is set to the same for all the 5G LAN UEs.

**Pre-Conditions:**

Test environment with SMF. The SMF may be simulated.

A dedicated DNN/S-NSSAI combination is defined to identify the 5G LAN service.

The security policy of the 5G LAN service is configured in the UDM.

**Execution Steps**

1. During the PDU session establishment procedure initiated by the UE1, the SMF1 sends a Nudm\_SDM\_Get Request message to the UDM under test with the dedicated DNN/S-NSSAI combination defined to identify the 5G LAN service, and SUPI1.
2. The UDM under test sends the Nudm\_SDM\_Get Response back to the SMF1 with UP security policy1.
3. During the PDU session establishment procedure initiated by the UE2, the SMF2 sends a Nudm\_SDM\_Get Request message to the UDM under test with the dedicated DNN/S-NSSAI combination, defined to identify the 5G LAN service and SUPI2.
4. The UDM under test sends the Nudm\_SDM\_Get Response back to the SMF2 with UP security policy2.
5. The tester compares the UP security policies contained in the Nudm\_SDM\_Get Response messages in step 2 and step 4.

NOTE 2: SMF1 and SMF2 could be the same network function.

**Expected Results:**

The confidentiality and integrity protection requirements of the UP security policies received in step 2 and step 4 are the same.

**Expected format of evidence:**

Save the logs and the communication flow in a .pcap file.

## 4.3 UDM-specific adaptations of hardening requirements and related test cases

### 4.3.1 Introduction

The present clause contains UDM-specific adaptations of hardening requirements and related test cases.

### 4.3.2 Technical baseline

There are no UDM-specific additions to clause 4.3.2 of TS 33.117 [3].

### 4.3.3 Operating systems

There are no UDM-specific additions to clause 4.3.3 of TS 33.117 [3].



#### 4.3.4 Web servers

There are no UDM-specific additions to clause 4.3.4 of TS 33.117 [3].

#### 4.3.5 Network devices

There are no UDM-specific additions to clause 4.3.5 of TS 33.117 [3].

#### 4.3.6 Network functions in service-based architecture

There are no UDM-specific additions to clause 4.3.6 in TS 33.117 [3].

### 4.4 UDM-specific adaptations of basic vulnerability testing requirements and related test cases

#### 4.4.1 Introduction

There are no UDM specific additions to clause 4.4.1 of TS 33.117 [3].

#### 4.4.2 Port scanning

There are no UDM specific additions to clause 4.4.2 of TS 33.117 [3].

#### 4.4.3 Vulnerability scanning

There are no UDM specific additions to clause 4.4.3 of TS 33.117 [3].

#### 4.4.4 Robustness and fuzz testing

The test cases under clause 4.4.4 of TS 33.117 [3] are applicable to UDM.

The interfaces defined for the UDM are in clause 4.2.3 of TS 23.501 [5].

According to clause 4.4.4 of TS 33.117 [3], the transport protocols available on the interfaces providing IP-based protocols need to be robustness tested. Following TCP/IP layer model and considering all the protocols over transport layer, for UDM, the following interface and protocols are in the scope of the testing:

- For Nudm: The TCP, TLS, HTTP2 and JSON protocols.

NOTE: There could be other interfaces and/or protocols requiring testing under clause 4.4.4 of TS 33.117 [3].

## Annex A (informative): Change history

| Change history |         |           |      |     |     |                                                                                                                         |             |
|----------------|---------|-----------|------|-----|-----|-------------------------------------------------------------------------------------------------------------------------|-------------|
| Date           | Meeting | TDoc      | CR   | Rev | Cat | Subject/Comment                                                                                                         | New version |
| 2019-09        | SA#85   |           |      |     |     | Change control version                                                                                                  | 16.0.0      |
| 2019-10        |         |           |      |     |     | EditHelp review                                                                                                         | 16.0.1      |
| 2019-12        | SA#86   | SP-191138 | 0001 | -   | F   | Corrections for clean-up and alignment                                                                                  | 16.1.0      |
| 2020-07        | SA#88E  | SP-200358 | 0002 | -   | F   | Update to the test case of Storing of UE authentication status by UDM                                                   | 16.2.0      |
| 2020-09        | SA#89E  | SP-200703 | 0003 | -   | F   | Clarification on the test cases if the UDM and AUSF are collocated                                                      | 16.3.0      |
| 2020-12        | SA#90e  | SP-201004 | 0004 | -   | F   | Reference of general SBA/SBI aspect in 33.514                                                                           | 16.4.0      |
| 2021-06        | SA#92e  | SP-210440 | 0005 | -   | B   | CR to include R-16 feature of UDM to 33.514                                                                             | 17.0.0      |
| 2023-06        | SA#100  | SP-230604 | 0006 | 1   | B   | Robustness interfaces and protocols defined for UDM                                                                     | 18.0.0      |
| 2023-06        | SA#100  | SP-230604 | 0007 | 1   | F   | SCAS release reference corrections                                                                                      | 18.0.0      |
| 2023-09        | SA#101  | SP-230904 | 0009 | -   | F   | Correction of UDM service naming                                                                                        | 18.1.0      |
| 2023-12        | SA#102  | SP-231339 | 0010 | 1   | F   | Added missing Test Name and Expected format of evidence                                                                 | 18.2.0      |
| 2023-12        | SA#102  | SP-231339 | 0011 | 2   | F   | Added UDM SCAS test cases for checking an invalid and uncompressed point in ECIES protection scheme for SUCI decryption | 18.2.0      |
| 2024-06        | SA#104  | SP-240669 | 0018 | 1   | A   | Correction to terms                                                                                                     | 18.3.0      |
| 2024-06        | SA#104  | SP-240669 | 0021 | -   | A   | Correction to abbreviations                                                                                             | 18.3.0      |
| 2024-06        | SA#104  | SP-240669 | 0024 | -   | A   | Correction to test names                                                                                                | 18.3.0      |
| 2024-06        | SA#104  | SP-240668 | 0027 | -   | F   | Editorial correction of TEST CASE                                                                                       | 18.3.0      |
| 2024-06        | SA#104  | SP-240668 | 0030 | -   | F   | Fuzz TLS                                                                                                                | 18.3.0      |
| 2025-01        | SA#106  | SP-241798 | 0032 | -   | F   | Updating test case about authentication status of UE by UDM                                                             | 19.0.0      |
| 2025-07        | SA#108  | SP-250657 | 0034 | -   | F   | Clean up of 33.514                                                                                                      | 19.1.0      |
| 2026-03        | SA#111  | SP-260261 | 0035 | -   | F   | Update references and execution steps to TS 33.514                                                                      | 20.0.0      |