The lengthconvert package

Marco Daniel E-mail: marco.daniel@mada-nada.de

Released 2013/06/13

Sometimes it's useful for some explanation to provide lengths in standardizations units instead of the default unit of TEX. This package can do this for your.

Contents

1 Basics 1

2 Usage 2

3 Options 2

4 Examples 3

5 lengthconvert Implementation 4

Change History 10

Index 11

1 Basics

The package needs the newest version of l3kernel available at CTAN. Internally it uses the modul l3fp to convert the length.

All allowed units in TEX are listed in the table below.

Table 1: Allowed TEX units

Unit	Measurement
pt	point
pc	pica(1pc=12pt)
in	inch (1 in = 72.27 pt)
bp	bigpoint(72bp=1in)
cm	centimeter (2.54 cm = 1 in)
mm	millimeter (10 mm = 1 cm)
dd	didot point (1157 dd = 1238 pt)
cc	cicero (1 cc = 12 dd)
sp	scaled point (65536 sp = 1 pt)

2 Usage

The usage is really simple. Pass the length to the command `\Convert` and get the result.

`\Convert` `\Convert[`⟨*options*⟩`] {`⟨*length*⟩`}`

The command converts the given length to the unit specified by an option. The default unit is cm. After the conversion the result will be printed.

`\Convertsetup` `\Convertsetup {`⟨*options*⟩`}`

Allows the specification of options.

3 Options

The package is simple and the options too.

`unit` The option accepts only the abbrevation unit. Allowed units are described in the table above.

You can also use only the abbrevation or a complete word. The following table lists all allowed inputs.

pt	pc	in	bp	cm	mm
dd	cc	sp	point	pica	inch
big-point	centimeter	millimeter	didot-point	cicero	scaled-point

`use-siunitx` It's a bool flag which can be either `true` or `false`. If it is true, the output of the new length is done by the package siunitx using the command `\SI`.

`precision` This option accepts an integer and specifies the precision of the output.

`number-only` It's a bool flag which can be either `true` or `false`. If it's true, only the number is printed.

4 Examples

Some examples are shown in the following table. In the left column you see the input and in the right the output.

`\Convert{36pt}`	1.26526 cm
`\Convert[precision=2]{36pt}`	1.27 cm
`\Convert[use-siunitx]{36pt}`	1.265 26 cm
`\Convert[unit=pt]{2cm}`	56.9055 pt
`\Convert[unit=dd,number-only]{2cm}`	53.18229
`\Convert[pt]{2cm}`	56.9055 pt
`\Convert[scaled-point]{2cm}`	3729359 sp

5 lengthconvert Implementation

```
⟨*package⟩
⟨@@=lconv⟩
\ProvidesExplPackage
  {lengthconvert}{2013/05/13}{1.0}{Convert length to another unit}
```

Make sure that the version of l3kernel in use is sufficiently new. This will also trap any problems with l3packages (as the two are now tied together, version-wise).

```
\@ifpackagelater { expl3 } { 2012/11/21 }
  { }
  {
    \PackageError { lengthtconvert } { Support~package~expl3~too~old }
      {
        You~need~to~update~your~installation~of~the~bundles~'l3kernel'~and~
        'l3packages'.\MessageBreak
        Loading~lengthtconvert~will~abort!
      }
    \tex_endinput:D
  }
```

Now load the support packages.

```
\RequirePackage{ l3keys2e }
```

__lconv_allowed_shortunits_clist
__lconv_allowed_longunits_clist
__lconv_allowed_allunits_clist

Save all allowed units in a clist

```
\clist_new:N \g___lconv_allowed_shortunits_clist
\clist_gset:Nn \g___lconv_allowed_shortunits_clist
   { pt , pc , in , bp , cm , mm , dd , cc ,sp }
\clist_new:N \g___lconv_allowed_longunits_clist
\clist_gset:Nn \g___lconv_allowed_longunits_clist
   { point , pica , inch , big-point , centimeter , millimeter ,
     didot-point , cicero , scaled-point }
\clist_new:N \g___lconv_allowed_allunits_clist
\clist_gset:NV \g___lconv_allowed_allunits_clist \g___lconv_allowed_shortunits_clist
\clist_gput_right:NV \g___lconv_allowed_allunits_clist \g___lconv_allowed_longunits_clist
```

(*End definition for* `\__lconv_allowed_shortunits_clist`*. This function is documented on page* **??**.)

__lconv_unit_tl

Save the default unit in a token list variable and provide them as option

```
\tl_new:N \l___lconv_unit_tl
\keys_define:nn { lengthconvert }
 {
```

```
   unit  .tl_set:N = \l___lconv_unit_tl
 }
\keys_set:nn { lengthconvert }
 {
  unit  = cm ,
 }
```

Provide also abbreviation and word of units

```
\tl_new:N \l__lconv_default_unit_tl
\keys_define:nn { lengthconvert }
 {
    pt    .meta:n  =
            {  unit   =   pt     },
    pc    .meta:n  =
            {  unit   =   pc     },
    in    .meta:n  =
            {  unit   =   in     },
    bp    .meta:n  =
            {  unit   =   bp     },
    cm    .meta:n  =
            {  unit   =   cm     },
    mm    .meta:n  =
            {  unit   =   mm     },
    dd    .meta:n  =
            {  unit   =   dd     },
    cc    .meta:n  =
            {  unit   =   cc     },
    sp    .meta:n  =
            {  unit   =   sp     },
    point .meta:n  =
            {  unit   =   pt     },
    pica  .meta:n  =
            {  unit   =   pc     },
    inch  .meta:n  =
            {  unit   =   in     },
    big-point  .meta:n  =
            {  unit   =   bp     },
    centimeter .meta:n  =
            {  unit   =   cm     },
    millimeter .meta:n  =
```

```
            {  unit   =   mm     },
    didot-point .meta:n  =
            {  unit   =   dd     },
    cicero .meta:n  =
            {  unit   =   cc     },
    scaled-point .meta:n  =
            {  unit   =   sp     },
 }
```

(*End definition for* `\__lconv_unit_tl`. *This function is documented on page* ??.)

`\l___lconv_use_siunitx_bool` Output should be done by sinutix.

```
\keys_define:nn { lengthconvert } {
  use-siunitx   .bool_set:N = \l___lconv_use_siunitx_bool
}
```

(*End definition for* `\l___lconv_use_siunitx_bool`. *This function is documented on page* ??.)

`\l__lconv_precision_tl` Specify the precision

```
\keys_define:nn { lengthconvert } {
  precision   .int_set:N = \l___lconv_precision_int
}
\keys_set:nn { lengthconvert }
 {
  precision  = 5 ,
 }
```

(*End definition for* `\l__lconv_precision_tl`. *This function is documented on page* ??.)

`\l___lconv_only_num_bool` Only the number should be used

```
\keys_define:nn { lengthconvert } {
  number-only  .bool_set:N = \l___lconv_only_num_bool
}
```

(*End definition for* `\l___lconv_only_num_bool`. *This function is documented on page* ??.)

Unknown options should be raised an error

```
\keys_define:nn { lengthconvert } {
  unknown .code:n =
    {
      \msg_error:nnx { lengthconvert } { option-unknown }
            { \exp_not:V \l_keys_key_tl }
    }
}
```

\Convertsetup User settings

```
\NewDocumentCommand \Convertsetup { m }
 {
  \keys_set:nn { lengthconvert } { #1 }
 }
```

(*End definition for* `\Convertsetup`. *This function is documented on page* 2.)

\Convert Expandable definition of the main command

```
\DeclareExpandableDocumentCommand \Convert { O{} m }
 {
  \group_begin:
    \keys_set:nn { lengthconvert } { #1 }
    \clist_if_in:NVTF \g__lconv_allowed_allunits_clist \l___lconv_unit_tl
     {
      \bool_if:NTF \l___lconv_use_siunitx_bool
       {
        \__lconv_using_siunitx:n { #2 }
       }
       {
        \__lconv_nousing_siunitx:n { #2 }
       }
     }
     {
      \msg_error:nnx { lengthconvert } { unit-unknown }
            { \exp_not:V \l___lconv_unit_tl }
     }
  \group_end:
 }
```

(*End definition for* `\Convert`. *This function is documented on page* 2.)

__lconv_calc_dim:n Basic calc command

```
\cs_new:Npn \__lconv_calc_dim:n #1
 {
  \fp_eval:n
     {
      round( \dim_to_fp:n { #1 } / 1\l___lconv_unit_tl , \l___lconv_precision_int)
     }
 }
```

(*End definition for* `\__lconv_calc_dim:n`. *This function is documented on page* ??.)

__lconv_using_siunitx:n Output using siunitx

```
\cs_new:Npn \__lconv_using_siunitx:n #1
 {
  \bool_if:NTF \l___lconv_only_num_bool
   {
    \num { \__lconv_calc_dim:n { #1 } }
   }
   {
    \SI { \__lconv_calc_dim:n { #1 } } { \l___lconv_unit_tl }
   }
 }
```

(*End definition for* `\__lconv_using_siunitx:n`*. This function is documented on page* **??**.)

__lconv_nousing_siunitx:n Output using not siunitx

```
\cs_new:Npn \__lconv_nousing_siunitx:n #1
 {
  \bool_if:NTF \l___lconv_only_num_bool
   {
    \__lconv_calc_dim:n { #1 }
   }
   {
    \__lconv_calc_dim:n { #1 } \, \l___lconv_unit_tl
   }
 }
```

(*End definition for* `\__lconv_nousing_siunitx:n`*. This function is documented on page* **??**.)

```
\msg_new:nnnn { lengthconvert } { option-unknown }
  { Unknown~option~'#1'~for~package~#2. }
  {
    LaTeX~has~been~asked~to~set~an~option~called~'#1'~
    but~the~#2~package~has~not~created~an~option~with~this~name.
  }
\msg_new:nnnn { lengthconvert } { unit-unknown }
  { Unknown~unit~'#1'~for~package~#2. }
  {
    You~are~setting~an~unit~'#1'~which~
    is~unknonw~for~the~package~#2.
  }
```

Finally apply the settings given at load time.

```
\ProcessKeysOptions { lengthconvert }
```

160 ⟨/package⟩

Change History

v1.0

General: First official release 1

v1.0a

General: fixed typo in package name . . 1

v1.0b

General: fixed some explanation of code 1

removed package parskip from documentation 1

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols

\, ... 144
\@ifpackagelater 5
__lconv_allowed_allunits_clist 17
__lconv_allowed_longunits_clist . . . 17
__lconv_allowed_shortunits_clist . . 17
__lconv_calc_dim:n 120, 120, 131, 134, 141, 144
__lconv_nousing_siunitx:n 111, 137, 137
__lconv_unit_tl 27
__lconv_using_siunitx:n . . 108, 127, 127

B

\bool_if:NTF 106, 129, 139

C

\clist_gput_right:NV 26
\clist_gset:Nn 18, 21
\clist_gset:NV 25
\clist_if_in:NVTF 104
\clist_new:N 17, 20, 24
\Convert *2*, 100, 100
\Convertsetup *2*, 96, 96
\cs_new:Npn 120, 127, 137

D

\DeclareExpandableDocumentCommand . 100
\dim_to_fp:n 124

E

\exp_not:V 93, 116

F

\fp_eval:n 122

G

\g___lconv_allowed_allunits_clist 24, 25, 26
\g___lconv_allowed_longunits_clist 20, 21, 26
\g___lconv_allowed_shortunits_clist 17, 18, 25
\g__lconv_allowed_allunits_clist . . 104
\group_begin: 102
\group_end: 118

K

\keys_define:nn 28, 37, 76, 79, 86, 89
\keys_set:nn 32, 82, 98, 103

L

\l___lconv_only_num_bool 86, 87, 129, 139
\l___lconv_precision_int 80, 124
\l___lconv_unit_tl 27, 30, 104, 116, 124, 134, 144
\l___lconv_use_siunitx_bool . 76, 77, 106
\l__lconv_default_unit_tl 36
\l__lconv_precision_tl 79
\l_keys_key_tl 93

M

\MessageBreak 11
\msg_error:nnx 92, 115
\msg_new:nnnn 147, 153

N

\NewDocumentCommand 96
\num 131
number-only (option) *3*

O

options:
number-only *3*
precision *3*
unit *2*

use-siunitx 3

P

\PackageError 8
precision (option) 3
\ProcessKeysOptions 159
\ProvidesExplPackage 3

R

\RequirePackage 16

S

\SI 134

T

\tex_endinput:D 14
\tl_new:N 27, 36

U

unit (option) 2
use-siunitx (option) 3