

Project 1: Java Thread Pool in C++11

Marco Di Rienzo

marco.dirienzo@stud.unifi.it

Abstract

The goal of this paper is to implement a simple thread pool library in C++11.

1. Introduction

The developed library is entirely written in standard C++11 and allows the creation of a simple thread pool. In particular the pool should be of fixed size, that is the number of threads in the pool will not vary for the whole pool lifetime. Threads of the pool may consume tasks as they become available.

The API of the library is inspired by the Java class `ThreadPoolExecutor`.

2. Documentation

2.1. Runnable

The `Runnable` interface should be implemented by any class whose instances are intended to be executed by a `FixedThreadPool`. The class must define a method of no arguments called `run`.

2.1.1 Methods

`void run()`

Submitting an object implementing interface `Runnable` to a `FixedThreadPool` will cause the object's `run` method to be called in a separately executing thread.

2.2. FixedThreadPool

This class allows the creation of a pool that reuses a fixed number of threads operating off a shared unbounded queue. At any point, at most a fixed number of threads will be active processing tasks. If additional tasks are submitted when all threads are active, they will wait in the queue until a thread is available. The threads in the pool will exist until it is explicitly shutdown.

2.2.1 Constructor & Destructor

`FixedThreadPool(int n_threads)`

Creates a `FixedThreadPool` with `n_threads` initial threads, the number of threads will remain constant for the whole pool lifetime.

`~FixedThreadPool`

Calls `shutdown` if pool is not already shut down.

2.2.2 Methods

`void execute(Runnable *command)`

Executes the given command at some time in the future. The command will be executed by a thread of the pool.

`size_t getPoolSize() const`

Returns the current number of threads in the pool.

`size_t getTaskCount() const`

Returns the approximate total number of tasks that have ever been scheduled for execution.

`bool isShutdown() const`

Returns `true` if this pool has been shut down.

`void shutdown()`

Initiates an orderly shutdown in which previously submitted tasks are executed, but no new tasks will be accepted.

`template<class T>`

`std::future<T> submit(Runnable *task, T result);`

Submits a `Runnable` task for execution and returns a `Future` representing that task. The `Future`'s `get` method will return the given result upon successful completion.

The task will be executed by a thread of the pool.

3. Implementation

A explanation on how non-trivial methods are implemented follows.

3.1. FixedThreadPool

The `FixedThreadPool` class implements some of the method of the Java class `ThreadPoolExecutor`. To do this, it maintains a `std::vector` of threads of fixed size and a `std::queue` of tasks shared among those threads. A mutex lock is also necessary to synchronize reads and writes to the queue and to the pool state. The uses of such resources by each of the implemented methods are explained next.

3.1.1 Instantiation

At pool instantiation, the specified number of threads will be created, each one of them running the same loop described by the following pseudocode:

Algorithm 1: Thread loop

```
while true do
    acquire pool shared queue lock;
    while pool not terminated and queue is empty
        do
            // block thread until wakeup
            wait(lock);
        end
        if pool terminated and queue is empty then
            return;
        end
        get first task in queue;
        release lock;
        execute task;
end
```

Every thread will wait for tasks to enter the shared queue, at which point one of them synchronously removes a task that can then be executed in parallel with others.

3.1.2 Shutdown

The `shutdown` method corresponds to the `shutdown` method of the Java `ExecutorService` interface. This method initiates an orderly shutdown in which previously submitted tasks are executed, but no new tasks will be accepted.

3.1.3 Execute

The `execute` method corresponds to the `execute` method of the Java `Executor` interface. It allows a task implementing the `Runnable` interface to be scheduled for execution at some time in the future.

Algorithm 2: Execute

```
acquire pool shared queue lock;
set pool to terminated;
// this unlocks threads waiting on empty queue
release lock;
// wake all threads up
notify_all();
join all threads of the pool;
```

Algorithm 3: Execute

```
Data: task
acquire pool shared queue lock;
if pool terminated then
    // do not allow enqueueing on terminated pool
    throw exception;
end
enqueue the task;
release lock;
// wake a thread up
notify();
```

3.1.4 Submit

The `submit` method corresponds to the `submit` method of the Java `ExecutorService` interface.

As such, it is similar to the `execute` method but it returns a `Future` to the caller which is able to retrieve the result at a later time.

To do this, a `std::future` representing the task is created and returned. An adapter class `RunnableFuture` has been implemented to be able to pass the future operation to the `execute` method.

Algorithm 4: Submit

```
Data: task, result
create an asynchronous operation that invokes the
    task and provides a future storing the result;
create a RunnableFuture wrapping the
    operation;
pass the RunnableFuture to execute;
return the future;
```
