CERTIFICATE OF CALIBRATION

TEKTON.

Device	1/2 Inch Drive Micrometer Torque Wrench
Item#	TRQ52402
Serial #	H5 5240202433
Torque Units	ft-lb
Torque Range	40 - 200

Summary of Accuracy at Calibration

	40 ft-lb	120 ft-lb	200 ft-lb
CW	0.8%	-0.2%	1.1%
CCW	-0.3%	0.0%	-0.3%

According to ISO 6789-1:2017, the maximum allowable deviation is +/- 4%.

Date of Calibration

2025-09-30

To maintain original accuracy, recalibrate every 12 months or 5000 cycles.

Set Torque	40 ft-lb		120 ft-lb		200 ft-lb	
Clockwise (CW)	Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
1	40.4	1.0%	119.4	-0.5%	202.5	1.3%
2	40.3	0.8%	119.6	-0.3%	202.2	1.1%
3	40.3	0.8%	119.9	-0.1%	201.9	1.0%
4	40.4	1.0%	120.1	0.1%	201.9	1.0%
5	40.3	0.8%	120.1	0.1%	201.9	1.0%
Average	40.3	0.8%	119.8	-0.2%	202.1	1.1%
Counterclockwise (CCW)	Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
1	39.8	-0.5%	120.1	0.1%	199.1	-0.5%
2	39.9	-0.3%	120.0	0.0%	199.4	-0.3%
3	39.9	-0.3%	119.9	-0.1%	199.6	-0.2%
4	40.0	0.0%	119.9	-0.1%	199.8	-0.1%
5	39.8	-0.5%	119.9	-0.1%	199.8	-0.1%
Average	39.9	-0.3%	120.0	0.0%	199.5	-0.3%

Test equipment
Model: PB-6036
Serial #: 047-15031901
Accuracy: +/- 1%

Test conditions
Inspector: Amanda
Temperature: 27°C
Humidity: 55%

Test standard
ISO 6789-1:2017

Scanned with CamScanner