CERTIFICATE OF CALIBRATION

TEKTON

Device	1/2 Inch Drive Micrometer Torque Wrench
Item#	TRQ52403
Serial #	L5 5240301607
Torque Units	ft-lb
Torque Range	40 - 300

Summary of Accuracy at Calibration

	40 ft-lb	180 ft-lb	300 ft-lb
CW	0.8%	0.8%	0.6%
CCW	-1.5%	0.8%	1.6%

According to ISO 6789-1:2017, the maximum allowable deviation is +/- 4%.

Date of Calibration

2025-12-08

To maintain original accuracy, recalibrate every 12 months or 5000 cycles.

Clockwise (CW)

Set Torque	40 ft-lb		180 ft-lb		300 ft-lb	
	Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
1	40.4	1.0%	180.7	0.4%	302.9	1.0%
2	40.3	0.8%	181.2	0.7%	302.3	0.8%
3	40.2	0.5%	181.5	0.8%	301.7	0.6%
4	40.2	0.5%	181.6	0.9%	301.3	0.4%
5	40.2	0.5%	181.8	1.0%	301.0	0.3%
Average	40.3	0.8%	181.4	0.8%	301.8	0.6%

Counterclockwise (CCW)

	Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
1	39.5	-1.3%	181.6	0.9%	304.3	1.4%
2	39.5	-1.3%	181.5	0.8%	304.1	1.4%
3	39.4	-1.5%	181.4	0.8%	304.1	1.4%
4	39.4	-1.5%	181.3	0.7%	304.4	1.5%
5	39.4	-1.5%	181.2	0.7%	307.6	2.5%
Average	39.4	-1.5%	181.4	0.8%	304.9	1.6%

Test equipment
Model: PB-6036
Serial #: 047-15031901
Accuracy: +/- 1%

Test conditions
Inspector: Amanda
Temperature: 27°C
Humidity: 55%

Test standard
ISO 6789-1:2017

Scanned with CamScanner