CERTIFICATE OF CALIBRATION

TEKTON

Device	1/2 Inch Drive Micrometer Torque Wrench
Item#	TRQ52403
Serial #	L5 5240301935
Torque Units	ft-lb
Torque Range	40 - 300

Summary of Accuracy at Calibration

	40 ft-lb	180 ft-lb	300 ft-lb
CW	-1.5%	0.2%	0.4%
CCW	-0.8%	-1.6%	-1.7%

According to ISO 6789-1:2017, the maximum allowable deviation is +/- 4%.

Date of Calibration

2025-12-08

To maintain original accuracy, recalibrate every 12 months or 5000 cycles.

Set Torque		40 ft-lb		180 ft-lb		300 ft-lb	
		Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
Clockwise (CW)	1	39.3	-1.8%	180.2	0.1%	302.0	0.7%
	2	39.5	-1.3%	180.1	0.1%	301.1	0.4%
	3	39.5	-1.3%	180.4	0.2%	300.7	0.2%
	4	39.4	-1.5%	180.6	0.3%	301.3	0.4%
	5	39.5	-1.3%	180.9	0.5%	300.9	0.3%
	Average	**39.4**	**-1.5%**	**180.4**	**0.2%**	**301.2**	**0.4%**
		Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
Counterclockwise (CCW)	1	39.7	-0.8%	177.3	-1.5%	294.6	-1.8%
	2	39.6	-1.0%	177.4	-1.4%	294.3	-1.9%
	3	39.7	-0.8%	177.2	-1.6%	294.6	-1.8%
	4	39.7	-0.8%	177.1	-1.6%	295.0	-1.7%
	5	39.6	-1.0%	177.2	-1.6%	295.3	-1.6%
	Average	**39.7**	**-0.8%**	**177.2**	**-1.6%**	**294.8**	**-1.7%**

Test equipment
Model: PB-6036
Serial #: 074-1706261
Accuracy: +/- 1%

Test conditions
Inspector: Tina
Temperature: 27°C
Humidity: 55%

Test standard
ISO 6789-1:2017

Scanned with CamScanner