CERTIFICATE OF CALIBRATION

TEKTON.

Device	1/4 Inch Drive Micrometer Torque Wrench
Item#	TRQ50402
Serial #	H5 5040202191
Torque Units	in-lb
Torque Range	20 - 200

Summary of Accuracy at Calibration

	20 in-lb	120 in-lb	200 in-lb
CW	3.0%	2.7%	2.0%
CCW	0.0%	0.6%	2.1%

According to ISO 6789-1:2017,
the maximum allowable deviation is +/- 4%.

Date of Calibration

2025-10-28

To maintain original accuracy, recalibrate every 12 months or 5000 cycles.

Set Torque		20 in-lb		120 in-lb		200 in-lb	
		Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
Clockwise (CW)	1	20.6	3.0%	123.5	2.9%	203.9	2.0%
	2	20.6	3.0%	123.4	2.8%	203.8	1.9%
	3	20.6	3.0%	123.2	2.7%	204.2	2.1%
	4	20.6	3.0%	123.0	2.5%	204.0	2.0%
	5	20.6	3.0%	122.9	2.4%	203.9	2.0%
	Average	20.6	3.0%	123.2	2.7%	204.0	2.0%
		Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
Counterclockwise (CCW)	1	20.0	0.0%	121.2	1.0%	204.9	2.5%
	2	20.0	0.0%	121.0	0.8%	204.5	2.3%
	3	20.0	0.0%	120.7	0.6%	204.2	2.1%
	4	20.0	0.0%	120.6	0.5%	203.8	1.9%
	5	20.0	0.0%	120.2	0.2%	203.8	1.9%
	Average	20.0	0.0%	120.7	0.6%	204.2	2.1%

Test equipment
Model: PB-6036
Serial #: 086-1711032
Accuracy: +/- 1%

Test conditions
Inspector: Tina
Temperature: 27°C
Humidity: 50%

Test standard
ISO 6789-1:2017

Scanned with CamScanner