CERTIFICATE OF CALIBRATION

TEKTON.

Device	1/4 Inch Drive Micrometer Torque Wrench
Item#	TRQ50402
Serial #	H5 5040202197
Torque Units	in-lb
Torque Range	20 - 200

Summary of Accuracy at Calibration

	20 in-lb	120 in-lb	200 in-lb
CW	1.5%	2.9%	2.2%
CCW	1.5%	1.2%	2.1%

According to ISO 6789-1:2017, the maximum allowable deviation is +/- 4%.

Date of Calibration

2025-10-29

To maintain original accuracy, recalibrate every 12 months or 5000 cycles.

Set Torque		20 in-lb		120 in-lb		200 in-lb	
		Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
Clockwise (CW)	1	20.3	1.5%	123.4	2.8%	204.9	2.5%
	2	20.2	1.0%	123.5	2.9%	204.5	2.3%
	3	20.3	1.5%	123.5	2.9%	204.4	2.2%
	4	20.3	1.5%	123.6	3.0%	204.0	2.0%
	5	20.3	1.5%	123.5	2.9%	203.8	1.9%
	Average	20.3	1.5%	123.5	2.9%	204.3	2.2%
Counterclockwise (CCW)		Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
	1	20.3	1.5%	121.8	1.5%	204.6	2.3%
	2	20.2	1.0%	121.6	1.3%	204.3	2.2%
	3	20.3	1.5%	121.5	1.3%	204.0	2.0%
	4	20.3	1.5%	121.2	1.0%	203.8	1.9%
	5	20.3	1.5%	121.1	0.9%	203.7	1.9%
	Average	20.3	1.5%	121.4	1.2%	204.1	2.1%

Test equipment

Model: PB-6036
Serial #: 086-1711032
Accuracy: +/- 1%

Test conditions

Inspector: Tina
Temperature: 27°C
Humidity: 50%

Test standard

ISO 6789-1:2017

Scanned with CamScanner