CERTIFICATE OF CALIBRATION

TEKTON.

Device	3/8 Inch Drive Micrometer Torque Wrench
Item#	TRQ51402
Serial #	K5 5140200155
Torque Units	ft-lb
Torque Range	10 - 100

Summary of Accuracy at Calibration

	10 ft-lb	60 ft-lb	100 ft-lb
CW	1.0%	1.3%	1.6%
CCW	0.0%	-1.8%	-1.1%

According to ISO 6789-1:2017, the maximum allowable deviation is +/- 4%.

Date of Calibration

2025-10-31

To maintain original accuracy, recalibrate every 12 months or 5000 cycles.

Set Torque		10 ft-lb		60 ft-lb		100 ft-lb	
		Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
Clockwise (CW)	1	10.1	1.0%	60.8	1.3%	101.7	1.7%
	2	10.1	1.0%	60.8	1.3%	101.7	1.7%
	3	10.1	1.0%	60.8	1.3%	101.6	1.6%
	4	10.1	1.0%	60.8	1.3%	101.6	1.6%
	5	10.1	1.0%	60.7	1.2%	101.5	1.5%
	Average	10.1	1.0%	60.8	1.3%	101.6	1.6%
		Measured Values	Deviation	Measured Values	Deviation	Measured Values	Deviation
Counterclockwise (CCW)	1	10.0	0.0%	58.9	-1.8%	99.0	-1.0%
	2	10.0	0.0%	58.9	-1.8%	99.0	-1.0%
	3	10.0	0.0%	58.9	-1.8%	98.9	-1.1%
	4	10.0	0.0%	58.9	-1.8%	98.9	-1.1%
	5	10.0	0.0%	58.9	-1.8%	98.7	-1.3%
	Average	10.0	0.0%	58.9	-1.8%	98.9	-1.1%

Test equipment
Model: PB-6036
Serial #: 077-1706264
Accuracy: +/- 1%

Test conditions
Inspector: Kelly
Temperature: 27°C
Humidity: 55%

Test standard
ISO 6789-1:2017

Scanned with CamScanner