

Maven CLI Options Reference

Options	Description
<code>-am, --also-make</code>	If project list is specified, also build projects required by the list
<code>-amd, --also-make-dependents</code>	If project list is specified, also build projects that depend on projects on the list
<code>-B, --batch-mode</code>	Run in non-interactive (batch) mode (disables output color)
<code>-b, --builder</code>	The id of the build strategy to use
<code>-C, --strict-checksums</code>	Fail the build if checksums don't match
<code>-c, --lax-checksums</code>	Warn if checksums don't match
<code>-cpu, --check-plugin-updates</code>	Ineffective, only kept for backward compatibility
<code>-D, --define</code>	Define a system property
<code>-e, --errors</code>	Produce execution error messages
<code>-emp, --encrypt-master-password</code>	Encrypt master security password
<code>-ep, --encrypt-password</code>	Encrypt server password
<code>-f, --file</code>	Force the use of an alternate POM file (or directory with pom.xml)
<code>-fae, --fail-at-end</code>	Only fail the build afterwards; allow all non-impacted builds to continue
<code>-ff, --fail-fast</code>	Stop at first failure in reactorized builds
<code>-fn, --fail-never</code>	NEVER fail the build, regardless of project result
<code>-gs, --global-settings</code>	Alternate path for the global settings file
<code>-gt, --global-toolchains</code>	Alternate path for the global toolchains file
<code>-h, --help</code>	Display help information
<code>-l, --log-file</code>	Log file where all build output will go (disables output color)
<code>-llr, --legacy-local-repository</code>	Use Maven 2 Legacy Local Repository behaviour, ie no use of <code>_remote.repositories</code> . Can also be activated by using <code>-Dmaven.legacyLocalRepo=true</code>
<code>-N, --non-recursive</code>	Do not recurse into sub-projects
<code>-npr, --no-plugin-registry</code>	Ineffective, only kept for backward compatibility
<code>-npu, --no-plugin-updates</code>	Ineffective, only kept for backward compatibility
<code>-nsu, --no-snapshot-updates</code>	Suppress SNAPSHOT updates
<code>-ntp, --no-transfer-progress</code>	Do not display transfer progress when downloading or uploading
<code>-o, --offline</code>	Work offline
<code>-P, --activate-profiles</code>	Comma-delimited list of profiles to activate
<code>-pl, --projects</code>	Comma-delimited list of specified reactor projects to build instead of all projects. A project can be specified by <code>[groupId]:artifactId</code> or by its relative path
<code>-q, --quiet</code>	Quiet output - only show errors
<code>-rf, --resume-from</code>	Resume reactor from specified project
<code>-s, --settings</code>	Alternate path for the user settings file
<code>-t, --toolchains</code>	Alternate path for the user toolchains file
<code>-T, --threads</code>	Thread count, for instance 2.0C where C is core multiplied
<code>-U, --update-snapshots</code>	Forces a check for missing releases and updated snapshots on remote repositories
<code>-up, --update-plugins</code>	Ineffective, only kept for backward compatibility

<code>-v, --version</code>	Display version information
<code>-V, --show-version</code>	Display version information WITHOUT stopping build
<code>-X, --debug</code>	Produce execution debug output