

Esercizio W10D4

Simulazione raccolta informazioni

Abstract:

La traccia chiedeva di eseguire una simulazione di raccolta informazioni con Metasploitable come macchina bersaglio mappando la rete locale ed esaminandola approfonditamente per identificare i servizi attivi, le relative versioni software ecc.

Come macchina attaccante è stata adoperata Kali linux ed è stata configurata come rete isolata la modalità Host-only.

La traccia richiedeva di utilizzare le metodologie descritte nella risorsa ufficiale *"15 most useful host scanning commands"*.

In particolare sono stati

```
(kali㉿kali)-[~]  
$ ping -c 4 192.168.50.101  
PING 192.168.50.101 (192.168.50.101) 56(84) bytes of data.  
64 bytes from 192.168.50.101: icmp_seq=1 ttl=64 time=1.17 ms  
64 bytes from 192.168.50.101: icmp_seq=2 ttl=64 time=0.543 ms  
64 bytes from 192.168.50.101: icmp_seq=3 ttl=64 time=0.610 ms  
64 bytes from 192.168.50.101: icmp_seq=4 ttl=64 time=0.439 ms  
  
— 192.168.50.101 ping statistics —  
4 packets transmitted, 4 received, 0% packet loss, time 3055ms  
rtt min/avg/max/mdev = 0.439/0.690/1.169/0.283 ms
```

```

kali$ sudo nmap -F -sV -O -Pn 192.168.50.101
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-19 11:52 -0400
Nmap scan report for 192.168.50.101
Host is up (0.00069s latency).
Not shown: 82 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          vsftpd 2.3.4
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp    open  telnet       Linux telnetd
25/tcp    open  smtp         Postfix smtpd
53/tcp    open  domain       ISC BIND 9.4.2
80/tcp    open  http         Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rpcbind      2 (RPC #100000)
139/tcp   open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
513/tcp   open  login?
514/tcp   open  shell        Netkit rshd
2049/tcp  open  nfs          2-4 (RPC #100003)
2121/tcp  open  ftp          ProFTPD 1.3.1
3306/tcp  open  mysql        MySQL 5.0.51a-3ubuntu5
5432/tcp  open  postgresql   PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp  open  vnc          VNC (protocol 3.3)
6000/tcp  open  X11          (access denied)
8009/tcp  open  ajp13        Apache Jserv (Protocol v1.3)
MAC Address: 08:00:27:41:D9:A3 (Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: Linux 2.6.X
OS CPE: cpe:/o:linux:linux_kernel:2.6
OS details: Linux 2.6.9 - 2.6.33
Network Distance: 1 hop
Service Info: Host: metasploitable.localdomain; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 37.71 seconds

kali@kali:~$

```

```

kali@kali:~$ sudo arp-scan --localnet
[sudo] password for kali:
Interface: eth0, type: EN10MB, MAC: 08:00:27:5a:87:bc, IPv4: 10.0.2.15
WARNING: Cannot open MAC/Vendor file ieee-oui.txt: Permission denied
WARNING: Cannot open MAC/Vendor file mac-vendor.txt: Permission denied
Starting arp-scan 1.10.0 with 256 hosts (https://github.com/royhills/arp-scan)
10.0.2.2      52:54:00:12:35:00      (Unknown: locally administered)
10.0.2.3      52:54:00:12:35:00      (Unknown: locally administered)

2 packets received by filter, 0 packets dropped by kernel
Ending arp-scan 1.10.0: 256 hosts scanned in 2.301 seconds (111.26 hosts/sec)
. 2 responded

kali@kali:~$

```

