

# 146. LRU Cache

Medium

 Topics

 Companies

Design a data structure that follows the constraints of a **Least Recently Used (LRU) cache**.

Implement the `LRUCache` class:

- `LRUCache(int capacity)` Initialize the LRU cache with **positive** size `capacity`.
- `int get(int key)` Return the value of the `key` if the key exists, otherwise return `-1`.
- `void put(int key, int value)` Update the value of the `key` if the `key` exists. Otherwise, add the `key-value` pair to the cache. If the

The functions `get` and `put` must each run in  $O(1)$  average time complexity.

### Example 1:

Input

```
["LRUCache", "put", "put", "get", "put", "get", "put", "get", "get", "get"]
[[2], [1, 1], [2, 2], [1], [3, 3], [2], [4, 4], [1], [3], [4]]
```

Output

```
[null, null, null, 1, null, -1, null, -1, 3, 4]
```

Explanation

```
LRUCache lRUCache = new LRUCache(2);
lRUCache.put(1, 1); // cache is {1=1}
lRUCache.put(2, 2); // cache is {1=1, 2=2}
lRUCache.get(1);    // return 1
lRUCache.put(3, 3); // LRU key was 2, evicts key 2, cache is {1=1, 3=3}
lRUCache.get(2);    // returns -1 (not found)
lRUCache.put(4, 4); // LRU key was 1, evicts key 1, cache is {4=4, 3=3}
lRUCache.get(1);    // return -1 (not found)
lRUCache.get(3);    // return 3
lRUCache.get(4);    // return 4
```

### Constraints:

- $1 \leq \text{capacity} \leq 3000$
- $0 \leq \text{key} \leq 10^4$
- $0 \leq \text{value} \leq 10^5$
- At most  $2 * 10^5$  calls will be made to `get` and `put`.

Seen this question in a real interview before? 1/4

Yes

No

Accepted 1.5M

Submissions 3.7M

Acceptance Rate 42.1%

 Topics

 Companies

 Similar Questions

 Discussion (157)