Org-Mode Reference Card (1/2)

(for version 6.30e)

Getting Started

 $\label{localist} $$ (add-to-list 'auto-mode-alist '("\\corg*" . org-mode)) $$ (define-key global-map "\C-cl" 'org-store-link)^1 $$ (define-key global-map "\C-ca" 'org-agenda)^1 $$$

To read the on-line documentation try M-x org-info

Visibility Cycling

rotate current subtree between states	TAB
rotate entire buffer between states	S-TAB
restore property-dependent startup visibility	C-u C-u TAB
show the whole file, including drawers C-u	C-u C-u TAB
reveal context around point	C-c C-r

Motion

next/previous heading	C-c C-n/p
next/previous heading, same level	C-c C-f/b
backward to higher level heading	C-c C-u
jump to another place in document	C-c C-j
previous/next plain list item	S-UP/DOWN ³

Structure Editing

insert new heading/item at current level insert new heading after subtree insert new TODO entry/checkbox item insert TODO entry/ckbx after subtree turn (head)line into item, cycle item type turn item/line into headline promote/demote heading promote/demote current subtree	M-RET C-RET M-S-RET C-S-RET C-c - C-c * M-LEFT/RIGHT M-S-LEFT/RIGHT
move subtree/list item up/down sort subtree/region/plain-list clone a subtree refile subtree kill/copy subtree yank subtree narrow buffer to subtree / widen	M-S-UP/DOWN C-c ^ C-c C-x c C-c C-w C-c C-x C-w/M-w C-c C-x C-y or C-y C-x n s/w

Archiving

toggle ARCHIVE tag	C-c C-x a
force cycling of an ARCHIVEd tree	C-TAB
move to Attic Sibling	C-c C-x A
move subtree to archive file	C-c C-x C-s

Filtering and Sparse Trees

construct a sparse tree by various criteria	C-c	/
view TODO's in sparse tree	C-c	C-v
global TODO list in agenda mode	C-c	a t^1
time sorted view of current org file	C-c	a L

Tables

Creating a table

just start typing, e.g.	Name Phone Age RET - TAB
convert region to table	C-c
separator at least 3 spaces	C-3 C-c

Commands available inside tables

The following commands work when the cursor is *inside a table*. Outside of tables, the same keys may have other functionality.

Re-aligning and field motion

re-align the table without moving the cursor	C-c C-c
re-align the table, move to next field	TAB
move to previous field	S-TAB
re-align the table, move to next row	RET
move to beginning/end of field	M-a/e

Row and column editing

move the current column left	M-LEFT/RIGHT
kill the current column	M-S-LEFT
insert new column to left of cursor position	M-S-RIGHT
move the current row up/down kill the current row or horizontal line insert new row above the current row insert hline below (C-u: above) current row insert hline and move to line below it sort lines in region	M-UP/DOWN M-S-UP M-S-DOWN C-c - C-c RET C-c ^

Regions

cut rectangular region	C-c C-x C-w
copy rectangular region	C-c C-x M-w
paste rectangular region	C-c C-x C-y
fill paragraph across selected cells	C-c C-q

Miscellaneous

to limit column width to N characters,	use	<n></n>	1
edit the current field in a separate wir	ndow	C-c'	
make current field fully visible		C-u TAB	
export as tab-separated file	M-x	org-table-e	xport
import tab-separated file	M-x	org-table-i	mport
sum numbers in current column/recta	ngle	C-c +	-

Tables created with the table.el package

insert a new table.el table	C-c	~
recognize existing table.el table	C-c	C-c
convert table (Org-mode \leftrightarrow table.el)	C-c	~

Spreadsheet

Formulas typed in field are executed by TAB, RET and C-c C-c. = introduces a column formula, := a field formula.

Example: Add Col1 and Col2 with printf format specification with constants from constants.el sum from 2nd to 3rd hline apply current column formula	=\$1+\$2 =\$1+\$2;%.2f =\$1/\$c/\$cm :=vsum(@II@III)
set and eval column formula set and eval field formula re-apply all stored equations to current re-apply all stored equations to entire to iterate table to stability rotate calculation mark through # *! ^show line, column, formula reference toggle grid / debugger	able C-u C-c * C-u C-u C-c *

Formula Editor

edit formulas in separate buffer	C-c '
exit and install new formulas	C-c C-c
exit, install, and apply new formulas	C-u C-c C-c
abort	C-c C-q
toggle reference style	C-c C-r
pretty-print Lisp formula	TAB
complete Lisp symbol	M-TAB
shift reference point	S-cursor
shift test line for column references	M-up/down
scroll the window showing the table	M-S-up/down
toggle table coordinate grid	C-c }

Links

globally store link to the current location	C-c 1 ¹
insert a link (TAB completes stored links)	C-c C-1
insert file link with file name completion	C-u C-c C-1
edit (also hidden part of) link at point	C-c C-1
open file links in emacsforce open in emacs/other window open link at pointforce open in emacs/other window record a position in mark ring jump back to last followed link(s) find next link find previous link edit code snippet of file at point	C-c C-o C-u C-c C-o mouse-1/2 mouse-3 C-c % C-c & C-c C-x C-n C-c C-x C-p C-c '

Internal Links

< <my target="">></my>	target
<< <my target="">>></my>	radio target ²
[[*this text]]	find headline
[[this text]]	find target or text in buffer
[[this text][description]]	optional link text

External Links

file:/home/dominik/img/mars.jpg	file, absolute file, relative
file:papers/last.pdf	
file:projects.org::*that text	find headline
file:projects.org::find me	find trgt/string
http://www.astro.uva.nl/~dominik	on the web
mailto:adent@galaxy.net	Email address
news:comp.emacs	Usenet group
bbdb:Richard Stallman	BBDB person
gnus:group	GNUS group
gnus:group#id	GNUS message
vm wl mhe rmail:folder	Mail folder
vm wl mhe rmail:folder#id	Mail message
info:emacs:Regexps	Info file:node
shell:ls *.org	shell command
elisp:(calendar)	elisp form
[[external link][description]]	optional link text

Completion

In-buffer completion completes TODO keywords at headline start, TeX macros after "\", option keywords after "#-", TAGS after ":", and dictionary words elsewhere.

complete word at point M-TAB

Org-Mode Reference Card (2/2)

(for version 6.30e)

TODO Items and Checkboxes

rotate the state of the current item select next/previous state select next/previous set toggle ORDERED property view TODO items in a sparse tree view 3rd TODO keyword's sparse tree	C-c C-t S-LEFT/RIGHT C-S-LEFT/RIGHT C-c C-x o C-c C-v C-3 C-c C-v
set the priority of the current item remove priority cookie from current item raise/lower priority of current item	C-c , [ABC] C-c , SPC S-UP/DOWN ³
insert new checkbox item in plain list toggle checkbox(es) in region/entry/at po toggle checkbox at point update checkbox statistics ($C-u$: whole fi	C-c C-c

Tags

set tags for current heading	C-c C-q
realign tags in all headings	C-u C-c C-q
create sparse tree with matching tags	C-c \
globally (agenda) match tags at cursor	C-c C-o

Properties and Column View

set property/effort special commands in property lines next/previous allowed value turn on column view capture columns view in dynamic block	C-c C-x p/e C-c C-c S-left/right C-c C-x C-c C-c C-x i
quit column view show full value edit value next/previous allowed value edit allowed values list make column wider/narrower move column left/right add new column Delete current column	q v e n/p or S-left/right a > / < M-left/right M-S-right M-S-left

Timestamps

Clocking time

start clock on current item	C-c C-x C-i
stop/cancel clock on current item	C-c C-x C-o/x
display total subtree times	C-c C-x C-d
remove displayed times	C-c C-c
insert/update table with clock report	C-c C-x C-r

Agenda Views

add/move current file to front of agenda remove current file from your agenda cycle through agenda file list set/remove restriction lock	C-c [C-c] C-' C-c C-x
compile agenda for the current week compile global TODO list compile TODO list for specific keyword match tags, TODO kwds, properties match only in TODO entries find stuck projects show timeline of current org file	C-c a a^1 C-c a t^1 C-c a T^1 C-c a m^1 C-c a m^1 C-c a t^1
configure custom commands agenda for date at cursor	$\mathtt{C-c}$ a \mathtt{C}^1 $\mathtt{C-c}$ $\mathtt{C-c}$

Commands available in an agenda buffer

View Org file

show original location of item	SPC/mouse-3
show and recenter window	L
goto original location in other window	TAB/mouse-2
goto original location, delete other windows	RET
show subtree in indirect buffer, ded. frame	C-c C-x b
toggle follow-mode	F

Change display

0
V
d w vm vy
D / G
E / R
1 / v 1/L
v a/A
r / g
/
s
f / b
. / j

Remote editing

Remote enting	
digit argument	0-9
change state of current TODO item	t
kill item and source	C-k
archive the subtree (file/tag/sibling)	\$ / a / A
refile the subtree	C-c C-w
set/show tags of current headline	: / T
set effort property (prefix=nth)	е
set / compute priority of current item	, / P
raise/lower priority of current item	$ exttt{S-UP/DOWN}^3$
run an attachment command	C-c C-a
schedule/set deadline for this item	C-c C-s/d
change timestamp to one day earlier/later	$ t S-LEFT/RIGHT^3$
change timestamp to today	>
insert new entry into diary	i

start/stop/cancel the clock on current item jump to running clock entry mark / unmark / execute bulk action	I / O / X J m / u / B
Misc	
follow one or offer all links in current entry	C-c C-o
Calendar commands	
find agenda cursor date in calendar	С
compute agenda for calendar cursor date	С
show phases of the moon	M
show sunrise/sunset times	S
show holidays	H
convert date to other calendars	C
Quit and Exit	
quit agenda, remove agenda buffer	q
exit agenda, remove all agenda buffers	x

LaTeX and cdlatex-mode

preview LaTeX fragment	C-c C-x C-l
expand abbreviation (cdlatex-mode)	TAB
insert/modify math symbol (cdlatex-mode)	'/,
insert citation using RefTeX	C-c C-x [

Exporting and Publishing

Exporting creates files with extensions .txt and .html in the current directory. Publishing puts the resulting file into some other place.

export/publish dispatcher	С-с С-е
export visible part only	C-c C-e v
insert template of export options	C-c C-e t
toggle fixed width for entry or region	C-c :

Comments: Text not being exported

Text before the first headline is not considered part of the document and is therefore never exported. Lines starting with # are comments and are not exported. Subtrees whose header starts with COMMENT are never exported.

toggle COMMENT keyword on entry C-c;

Dynamic Blocks

update dynamic block at point		C-c	C-x	C-u
update all dynamic blocks	C-u	C-c	C-x	C-u

Notes

- ¹ This is only a suggestion for a binding of this command. Choose your own key as shown under INSTALLATION.
- 2 After changing a #+KEYWORD or <<<target>>> line, press C-c C-c with the cursor still in the line to update.
- 3 Keybinding affected by org-support-shift-select and org-replace-disputed-keys.

Copyright © 2009 Free Software Foundation, Inc. v6.30e for Org-Mode 6.30e, 2009 Author: Philip Rooke

based on refcard design and format by Stephen Gildea

Permission is granted to make and distribute copies of this card provided the copyright notice and this permission notice are preserved on all copies.