

Getting started with projects based on dual-core STM32H7 microcontrollers in STM32CubeIDE

Introduction

This application note describes how to get started with projects based on STM32H7 Series dual-core microcontrollers in the STMicroelectronics [STM32CubeIDE](#) integrated development environment.



1 General information

STM32CubeIDE supports STM32 32-bit products based on the Arm® Cortex® processor.

Note: Arm is a registered trademark of Arm Limited (or its subsidiaries) in the US and/or elsewhere.



1.1 Prerequisites

The following tools are prerequisites for understanding the tutorial in this document and developing an application based on the STM32H7 Series:

- STM32CubeIDE 1.4.0 or newer
- STM32Cube_FW_H7_V1.7.0 or newer
- STM32CubeMX 6.0.0 or newer

Users are advised to keep updated with the documentation evolution of the STM32H7 Series at www.st.com/en/microcontrollers-microprocessors/stm32h7-series.html.

1.2 The use cases in this document

In the STM32CubeIDE context, users have different ways to explore and get started with the development of projects based on the STM32H7 Series. From the list below, select the description that best fits the use case considered and refer to the corresponding section in this application note:

- I already have an SW4STM32 project with an ioc file:
Refer to [Section 2.2 Import an SW4STM32 project with an ioc file](#)
- I already have an SW4STM32 project without an ioc file:
Refer to [Section 2.3 Import an SW4STM32 project without an ioc file](#)
- I want to learn with and explore example projects:
Refer to [Section 2.5 Import a project from the STM32CubeH7 MCU Package](#)
- I want to start a first STM32H7 project:
 - Empty project – No STM32CubeMX support for maximum flexibility.
Refer to [Section 2.4 Create an empty project based on the template in the STM32CubeH7 MCU Package](#)
 - STM32CubeH7 project – STM32CubeMX-managed project.
Refer to [Section 2.1 Create a new STM32 project](#)

1.3 Specific features of dual-core microcontrollers in the STM32H7 Series

The most obvious feature of a dual-core STM32H7 device is its significant performance boost that comes from the addition of an Arm® Cortex®-M4 core besides the Arm® Cortex®-M7 core. Dual-core STM32H7 devices are also very flexible. This application note is a simple getting-started guide to get up and running with a debug session when both cores are running. It does not cover such additional features as the flexibility of being able to boot on either core or the fact that each core can exist in an independent power domain to optimize energy consumption.


1.3.1 Dual-core STM32H7 project structure

When a dual-core STM32H7 project is created, its structure is automatically made hierarchical. The project structure for single-core projects is flat. On the contrary, in a multi-core project, the hierarchical project structure is used. When the user creates or imports a dual-core STM32H7 project, it consists of one root project together with sub-projects, referred to as MCU projects, for each core.

The MCU projects are real CDT™ projects that can contain both build and debug configurations. On the contrary, the root project is a simple container that allows sharing common code between the cores. The root project can contain neither build nor debug configurations.

If the project is not shown in a hierarchical structure, this can be changed as shown in [Figure 1](#).

Figure 1. Setting the project hierarchical view




2 Create and import projects

This chapter describes how to create or import projects for dual-core microcontrollers in the [STM32H7 Series](#).

2.1 Create a new STM32 project


To start a new project, go to **[File]>[New]>[STM32 Project]** as shown in [Figure 2](#).

Figure 2. New STM32 project



Select the desired MCU or board. In the example illustrated in Figure 3, the selected board is the NUCLEO-H745ZI-Q. Click on [Next >].

Figure 3. Target selection



After the target selection comes the project setup step shown in Figure 4. The *Targeted Project Type* setting determines whether the project gets generated by STM32CubeMX or not. An *Empty* project is a skeleton of a project that needs building upon while *STM32Cube* indicates an STM32CubeMX-managed project.

Figure 4. Project setup

IDE STM32 Project

Project Setup

Setup STM32 project

Project Name: NUCLEO-H745ZI-Q

☒ Use default location

Location: C:/Users/.../STM32CubeIDE/workspace Browse...

Options

Targeted Language

☒ C ☐ C++

Targeted Binary Type

☒ Executable ☐ Static Library

Targeted Project Type

☒ STM32Cube ☐ Empty


? < Back Next > Finish Cancel

2.2 Import an SW4STM32 project with an ioc file

If the project already contains an ioc file, the easiest way to import the project into a working STM32CubeIDE environment is to copy it and open the copy through STM32CubeMX stand alone, then, in the *Project Manager*, change the *Toolchain / IDE* to STM32CubeIDE and regenerate the project.

After the project is regenerated, go to **[File]>[Import...]** and choose to import it as an *Existing projects into workspace* as shown in Figure 5.

Figure 5. Import an existing project with an ioc file




Then copy the code inside the different `/* USER CODE BEGIN */` blocks that exist in the project into the new STM32CubeIDE environment.

2.3

Import an SW4STM32 project without an ioc file

To make sure the project gets a hierarchical structure, the recommended way is to go to **[File]>[New]>[STM32 Project]** as shown in Figure 6.

Figure 6. New STM32 project



Select the device for the project being imported and click on **[Next >]**.

When setting up the project as shown in , make sure the *Targeted Project Type* is set to *Empty* and click on [Finish].

Figure 7. Project setup

IDE STM32 Project

Project Setup

Setup STM32 project

Project Name: NUCLEO-H745ZI-Q

☒ Use default location

Location: C:/Users/.../STM32CubeIDE/workspace Browse...

Options

Targeted Language

☒ C ☐ C++

Targeted Binary Type

☒ Executable ☐ Static Library

Targeted Project Type


☐ STM32Cube ☒ Empty

? < Back Next > **Finish** Cancel

After the empty hierarchical project is generated:

1. Go to **[File]>[Import...]**
2. Import the SW4STM32 project as *Import ac6 System Workbench for STM32 Project*
3. Copy and paste the project files and resources into the sub-project of the empty project as shown in Figure 8

Figure 8. Copy project content to empty sub-project



Note: It is not recommended to import the `.cproject`, `.project` or `.settings` files.

It is important to remember to configure also the same build settings used previously while the project was in the SW4STM32 environment. If the project contains linked resources, these need to be updated to point to the correct resource in the file system.

This process is necessary because, when importing without any special treatment a project from SW4STM32 that does not have an `ioc` file, it is imported into STM32CubeIDE with a flat project structure.


2.4 Create an empty project based on the template in the STM32CubeH7 MCU Package

Follow the same steps as in Section 2.3 Import an SW4STM32 project without an `ioc` file but use STM32Cube_FW_H7 firmware in the STM32CubeH7 MCU Package as input.

2.5 Import a project from the STM32CubeH7 MCU Package


In order to import the STM32Cube firmware project into STM32CubeIDE, go to [File]>[Import], select *Existing Projects into Workspace* as shown in Figure 9, and click on [Next >].

Figure 9. Import of firmware project into STM32CubeIDE



Then select the correct project. A project example is by default located at `$HOME\STM32Cube\Repository\STM32Cube_FW_H7_VX.X.X\Projects\NUCLEO-H745ZI-Q\Examples\GPIO\GPIO_EXTI`.

Figure 10. Firmware project selection




After selecting the project, click on [Finish] to import and build the project.

3 Debugging

This chapter highlights some of the points to bear in mind while debugging a device in the STM32H7 Series. In the next two sections, this application note covers the configurations needed to start debug sessions with ST-LINK GDB server and OpenOCD.

To start configuring the launch of the debug session, right-click the sub-project (in this example, the Cortex[®]-M7) and select **[Debug As]>[Debug Configurations...]** as shown in Figure 11.

Figure 11. ST-LINK GDB server debug configuration (1 of 6) and OpenOCD debug configuration (1 of 3)




Note: For the rest of this section, examples are based on the NUCLEO-H755ZI-Q board.

3.1 Setting up with ST-LINK GDB server

Since the STM32CubeMX default project puts the Cortex®-M4 in the DeepSleep mode, the **[Reset behaviour]** field must be set to *Connect under reset* to be able to communicate with the CPU (refer to [Figure 12](#)). Make sure to check the *Halt all cores* option next to it to prevent the Cortex®-M4 from starting to execute the code and end up in the DeepSleep mode in this example. In the debug configuration, select *Enable shared ST-LINK*, switch to the *Startup* tab and select *Add...*.


Figure 12. ST-LINK GDB server debug configuration (2 of 6)



Startup tab - Cortex®-M7


The Cortex®-M7 debug configuration is responsible for loading both the Cortex®-M7 and Cortex®-M4 images. Go to the *Startup* tab to do this as shown in Figure 13:

Figure 13. ST-LINK GDB server debug configuration (3 of 6)



To also download the Cortex®-M4 image, click **[Add...]**, browse the correct project and build the configuration. The result is shown in Figure 14.

Figure 14. ST-LINK GDB server debug configuration (4 of 6)




The order in the load list is very important. The last entry in the list, marked by a green arrow (refer to Figure 13, is the image debugged with this debug configuration; Consequently, the debugger fetches the program counter value (PC) from this image.

Startup tab - Cortex®-M4

As shown in Figure 15:


- Make sure that the *Port number* exceeds the value of the previous debug configuration by at least 3 (61238 in this example)
- Select 3 – Cortex-M4 for [Access port]
- Select None for [Reset behaviour]
- Select *Enable shared ST-LINK*

Figure 15. ST-LINK GDB server debug configuration (5 of 6)



Go to the *Startup* tab and select [Edit...]>[Disable Download]. This is required since the download is already performed by the Cortex®-M7 configuration (refer to Figure 16).

Figure 16. ST-LINK GDB server debug configuration (6 of 6)




The configuration is complete.

3.1.1 Launching the configurations

1. Launch the Cortex[®]-M7 configuration to download both the Cortex[®]-M4 and Cortex[®]-M7 images
2. Set the Cortex[®]-M7 core running so that the HSEM semaphore is released and Cortex[®]-M4 wakes up from Stop mode
3. Launch the Cortex[®]-M4 configuration using the arrow next to the debug icon. It is in the running mode and the user can halt it.

Figure 17. ST-LINK GDB server debug configuration launch




Note: After creating the debug configurations for both cores, they are not shown in the scroll-down menu if they have never been launched before. This is because the arrow provides access to the history of latest launches, with a grayed "no history" message if there are none. First-time debug launch must be done through the debug configuration wizard.

When debugging an STM32H7 device with the ST-LINK GDB server, it is possible to create a launch group, which offers the following advantages:

- The user can launch the debug session on both cores with only one launch configuration as shown in Figure 18.

Figure 18. ST-LINK GDB server launch group




- The user can stop both cores using the launch group. This avoids having to terminate both debug sessions individually.

3.1.2 Cross-trigger Interface

The cross-trigger interface is used to send halt signals from one core to the other. To enable the Cortex®-M4 to halt the Cortex®-M7, apply the following configuration:

- In the Cortex®-M4 debug configuration: select *Signal halt events to other cores*
- In the Cortex®-M7 debug configuration: select *Allow other cores to halt this core*

Figure 19. ST-LINK GDB server debug cross-trigger interface




Note: Checking both checkboxes in both debug configurations enables both cores to halt each other.

3.2 Setting up with OpenOCD

Select *ST-LINK (OpenOCD)* as the [Debug probe]. Select *Autostart local GDB server* for the configuration that launches first, which is the Cortex®-M7 in the example in Figure 20. Set all the default options and verify that:

- *Connect under reset* is selected as [Reset Mode].
- [Shared ST-LINK] is selected; this option is mandatory to run the multicore target.


Figure 20. OpenOCD debug configuration (2 of 3)



Create the debug configuration for the other core, which is the Cortex®-M4 in the example in Figure 21:

- Select *ST-LINK (OpenOCD)* as the **[Debug probe]**
- Select *Autostart local GDB server* as default
- Make sure that the *Port number* exceeds the value of the previous debug configuration by at least 2 (3335 in this example)
- Open **[Generator Options]** and select *Core reset* as **[Reset Mode]**

Figure 21. OpenOCD debug configuration (3 of 3)




The configuration of the *Startup* tab is the same as with the ST-LINK GDB server probe for both debug configurations (refer to *Startup tab - Cortex-M7* and *Startup tab - Cortex-M4* in Section 3.1 Setting up with ST-LINK GDB server).

3.2.1 Launching the configurations

After both debug configurations are set up, save them and click on the arrow next to the debug icon to make sure launching the autostarting local GDB server first (the Cortex[®]-M7 in this example). After this first launch, click on the same arrow again and launch the other configuration.

Figure 22. OpenOCD debug configuration launch




Note: After creating the debug configurations for both cores, they are not shown in the scroll-down menu if they have never been launched before. This is because the arrow provides access to the history of latest launches, with a grayed “no history” message if there are none. First-time debug launch must be done through the debug configuration wizard.

When debugging an STM32H7 device with OpenOCD, it is possible to create a launch group, which offers the following advantages:


- The user can launch the debug session on both cores with only one launch configuration.

Figure 23. Launch OpenOCD debug on both cores



- The user can stop both cores using the launch group. This avoids having to manually terminate both debug sessions individually. In Figure 24, the launch group in pink handles each of the cores in green.

Figure 24. Stop OpenOCD debug on both cores




3.2.2 Cross-trigger interface

The cross-trigger interface is used to send halt signals from one core to the other. To enable the Cortex®-M4 to halt the Cortex®-M7, apply the following configuration:

- In the Cortex®-M4 debug configuration: select *Signal halt events to other cores*
- In the Cortex®-M7 debug configuration: select *Allow other cores to halt this core*

Figure 25. OpenOCD debug cross-trigger interface



Note: Checking both checkboxes in both debug configurations enables both cores to halt each other.

Revision history

Table 1. Document revision history

Date	Revision	Changes
21-Nov-2019	1	Initial release.
23-Jul-2020	2	Reorganized <i>Section 3 Debugging</i> : <ul style="list-style-type: none"> Updated <i>Section 3.1 Setting up with ST-LINK GDB server</i>, <i>Section 3.1.1 Launching the configurations</i>, and added <i>Figure 18. STLINK GDB server launch group</i> Updated <i>Section 3.2 Setting up with OpenOCD</i>, <i>Figure 20. OpenOCD debug configuration (2 of 3)</i>, <i>Figure 21. OpenOCD debug configuration (3 of 3)</i> and <i>Section 3.2.2 Cross-trigger interface</i>
10-Jun-2021	3	Updated Figure 11 in <i>Section 3 Debugging</i> .

Contents

1	General information	2
1.1	Prerequisites	2
1.2	The use cases in this document	2
1.3	Specific features of dual-core microcontrollers in the STM32H7 Series.	2
1.3.1	Dual-core STM32H7 project structure	2
2	Create and import projects	4
2.1	Create a new STM32 project	4
2.2	Import an SW4STM32 project with an <code>ioc</code> file	6
2.3	Import an SW4STM32 project without an <code>ioc</code> file	7
2.4	Create an empty project based on the template in the STM32CubeH7 MCU Package	9
2.5	Import a project from the STM32CubeH7 MCU Package	10
3	Debugging	11
3.1	Setting up with ST-LINK GDB server	12
3.1.1	Launching the configurations	17
3.1.2	Cross-trigger Interface	18
3.2	Setting up with OpenOCD	19
3.2.1	Launching the configurations	21
3.2.2	Cross-trigger interface.	22
	Revision history	23
	Contents	24
	List of figures.	25

List of figures

Figure 1.	Setting the project hierarchical view.	3
Figure 2.	New STM32 project.	4
Figure 3.	Target selection	5
Figure 4.	Project setup	6
Figure 5.	Import an existing project with an ioc file	7
Figure 6.	New STM32 project.	7
Figure 7.	Project setup	8
Figure 8.	Copy project content to empty sub-project	9
Figure 9.	Import of firmware project into STM32CubeIDE.	10
Figure 10.	Firmware project selection	10
Figure 11.	ST-LINK GDB server debug configuration (1 of 6) and OpenOCD debug configuration (1 of 3)	11
Figure 12.	ST-LINK GDB server debug configuration (2 of 6)	12
Figure 13.	ST-LINK GDB server debug configuration (3 of 6)	13
Figure 14.	ST-LINK GDB server debug configuration (4 of 6)	14
Figure 15.	ST-LINK GDB server debug configuration (5 of 6)	15
Figure 16.	ST-LINK GDB server debug configuration (6 of 6)	16
Figure 17.	ST-LINK GDB server debug configuration launch	17
Figure 18.	ST-LINK GDB server launch group	17
Figure 19.	ST-LINK GDB server debug cross-trigger interface	18
Figure 20.	OpenOCD debug configuration (2 of 3)	19
Figure 21.	OpenOCD debug configuration (3 of 3)	20
Figure 22.	OpenOCD debug configuration launch.	21
Figure 23.	Launch OpenOCD debug on both cores.	21
Figure 24.	Stop OpenOCD debug on both cores	22
Figure 25.	OpenOCD debug cross-trigger interface	22

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2021 STMicroelectronics – All rights reserved