

REGOLATORI DC/DC

Id	PN/REFERENCE	ALTERNATIVE
1	R-785.0-0.5 (RECOM)	TSR 0.5-2450 (TRACO POWER)
2	R-78C15-1.0 (RECOM)	TSR 1-24150 (TRACO POWER)
3	R-78C12-1.0 (RECOM)	TSR 1-24120 (TRACO POWER)
4	ECOS1JA472CA oppure SLP472M050C5P3	Alternativa a 85°, stesse dimensioni
5	BNX002-01	BNX012-01
6	UC3841DW (obsoleto)	UC2841DW
7	FSL400B THERMAL GAP 60x35mm	Equivalente ?
8	DAC8512FSZ	DAC7611U TEXAS INSTRUMENT

ELIMINAZIONE COMPONENTI PER TENSIONE GRIGLIA (MAI USATA)

Id	REFERENCE	P/N/Prezzo
1	J10	MLSS156-2 (0.18)
2	JP10	Jumper
3	OC12	MOC3063SR2M (0.2)
4	Q26	BSS138K (0.01)
5	R180	
6	R179	
7	TP31,TP33	Test Points (0.3)
8	PD5	MB4S (0.2)
9	C91	
10	C92	ECA2CM100 (0.2)
11	R170	
12	U38	LR8N8-G (0.41)
13	R172,R173,R176,R181,R182	
14	OC11	TCMT4106 (0.5)
15	R174,R175,R177,R178	

SELEZIONE 2 FUOCHI INVECE CHE 4 FUOCHI ?:

Id	REFERENCE	P/N/Prezzo
1	K11,K12	32.21.7.012.2000 RELAY PTH (2x 1,32)
NOTA: OCCORRE AGGIUNGERE UN PONTICELLO TRA PIN 12 e 14 DI K11		