



PASSO A PASSO GERAR E RODAR SCRIPT DUMP & LOAD BINÁRIO





SUMÁRIO:

PASSO a PASSO DUMP & LOAD	3
SCRIPT BINÁRIO	3
RODAR O TABANALYS ANTES	3
CONECTAR AO BANCO = emsfnd	3
DUMP DF	4
DUMP USERS	4
DUMP SEQ	5
SCRIPT DUMP	7
ARMAZENAMENTO DADOS BINÁRIO	8
ARQUIVO DE LOG DUMP BINÁRIO	8
CRIAR OS BANCOS VAZIOS	9
LOAD DF, USERS e SEQ	9
RODAR O SCRIPT LOAD BINÁRIO	9
ARQUIVO DE LOG LOAD BINÁRIO	10
REINDEXAÇÃO	10
RODAR O TABANALYS DEPOIS	11
COMPARAR ARQUIVOS TABANALYS	12





PASSO a PASSO DUMP & LOAD SCRIPT BINÁRIO

RODAR O TABANALYS ANTES

proutil emsfnd -C tabanalys > /BKP/DUMP/emsfnd/emsfnd_antes.tab

CONECTAR AO BANCO = emsfnd

```
REDHAT7:/BKP/DUMP # cd /totvs/bancos/
REDHAT7:/totvs/bancos # mpro emsfnd
```

mpro emsfnd







DUMP DF

```
192.168.0.177 - PuTTY
                                                ×
Database Schema Admin DataServer Utilities PRO/SQL Tools
          x Dump Data and Dex Data Definitions (.df file)...
                                                    x
          x Load Data and Dex Table Contents (.d file)...
                                                    x
          x Database Identifx SQL Views...
                                                    x
          lqqqqqqqqx Export Data -> x User Table Contents...
          x Import Data -> x Security Domains...
                                                    x
   x You may x Create Bulk Loadx Security Permissions...
                                                    x
   x Enable Large Keyx Auto-Connect Records only...
                                                    x
   mqqqqqqqqx Alternate Bufferx Collation Tables...
                                                    x
          mqqqqqqqqqqqqqqqqx Sequences Definitions...
                      x Sequences Current Values...
                                                    x
                      x Database Identification Properties...
                                                    х
                      x Database Options...
                      x Audit Policies ->
                      x Audit Data...
Main Menu
                      Database: emsfnd (PROGRESS)
                      x Create Incremental .df File...
                      x Change Data Capture Policies (.cd file)... x
```

DUMP USERS

```
×
192.168.0.177 - PuTTY
                                                       Database Schema Admin DataServer Utilities PRO/SQL Tools
            x Dump Data and Dex Data Definitions (.df file)...
            x Load Data and Dex Table Contents (.d file)...
            x Database Identifx SQL Views...
                                                            x
                         x Security ->
    lqqqqqqqqqx Export Data -> x User Table Contents...
           x Import Data -> x Security Domains...
                                                            х
    x You may x Create Bulk Loadx Security Permissions...
    x Enable Large Keyx Auto-Connect Records only...
                                                            x
    mqqqqqqqqx Alternate Bufferx Collation Tables...
                                                            x
           mqqqqqqqqqqqqqqqqx Sequences Definitions...
                         x Sequences Current Values...
                                                            х
                         x Database Identification Properties...
                                                            х
                         x Database Options...
                         x Audit Policies ->
                                                            x
                         x Audit Data...
Main Menu
                         \mathbf{x} dddddddddddddddddddddddddddddddddd \mathbf{x}
Database: emsfnd (PROGRESS)
                         x Create Incremental .df File...
                         x qqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqq
                         x Change Data Capture Policies (.cd file)... x
```





DUMP SEQ

```
192,168,0,177 - PuTTY
                                                          X
Database Schema Admin DataServer Utilities PRO/SQL Tools
            x Dump Data and Dex Data Definitions (.df file)...
            x Load Data and Dex Table Contents (.d file)...
            x Database Identi<u>f</u>x <u>SQL</u> <u>V</u>iews...
                                                               ×
    x Import Data -> x Security Domains...
                                                               x
    x You may x Create Bulk Loadx Security Permissions...
    x Enable Large Keyx Auto-Connect Records only...
    mqqqqqqqqx Alternate Bufferx Collation Tables...
                                                               x
            mqqqqqqqqqqqqqqqqx Sequences Definitions...
                                                               x
                           x Sequences Current Values...
                                                               x
                           x Database Identification Properties...
                           x Database Options...
                           \mathbf{x} ddddddddddddddddddddddddddddddddddd \mathbf{x}
                           x Audit Policies ->
                           x Audit Data...
Main Menu
                           \mathbf{x} qqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqq\mathbf{x}
Database: emsfnd (PROGRESS)
                           x Create Incremental .df File...
                           x Change Data Capture Policies (.cd file)... x
                           mqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqq
```

EXECUTAR PROGRAMA GERA_SCRIPT_BINARIO.p

```
192.168.0.177 - PuTTY
                                                       X
                                                   File Edit Search Buffer Compile Tools Help
qqqqqqq
    x File Name:
                                                 x
    x gera script binario.p
                                                 x
    x /totvs/scripts
    x Files:
                           Directories:
    \mathbf{x} lqqqqqqqqqqqqqqqqqqqqqqq\mathbf{x} lqqqqqqqqqqqqqqqqqqqqqqqqq\mathbf{x}
    x x criarbancos
                                                 x
                           x> .
    x x datasul.pf
                           х
    x x datasulCargaBancos
                           х
                             emsfnd
                                                 х
    x x datasulCargaBancos OLD
                           x
                                                 x
    x x datasulDescargaBancos
    x x> gera script binario.p
                           x
    x
    x
                     <OK> <Cancel>
                                                 ×
F1=RUN F3=MENUS F5=OPEN F6=SAVE F8=CLOSE
                                                   Insert
```

São Paulo Rua Anésia Maria, 225 -PIQUERI - São Paulo - SP Fone: +55 11 3562-7305 www.muniztec.com.br





Colocar o caminho onde será armazenado o script - binario

/BKP/DUMP/emsfnd

No diretório onde estão os bancos, ir gerar dois arquivos:

- 1. dump_emsfnd.sh
- 2. load_emsfnd.sh

```
# 192.168.0.177 - PuTTY

total 467628
-rw-r--r-- 1 root root 66893 Oct 28 15:10 dump_emsfnd.sh
-rw-r--r-- 1 root root 66893 Oct 28 15:10 load_emsfnd.sh
```





SCRIPT DUMP

```
192.168.0.177 - PuTTY
                                                                         echo 'Inicio do Processamento de Exportação ' `date` > emsfnd.log
echo 'Inicio tabela agenda rpw' `date` >> emsfnd.log
proutil emsfnd -C dump agenda_rpw /BKP/DUMP/emsfnd -RO -B 100 -spin 2000 >> emsf
nd.log
 echo 'Fim tabela agenda rpw' `date` >> emsfnd.log
echo 'Inicio tabela aplicat disposit mov' `date` >> emsfnd.log
proutil emsfnd -C dump aplicat_disposit_mov /BKP/DUMP/emsfnd -RO -B 100 -spin 20
00 >> emsfnd.log
 echo 'Fim tabela aplicat disposit mov' `date` >> emsfnd.log
echo 'Inicio tabela aplicat_disposit_mov_usuar' `date` >> emsfnd.log
proutil emsfnd -C dump aplicat_disposit_mov_usuar /BKP/DUMP/emsfnd -RO -B 100 -s
pin 2000 >> emsfnd.log
 echo 'Fim tabela aplicat_disposit_mov_usuar' `date` >> emsfnd.log
echo 'Inicio tabela aplicat dtsul' `date` >> emsfnd.log
proutil emsfnd -C dump aplicat_dtsul /BKP/DUMP/emsfnd -RO -B 100 -spin 2000 >> e
```

Na linha de comando do LINUX, executar o programa

dump_emsfnd.sh







ARMAZENAMENTO DADOS BINÁRIO

```
192.168.0.177 - PuTTY
 2 192.168.0.177 - PuTTY
                                                                                                                               REDHAT7:/BKP/DUMP/emsfnd # ls -1 | more
total 26156
-rw-r--r-- 1 root root
-rw-r--r-- 1 root root
-rw-r--r-- 1 root root
                                             934 Oct 28 15:15 HIBERNATE UNIQUE KEY.bd
                                            1153 Oct 28 15:15 agenda rpw.bd
1034 Oct 28 15:15 aplicat disposit mov.bd
1042 Oct 28 15:15 aplicat disposit mov usuar.bd
-rw-r--r-- 1 root root
-rw-r--r-- 1 root root
-rw-r--r-- 1 root root
                                            2880 Oct 28 15:15 aplicat_dtsul.bd
2528 Oct 28 15:15 aplicat_dtsul_segur.bd
-rw-r--r-- 1 root root
-rw-r--r-- 1 root root
-rw-r--r-- 1 root root
                                           3802 Oct 28 15:15 bco_empres.bd
                                         984 Oct 28 15:15 bco_histor_conex.bd
1015 Oct 28 15:15 bco_histor_seq_conex.bd
-rw-r--r- 1 root root 994 Oct 28 15:15 bco_timeout.bd

-rw-r--r- 1 root root 990 Oct 28 15:15 cadast_liter.bd


-rw-r--r- 1 root root 8848347 Oct 28 15:15 cadast_msg.bd
-rw-r--r- 1 root root 1042 Oct 28 15:15 catal_docto_anexo.bd

-rw-r--r- 1 root root 1001 Oct 28 15:15 catal_img.bd

-rw-r--r- 1 root root 995 Oct 28 15:15 catal_som.bd
-rw-r--r-- 1 root root
-rw-r--r-- 1 root root
                                           1000 Oct 28 15:15 catal_video.bd
                                             4756 Oct 28 15:15 configur.bd
                                            1056 Oct 28 15:15 configur_layout_impres.bd
-rw-r--r-- l root root
-rw-r--r-- 1 root root
-rw-r--r-- 1 root root
                                             1000 Oct 28 15:15 configur_propried.bd
                                            1055 Oct 28 15:15 configur_tip_imprsor.bd
1017 Oct 28 15:15 contexto_sessao_fnd.bd
-rw-r--r-- l root root
                                             1030 Oct 28 15:15 contexto trans fnd.bd
```

ARQUIVO DE LOG DUMP BINÁRIO

NO FINAL DO DUMP BINARIO e gerado um LOG no mesmo diretório do banco:







LOAD

CRIAR OS BANCOS VAZIOS

```
REDHAT7:/totvs/banco # prostrct create emsfnd -blocksize 8192
Formatting extents:
                      area name path name
  size
         Primary Recovery Area /totvs/banco/emsfnd.bl 00:00:00
                    Schema Area /totvs/banco/emsfnd.dl 00:00:00
REDHAT7:/totvs/banco # procopy /usr/dlc/empty8 emsfnd
Procopy session begin for root on /dev/pts/1. (451)
Copying /usr/dlc/empty8 to emsfnd... (6715)
Start writing data blocks. (6718)
15:30:28 10 Percent complete.
15:30:28 20 Percent complete.
15:30:28 30 Percent complete.
15:30:28 40 Percent complete.
15:30:28 50 Percent complete.
15:30:28 60 Percent complete.
15:30:28 70 Percent complete.
15:30:28 80 Percent complete.
15:30:28 90 Percent complete.
15:30:28 100 Percent complete.
385 blocks copied. (6720)
...Copy complete. (6722)
Database copied from /usr/dlc/empty8. (1365)
Procopy session end. (334)
REDHAT7:/totvs/banco #
```

LOAD DF, USERS e SEQ

RODAR O SCRIPT LOAD BINÁRIO

load emsfnd.sh

```
REDHAT7:/totvs/banco # sh load_emsfnd.sh
```





ARQUIVO DE LOG LOAD BINÁRIO

No final do LOAD Binário será geradoo LOG

more emsfnd.log

```
Thu Oct 28 16:05:35 -03 2021
Inicio do Processamento de Exportacao
Inicio tabela agenda_rpw Thu Oct 28 16:05:35 -03 2021
OpenEdge Release 11.7.9 as of Fri Dec 4 18:16:01 EST 2020
** This session is being run with the no-integrity (-i) option. (512)
Binary Dump created on Thu Oct 28 15:15:06 2021
from database /totvs/bancos/emsfnd. (6203)
Loading table agenda_rpw, Table number l
starting with record 1, section 1. (6204)
Loaded 1 records. (15167)
YOU SHOULD REBUILD THE FOLLOWING INDEXES IN TABLE PUB.agenda rpw:
agndrpw_id
agndrpw ix2
agndrpw ix3
Binary Load complete. (6256)
Fim tabela agenda_rpw Thu Oct 28 16:05:35 -03 2021
Inicio tabela aplicat_disposit_mov Thu Oct 28 16:05:35 -03 2021
OpenEdge Release 11.7.9 as of Fri Dec 4 18:16:01 EST 2020
** This session is being run with the no-integrity (-i) option. (512)
Binary Dump created on Thu Oct 28 15:15:06 2021
from database /totvs/bancos/emsfnd. (6203)
Loading table aplicat_disposit_mov, Table number 2
starting with record 1, section 1. (6204)
Loaded 0 records. (15167)
Binary Load complete. (6256)
Fim tabela aplicat disposit mov Thu Oct 28 16:05:35 -03 2021
Inicio tabela aplicat_disposit_mov_usuar Thu Oct 28 16:05:35 -03 2021
OpenEdge Release 11.7.9 as of Fri Dec 4 18:16:01 EST 2020
** This session is being run with the no-integrity (-i) option. (512)
Binary Dump created on Thu Oct 28 15:15:06 2021
from database /totvs/bancos/emsfnd. (6203)
Loading table aplicat_disposit_mov_usuar, Table number 3
starting with record 1, section 1. (6204)
Loaded 0 records. (15167)
Binary Load complete. (6256)
Fim tabela aplicat_disposit_mov_usuar Thu Oct 28 16:05:35 -03 2021
Inicio tabela aplicat_dtsul Thu Oct 28 16:05:35 -03 2021
OpenEdge Release 11.7.9 as of Fri Dec 4 18:16:01 EST 2020
```

REINDEXAÇÃO

proutil emsfnd -C idxbuild all

OBS.: não coloquei parâmetro nenhum pois minha base e pequena.





```
Index 149 ( PUB.log_exec_prog_aux, lgxcprgx_id ): activated (8830)
Index 150 ( PUB.log exec prog aux, lgxcprgx id prog dtsul ): activated (8830)
Index 17 ( PUB.aplicat_dtsul, aplctdts_01 ): activated (8830)
Index 18 ( PUB.aplicat dtsul, aplctdts 02 ): activated (8830)
Index 19 ( PUB.aplicat_dtsul, aplctdts_frwk ): activated (8830)
Index 16 ( PUB.aplicat_dtsul, aplctdts_id ): activated (8830)
Index 20 ( PUB.aplicat_dtsul, aplctdts_seq ): activated (8830)
Index 285 ( PUB.usuar_mestre_aux, usrmstra_id ): activated (8830)
Index 286 ( PUB.usuar_mestre_aux, usrmstra_ix ): activated (8830)
Index 288 ( PUB.usuar mestre ext, usrmstrx 01 ): activated (8830)
Index 287 ( PUB.usuar mestre ext, usrmstrx id ): activated (8830)
Index 289 ( PUB.usuar_mestre_ext, usrmstrx_srmstr ): activated (8830)
Index 290 ( PUB.usuar_mestre_histor_senha, usrmstrh_id ): activated (8830)
Index 292 ( PUB.usuar_prefer, usrprfr_01 ): activated (8830)
Index 291 ( PUB.usuar prefer, usrprfr id ): activated (8830)
Index 293 ( PUB.usuar prefer campo, usrprfrc id ): activated (8830)
Index 294 ( PUB.usuar prefer frame, usrprfrf id ): activated (8830)
Index 295 ( PUB.usuar_prefer_var, usrprfrv_id ): activated (8830)
Index 297 ( PUB.usuar_rec, idx_date ): activated (8830)
Index 296 ( PUB.usuar_rec, pk_usuar_rec ): activated (8830)
Index 298 ( PUB.usuar rec, usuarrec funcao ): activated (8830)
Index 299 ( PUB.usuar servid exec, codigo id ): activated (8830)
Index 301 ( PUB. video, video 01 ): activated (8830)
Index 302 ( PUB.video, video_02 ): activated (8830)
Index 300 ( PUB.video, video_id ): activated (8830)
417 indexes were rebuilt. (11465)
Index rebuild complete. 0 error(s) encountered. Elapsed time: 14.262
REDHAT7:/totvs/banco #
```

RODAR O TABANALYS DEPOIS

proutil emsfnd -C tabanalys > /BKP/DUMP/emsfnd/emsfnd_antes.tab





COMPARAR ARQUIVOS TABANALYS

ANTES e DEPOIS

