

A shuffled complex evolution algorithm for the multidimensional knapsack problem

CIARP 2015
XX Iberoamerican Congress
on Pattern Recognition



Marcos Baroni & Flávio Varejão

Universidade Federal do Espírito Santo - Departamento de Informática

marcos.baroni@aluno.ufes.br

Abstract

This work addresses the application of a population based evolutionary algorithm called shuffled complex evolution (SCE) in the multidimensional knapsack problem. The SCE regards a natural evolution happening simultaneously in independent communities. The performance of the SCE algorithm is verified through computational experiments using well-known problems from literature and randomly generated problem as well. The SCE proved to be very effective in finding good solutions demanding a very small amount of processing time.

Keywords: Multidimensional knapsack problem, Meta-heuristics, Artificial Intelligence

Introduction

The multidimensional knapsack problem (MKP) is a strongly NP-hard combinatorial optimization problem which can be viewed as a resource allocation problem and defined as follows:

$$\begin{aligned} & \text{maximize} \sum_{j=1}^n p_j x_j \\ & \text{subject to} \sum_{j=1}^n w_{ij} x_j \leq c_i \quad i \in \{1, \dots, m\} \\ & \quad x_j \in \{0, 1\}, \quad j \in \{1, \dots, n\}. \end{aligned}$$

The multidimensional knapsack problem can be applied on budget planning scenarios and project selections [5], cutting stock problems [4], loading problems [6], allocation of processors and databases in distributed computer programs [3].

The problem is a generalization of the well-known knapsack problem (KP) in which $m = 1$. However it is a NP-hard problem significantly harder to solve in practice than the KP. Due its simple definition but challenging difficulty of solving, the MKP is often used to to verify the efficiency of novel metaheuristics. A good review for the MKP is given by [2].

In this paper we address the application of a metaheuristic called shuffled complex evolution (SCE) to the multidimensional knapsack problem. The SCE is a metaheuristic, proposed by Duan in [1], which combines the ideas of a controlled random search with the concepts of competitive evolution and shuffling.

The SCE for the MKP




Figure 1: figure caption

Figure 2: figure caption

Computational experiments

	Value	Description
N	20	# of complexes
M	20	# of individuals in each complex
P	5	# of individuals in each subcomplex
K	300	# of algorithm iterations
K'	20	# of iterations of evolving process
c	$n/5$	# of genes carried from parent in crossing

Table 1: Parameters used in SCE algorithm.

n	m	α	SCIP t (s)	SCE t (s)	gap (%)
100	5	0.25	0.81	97.6	
		0.50	0.86	97.0	
		0.75	1.02	96.7	
			average gap	97.1	
250	5	0.25	1.75	95.3	
		0.50	1.83	95.0	
		0.75	2.24	94.7	
			average gap	95.0	
500	5	0.25	3.23	93.7	
		0.50	3.40	93.7	
		0.75	3.91	93.3	
			average gap	93.6	

Table 2: SCE performance on Chu-Beasley problems.

Table 3: SCE performance on random generated problems.

Conclusions

In this work we addressed the application of the shuffled complex evolution (SCE) to the multidimensional knapsack problem and investigated its performance through several computational experiments. The SCE algorithm, which combines the ideas of a controlled random search with the concepts of competitive evolution proved to be very effective in finding good solution for hard instances of MKP, demanding a very small amount of processing time to reach high quality solutions for MKP.

Future remarks

- Application of problem reduction procedures for the MKP;
- Investigation of different crossing procedures;
- Use of local search in the process of evolving complexes.

References

- [1] Qingyun Duan, Soroosh Sorooshian, and Vijai Gupta. Effective and efficient global optimization for conceptual rainfall-runoff models. *Water resources research*, 28(4):1015–1031, 1992.
- [2] Arnaud Freille and Gérard Plateau. An efficient preprocessing procedure for the multidimensional 0–1 knapsack problem. *Discrete Applied Mathematics*, 49(1):189–212, 1994.
- [3] B. Gavish and H. Pirkul. Allocation of data bases and processors in a distributed computing system. 1982.
- [4] P. C. Gilmore and R. E. Gomory. The Theory and Computation of Knapsack Functions. *Operations Research*, 14:1045–1074, 1966.
- [5] C McMillan and DR Plaine. Resource allocation via 0–1 programming. *Decision Sciences*, 4:119–132, 1973.
- [6] W. Shih. A Branch and Bound Method for the Multiconstraint Zero-One Knapsack Problem. *Journal of The Operational Research Society*, 30:369–378, 1979.

Acknowledgements

Research supported by Fundação de Amparo à Pesquisa do Espírito Santo.