

Ar Condicionado Série Eco

MS-12HVCG/ECO | MS-18HVCJ/ECO | MS-24HVCJ/ECO |





Características técnicas

Series					M PLUS Series	M PLUS Series	M PLUS Series
Model					MS-12HVCJ#	MS-18HVCJ#	MS-24HVCJ#
Tvne					INVERTER	INVERTER	INVERTER
Items				Unit	Heating Pump	Heating Pump	Heating Pump
Nameplate Parameter	Rated Capacity	Cooling	W	3500(1000~4100)	5200(1500~5900)	7100(2400~7900)	
		Heating	W	3600(1000~4400)	5300(1600~6000)	7320(2400~8200)	
	Rated Power Consumption	Cooling	W	1085	1605	2180	
		Heating	W	970	1415	1950	
	Rated Running Current	Cooling	A	5.2	7.7	10.4	
		Heating	A	4.6	6.8	9.3	
	Max.Input Power			W	1600	2400	3400
	Max.Input Current			A	9.1	11.2	15.9
	EER Cooling: Btu/h.W or WIW			SEER	A++ 6.80	A++ 6.60	A++ 6.50
	COP Heating			sCOP	A+/A+++ 4.2/5.3	A+/A+++ 4.2/5.1	A+/A+++ 4.2/5.1
	Power supply source			VIPh/Hz	220~240V-1-50Hz	220~240V-1-50Hz	220~240V-1-50Hz
	Refrigerant			type	R32	R32	R32
	Refrigerant Charged			gL	480g/675/0.324tonn	810g/675/0.547tonn	1000g/675/0.675ton
	Max.Discharge Pressure			Mpa	4.2	4.2	4.2
	Max.Suction Pressure			Mpa	1.2	1.2	1.2
	Air Flow Volume			m3/h	370/430/520/580/65	610/700/780/870/90	630/820/990/1100/1
	Noise level[+1-3dB]			dB(A)	20/24/27/31/35	24/28/33/37/42	26/32/35/39/45
	Noise level[+1-3dB]			dB(A)	49	50	52
	Indoor unit weight(Net)			Kg	8.5	11	14
	Outdoor unit weight(Net)			Kg	20	25	32
	Indoorunit weight(Gross)			Kg	10.5	13	16
	Outdoor unit weight(Gross)			Kg	22	27	35
Indoor unit configurati on	Fan system	Fan	Type		cross-flow fan	cross-flow fan	Cross-flow fan
			Material		AS	AS	AS
Outdoor unit configurati on	Fan motor		Type	AC/DC	AC	AC	AC
	Dimensio n	Net Dimension		mm	825*290*200	940*320*230	1120*320*230
		Packing Dimension		mm	880*350*270	985*375*315	1168*405*325
	Stop Valve		Liquid Valve	Inch	1/4"	1/4"	1/4"
			Gas Valve	Inch	3/8"	1/2"	5/8"
	Compres sor Paramete r	Drive mode		AC/DC	DC	DC	DC
		type			ROTARY	ROTARY	ROTRAY
		Brand			GMCC-TOSHIBA	GMCC-TOSHIBA	GMCC-TOSHIBA
	Fan system	Fan	Blade Material		AS	AS	AS
		Fan motor	Type	AC/DC	DC	DC	DC
	Power	Type		Outdoor	Outdoor	Outdoor	
	Throttling gear			Capillary	Capillary	capillary	
Dimensio n	Net Dimension		mm	738*246*462	788*300*540	888*295*600	
	Packing Dimension(Width xDepthxHeight)TillValve cover		mm	775*315*515	825*380*590	915*390*670	
Container Loading Qty(CBU)40'HC					320	220	170
Common parameters	Max pipe length			m	25m	30m	35m
	Max height difference			m	10m	15m	20m
	Standard pipe lenqth(no additional refrigerant			m	3m	3m	3m
	Ambient temperature(cooling)			℃	+16~+52	+16~+52	+16~+52
	Ambient temperature(heating)			℃	-15~+24	-15~+24	-15~+24
	Operation temperature			℃	16-32℃	16-32℃	16-32℃
	Ambient Temperature			℃	-15-52℃	-15-52℃	-15-52℃
	Degree of protection(IN)(OUT)(IPX0 etc)				IPX0/IPX4	IPX0/IPX4	IPX0/IPX4
Class of electric protection(IN)/(OUT)/(I/II etc)				I/	I/	I/	