

```
1 //Load and broadcast CSR row pointers
2 row_fbrr = DnsFbrT(0, num_rows);
3 row_ptbs = row_fbrr.add_mem_str(a->ptrs);
4 row_ptes = row_fbrr.add_mem_str(a->ptrs+1);
5 row_grpt = BCast(row_fbrr);
6 //Load two row elements (and vec vals) in lockstep
7 //TUx1 have step=2, TU01 has offset=0, TU11 has offset=1
8 col_fbrr0 = RngFbrT(row_ptbs, row_ptes, 0, 2);
9 col_idx0 = col_fbrr0.add_mem_str(a->idxs);
10 nnz_val0 = col_fbrr0.add_mem_str(a->vals);
11 vec_val0 = col_fbrr0.add_mem_str(b, col_idx0);
12 col_fbrr1 = RngFbrT(row_ptbs, row_ptes, 1, 2);
13 col_idx1 = col_fbrr1.add_mem_str(a->idxs);
14 nnz_val1 = col_fbrr1.add_mem_str(a->vals);
15 vec_val1 = col_fbrr1.add_mem_str(b, col_idx1);
16 col_grpt = LockStep(col_fbrr0, col_fbrr1);
17 nnz_val = col_grpt.add_vec_str(nnz_val0, nnz_val1);
18 vec_val = col_grpt.add_vec_str(vec_val0, vec_val1);
19 //Set the row-end and row-ite callbacks and operands
20 col_grpt.add_callback(GITE, ri, {nnz_val, vec_val});
21 col_grpt.add_callback(GEND, re, {});
```