Capitol Manufacturing
1125 Capitol Avenue
Crowley, LA 70526

Commanding a Higher Standard℠

Phoenix * Capitol * Camco
CapProducts

Certified Material Test Report

Printed: 5/6/2026 Certified: 02/17/2026

Customer
DNOW LP
1701 GOVER PARKWAY

MOUNT PLEASANT ,MI 48858

P.O. 26798545
Tag 3536
Material
ASTM A106B-2019a / ASME SA106B-2023 Edition

Heat No 4804P
Heat Code 79QU
Order # 95496

Part Number
15112008

Description
2 X 4" XHSML BK STL NIPL TBE

Chemical Properties

C	Mn	P	S	Si	Cu	Ni	Cr
0.1920	0.6420	0.0150	0.0090	0.2510	0.1350	0.0590	0.1050

C Eq. Long
0.3376

Mo	V	Co	Al	Nb	N	Pb	Sn	Ta	Ti
0.0210	0.0025			0.0012					

Additional Chemical Properties

CE CSA
N/A

Cr + Cu + Ni
0.2990

Mechanical Properties

Tensile (PSI)	Yield (PSI)	Elong. % in 2 in. or 4D	R of A %	HBW	HBW2
68226	46138	36.4		131	133

Charpy Minimum Impact - ft/lbs

Test 1	Test 2	Test 3	Average	Test Temp.	Test Size

Fracture Appearance - %

Test 1	Test 2	Test 3	Average

* Hydro test passed. at 2500 psi.
* Ultrasonic test passed
* Bend test passed.

We hereby certify that these parts were manufactured, sampled, tested, and inspected in accordance with the product specifications stated and were found to meet the requirements.
This document is according to EN 10204 Inspection Certificate 3.1 requirements.
These products meet the requirements of the latest editions of NACE MR0175/ISO 15156 and NACE MR0103. No weld repair has been performed on these products. This material was not exposed to mercury or any other metal alloy that is liquid at ambient temperatures during processing or while in our possession.

Meets ASME SA 106 Grade B Requirements.