EDGEN MURRAY

an EDGEN Company

Packing List : 423161-1
Ship Date :
Cust/Ship to: 1641/36

Item	Product	Mill/Heat	Tag/ID	Qty	Pcs	Total
13-1	Forged Hex Plug ASTM A/SA105 NPT Threaded 1" 3000#\6000#	BON/J388	326482-18		8	8.00
14-1	Forged Hex Bush ASTM A/SA105 NPT Threaded 0.50" x 0.25" 3000\6000# ½" x ¼" Bushing THRD	BON/J304	325949-4		6	.36
15-1	Forged Hex Bush ASTM A/SA105 NPT Threaded 1" x 0.25" 1" x ¼" Bushing THRD	BON/J173 BON/J173	325949-5 325949-5		1 5 Total 6	.21 1.05 1
16-1	Forged Hex Bush ASTM A/SA105 NPT Threaded 2" x 1" 3000\6000# 2" x 1" Bushing THRD	BON/J400	327746-13		4	3.68
17-1	Forged Hex Bush ASTM A/SA105 NPT Threaded 2" x 0.50" 3000\6000# 2" x ½" Bushing THRD	BON/J404	328867-5		4	3.68
19-1	Forged Hex Bush ASTM A/SA105 NPT Threaded 1" x 0.50"-3000\6000# 1" x ½" Bushing THRD	BON/J313	326482-10		6	1.32
22-1	Forged Hex Plug ASTM A/SA105 NPT Threaded 0.50" 3000#\6000# ½" Plugs Bonny	BON/J229	327746-15		9	1.26
23-1	Pipe SMLS Nipple ASTM A106-B 2" x 6" XXH Thrd Both Ends	CPM/79L3	319074-17		2	9.04
24-1	2" 3000# THRD BALL VALVE - WKM#B138-CS-43-CS BODY: CS TRIM: CS, ACETAL PLASTIC SEAT ANSI B16.34 PORT: FULL LEVER OPERATED	WKM/-	327985-3		2	46.00
25-1	Forged Hex Plug ASTM A/SA105 NPT Threaded 2" 3000\6000#					

CERTIFIED MILL TEST REPORT

The Best Value - Price, Quality, Service All The Time.

LOG NO. F00000000238814

BONNEY FORGE CORPORATION
P.O. BOX 330 • 14496 CROGHAN PIKE • MOUNT UNION, PA 17066-0330
(814) 542-2545 • (800) 345-7546 • FAX (814) 542-4906
www.bonneyforge.com

CUSTOMER: EDGEN MURRAY CORPORATION **DATE** 03/10/2026

CUSTOMER ORDER NO.: RMS-326482 **BONNEY ORDER NO.** B000378864

SHIP TO: EDGEN MURRAY CORPORATION
8445 MILLER RD 2
HOUSTON TX 77049
United States

ITEM	QUANTITY	LOT NO.	GRADE OR SPECIFICATION NO. CHEMICAL ANALYSIS, PHYSICAL PROPERTIES, REMARKS:
10	75	J313	1 X 1/2 3M/6M A105 HXBU T SA/A105 Al 0.026 C 0.200 Co 0.007 Cr 0.100 Cu 0.220 Mn 1.010 Mo 0.020 Nb 0.002 Ni 0.080 P 0.006 S 0.022 Si 0.220 V 0.024 CE(Long Formula) = 0.42 T/S(PSI) 78,700 Y/S(PSI) 53,500 EL(%) 48.00 RA(%) 45.00 Brinell Hardness 163 BHN 165 BHN
11	25	J313	1 X 3/4 3M/6M A105 HXBU T SA/A105 Al 0.026 C 0.200 Co 0.007 Cr 0.100 Cu 0.220 Mn 1.010 Mo 0.020 Nb 0.002 Ni 0.080 P 0.006 S 0.022 Si 0.220 V 0.024 CE(Long Formula) = 0.42 T/S(PSI) 78,700 Y/S(PSI) 53,500 EL(%) 48.00 RA(%) 45.00 Brinell Hardness 163 BHN 165 BHN
12	50	J183	2 X 1/2 3M/6M A105 HXBU T SA/A105 Al 0.025 C 0.190 Co 0.005 Cr 0.170 Cu 0.280 Mn 0.970 Mo 0.020 Nb 0.002 Ni 0.080 P 0.012 S 0.015 Si 0.237 V 0.032 CE(Long Formula) = 0.42 T/S(PSI) 79,400 Y/S(PSI) 53,300 EL(%) 28.00 RA(%) 57.00 Brinell Hardness 165 BHN 166 BHN
13	25	J279	2 X 3/4 3M/6M A105 HXBU T SA/A105 Al 0.031 C 0.180 Cb 0.003 Co 0.005 Cr 0.150 Cu 0.260 Mn 0.990 Mo 0.010 Ni 0.070 P 0.009 S 0.025 Si 0.221 V 0.023 CE(Long Formula) = 0.40 T/S(PSI) 78,700 Y/S(PSI) 51,800 EL(%) 25.00 RA(%) 56.00 Brinell Hardness 161 BHN 161 BHN

1"X 1/2" BUSHING THRD

We certify that the data on this sheet is a true copy taken from our records of material furnished us by the production mill, or as obtained by additional laboratory checks.

by Natalie Miller
Natalie Miller
Quality Assurance Representative

CMTR: Rev 3

***