INTERNATIONAL WFI NUCLEAR PRODUCTS
Manufacturer of Piping and Pressure Vessel Components
4404 Haygood St - Houston, TX 77022
Phone: 713-695-3633 Fax: 713-695-3528
A Bonney Forge Company

Sold To: MAVERICK INTERNATIONAL, LTD.
18291 ENGLIN ROAD
WINNIE TX 77665
United States

MTR #: 460,729
PO #: 4067311
Sales Order #: C002609225
Date: 09/21/2026

This product has not come in direct contact with mercury or any of its compounds, nor with any mercury-containing device employing a single boundary of containment. No welding performed.

We certify that the contents of this report are correct and accurate, and that all test results and operations performed by WFI or its subcontractors are in compliance with the material specification and requirements of the referenced code or standard, and that the material conforms to the dimensional requirements of the order. This document is in accordance with EN10204 3.1.

Certified Material Test Report

Heat Code: 9869AH
Material: A694 16 F52

Item	Quantity	Description
1	1	36 - 3 X 1 3M SWP
		A694F52

Chemical Composition

Ladle	Al	B	C	Cr	CR+MO	Cu	Mn	Mn/C	Mo	Nb	Ni	P
	0.021	0.0001	0.210	0.12	0.13	0.09	0.970	4.619	0.010	0.0020	0.040	0.008
	RE(1)	S	Si	Ti	V							
	0.26	0.0210	0.270	0.001	0.00							
	Carbon Equivalency (C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15):				0.41							
Product	Al	B	C	Co	Cr	Cu	Mn	Mn/C	Mo	Nb	Ni	P
	0.017	0.0005	0.209	0.007	0.11	0.10	0.939	4.493	0.015	<0.0010	0.039	0.008
	RE(1)	S	Si	V								
	0.26	0.0213	0.269	0.00								
	Carbon Equivalency (C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15):				0.40							

RE(1) = Cu + Ni + Cr + Mo + V

	Tensile PSI	Yield PSI	Elong (4D) %	RA %	Hardness
Product	84,900	61,400	34.10	71.80	163 BHN 163 BHN

Charpy V-Notch Properties

Specimen Size	Test Temperature	Ft Lbs	% Shear	MLE	Direction
10mm x 10mm	-50 F	155/160/155	100/100/100	66/71/91	Longitudinal

MILL/COUNTRY OF ORIGIN: CHARTER STEEL (MELTED AND MANUFACTURED: SAUKVILLE, WISCONSIN / USA) - HEAT NO.: 21044710 (BONNEY FORGE (MT.UNION, PS (USA)) - HEAT NO.: 52464

IN ACCORDANCE WITH ANSI/NACE MR0175 / ISO 15156-2021
STEEL IS FULLY KILLED AND PRODUCED TO A FINE GRAIN PRACTICE

AUSTENITIZED AT 1675±25°F FOR A MINIMUM OF 60 MINUTES PER INCH OF SECTION THICKNESS, BUT NO LESS THAN 60 MINUTES AT TEMPERATURE (WATER QUENCHED); TEMPERED BETWEEN 1000-1025°F FOR 60 MINUTES OF SECTION THICKNESS (STILL AIR COOLED).

Monica Rogers Quality Assurance Representative

INTERNATIONAL WFI NUCLEAR PRODUCTS
Manufacturer of Piping and Pressure Vessel Components
4404 Haygood St - Houston, TX 77022
Phone: 713-695-3633 Fax: 713-695-3528
A Bonney Forge Company

Sold To: MAVERICK INTERNATIONAL, LTD.
18291 ENGLIN ROAD
WINNIE TX 77665
United States

MTR #: 460,729
PO #: 4067311
Sales Order #: C002609225
Date: 09/21/2026

This product has not come in direct contact with mercury or any of its compounds, nor with any mercury-containing device employing a single boundary of containment. No welding performed.

We certify that the contents of this report are correct and accurate, and that all test results and operations performed by WFI or its subcontractors are in compliance with the material specification and requirements of the referenced code or standard, and that the material conforms to the dimensional requirements of the order. This document is in accordance with EN10204 3.1.

Certified Material Test Report

Heat Code: 9869AH
Material: A694 16 F52

Item	Quantity	Description
2	1	36 - 3 X 1 3M SWP
		A694F52

Chemical Composition

Ladle	Al	B	C	Cr	CR+MO	Cu	Mn	Mn/C	Mo	Nb	Ni	P
	0.021	0.0001	0.210	0.12	0.13	0.09	0.970	4.619	0.010	0.0020	0.040	0.008
	RE(1)	S	Si	Ti	V							
	0.26	0.0210	0.270	0.001	0.00							
	Carbon Equivalency (C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15):				0.41							
Product	Al	B	C	Co	Cr	Cu	Mn	Mn/C	Mo	Nb	Ni	P
	0.017	0.0005	0.209	0.007	0.11	0.10	0.939	4.493	0.015	<0.0010	0.039	0.008
	RE(1)	S	Si	V								
	0.26	0.0213	0.269	0.00								
	Carbon Equivalency (C+Mn/6+(Cr+Mo+V)/5+(Ni+Cu)/15):				0.40							

RE(1) = Cu + Ni + Cr + Mo + V

	Tensile PSI	Yield PSI	Elong (4D) %	RA %	Hardness
Product	84,900	61,400	34.10	71.80	163 BHN 163 BHN

Charpy V-Notch Properties

Specimen Size	Test Temperature	Ft Lbs	% Shear	MLE	Direction
10mm x 10mm	-50 F	155/160/155	100/100/100	66/71/91	Longitudinal

MILL/COUNTRY OF ORIGIN: CHARTER STEEL (MELTED AND MANUFACTURED: SAUKVILLE, WISCONSIN / USA) - HEAT NO.: 21044710
(BONNEY FORGE (MT.UNION, PS (USA)) - HEAT NO.: 52464

IN ACCORDANCE WITH ANSI/NACE MR0175 / ISO 15156-2021
STEEL IS FULLY KILLED AND PRODUCED TO A FINE GRAIN PRACTICE

AUSTENITIZED AT 1675±25°F FOR A MINIMUM OF 60 MINUTES PER INCH OF SECTION THICKNESS, BUT NO LESS THAN 60 MINUTES AT TEMPERATURE (WATER QUENCHED); TEMPERED BETWEEN 1000-1025°F FOR 60 MINUTES OF SECTION THICKNESS (STILL AIR COOLED).

Monica Rogers Quality Assurance Representative