CERTIFIED MILL TEST REPORT

The Best Value - Price, Quality, Service All The Time.

LOG NO. F00000000243867

BONNEY FORGE CORPORATION
P.O. BOX 330 • 14496 CROGHAN PIKE • MOUNT UNION, PA 17066-0330
(814) 542-2545 • (800) 345-7546 • FAX (814) 542-4906
www.bonneyforge.com

CUSTOMER: DODSON VALCO, INC

DATE 06/09/2026

CUSTOMER ORDER NO.: 465138

BONNEY ORDER NO. B000383365

SHIP TO: DODSON VALCO, INC (STONE MOUNTAIN)
5650 PONCE DE LEON AVENUE
STONE MOUNTAIN GA 30083
United States

ITEM	QUANTITY	LOT NO.	GRADE OR SPECIFICATION NO. CHEMICAL ANALYSIS, PHYSICAL PROPERTIES, REMARKS:
		H5CY	11/2 3000 A105 UNAR T SA/A105
		NUT	Al 0.027 C 0.180 Co 0.006 Cr 0.100 Cu 0.160 Mn 1.060 Mo 0.030 Nb 0.003 Ni 0.060 P 0.008 S 0.020 Si 0.240 V 0.030 CE(Long Formula) = 0.40 T/S(PSI) 78,509 Y/S(PSI) 58,161 EL(%) 31.95 RA(%) 57.21 Brinell Hardness 156 BHN 159 BHN Country Of Origin (Melt): UNITED STATES
41	25	J346	1 X 1/4 3M/6M A105 HXBU T SA/A105 Al 0.023 C 0.190 Co 0.010 Cr 0.110 Cu 0.080 Mn 0.980 Mo 0.020 Nb 0.002 Ni 0.040 P 0.005 S 0.024 Si 0.270 V 0.003 CE(Long Formula) = 0.39 T/S(PSI) 74,000 Y/S(PSI) 51,000 EL(%) 31.00 RA(%) 62.00 Brinell Hardness 138 BHN 140 BHN Country Of Origin (Melt): UNITED STATES
42	125	J173	1 X 3/8 3M/6M A105 HXBU T SA/A105 Al 0.034 C 0.200 Co 0.004 Cr 0.090 Cu 0.180 Mn 0.980 Mo 0.010 Nb 0.001 Ni 0.060 P 0.006 S 0.022 Si 0.190 V 0.026 CE(Long Formula) = 0.40 T/S(PSI) 77,500 Y/S(PSI) 53,400 EL(%) 34.00 RA(%) 30.00 Brinell Hardness 166 BHN 166 BHN Country Of Origin (Melt): UNITED STATES
43	75	J346	1 X 1/2 3M/6M A105 HXBU T SA/A105 Al 0.023 C 0.190 Co 0.010 Cr 0.110 Cu 0.080 Mn 0.980 Mo 0.020 Nb 0.002 Ni 0.040 P 0.005 S 0.024 Si 0.270 V 0.003 CE(Long Formula) = 0.39 T/S(PSI) 74,000 Y/S(PSI) 51,000 EL(%) 31.00 RA(%) 62.00 Brinell Hardness 138 BHN 140 BHN Country Of Origin (Melt): UNITED STATES

We certify that the data on this sheet is a true copy taken from our records of material furnished us by the production mill, or as obtained by additional laboratory checks.

by Billie Jo Clemens

Billie Jo Clemens
Quality Assurance Representative

CMTR: Rev 3

CERTIFIED MILL TEST REPORT

The Best Value - Price, Quality, Service All The Time.

LOG NO. F00000000243867

BONNEY FORGE CORPORATION
P.O. BOX 330 • 14496 CROGHAN PIKE • MOUNT UNION, PA 17066-0330
(814) 542-2545 • (800) 345-7546 • FAX (814) 542-4906
www.bonneyforge.com

CUSTOMER: DODSON VALCO, INC

DATE 06/09/2026

CUSTOMER ORDER NO.: 465138

BONNEY ORDER NO. B000383365

SHIP TO: DODSON VALCO, INC (STONE MOUNTAIN)
5650 PONCE DE LEON AVENUE
STONE MOUNTAIN GA 30083
United States

ITEM	QUANTITY	LOT NO.	GRADE OR SPECIFICATION NO. CHEMICAL ANALYSIS, PHYSICAL PROPERTIES, REMARKS:
99	6	9837AF	18-16 X 8 STD A105N WELD B SA/A105N

Al 0.020 C 0.172 Cr 0.140 Cu 0.180 Mn 0.977 Mo 0.039 Ni 0.097 P 0.014
S 0.022 Si 0.256 V 0.030
CE(Long Formula) = 0.40
T/S(PSI) 73,300 Y/S(PSI) 49,900 EL(%) 35.10 RA(%) 67.31
Brinell Hardness 149 BHN 149 BHN
Country Of Origin (Melt): UNITED STATES

1. THE FITTINGS SUPPLIED ARE IN ACCORDANCE WITH PURCHASE ORDER SPECIFICATIONS.
2. CERTIFYING ASTM A105-24 / ASME SA105-23 EDITION.
3. THE PRODUCT SUPPLIED WAS INSPECTED IN ACCORDANCE WITH EN 10204:2004 EDITION TYPE 3.1 INSPECTION DOCUMENT. (EUROPEAN STANDARD)
4. ELONGATION TEST RESULTS ARE OBTAINED USING STANDARD ROUND SPECIMEN, 2 INCH OR 50 MM GAGE LENGTH.
5. ITEM - 1, 2, 3, 4, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 40, 41, 42, 43, 44, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 78, 79, 80, 81, 82, 83, 84, 85, 88, 89, 90, 91, 92, 96, 100 -THE MATERIAL SUPPLIED MEETS THE REQUIREMENTS OF NACE MR0175/ISO 15156-2 - 2015 EDITION.
6. ITEM - 98, 99 -THE MATERIAL SUPPLIED IDENTIFIED AS A105N WAS NORMALIZED IN ACCORDANCE WITH ASTM A105 HEAT TREATING REQUIREMENTS.
7. ITEM - 98, 99 -THE MATERIAL SUPPLIED AS A105N MEETS THE REQUIREMENTS OF BOTH NACE MR0103/ISO 17945 - 2015 & NACE MR0175/ISO 15156-2 - 2015 EDITION.
8. ITEM - 16, 26 -THE MATERIAL SUPPLIED IDENTIFIED AS SA/A105-QT WAS QUENCHED AND TEMPERED IN ACCORDANCE WITH ASTM A105 HEAT TREATING REQUIREMENTS.

We certify that the data on this sheet is a true copy taken from our records of material furnished us by the production mill, or as obtained by additional laboratory checks.

by Billie Jo Clemens

Billie Jo Clemens
Quality Assurance Representative

CMTR: Rev 3