

Our Order 2492378-9-1 Your Order 74769-03
Heat 038570
Desc Pipe ERW API 5L X65,20.000 x .594 - 20" S-40 DRL

Packing List 407195-4 (1/14/2026)

Image 556094

Job: 74769
PO: 7476903
BOM: 3
Pages: 5
Heat: 038570



MANNESMANN
LINE PIPE

Ein Unternehmen der Salzgitter Gruppe

Inspection certificate 3.1 EN 10204:2004 (A02)		No. (A03) Page Date	20002993 1/5 11.07.2025
No. (A07) Purchaser (A06)	65705 28.02.2025 Salzgitter Mannesmann International (USA) Inc. 1770 St. James Place, Suite 600 77056-3499 HOUSTON USA	No. (A07) Customer (A05)	
Product (B01)	steel line pipe, HFW-HFI-longitudinally welded	Works order No. (A08)	0603011475
Steel grade and terms of delivery (B02-B03)	API SPEC 5L 46TH PSL 2 X65M Impact Requirements according to API 5L 46th: Pipe body at M46°C (M50°F), HAZ M29° C (M20°F), fusion line at M20°C (M4°F) and additionally fusion line at M29°C (M20°F) for information only. Hardness according to NACE MR0175 / ISO 15156 and NACE MR0103, tested 100% SMYS.	Dispatch note No. Inspection (A05) Manufacturer acc.	0080036156 10.07.2025
Cond. of delivery: Weld zone inductive annealed (Temperature minimum 1600°F / 871°C)			

Material data (B01-B99)						
Item	Heat No. (B07)	Quantity (B08)	Cond. of delivery (B04)	D x T x Length (B09-B11)	Length (B09-B11)	Weight (B12)
010	038570	32	U	20,000 x 0,594 x 44,967	1.421,684	175.215
Σ		32	U: as rolled		1.421,684	175.215
The mentioned length and weight refers to the product in delivery condition						

Product description (B06)
Inside conditions (B06) Surface: black
Outside conditions (B06) Surface: black temporary anti-corrosive protection laquer approx. 35 my thickness
ends (B06) End 1: bevelled 30 +5/-0°, root face 1,6 +/-0,8 mm End 2: bevelled 30 +5/-0°, root face 1,6 +/-0,8 mm End protection: without plastic caps
Marking of the product (B06) Longitudinal marking at one end: Pipe-no. X65M 20.000 0.594 Internal marking at both ends: Barcode Pipe-no. Manufacturers sign HAMM API SPEC 5L 0256 API monogram MM-YY 20.000 0.594 X65M PSL 2 HFW A HEAT NO. Heat-no. Single pipe length (ft) Pipe-no. TESTED 3660 PSI MADE IN GERMANY P.O. No. 65705 mill order no. Product No.


MANNESMANN
LINE PIPE

Ein Unternehmen der Salzgitter Gruppe

Inspection certificate 3.1
EN 10204:2004
 (A02)

 No. (A03) **20002993**
 Page 2/5
 Date 11.07.2025

Ladle analysis (C70-C99)
 Manufacturer standard

Heat No. (B07)	C %	Si %	Mn %	P %	S %	Cu %	Cr %	Ni %	Mo %	V %
	≤ 0,10	≤ 0,45	≤ 1,70	≤ 0,025	≤ 0,015	≤ 0,50	≤ 0,50	≤ 0,50	≤ 0,50	
038570	0,05	0,17	1,04	0,010	0,003	0,02	0,03	0,03	0,12	0,003
Heat No. (B07)	Ti %	Nb %	B %	EV1 1) %						
			≤ 0,0010	≤ 0,15						
038570	0,02	0,07	0,0001	0,09						

1) EV1: Nb+V+Ti

 Steelmaking process: Basic oxygen process
 (C70)

 Steel Manufacturer incl. country of melt and pour (A01):
 Salzgitter Flachstahl GmbH, Watenstedt, Eisenhüttenstraße 99, 38239 SALZGITTER
 GERMANY

 Coil Manufacturer (A01):
 Salzgitter Flachstahl GmbH, Watenstedt, Eisenhüttenstraße 99, 38239 SALZGITTER
 GERMANY

Product analysis (C70-C99)
 ISO/TR 9769

Test type: Lot Testing

Specimen No. (C00)	Heat No. (B07)	C %	Si %	Mn %	P %	S %	Cu %	Cr %	Ni %
		≤ 0,10	≤ 0,45	≤ 1,70	≤ 0,025	≤ 0,015	≤ 0,50	≤ 0,50	≤ 0,50
2001590673 *)	038570	0,06	0,17	1,00	0,009	0,003	0,02	0,03	0,03
2001590674 *)	038570	0,06	0,17	1,00	0,009	0,003	0,02	0,03	0,03
Specimen No. (C00)	Heat No. (B07)	Mo %	V %	Ti %	Nb %	B %	EV1 1) %	EV2 2) %	
		≤ 0,50				≤ 0,0010	≤ 0,25	≤ 0,15	
2001590673 *)	038570	0,10	0,01	0,03	0,07	0,0003	0,13	0,10	
2001590674 *)	038570	0,10	0,01	0,03	0,07	0,0003	0,13	0,10	

1) EV1: PCM = C+Si/30+(Mn+Cu+Cr)/20+Mo/15+Ni/50+V/10+5*B

2) EV2: Nb+V+Ti

*) The sample pipe is not part of the delivery



MANNESMANN
LINE PIPE

Ein Unternehmen der Salzgitter Gruppe

Inspection certificate 3.1
EN 10204:2004
(A02)

No. (A03) **20002993**
Page 3/5
Date 11.07.2025

Tensile test (C10-C29)

ISO 6892-1

Test type: Lot testing

Condition specimen: Specimen as delivery condition/Pipe as rolled

Specimen shape: Flat tensile test

Specimen No. (C00)	Heat No. (B07)	Location (C01)	Orient. (C02)	Height of specimen (C11)	Width of specimen (C12)	Yield strength (C11) Rt 0,5 psi 65300-87000	Tensile strength (C12) Rm psi 77600-110200	Rt0,5/Rm
2001590673 *)	038570	BM	T180	0,60	1,58	74694	88473	0,84
Specimen No. (C00)	Heat No. (B07)	Location (C01)	Orient. (C02)	Elongation (C13) 2 in % ≥24				
2001590673 *)	038570	BM	T180	41				
Specimen No. (C00)	Heat No. (B07)	Location (C01)	Orient. (C02)	Height of specimen (C11)	Width of specimen (C12)	Tensile strength (C12) Rm psi 77600-110200		
2001590673 *)	038570	WL	T000	0,60	1,58	80206		

1) BM : Base material

WL : Weld seam

*) The sample pipe is not part of the delivery

2) T000 : Transversal 0°

T180 : Transversal 180°

Charpy impact test (C40-C49)

ASTM A 370

Test type: Lot testing

Condition specimen: Specimen as delivery condition/Pipe as rolled

Type of notch: V-notch

Specimen size: 1/1 specimen

Specimen No. (C00)	Heat No. (B07)	Location (C01)	Orient. (C02)	Temp. (C03)	Impact energy (C42-C43) 1 ft lbf ≥ 15	2	3	MW 3) ft lbf ≥ 20
2001590673 *)	038570	BM	T090	-051	172	167	183	174
Specimen No. (C00)	Heat No. (B07)	Location (C01)	Orient. (C02)	Temp. (C03)	Shear fracture (C42-C43) 1 %	2	3	MW 3) %
2001590673 *)	038570	BM	T090	-051	100	100	100	100

1) BM : Base material

HAZ3 : Heat affected zone 3 mm

WL : Weld seam

*) The sample pipe is not part of the delivery

2) T000 : Transversal 0°

T090 : Transversal 90°

3) MW : Average

Our Order 2492378-9-1 Your Order 74769-03
Heat 038570
Desc Pipe ERW API 5L X65,20.000 x .594 - 20" S-40 DRL

Packing List 407195-4 (1/14/2026)

Image 556094



MANNESMANN
LINE PIPE

Ein Unternehmen der Salzgitter Gruppe

Inspection certificate 3.1		No. (A03)	20002993
EN 10204:2004		Page	4/5
(A02)		Date	11.07.2025

Charpy impact test (C40-C49)								
ASTM A 370								
Test type: Lot testing								
Condition specimen: Specimen as delivery condition/Pipe as rolled								
Type of notch: V-notch								
Specimen size: 1/1 specimen								
Specimen No. (C00)	Heat No. (B07)	Location (C01)	Orient. (C02)	Temp. (C03)	Impact energy (C42-C43)			
		1)	2)	° F	1 ft lbf ≥ 15	2	3	MW 3) ft lbf ≥ 20
2001590673 *)	038570	HAZ3	T000	-020	218	218	215	217
2001590673 *)	038570	WL	T000	-004	71	47	158	92
Specimen No. (C00)	Heat No. (B07)	Location (C01)	Orient. (C02)	Temp. (C03)	Impact energy (C42-C43)			
		1)	2)	° F	1 ft lbf	2	3	MW 3) ft lbf
2001590673 *)	038570	WL	T000	-020	152	66	49	89
1) BM: Base material								
HAZ3: Heat affected zone 3 mm								
WL: Weld seam								
*) The sample pipe is not part of the delivery								
2) T000: Transversal 0°								
T090: Transversal 90°								
3) MW: Average								

Destructive tests (D51-D59)	
Flattening test according to ISO 8492:	Satisfactory
Metallographic determination of micro and macro structure:	Satisfactory
Determination of indentation hardness by hardness Vickers max. 250 HV10 according to ISO 6507-1:	Satisfactory

Non-destructive tests (D02-D50)	
Visual and dimensional inspection:	Satisfactory
Ultrasonic testing of weld seam for the detection of longitudinal imperfections according to ISO 10893-11, acceptance level U3:	Satisfactory
Hydrostatic test 3660 PSI, holding time 10 s:	Satisfactory
Check for residual magnetism at the pipe ends max. 30 Gauss:	Satisfactory

Pipe list (B01-B99)							
Item	Pipe No. (B07)	Product No. (B07)	Heat No. (B07)	Inspection No. (B07)	Cond. of delivery (B04)	Length (B09-B11) ft	Weight (B12) lbs
010	2001590683	GPO704002	038570	0	U	44, 436	5.476
010	2001590685	GPO704004	038570	0	U	44, 948	5.540
010	2001590686	GPO704005	038570	0	U	44, 934	5.538
010	2001590687	GPO704006	038570	0	U	44, 934	5.538
010	2001590688	GPO704007	038570	0	U	44, 944	5.540
U: as rolled							

Our Order 2492378-9-1 Your Order 74769-03
Heat 038570
Desc Pipe ERW API 5L X65,20.000 x .594 - 20" S-40 DRL

Packing List 407195-4 (1/14/2026)

Image 556094



MANNESMANN
LINE PIPE

Ein Unternehmen der Salzgitter Gruppe

Inspection certificate 3.1
EN 10204:2004
(A02)

No. (A03) **20002993**
Page 5/5
Date 11.07.2025

Pipe list (B01-B99)

Item	Pipe No. (B07)	Product No. (B07)	Heat No. (B07)	Inspection No. (B07)	Cond. of delivery (B04)	Length (B09-B11) ft	Weight (B12) lbs
010	2001590689	GPO704008	038570	0	U	44,951	5.540
010	2001590690	GPO704009	038570	0	U	44,938	5.538
010	2001590691	GPO704010	038570	0	U	44,938	5.538
010	2001590692	GPO704011	038570	0	U	44,948	5.540
010	2001590693	GPO704012	038570	0	U	31,027	3.823
010	2001590696	GPO705002	038570	0	U	44,426	5.476
010	2001590697	GPO705003	038570	0	U	44,941	5.538
010	2001590698	GPO705004	038570	0	U	44,938	5.538
010	2001590699	GPO705005	038570	0	U	44,944	5.540
010	2001590700	GPO705006	038570	0	U	44,957	5.540
010	2001590701	GPO705007	038570	0	U	44,941	5.538
010	2001590702	GPO705008	038570	0	U	44,938	5.538
010	2001590703	GPO705009	038570	0	U	44,951	5.540
010	2001590704	GPO705010	038570	0	U	44,954	5.540
010	2001590705	GPO705011	038570	0	U	44,944	5.540
010	2001590706	GPO705012	038570	0	U	44,393	5.472
010	2001590709	GPO706002	038570	0	U	44,446	5.478
010	2001590710	GPO706003	038570	0	U	44,951	5.540
010	2001590711	GPO706004	038570	0	U	44,948	5.540
010	2001590712	GPO706005	038570	0	U	44,934	5.538
010	2001590713	GPO706006	038570	0	U	44,948	5.540
010	2001590714	GPO706007	038570	0	U	44,951	5.540
010	2001590715	GPO706008	038570	0	U	44,941	5.538
010	2001590716	GPO706009	038570	0	U	44,938	5.538
010	2001590717	GPO706010	038570	0	U	44,951	5.540
010	2001590718	GPO706011	038570	0	U	44,951	5.540
010	2001590719	GPO706012	038570	0	U	44,400	5.472
Quantity (B08)	32	U: as rolled				1.421,684	175.215

Statement of compliance:

The products have been tested in accordance with the purchase specification and are found to be satisfactory. Alteration of this testimonial and certification or use for other products is not allowed and are regarded as falsification of documents and will be subjected to criminal jurisdiction.

We hereby certify that the delivered material complies with the terms of the order,
(Z01)



Trademark
(A04)

Mannesmann Line Pipe GmbH
Kissinger Weg
59067 HAMM
GERMANY
(A01)

A

Inspection Stamp
(Z03)

Inspection Representative
(Z02)

Pinto

Mannesmann Line Pipe GmbH · In der Steinwiese 31, 57074 Siegen, Germany · Briefanschrift: Postfach 12 01 52, 57022 Siegen, Germany ·
Telefon: 0271 691-0 · Telefax: 0271 691-299 · E-Mail: info.mlp@mannesmann.com · Internet: www.mannesmann-linepipe.com ·
Geschäftsführung: Andreas Betzler · Dr. Carsten Holste · Sitz der Gesellschaft: Siegen · Registergericht: Amtsgericht Siegen ·
Registernummer: HRB1435 · Bankverbindung: Commerzbank AG, Siegen, BLZ 46040033, Konto 836084400, IBAN DE 68460400330836084400,
S.W.I.F.T.: COBA DE FF 460 · Ust-IdNr.: DE 811 151 335 · Steuer-Nr.: 51/200/00033 · EORI-Nr.: DE6411185