

**MAVERICK TUBE CORPORATION**

Hickman Plant  
5020 N COUNTY RD 967  
BLYTHEVILLE, AR 72315  
(870) 776-5000 tel  
(870) 776-5008 fax

**MILL TEST CERTIFICATE**

Number:

**108817291.0.7**

Page:

**1 / 6**Date: **July 15, 2026**

|                                                                                             |  |               |                                       |                       |                                   |                                        |                                    |                             |  |
|---------------------------------------------------------------------------------------------|--|---------------|---------------------------------------|-----------------------|-----------------------------------|----------------------------------------|------------------------------------|-----------------------------|--|
| Customer: MRC Global   CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427 |  |               | Customer's Order Item: 39080737/SO/70 |                       | Customer's Reference: US1119929PO |                                        | Manufacturer's Works Order N°: N/A |                             |  |
| Manufacturing Process: HFW                                                                  |  |               | Product Type: Line Pipe               |                       |                                   |                                        |                                    | Surface: Bare               |  |
| Standard or Specification: API Spec 5L 46th Edition 04/2018                                 |  |               |                                       |                       | Steel Grade: X65M PSL 2           |                                        |                                    | Ends: Plain End Bevelled    |  |
| Dimensions: 16.000 x 0.500 in                                                               |  | Schedule: N/A |                                       | Length: 35'MIN 45'MAX |                                   | Quantity: 12 PCS<br>520 FT<br>43163 LB |                                    | Nominal Weight: 82.85 LB/FT |  |

**TENSILE TEST**

| Heat N° | Sample N° | Zone | Lot N°  | Specimen condition |    |      |     | Specimen dimensions |             | Test temp | Y.S.         | U.T.S.    | Y.S./U.T.S. | Elongation |      |   |
|---------|-----------|------|---------|--------------------|----|------|-----|---------------------|-------------|-----------|--------------|-----------|-------------|------------|------|---|
|         |           |      |         | Ls                 | Sc | Type | Ori | Size                | .5% EUL     |           | Req.         | Req. Max. | Lo          | Min.       | Obt. |   |
|         |           |      |         |                    |    |      |     |                     | Min: 65 300 |           | Min: 77 600  |           |             |            |      |   |
|         |           |      |         |                    |    |      |     |                     | Max: 87 000 |           | Max: 110 200 |           |             |            |      |   |
|         |           |      |         |                    |    |      |     |                     |             | F         | psi          | psi       |             | in         | %    | % |
| 2161576 | 220920    | E1   | 2161576 | B                  | AM | Ss   | T   | 1.500               | RT          | 76 406    | 90 982       | 0.83      | 2.0         | 23.0       | 33.1 |   |
| 2262234 | 220722    | E1   | 2262234 | B                  | AM | Ss   | T   | 1.500               | RT          | 75 714    | 87 026       | 0.87      | 2.0         | 23.0       | 36.1 |   |
| 2262235 | 220723    | E1   | 2262235 | B                  | AM | Ss   | T   | 1.500               | RT          | 74 641    | 88 228       | 0.84      | 2.0         | 23.0       | 31.1 |   |

AM: As manufactured

B: Body

E1 / E2: Ends of Sampling

Lo: Initial length

Ls: Location of sample

Max: Maximum

Min: Minimum

Obt: Obtained

Ori: Orientation

Req. Max: Required maximum

Req: Required

RT: Room temperature

Sc: Specimen condition

Ss: Strip specimen

T: Transversal

U.T.S: Ultimate tensile strength

Y.S: Yield strength

| Heat N° | Sample N° | Zone | Lot N°  | Specimen condition |    |      |     | Specimen dimensions | Test temp | U.T.S. |      |
|---------|-----------|------|---------|--------------------|----|------|-----|---------------------|-----------|--------|------|
|         |           |      |         | Ls                 | Sc | Type | Ori |                     |           | Size   | Req. |
|         |           |      |         |                    |    |      |     | Min: 77 600         |           |        |      |
|         |           |      |         |                    |    |      |     | Max: 110 200        |           |        |      |
|         |           |      |         |                    |    |      |     |                     |           | F      | psi  |
| 2161576 | 220920    | E1   | 2161576 | W                  | AM | Ss   | T   | 1.500               | RT        | 80 628 |      |
| 2262234 | 220722    | E1   | 2262234 | W                  | AM | Ss   | T   | 1.500               | RT        | 88 108 |      |
| 2262235 | 220723    | E1   | 2262235 | W                  | AM | Ss   | T   | 1.500               | RT        | 91 251 |      |

AM: As manufactured

Min: Minimum

Sc: Specimen condition

W: Weld

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant  
5020 N COUNTY RD 967  
BLYTHEVILLE, AR 72315  
(870) 776-5000 tel  
(870) 776-5008 fax

**MILL TEST CERTIFICATE**

Number:

**108817291.0.7**

Page:

**2 / 6**Date: **July 15, 2026**

|                                                                                                    |  |                      |                                |                                              |                                          |                                          |  |                                           |                      |                                    |
|----------------------------------------------------------------------------------------------------|--|----------------------|--------------------------------|----------------------------------------------|------------------------------------------|------------------------------------------|--|-------------------------------------------|----------------------|------------------------------------|
| Customer: <b>MRC Global   CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427</b> |  |                      |                                | Customer's Order Item: <b>39080737/SO/70</b> |                                          | Customer's Reference: <b>US1119929PO</b> |  | Manufacturer's Works Order N°: <b>N/A</b> |                      |                                    |
| Manufacturing Process: <b>HFW</b>                                                                  |  |                      | Product Type: <b>Line Pipe</b> |                                              |                                          |                                          |  |                                           | Surface: <b>Bare</b> |                                    |
| Standard or Specification: <b>API Spec 5L 46th Edition 04/2018</b>                                 |  |                      |                                |                                              | Steel Grade: <b>X65M PSL 2</b>           |                                          |  | Ends: <b>Plain End Bevelled</b>           |                      |                                    |
| Dimensions: <b>16.000 x 0.500 in</b>                                                               |  | Schedule: <b>N/A</b> | Length: <b>35'MIN 45'MAX</b>   |                                              | Quantity: <b>12 PCS</b><br><b>520 FT</b> |                                          |  | 43163 LB                                  |                      | Nominal Weight: <b>82.85 LB/FT</b> |

**TENSILE TEST**

|                           |  |  |                      |  |  |                                  |  |  |
|---------------------------|--|--|----------------------|--|--|----------------------------------|--|--|
| E1 / E2: Ends of Sampling |  |  | Ori: Orientation     |  |  | Ss: Strip specimen               |  |  |
| Ls: Location of sample    |  |  | Req: Required        |  |  | T: Transversal                   |  |  |
| Max: Maximum              |  |  | RT: Room temperature |  |  | U.T.S: Ultimate tensile strength |  |  |

**CHEMICAL COMPOSITION**

|         |           |         |      |     | Composition % |     |     |    |    |    |    |         |        |    |    |    |    |    |    |    |    |    |         |
|---------|-----------|---------|------|-----|---------------|-----|-----|----|----|----|----|---------|--------|----|----|----|----|----|----|----|----|----|---------|
|         |           |         |      |     | X 100         |     |     |    |    |    |    |         | X 1000 |    |    |    |    |    |    |    |    |    | X 10000 |
|         |           |         |      |     |               |     |     |    |    |    |    |         |        |    |    |    |    |    |    |    |    |    |         |
|         |           |         |      |     | C             | Mn  | Si  | Cu | Ni | Cr | Mo | C-E-Pcm | P      | S  | Al | Sn | Nb | V  | Ti | Ca | N  | B  |         |
| Heat N° | Sample N° | Lot N°  | Ls   | H   | Max           | 12  | 160 | 45 | 50 | 30 | 30 | 15      | 25     | 25 | 15 | -- | -- | -- | -- | -- | -- | 10 |         |
|         |           |         |      | Min | --            | --  | --  | -- | -- | -- | -- | --      | --     | -- | -- | -- | -- | -- | -- | -- | -- | -- |         |
|         |           |         |      | P   | Max           | 12  | 160 | 45 | 50 | 30 | 30 | 15      | 25     | 25 | 15 | -- | -- | -- | -- | -- | -- | 10 |         |
|         |           |         |      | Min | --            | --  | --  | -- | -- | -- | -- | --      | --     | -- | -- | -- | -- | -- | -- | -- | -- | -- |         |
| 2161576 | 4187078   | 2161576 | B.M. | H   | 4             | 135 | 18  | 15 | 4  | 6  | 1  | 13      | 12     | -- | 20 | 10 | 47 | 47 | 2  | 1  | 8  | -- |         |
| 2262234 | 4187105   | 2262234 | B.M. | H   | 4             | 136 | 19  | 13 | 4  | 6  | 1  | 13      | 12     | -- | 30 | 10 | 44 | 49 | 3  | 1  | 8  | -- |         |
| 2262235 | 4187117   | 2262235 | B.M. | H   | 4             | 132 | 19  | 14 | 4  | 6  | 1  | 12      | 11     | 1  | 30 | 10 | 43 | 47 | 2  | 1  | 7  | -- |         |
| 2161576 | 4189275   | 2161576 | B.M. | P   | 4             | 140 | 22  | 11 | 3  | 5  | 1  | 14      | 10     | 2  | 35 | -- | 42 | 55 | 3  | 3  | -- | 10 |         |
| 2161576 | 4189295   | 2161576 | B.M. | P   | 4             | 133 | 20  | 14 | 4  | 6  | 1  | 14      | 11     | 2  | 30 | 10 | 43 | 52 | 2  | 3  | 4  | 10 |         |
| 2262234 | 4187689   | 2262234 | B.M. | P   | 3             | 134 | 21  | 13 | 4  | 6  | 1  | 13      | 13     | 1  | 40 | 10 | 40 | 54 | 3  | 2  | -- | 10 |         |
| 2262234 | 4187709   | 2262234 | B.M. | P   | 3             | 133 | 21  | 13 | 4  | 6  | 1  | 13      | 11     | 2  | 41 | 10 | 41 | 53 | 3  | 2  | -- | 10 |         |
| 2262235 | 4188966   | 2262235 | B.M. | P   | 4             | 135 | 21  | 13 | 4  | 5  | 1  | 14      | 11     | 2  | 38 | 10 | 40 | 53 | 3  | 5  | -- | 10 |         |
| 2262235 | 4188986   | 2262235 | B.M. | P   | 5             | 137 | 21  | 13 | 4  | 6  | 1  | 14      | 11     | 2  | 39 | 10 | 41 | 54 | 3  | 4  | -- | 10 |         |

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant  
5020 N COUNTY RD 967  
BLYTHEVILLE, AR 72315  
(870) 776-5000 tel  
(870) 776-5008 fax

**MILL TEST CERTIFICATE**

Number:

**108817291.0.7**

Page:

**3 / 6**Date: **July 15, 2026**

|                                                                                                    |  |                      |                                              |                              |                                          |                                          |                                           |                                                       |  |
|----------------------------------------------------------------------------------------------------|--|----------------------|----------------------------------------------|------------------------------|------------------------------------------|------------------------------------------|-------------------------------------------|-------------------------------------------------------|--|
| Customer: <b>MRC Global   CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427</b> |  |                      | Customer's Order Item: <b>39080737/SO/70</b> |                              | Customer's Reference: <b>US1119929PO</b> |                                          | Manufacturer's Works Order N°: <b>N/A</b> |                                                       |  |
| Manufacturing Process: <b>HFW</b>                                                                  |  |                      | Product Type: <b>Line Pipe</b>               |                              |                                          |                                          |                                           | Surface: <b>Bare</b>                                  |  |
| Standard or Specification: <b>API Spec 5L 46th Edition 04/2018</b>                                 |  |                      |                                              |                              | Steel Grade: <b>X65M PSL 2</b>           |                                          |                                           | Ends: <b>Plain End Bevelled</b>                       |  |
| Dimensions: <b>16.000 x 0.500 in</b>                                                               |  | Schedule: <b>N/A</b> |                                              | Length: <b>35'MIN 45'MAX</b> |                                          | Quantity: <b>12 PCS</b><br><b>520 FT</b> |                                           | Nominal Weight: <b>43163 LB</b><br><b>82.85 LB/FT</b> |  |

**CHEMICAL COMPOSITION**

|                 |                        |              |            |
|-----------------|------------------------|--------------|------------|
| B.M: Base metal | H: Heat                | Max: Maximum | P: Product |
| CE-Pcm: CE-Pcm  | Ls: Location of sample | Min: Minimum |            |

**THROUGH WALL HARDNESS**

| Required values |           |      | Individuals |           |                    | Average |         |         | Hardness type:HRBW |  |  |
|-----------------|-----------|------|-------------|-----------|--------------------|---------|---------|---------|--------------------|--|--|
|                 |           |      | Min: -      | Max: 94.0 | Var: --            | Min: -- | Max: -- | Var: -- |                    |  |  |
| Heat N°         | Sample N° | Zone | Lot N°      | Pipe N°   | Specimen condition |         | Quad.   | Scale   | Avg.               |  |  |
|                 |           |      |             |           | Ls                 | Sc      |         |         |                    |  |  |
| 2161576         | 220920    | -    | 2161576     | -         | B                  | AM      | -       | HRBW    | 91.1               |  |  |
| 2262234         | 220722    | -    | 2262234     | -         | B                  | AM      | -       | HRBW    | 90.6               |  |  |
| 2262235         | 220723    | -    | 2262235     | -         | B                  | AM      | -       | HRBW    | 90.6               |  |  |

|                     |                        |                        |
|---------------------|------------------------|------------------------|
| AM: As manufactured | Ls: Location of sample | Quad: Quadrant         |
| Avg: Average        | Max: Maximum           | Sc: Specimen condition |
| B: Body             | Min: Minimum           | Var: Variation         |

**IMPACT TEST**

| Type: Charpy V |           |         | Orientation: T |    |          |      | Unit: ft.lb     |     |                 |      | Shear area %   |     |                |      |
|----------------|-----------|---------|----------------|----|----------|------|-----------------|-----|-----------------|------|----------------|-----|----------------|------|
| Position:      |           |         | Temp: 32       |    | Unit: F  |      | Ind.Min.Reg: 11 |     | Req.Min.Avg: 15 |      | Ind.Min.Reg: - |     | Req.Min.Avg: - |      |
| Heat N°        | Sample N° | Lot N°  | Ls             | Sc | T.T<br>F | Size | Results         |     |                 |      | Results        |     |                |      |
|                |           |         |                |    |          | -    | 1               | 2   | 3               | Avg. | 1              | 2   | 3              | Avg. |
| 2161576        | 220920    | 2161576 | B              | AM | 32       | 3/4  | 98              | 213 | 170             | 160  | 80             | 100 | 100            | 93   |

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant  
5020 N COUNTY RD 967  
BLYTHEVILLE, AR 72315  
(870) 776-5000 tel  
(870) 776-5008 fax

**MILL TEST CERTIFICATE**

Number:

**108817291.0.7**

Page:

**4 / 6**Date: **July 15, 2026**

|                                                                                                    |  |                      |                                              |  |                                                             |  |                                           |                                    |
|----------------------------------------------------------------------------------------------------|--|----------------------|----------------------------------------------|--|-------------------------------------------------------------|--|-------------------------------------------|------------------------------------|
| Customer: <b>MRC Global   CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427</b> |  |                      | Customer's Order Item: <b>39080737/SO/70</b> |  | Customer's Reference: <b>US1119929PO</b>                    |  | Manufacturer's Works Order N°: <b>N/A</b> |                                    |
| Manufacturing Process: <b>HFW</b>                                                                  |  |                      | Product Type: <b>Line Pipe</b>               |  |                                                             |  |                                           | Surface: <b>Bare</b>               |
| Standard or Specification: <b>API Spec 5L 46th Edition 04/2018</b>                                 |  |                      |                                              |  | Steel Grade: <b>X65M PSL 2</b>                              |  |                                           | Ends: <b>Plain End Bevelled</b>    |
| Dimensions: <b>16.000 x 0.500 in</b>                                                               |  | Schedule: <b>N/A</b> | Length: <b>35'MIN 45'MAX</b>                 |  | Quantity: <b>12 PCS</b><br><b>520 FT</b><br><b>43163 LB</b> |  |                                           | Nominal Weight: <b>82.85 LB/FT</b> |

**IMPACT TEST**

| Type: Charpy V |           |         | Orientation: T |    |         |      | Unit: ft.lb     |     |                 |      | Shear area %   |     |                |      |
|----------------|-----------|---------|----------------|----|---------|------|-----------------|-----|-----------------|------|----------------|-----|----------------|------|
| Position:      |           |         | Temp: 32       |    | Unit: F |      | Ind.Min.Reg: 11 |     | Req.Min.Avg: 15 |      | Ind.Min.Reg: - |     | Req.Min.Avg: - |      |
| Heat N°        | Sample N° | Lot N°  | Ls             | Sc | T.T     | Size | Results         |     |                 |      | Results        |     |                |      |
|                |           |         |                |    | F       | -    | 1               | 2   | 3               | Avg. | 1              | 2   | 3              | Avg. |
| 2262234        | 220722    | 2262234 | B              | AM | 32      | 3/4  | 112             | 100 | 119             | 110  | 85             | 85  | 85             | 85   |
| 2262235        | 220723    | 2262235 | B              | AM | 32      | 3/4  | 119             | 209 | 198             | 175  | 80             | 100 | 100            | 93   |

AM: As manufactured

Ind. Min. Req: Individual Minimum Required

Sc: Specimen condition

Avg: Average

Ls: Location of sample

T.T: Test temperature

B: Body

Req. Min. Avg: Required minimum average

Temp: Temperature

**FLATTENING TEST**

|           |         |           |        |           |         |           |        |           |         |           |        |
|-----------|---------|-----------|--------|-----------|---------|-----------|--------|-----------|---------|-----------|--------|
| Standard: |         |           |        | Standard: |         |           |        | Standard: |         |           |        |
| Heat N°   | Lot N°  | Sample N° | Result | Heat N°   | Lot N°  | Sample N° | Result | Heat N°   | Lot N°  | Sample N° | Result |
| 2161576   | 2161576 | 220920    | Good   | 2262234   | 2262234 | 220722    | Good   | 2262235   | 2262235 | 220723    | Good   |

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant  
5020 N COUNTY RD 967  
BLYTHEVILLE, AR 72315  
(870) 776-5000 tel  
(870) 776-5008 fax

**MILL TEST CERTIFICATE**

Number:

**108817291.0.7**

Page:

**5 / 6**Date: **July 15, 2026**

|                                                                                                    |                      |                                              |                                                          |                                          |                                           |
|----------------------------------------------------------------------------------------------------|----------------------|----------------------------------------------|----------------------------------------------------------|------------------------------------------|-------------------------------------------|
| Customer: <b>MRC Global   CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427</b> |                      | Customer's Order Item: <b>39080737/SO/70</b> |                                                          | Customer's Reference: <b>US1119929PO</b> | Manufacturer's Works Order N°: <b>N/A</b> |
| Manufacturing Process: <b>HFW</b>                                                                  |                      | Product Type: <b>Line Pipe</b>               |                                                          |                                          | Surface: <b>Bare</b>                      |
| Standard or Specification: <b>API Spec 5L 46th Edition 04/2018</b>                                 |                      |                                              | Steel Grade: <b>X65M PSL 2</b>                           |                                          | Ends: <b>Plain End Bevelled</b>           |
| Dimensions: <b>16.000 x 0.500 in</b>                                                               | Schedule: <b>N/A</b> | Length: <b>35"MIN 45"MAX</b>                 | Quantity: <b>12 PCS</b><br><b>520 FT</b> <b>43163 LB</b> |                                          | Nominal Weight: <b>82.85 LB/FT</b>        |

**HYDROSTATIC TEST**

| Pressure |       | Time    | Results      |
|----------|-------|---------|--------------|
| Unit     | Value | Seconds |              |
| psi      | 2,970 | 5       | Satisfactory |

**SUPPLEMENTARY INFORMATION**

| Supplementary Information                                                                                                                                                                                                                                                                                                               | Supplementary Information                                                                                                                   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| This material has been manufactured, sampled, tested and inspected in accordance with this specification and has been found to meet the requirements called for by the above order.<br>This product is silicon and/or aluminum fully killed.<br>NDT OK; Longitudinal UT and Transverse EMI with ID/OD N-10 Notches (1.0" L and .039" W) | verified by 1/8" TDH<br>BODY TENSILE SOURCED 180° FROM WELD LINE; CVN SAMPLES SOURCED 90° FROM WELD LINE; CVN SAMPLES TESTED BY 8mm STRIKER |
| Heat Treatment                                                                                                                                                                                                                                                                                                                          | Heat Treatment                                                                                                                              |
| The minimum weld seam heat treatment temperature is 1650F.                                                                                                                                                                                                                                                                              |                                                                                                                                             |
| Steel Vendor Name and Manufactured                                                                                                                                                                                                                                                                                                      | Steel Vendor Name and Manufactured                                                                                                          |
| 2161576,NUCOR STEEL HICKMAN,ARMOREL,AR,Melted and Manufactured in USA<br>2262234,NUCOR STEEL HICKMAN,ARMOREL,AR,Melted and Manufactured in USA                                                                                                                                                                                          | 2262235,NUCOR STEEL HICKMAN,ARMOREL,AR,Melted and Manufactured in USA                                                                       |

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant  
5020 N COUNTY RD 967  
BLYTHEVILLE, AR 72315  
(870) 776-5000 tel  
(870) 776-5008 fax

**MILL TEST CERTIFICATE**

Number:

**108817291.0.7**

Page:

**6 / 6**Date: **July 15, 2026**


|                                                                                                    |                      |                                              |                                                          |                                          |                                           |
|----------------------------------------------------------------------------------------------------|----------------------|----------------------------------------------|----------------------------------------------------------|------------------------------------------|-------------------------------------------|
| Customer: <b>MRC Global   CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427</b> |                      | Customer's Order Item: <b>39080737/SO/70</b> |                                                          | Customer's Reference: <b>US1119929PO</b> | Manufacturer's Works Order N°: <b>N/A</b> |
| Manufacturing Process: <b>HFW</b>                                                                  |                      | Product Type: <b>Line Pipe</b>               |                                                          |                                          | Surface: <b>Bare</b>                      |
| Standard or Specification: <b>API Spec 5L 46th Edition 04/2018</b>                                 |                      |                                              | Steel Grade: <b>X65M PSL 2</b>                           |                                          | Ends: <b>Plain End Bevelled</b>           |
| Dimensions: <b>16.000 x 0.500 in</b>                                                               | Schedule: <b>N/A</b> | Length: <b>35"MIN 45"MAX</b>                 | Quantity: <b>12 PCS</b><br><b>520 FT</b> <b>43163 LB</b> |                                          | Nominal Weight: <b>82.85 LB/FT</b>        |

**SUMMARY REPORT**

| Heat N° | Quantity | Length  | Weight     | Heat N° | Quantity | Length | Weight    | Heat N° | Quantity | Length  | Weight    |
|---------|----------|---------|------------|---------|----------|--------|-----------|---------|----------|---------|-----------|
|         | (Pieces) | FT      | LB         |         | (Pieces) | FT     | LB        |         | (Pieces) | FT      | LB        |
| 2161576 | 7        | 308.766 | 25,584.682 | 2262234 | 2        | 78.789 | 6,528.541 | 2262235 | 3        | 133.356 | 11,050.21 |

The product certified herein has been manufactured, sampled, tested and inspected in accordance with the stated specifications and has been found to meet the requirements.

We, Tenaris, hereby acknowledge the restrictions as per article 3g(1) of Council Regulation (EU) No 833/2014, as amended, and confirm that our company is compliant with this legislation. Consequently, we, Tenaris, hereby represent and warrant that the steel products covered by this certificate, as listed in Annex XVII of Council Regulation (EU) No 833/2014 of 31 July 2014 and its subsequent amendments, do not originate from Russia. Furthermore, we confirm that the steel products covered by this certificate, as listed in Annex XVII of Council Regulation (EU) No 833/2014 of 31 July 2014 and its subsequent amendments, as required under article 3g(1)(d) (as amended) and related guidelines do not incorporate any steel or iron products as listed in the same Annex XVII originating in Russia when having been processed in a third country. We also acknowledge the equivalent restrictions as per Clause 17e of Norway's Russia Regulations of 15 August 2014 No. 1076 (FOR-2014-08-15-1076) and Regulations 46IA and 46IB of the UK Russia (Sanctions) (EU Exit) Regulations 2019, and confirm that our company is compliant with these laws as well.

| CUSTOMER / THIRD PARTY                                                                      |  | TENARIS QUALITY DEPARTMENT SIGNATURE                                                                                                                      |                                                                                                                                                    |
|---------------------------------------------------------------------------------------------|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| INSPECTION COMPANY<br>COMPAÑÍA DE INSPECCIÓN<br><br>Company Name: N/A<br>Employee Name: N/A |  | <br>QUALITY CERTIFICATION DEPT.<br><br>Francisco G. Pinilla Portales | <br>CHIEF OF QUALITY CERTIFICATION DEPT.<br><br>Kyle McCarthy |

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.