

Our Order 2492378-8-1 Your Order 74769-03
Heat 2253578
Desc Pipe ERW API 5L X65, 16.000 x .500 - 16" S-XS SRL

Packing List 407195-4 (1/14/2026)

Image 548209



MILL TEST CERTIFICATE

Number: **9901416.0.9**
Page: **1 / 7**
Date: **July 31, 2025**

MAVERICK TUBE CORPORATION
Hickman Plant
5920 N. GARFIELD RD. 16.7
MILYTHEVILLE, AR 72310
(870) 775-5023 Ext
(870) 775-5028 Fax

Customer: Edgen		Customer's Order Item: 990141650/90		Customer's Reference: 315867		Manufacturer's Works Order N°: N/A	
Manufacturing Process: HPFW		Product Type: Line Pipe		Surface: Bare		Ends: Plain End Bevelled	
Standard or Specification: API Spec. 5L 46th Ed. 04/2018		Steel Grade: X65M PSL 2		Quantity: 130 PCS		Nominal Weight: 82.85 LB/FT	
Dimensions: 16.000 x 0.500 In		Schedule: N/A		Length: Double Random		455208 LB	
				455208 LB			

TENSILE TEST

Heat N°	Sample N°	Zone	Lot N°	Specimen condition				Specimen dimensions		Test temp	Y.S.		U.T.S.		Y.S./U.T.S		Elongation		
				Is	Sc	Type	Ori	Size	Req.		Min. 65 BUL Max. 87 000	77 600 Max. 101 200	Req. Max. 0.93	Lo	Min.	Obt.			
In	F	psi	psi	In	%	%													
2253573	206229	E1	2253573	B	AM	Ss	T	1.500	RT	70638		84903	0.83	2.0	23.0	36.2			
2253574	206215	E1	2253574	B	AM	Ss	T	1.500	RT	75951		87133	0.87	2.0	21.0	36.3			
2253575	206164	E1	2253575	B	AM	Ss	T	1.500	RT	74240		88351	0.84	2.0	21.0	35.9			
2253578	206214	E1	2253578	B	AM	Ss	T	1.500	RT	75178		87120	0.86	2.0	23.0	37.2			
2253580	206213	E1	2253580	B	AM	Ss	T	1.500	RT	73667		85230	0.86	2.0	23.0	35.9			

AM: As manufactured	Max: Maximum	Req: Required	U.T.S: Ultimate tensile strength
B: Body	Min: Minimum	RT: Room temperature	Y.S: Yield strength
E1 / E2: Ends of Sampling	Obt: Obtained	Sc: Specimen condition	
Lo: Initial length	Ori: Orientation	Ss: Strip specimen	
Is: Location of sample	Req. Max: Required maximum	T: Transversal	

Heat N°	Sample N°	Zone	Lot N°	Specimen condition				Specimen dimensions		Test temp	U.T.S.	
				Is	Sc	Type	Ori	Size	Req.		Min: 77 600	
												Max: 110 200
								h	F	psi		
2253573	206229	E1	2253573	W	AM	Ss	T	1.500	RT	84 930		
2253574	206215	E1	2253574	W	AM	Ss	T	1.500	RT	87 906		
2253575	206164	E1	2253575	W	AM	Ss	T	1.500	RT	85 489		

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

APPROVED

Kevin Jackson, 2/6/2026, 3:19:35 PM

Our Order 2492378-8-1 Your Order 74769-03
Heat 2253578
Desc Pipe ERW API 5L X65,16.000 x .500 - 16" S-XS SRL

Packing List 407195-4 (1/14/2026) Image 548209



MAVERICK TUBE CORPORATION
Houston, Texas
5020 N. GULFVIEW RD. #100
SHELBYVILLE, KY 40381
(502) 775-5003 tel
(502) 775-5038 fax



MILL TEST CERTIFICATE

Number: 9901416.0.9
Page: 2/7
Date: July 31, 2025

Customer: Edgen		Customer's Order Item: 9901416/SO/90		Customer's Reference: 315867		Manufacturer's Works Order N°: N/A	
Manufacturing Process: HPW		Product Type: Line Pipe		Steel Grade: X65M PSL 2		Surface: Bare	
Standard or Specification: API Spec. 5L 46th Ed. 04/2018		Dimensions: 16.000 x 0.500 in		Schedule: N/A		Length: Double Random	
				Quantity: 130 PCS 5494 FT		455208 LB	
						Ends: Plain End Bevelled	
						Nominal Weight: 82.85 LB/FT	

TENSILE TEST

Heat N°	Sample N°	Zone	Lot N°	Specimen condition				Specimen dimensions		Test temp	U.T.S.	
				Ls	Sc	Type	Ori	Size			Req.	Min: 77 600 Max: 110 200
								in	F	psi		
2253578	206214	E1	2253578	W	AM	Ss	T	1.200		RT	85864	
2253580	206213	E1	2253580	W	AM	Ss	T	1.300		RT	88989	

AM: As manufactured	Min: Minimum	Sc: Specimen condition	W: Weld
E1 / E2: Ends of Sampling	Ori: Orientation	Ss: Strip specimen	
Ls: Location of sample	Req: Required	T: Transversal	
Max: Maximum	RT: Room temperature	U.T.S: Ultimate tensile strength	

CHEMICAL COMPOSITION

Composition %																
x 100																
	C	Mn	P	S	Si	Cu	Ni	Cr	Mo	Al	Sn	Nb	V	Ti	Ca	B
H	Max	0.12	1.6	0.025	0.015	0.45	0.5	0.3	0.3	0.15	—	—	—	—	—	0.001
Min	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
P	Max	0.12	1.6	0.025	0.015	0.45	0.5	0.3	0.3	0.15	—	—	—	—	—	0.001
Min	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Heat N°	Sample N°	Lot N°	Ls	P	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
2253573	4151903	2253573	B.A1	H	0.04	1.39	0.012	0.001	0.2	0.1	0.03	0.04	0.01	0.04	0	0.007

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade mark green colored "Tenaris" is stamped. In case the owner of the original certificate wants to release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

Our Order 2492378-8-1 Your Order 74769-03
Heat 2253578
Desc Pipe ERW API 5L X65,16.000 x .500 - 16" S-XS SRL

Packing List 407195-4 (1/14/2026) Image 548209



MAVERICK TUBE CORPORATION
Hickman Plant
15201 N CLARK RD 067
REYNOLDSVILLE, WV 25375
(878) 776-5030 tel
(878) 776-5038 fax

MILL TEST CERTIFICATE

Number: 9901416.0.9
Page: 3 / 7
Date: July 31, 2025

Customer: Edgen

Customer's Order Item: 9901416/SO/90

Customer's Reference: 315867

Manufacturer's Works Order #: N/A

Manufacturing Process: HFW

Product Type: Line Pipe

Surface: Bare

Standard or Specification: API Spec. SL 46th Ed. 04/2018

Steel Grade: X65M PSL 2

Ends: Plain End Bevelled

Dimensions: 16.000 x 0.500 in

Schedule: N/A

Length: Double Random

Quantity: 130 PCS
5494 FT
455208 LB

Nominal Weight: 82.85 LB/FT

CHEMICAL COMPOSITION

					Composition %																	
					X %																	
					C	Mn	P	S	Si	Cu	Ni	Cr	Mo	Al	Sn	Nb	V	Ti	Ca	B	N	Fe-Pb
					H	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
Heat N°	Sample N°	Lot N°	Ls	P	0.12	1.6	0.025	0.015	0.45	0.5	0.3	0.3	0.15	—	—	—	—	—	—	—	—	
					—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Heat N°	Sample N°	Lot N°	Ls	P	0.12	1.6	0.025	0.015	0.45	0.5	0.3	0.3	0.15	—	—	—	—	—	0.001	—	0.25	
2253574	4151921	2253574	B.A.I.	H	0.04	1.38	0.012	0.001	0.2	0.1	0.03	0.04	0.01	0.03	0	0.045	0.035	0.003	0.001	0	0.007	0.129
2253575	4151928	2253575	B.A.I.	H	0.04	1.34	0.012	0.001	0.19	0.11	0.04	0.04	0.01	0.03	0.01	0.043	0.062	0.007	0.007	0	0.007	0.178
2253578	4153410	2253578	B.A.I.	H	0.05	1.35	0.012	0.001	0.21	0.11	0.04	0.05	0.01	0.03	0.01	0.045	0.05	0.003	0.002	0	0.006	0.139
2253580	4151932	2253580	B.A.I.	H	0.06	1.32	0.012	0.001	0.19	0.13	0.06	0.04	0.01	0.03	0.01	0.043	0.055	0.003	0.001	0	0.007	0.147
2253573	4154151	2253573	B.A.I.	P	0.037	1.29	0.011	0.002	0.24	0.09	0.04	0.01	0.01	0.046	0	0.043	0.051	0.004	0.003	0.001	0.002	0.132
2253573	4154171	2253573	B.A.I.	P	0.046	1.38	0.011	0.002	0.14	0.1	0.04	0.04	0.01	0.044	0	0.043	0.051	0.004	0.003	0.001	0.001	0.131
2253574	4154128	2253574	B.A.I.	P	0.036	1.37	0.011	0.002	0.23	0.09	0.03	0.01	0.01	0.035	0	0.043	0.047	0.003	0.004	0	0.001	0.125
2253574	4154148	2253574	B.A.I.	P	0.037	1.39	0.012	0.001	0.23	0.09	0.03	0.01	0.01	0.038	0	0.043	0.048	0.004	0.004	0.001	0.002	0.132
2253575	4153555	2253575	B.A.I.	P	0.044	1.36	0.013	0.002	0.22	0.09	0.03	0.04	0.01	0.034	0	0.047	0.049	0.003	0.003	0.001	0.006	0.157
2253575	4153575	2253575	B.A.I.	P	0.043	1.36	0.012	0.002	0.22	0.09	0.04	0.04	0.01	0.034	0	0.047	0.049	0.003	0.004	0.001	0.007	0.146
2253578	4153499	2253578	B.A.I.	P	0.046	1.33	0.011	0.001	0.24	0.1	0.04	0.05	0.01	0.031	0	0.042	0.042	0.004	0.002	0.001	0.008	0.139
2253578	4153519	2253578	B.A.I.	P	0.045	1.35	0.01	0.001	0.25	0.1	0.04	0.05	0.01	0.031	0	0.042	0.042	0.004	0.003	0.001	0.003	0.139
2253580	4153703	2253580	B.A.I.	P	0.055	1.32	0.01	0.002	0.22	0.1	0.05	0.05	0.01	0.038	0	0.047	0.047	0.004	0.003	0	0.009	0.142
2253580	4153723	2253580	B.A.I.	P	0.06	1.34	0.01	0.001	0.23	0.1	0.05	0.04	0.01	0.04	0.01	0.042	0.048	0.004	0.004	0.001	0.005	0.153

B.M: Base metal
CE-Pcm: CE-Pcm

H: Heat
Ls: Location of sample

Max: Maximum
Min: Minimum

P: Product

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any univoid or not allowed use. Any alteration and/or falsification will be subjected to the law.

Heat 2253578

Desc Pipe ERW API 5L X65, 16.000 x .500 - 16" S-XS SRL



MILL TEST CERTIFICATE

Number:

9901416.0.9

Page:

4/7

Date: July 31, 2025

MAVERICK TUBE CORPORATION
Hickman Plant
5923 N. GARDEN RD. 567
BLYTHEVILLE, AR 72315
(870) 775-5635 tel
(870) 775-5635 fax

Customer: Edgen		Customer's Order Item: 9901416/SO/90		Customer's Reference: 315867		Manufacturer's Works Order N°: N/A	
Manufacturing Process: HPFW		Product Type: Line Pipe		Surface: Rare		Ends: Plain End Bevelled	
Standard or Specification: API Spec. 5L 46th Ed. 04/2018				Steel Grade: X65M PSL 2		Nominal Weight: 82.85 LB/FT	
Dimensions: 16.000 x 0.500 In		Schedule: N/A		Length: Double Random		Quantity: 130 PCS 5494 FT 455208 LB	

THROUGH WALL HARDNESS

Required values			Individuals			Average			Hardness type: HRBW		
Heat N°	Sample N°	Zone	Min. =	Max. =	Var. =	Min. =	Max. =	Var. =			
			Pipe N°			Specimen condition			Scale		
						Ls			Sc		
2253573	206229	+	2253573	+		B			AM		91.0
2253574	206215	+	2253574	+		B			AM		91.3
2253575	206164	+	2253575	+		B			AM		92.4
2253578	206214	+	2253578	+		B			AM		89.6
2253580	206213	+	2253580	+		B			AM		90.5

AM: As manufactured

Ls: Location of sample

Quad: Quadrant

Avg: Average

Max: Maximum

Sc: Specimen condition

B: Body

Min: Minimum

Var: Variation

IMPACT TEST

Type: Charpy V			Orientation: T			Unit: ft.lb			Shear area %		
Position:			Temp: 32			Unit: F			Ind. Min. Req: 11		
									Reg. Min. Avg: 15		
Heat N°	Sample N°	Lot N°	Ls	Sc	T, T	Size	Results		Ind. Min. Req: -	Reg. Min. Avg: -	
									Results		
2253573	206229	2253573	B	AM	32	3/4	199	202	187	196	90
2253574	206215	2253574	B	AM	32	3/4	222	225	196	214	90
2253575	206164	2253575	B	AM	32	3/4	142	224	219	195	100
2253578	206214	2253578	B	AM	32	3/4	201	204	192	199	100
2253580	206213	2253580	B	AM	32	3/4	245	221	217	228	100

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade mark green colored, "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or fabrication will be subjected to the law.

Our Order 2492378-8-1 Your Order 74769-03
Heat 2253578
Desc Pipe ERW API 5L X65,16.000 x .500 - 16" S-XS SRL

Packing List 407195-4 (1/14/2026) Image 548209



MILL TEST CERTIFICATE

Number: 9901416.0.9
Page: 5 / 7
Date: July 31, 2025

MAVERICK TUBE CORPORATION
Pickman Place
5520 N COUNTY RD 917
GUYTONVILLE, AR 72349
(870) 776-5090 tel
(870) 776-5096 fax

Customer: Edgen		Customer's Order Item: 9901416/SO/90		Customer's Reference: 313867	Manufacturer's Works Order N°: N/A
Manufacturing Process: HPW		Product Type: Line Pipe		Surface: Bare	
Standard or Specification: API Spec. 5L 46th Ed. 04/2018			Steel Grade: X65M PSL 2		Ends: Plain End Bevelled
Dimensions: 16.000 x 0.500 in	Schedule: N/A	Length: Double Random	Quantity: 130 PCS	455208 LB	Nominal Weight: 82.85 LB/FT

IMPACT TEST

AM: As manufactured	Ind, Min, Req: Individual Minimum Required	Sc: Specimen condition
Avg: Average	Is: Location of sample	T.T: Test temperature
B: Body	Req, Min, Avg: Required minimum average	Temp: Temperature

FLATTENING TEST

Standard:				Standard:				Standard:			
Heat N°	Lot N°	Sample N°	Result	Heat N°	Lot N°	Sample N°	Result	Heat N°	Lot N°	Sample N°	Result
2253573	2253573	206229	Good	2253575	2253575	206164	Good	2253580	2253580	206213	Good
2253574	2253574	206215	Good	2253578	2253578	206214	Good				

HYDROSTATIC TEST

Pressure		Time		Results
Unit	Value	Seconds		
psi	2970	5		Satisfactory

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

Our Order 2492378-8-1 Your Order 74769-03
Heat 2253578
Desc Pipe ERW API 5L X65,16.000 x .500 - 16" S-XS SRL

Packing List 407195-4 (1/14/2026) Image 548209



MAVERICK TUBE CORPORATION
Hickman Plant
3020 N. GOLIAD RD. #67
BRYAN, TEXAS 77803
(781) 776-5033 fax
(781) 776-5036 fax

MILL TEST CERTIFICATE

Number:
9901416.0.9

Page:
6/7

Date: July 31, 2025

Customer: Edgen

Customer's Order Item:
9901416/SO/90

Customer's Reference:
315867

Manufacturer's Works Order N°:
N/A

Manufacturing Process:
HFW

Product Type:
Line Pipe

Surface:
Bare

Standard or Specification:
API Spec. 5L 46th Ed. 04/2018

Steel Grade:
X65M PSL 2

Ends:
Plain End Bevelled

Dimensions:
16.000 x 0.500 in

Schedule:
N/A

Length:
Double Random

Quantity: 130 PCS
5494 FT

455208 LB

Nominal Weight:
82.85 LB/FT

SUPPLEMENTARY INFORMATION

Supplementary Information

This material has been manufactured, sampled, tested and inspected in accordance with this specification and has been found to meet the requirements called for by the above order.
This product is silicon and/or aluminium fully killed.

Heat Treatment

The minimum weld seam heat treatment temperature is 1650F.

Steel Vendor Name and Manufactured

2253573,NUCOR STEEL HICKMAN,ARMOREL,AR,Melnd and Manufactured in USA
2253574,NUCOR STEEL HICKMAN,ARMOREL,AR,Melnd and Manufactured in USA
2253575,NUCOR STEEL HICKMAN,ARMOREL,AR,Melnd and Manufactured in USA

Supplementary Information

NDT OK; Longitudinal UT with ID/OD N-10 Notches (2.0" L x .040" W) verified by 1/8" FDH
BODY TENSILE SOURCED 180" FROM WELD LINE, CVN SAMPLES SOURCED 90" FROM WELD LINE; CVN SAMPLES TESTED BY 8mm STRIKER

Steel Vendor Name and Manufactured

2253576,NUCOR STEEL HICKMAN,ARMOREL,AR,Melnd and Manufactured in USA
2253580,NUCOR STEEL HICKMAN,ARMOREL,AR,Melnd and Manufactured in USA

SUMMARY REPORT

Heat N°	Quantity	Heat N°	Quantity	Heat N°	Quantity	Heat N°	Quantity	Heat N°	Quantity
	(Pieces)		(Pieces)		(Pieces)		(Pieces)		(Pieces)
2253573	50	2253574	43	2253575	12	2253576	13	2253580	12

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

Our Order 2492378-8-1 Your Order 74769-03
Heat 2253578
Desc Pipe ERW API 5L X65,16.000 x .500 - 16" S-XS SRL

Packing List 407195-4 (1/14/2026)

Image 548209



MAVERICK TUBE CORPORATION
Houston, Texas
4020 N. GULF SHORE RD. #67
BAYTOWN, TEXAS 77521-1118
(281) 776-5500 Ext.
(877) 776-5505 Int.



MILL TEST CERTIFICATE

Number:

9901416.0.9

Page:

7/7

Date: July 31, 2025

Customer: Edgen		Customer's Order Item: 9901416/SU/90		Customer's Reference: 315867	Manufacturer's Works Order N°: N/A
Manufacturing Process: HPW		Product Type: Line Pipe			Surface: Bare
Standard or Specification: API Spec. 5L 46th Ed. 04/2018			Steel Grade: X65M PSL 2		Ends: Plain End Bevelled
Dimensions: 16.000 x 0.500 in	Schedule: N/A	Length: Double Random	Quantity: 130 PCS 5494 FT	455208 LB	
				Nominal Weight: 82.85 LB/FT	

The product certified herein has been manufactured, sampled, tested and inspected in accordance with the stated specifications and has been found to meet the requirements.

This certificate is not a declaration of origin nor may it be used as a declaration of origin.

We, Tenaris, hereby acknowledge the restrictions as per article 3g(1) of Council Regulation (EU) No 833/2014, as amended, and confirm that our company is compliant with this legislation.

Consequently, we, Tenaris, hereby represent and warrant that the steel products covered by this certificate, as listed in Annex XVIII of Council Regulation (EU) No 833/2014 of 31 July 2014 and its subsequent amendments, do not originate from Russia. Furthermore, we confirm that the steel products covered by this certificate, as listed in Annex XVII of Council Regulation (EU) No 833/2014 of 31 July 2014 and its subsequent amendments, as required under article 3g(1)(d) (as amended) and related guidelines do not incorporate any steel or iron products as listed in the same Annex XVII originating in Russia when having been processed in a third country.

We also acknowledge the equivalent restrictions as per Clause 17e of Norway's Russia Regulations of 15 August 2014 No. 1076 (JOR-2014-08-15-1076) and Regulations 46IA and 46IB of the UK Russia (Sanctions) (EU Exit) Regulations 2019, and confirm that our company is compliant with these laws as well.

CUSTOMER / THIRD PARTY		TENARIS QUALITY DEPARTMENT SIGNATURE	
INSPECTION COMPANY COMPANIA DE INSPECCION Company Name: N/A Employee Name: N/A		 QUALITY CERTIFICATION DEPT. Francisco G. Pinilla Portales	 CHIEF OF QUALITY CERTIFICATION DEPT. Kyle McCarthy

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or fabrication will be subjected to the law.