

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817290.0.7

Page:

1 / 6Date: **July 14, 2026**

Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427			Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO		Manufacturer's Works Order N°: N/A	
Manufacturing Process: HFW			Product Type: Line Pipe					Surface: Bare
Standard or Specification: API Spec 5L 46th Edition 04/2018					Steel Grade: X65M PSL 2		Ends: Plain End Bevelled	
Dimensions: 16.000 x 0.500 in		Schedule: N/A	Length: 35'MIN 45'MAX		Quantity: 12 PCS 503 FT 41716 LB		Nominal Weight: 82.85 LB/FT	

TENSILE TEST

Heat N°	Sample N°	Zone	Lot N°	Specimen condition				Specimen dimensions		Test temp	Y.S.	U.T.S.	Y.S./U.T.S.	Elongation		
				Ls	Sc	Type	Ori	Size	.5% EUL		Req.	Req. Max.	Lo	Min.	Obt.	
									Min: 65 300		Min: 77 600					
									Max: 87 000		Max: 110 200					
									F	psi	psi	0.93	in	%	%	
2161576	220920	E1	2161576	B	AM	Ss	T	1.500	RT	76 406	90 982	0.83	2.0	23.0	33.1	
2262233	220721	E1	2262233	B	AM	Ss	T	1.500	RT	71 262	87 852	0.81	2.0	23.0	35.5	
2262234	220722	E1	2262234	B	AM	Ss	T	1.500	RT	75 714	87 026	0.87	2.0	23.0	36.1	

AM: As manufactured

B: Body

E1 / E2: Ends of Sampling

Lo: Initial length

Ls: Location of sample

Max: Maximum

Min: Minimum

Obt: Obtained

Ori: Orientation

Req. Max: Required maximum

Req: Required

RT: Room temperature

Sc: Specimen condition

Ss: Strip specimen

T: Transversal

U.T.S: Ultimate tensile strength

Y.S: Yield strength

Heat N°	Sample N°	Zone	Lot N°	Specimen condition				Specimen dimensions		Test temp	U.T.S.	
				Ls	Sc	Type	Ori	Size	Min: 77 600 Max: 110 200			
											F	psi
2161576	220920	E1	2161576	W	AM	Ss	T	1.500	RT	80 628		
2262233	220721	E1	2262233	W	AM	Ss	T	1.500	RT	89 638		
2262234	220722	E1	2262234	W	AM	Ss	T	1.500	RT	88 108		

AM: As manufactured

Min: Minimum

Sc: Specimen condition

W: Weld

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817290.0.7

Page:

2 / 6Date: **July 14, 2026**

Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427			Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO		Manufacturer's Works Order N°: N/A		
Manufacturing Process: HFW		Product Type: Line Pipe						Surface: Bare	
Standard or Specification: API Spec 5L 46th Edition 04/2018				Steel Grade: X65M PSL 2			Ends: Plain End Bevelled		
Dimensions: 16.000 x 0.500 in		Schedule: N/A	Length: 35'MIN 45'MAX		Quantity: 12 PCS 503 FT		Nominal Weight: 41716 LB 82.85 LB/FT		

TENSILE TEST

E1 / E2: Ends of Sampling

Ori: Orientation

Ss: Strip specimen

Ls: Location of sample

Req: Required

T: Transversal

Max: Maximum

RT: Room temperature

U.T.S: Ultimate tensile strength

CHEMICAL COMPOSITION

					Composition %																		
					X 100									X 1000									X 10000
					C	Mn	Si	Cu	Ni	Cr	Mo	CE-Pcm	P	S	Al	Sn	Nb	V	Ti	Ca	N	B	
					H	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min
Heat N°	Sample N°	Lot N°	Ls	P	Max	12	160	45	50	30	30	15	25	25	15	--	--	--	--	--	--	--	10
				Min	Min	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
2161576	4187078	2161576	B.M.	H	4	135	18	15	4	6	1	13	12	--	20	10	47	47	2	1	8	--	--
2262233	4187114	2262233	B.M.	H	4	134	18	13	5	6	1	12	13	--	30	10	44	46	3	1	7	--	--
2262234	4187105	2262234	B.M.	H	4	136	19	13	4	6	1	13	12	--	30	10	44	49	3	1	8	--	--
2161576	4189275	2161576	B.M.	P	4	140	22	11	3	5	1	14	10	2	35	--	42	55	3	3	--	10	--
2161576	4189295	2161576	B.M.	P	4	133	20	14	4	6	1	14	11	2	30	10	43	52	2	3	4	10	--
2262233	4187645	2262233	B.M.	P	4	132	20	13	4	6	1	13	1	1	33	10	39	50	3	2	--	10	--
2262233	4187665	2262233	B.M.	P	4	133	21	14	4	6	1	13	11	2	39	10	42	53	3	3	--	10	--
2262234	4187689	2262234	B.M.	P	3	134	21	13	4	6	1	13	13	1	40	10	40	54	3	2	--	10	--
2262234	4187709	2262234	B.M.	P	3	133	21	13	4	6	1	13	11	2	41	10	41	53	3	2	--	10	--

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817290.07

Page:

3 / 6Date: **July 14, 2026**

Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427			Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO		Manufacturer's Works Order N°: N/A		
Manufacturing Process: HFW			Product Type: Line Pipe					Surface: Bare	
Standard or Specification: API Spec 5L 46th Edition 04/2018					Steel Grade: X65M PSL 2			Ends: Plain End Bevelled	
Dimensions: 16.000 x 0.500 in		Schedule: N/A	Length: 35'MIN 45'MAX		Quantity: 12 PCS 503 FT			Nominal Weight: 82.85 LB/FT	
					41716 LB				

CHEMICAL COMPOSITION

B.M: Base metal	H: Heat	Max: Maximum	P: Product
CE-Pcm: CE-Pcm	Ls: Location of sample	Min: Minimum	

THROUGH WALL HARDNESS

Required values			Individuals			Average			Hardness type:HRBW			
			Min: -	Max: 94.0	Var: --	Min: --	Max: --	Var: --				
Heat N°	Sample N°	Zone	Lot N°	Pipe N°	Specimen condition		Quad.	Scale	Avg.			
					Ls	Sc						
2161576	220920	-	2161576	-	B	AM	-	HRBW	91.1			
2262233	220721	-	2262233	-	B	AM	-	HRBW	90.1			
2262234	220722	-	2262234	-	B	AM	-	HRBW	90.6			

AM: As manufactured	Ls: Location of sample	Quad: Quadrant
Avg: Average	Max: Maximum	Sc: Specimen condition
B: Body	Min: Minimum	Var: Variation

IMPACT TEST

Type: Charpy V			Orientation: T				Unit: ft.lb				Shear area %			
Position:			Temp: 32		Unit: F		Ind.Min.Reg: 11		Req.Min.Avg: 15		Ind.Min.Reg: -		Req.Min.Avg: -	
Heat N°	Sample N°	Lot N°	Ls	Sc	T.T F	Size	Results				Results			
						-	1	2	3	Avg.	1	2	3	Avg.
2161576	220920	2161576	B	AM	32	3/4	98	213	170	160	80	100	100	93

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817290.07

Page:

4 / 6Date: **July 14, 2026**

Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427			Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO		Manufacturer's Works Order N°: N/A		
Manufacturing Process: HFW			Product Type: Line Pipe					Surface: Bare	
Standard or Specification: API Spec 5L 46th Edition 04/2018					Steel Grade: X65M PSL 2			Ends: Plain End Bevelled	
Dimensions: 16.000 x 0.500 in		Schedule: N/A	Length: 35'MIN 45'MAX		Quantity: 12 PCS 503 FT 41716 LB			Nominal Weight: 82.85 LB/FT	

IMPACT TEST

Type: Charpy V			Orientation: T				Unit: ft.lb				Shear area %			
Position:			Temp: 32		Unit: F		Ind.Min.Reg: 11		Req.Min.Avg: 15		Ind.Min.Reg: -		Req.Min.Avg: -	
Heat N°	Sample N°	Lot N°	Ls	Sc	T.T	Size	Results				Results			
					F	-	1	2	3	Avg.	1	2	3	Avg.
2262233	220721	2262233	B	AM	32	3/4	142	222	125	163	90	100	90	93
2262234	220722	2262234	B	AM	32	3/4	112	100	119	110	85	85	85	85

AM: As manufactured

Ind. Min. Req: Individual Minimum Required

Sc: Specimen condition

Avg: Average

Ls: Location of sample

T.T: Test temperature

B: Body

Req. Min. Avg: Required minimum average

Temp: Temperature

FLATTENING TEST

Standard:				Standard:				Standard:			
Heat N°	Lot N°	Sample N°	Result	Heat N°	Lot N°	Sample N°	Result	Heat N°	Lot N°	Sample N°	Result
2161576	2161576	220920	Good	2262233	2262233	220721	Good	2262234	2262234	220722	Good

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817290.07

Page:

5 / 6Date: **July 14, 2026**

Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427		Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO	Manufacturer's Works Order N°: N/A
Manufacturing Process: HFW		Product Type: Line Pipe			Surface: Bare
Standard or Specification: API Spec 5L 46th Edition 04/2018			Steel Grade: X65M PSL 2		Ends: Plain End Bevelled
Dimensions: 16.000 x 0.500 in	Schedule: N/A	Length: 35"MIN 45"MAX	Quantity: 12 PCS 503 FT 41716 LB		Nominal Weight: 82.85 LB/FT

HYDROSTATIC TEST

Pressure		Time	Results
Unit	Value	Seconds	
psi	2,970	5	Satisfactory

SUPPLEMENTARY INFORMATION

Supplementary Information	Supplementary Information
This material has been manufactured, sampled, tested and inspected in accordance with this specification and has been found to meet the requirements called for by the above order. This product is silicon and/or aluminum fully killed. NDT OK; Longitudinal UT and Transverse EMI with ID/OD N-10 Notches (1.0" L and .039" W)	verified by 1/8" TDH BODY TENSILE SOURCED 180° FROM WELD LINE; CVN SAMPLES SOURCED 90° FROM WELD LINE; CVN SAMPLES TESTED BY 8mm STRIKER
Heat Treatment	Heat Treatment
The minimum weld seam heat treatment temperature is 1650F.	
Steel Vendor Name and Manufactured	Steel Vendor Name and Manufactured
2161576,NUCOR STEEL HICKMAN,ARMOREL,AR,Melted and Manufactured in USA 2262233,NUCOR STEEL HICKMAN,ARMOREL,AR,Melted and Manufactured in USA	2262234,NUCOR STEEL HICKMAN,ARMOREL,AR,Melted and Manufactured in USA

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817290.07

Page:

6 / 6Date: **July 14, 2026**


Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427		Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO	Manufacturer's Works Order N°: N/A
Manufacturing Process: HFW		Product Type: Line Pipe			Surface: Bare
Standard or Specification: API Spec 5L 46th Edition 04/2018			Steel Grade: X65M PSL 2		Ends: Plain End Bevelled
Dimensions: 16.000 x 0.500 in	Schedule: N/A	Length: 35"MIN 45"MAX	Quantity: 12 PCS 503 FT 41716 LB		Nominal Weight: 82.85 LB/FT

SUMMARY REPORT

Heat N°	Quantity	Length	Weight	Heat N°	Quantity	Length	Weight	Heat N°	Quantity	Length	Weight
	(Pieces)	FT	LB		(Pieces)	FT	LB		(Pieces)	FT	LB
2161576	3	131.87	10,926.747	2262233	4	159.485	13,214.512	2262234	5	212.106	17,575.436

The product certified herein has been manufactured, sampled, tested and inspected in accordance with the stated specifications and has been found to meet the requirements.

We, Tenaris, hereby acknowledge the restrictions as per article 3g(1) of Council Regulation (EU) No 833/2014, as amended, and confirm that our company is compliant with this legislation. Consequently, we, Tenaris, hereby represent and warrant that the steel products covered by this certificate, as listed in Annex XVII of Council Regulation (EU) No 833/2014 of 31 July 2014 and its subsequent amendments, do not originate from Russia. Furthermore, we confirm that the steel products covered by this certificate, as listed in Annex XVII of Council Regulation (EU) No 833/2014 of 31 July 2014 and its subsequent amendments, as required under article 3g(1)(d) (as amended) and related guidelines do not incorporate any steel or iron products as listed in the same Annex XVII originating in Russia when having been processed in a third country. We also acknowledge the equivalent restrictions as per Clause 17e of Norway's Russia Regulations of 15 August 2014 No. 1076 (FOR-2014-08-15-1076) and Regulations 46IA and 46IB of the UK Russia (Sanctions) (EU Exit) Regulations 2019, and confirm that our company is compliant with these laws as well.

CUSTOMER / THIRD PARTY	TENARIS QUALITY DEPARTMENT SIGNATURE
INSPECTION COMPANY COMPAÑÍA DE INSPECCIÓN Company Name: N/A Employee Name: N/A	 QUALITY CERTIFICATION DEPT. Francisco G. Pinilla Portales  CHIEF OF QUALITY CERTIFICATION DEPT. Kyle McCarthy

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.